# Contracts vulnerabilities

### Vulnerabilities list

Contracts vulnerabilities	1
Vulnerabilities list	1
Involved contracts and level of the bugs	1
Vulnerabilities	2
1. depositServiceDonationsETH function (services state)	2
2. depositServiceDonationsETH function (OLAS incentives)	2
3. deposit method	3
4. checkpoint method - cross-year	4
5. Treasury Fund Token Management	4
6. Encoded inflation schedule	5
7. Withheld tokens	5
8. changeManagers function (specifically - voteWeighting)	6

# Involved contracts and level of the bugs

The present document describes issues affecting Tokenomics contracts

# **Vulnerabilities**

1. depositServiceDonationsETH function (services state)

### Severity: Low

The following function is implemented in the Treasury contract:

```
function depositServiceDonationsETH(uint256[] memory serviceIds, uint256[]
memory amounts) external payable
```

This service donating function calls another function from the Tokenomics contract that ultimately results in calling the internal function \_trackServiceDonations(). The latter one checks whether agent and component lds of each of the passed service ld exist, and if not, reverts with the ServiceNeverDeployed() error. The error arises from the fact that the service was never deployed, and its underlying component and agent lds were not

assigned (the assignment of underlying component and/or agent lds to a service happens during the deployment of the service itself).

However, after a specific service is deployed at least once and then terminated, it can be updated and re-deployed again. In particular, the service can be updated with a different set of agent Ids, making the donation distribution setup invalid for the following reason. If this updated service receives a donation before it is re-deployed, the donation will be distributed between its old component and agent Ids owners and not the new ones.

Therefore, donating to an updated service before its redeployment can affect the correct distribution of rewards in the Tokenomics contract. We recommend not to donate when a service is not in the <code>Deployed</code> or <code>TerminatedBonded</code> state (e.g. any service with <code>serviceIds[i]</code> not in <code>Deployed</code> or <code>TerminatedBonded</code> state must not be passed as input parameters to the function <code>depositServiceDonationsETH</code>). The state of the service can be easily checked via the <code>ServiceRegistry</code> contract view function <code>getService(uint256 serviceId)</code>.

# 2. depositServiceDonationsETH function (OLAS incentives)

#### Severity: Informative

The following function is implemented in the Treasury contract:

function depositServiceDonationsETH(uint256[] memory serviceIds, uint256[]
memory amounts) external payable

If a DAO member, holding the veOLAS threshold<sup>1</sup>, uses this method to donate ETH to a specific service, or if the service owner is a DAO member holding the veOLAS threshold<sup>2</sup>, the owners of the agents and components referenced in that service are entitled to receive a share of the donation and OLAS top-ups generated through inflation.

While the current approach encourages service registration and donations through the utilization of all available OLAS each epoch, this might be utilized in a counter-intended way by malicious donators or malicious service-owners. If a donator (or the service-owner) owns all the underlying components and agents, meets the sufficient veOLAS requirement, and makes only a small donation to their service, they could accrue

<sup>&</sup>lt;sup>1</sup> Currently, the threshold for participation is set at 10000 veOLAS, and adjustments to this threshold can be made through a governance voting process.

<sup>&</sup>lt;sup>2</sup> Currently, the threshold for participation is set at 10000 veOLAS, and adjustments to this threshold can be made through a governance voting process.

a significant number of OLAS tokens through inflation top-ups at a low cost. This behavior may yield considerable gains initially but becomes less profitable as more major players utilize the protocol, leading to more donations being distributed among multiple services and stakeholders.

3. deposit method

Severity: High

In the depository contracts, the following method is implemented:

function deposit(uint256 productId, uint256 tokenAmount) external

This method allows users to deposit tokens, acquiring OLAS tokens at a discounted rate. A potential concern can arise ten years after OLAS token launch in the case of an epoch crossing into year intervals. In this scenario, a portion of OLAS becomes mintable only in the eleventh year, as a result of the 1 billion fixed supply constraint for the initial ten years.

The creation of bonding programs with payouts leading to exceeding the total OLAS supply mintable before ten years and the bonder's depositing the full amount expecting these payouts lead to a silent return in the OLAS mint () method and not a revert. This results in successful product deposit and a consequent loss of OLAS payouts for bonders.

To address this, a more specific check for epoch crossing year intervals can be integrated into the tokenomics <code>checkpoint()</code> method. In the absence of redeploying a new contract, it is recommended to carefully propose the creation of bonding programs at the end of the tenth year. These programs should be structured ensuring that the payouts are designed to keep the total amount of OLAS minted below 1 billion OLAS before the ten-year mark. This precautionary measure prevents eventual lost OLAS payouts.

4. checkpoint method - cross-year

Severity: Informative

In the tokenomics contracts, the following method is implemented:

function checkpoint() external

This method allows users to deposit tokens, acquiring OLAS tokens at a discounted rate. A potential concern may arise in the event of an epoch crossing into year intervals, where a portion of OLAS larger than the year inflation limit becomes mintable.

The creation of bonding programs with payouts leading to an excess of the total OLAS mintable before the specified year and the bonder depositing the full amount may result in an amount of minted OLAS exceeding the year inflation limit. It's crucial to note that, at most, only the amount reserved for the remaining time of the epoch from the following year can be minted.

To address this, a more specific check for epoch crossing year intervals can be integrated into the tokenomics <code>checkpoint()</code> method. In the absence of redeploying a new contract, it is recommended to carefully propose the creation of bonding programs for epoch-crossing years. These programs should be structured to ensure that the payouts are designed in a manner that keeps the total amount of OLAS minted below the year inflation limit.

### 5. Treasury Fund Token Management

#### **Severity**: Informative

By design, within the Treasury contract, there is currently no mechanism in place to facilitate the removal of tokens other than ETH that have not been added to the Treasury through the treasury *depositTokenForOLAS()* method.

Therefore, we strongly recommend refraining from transferring funds directly to the Treasury contract that does not adhere to the established tokenomics logic. This precautionary measure will help prevent potential freezing of funds within the Treasury contract

#### Encoded inflation schedule

#### **Severity**: Informative

If donors in a given epoch fail to meet the veOLAS threshold for donating ETH to specific services within 10 years of OLAS token creation, the reserved OLAS inflation for top-ups remains inactive. Although accounted for in the inflation schedule of that epoch, that amount is essentially deducted from the inflation schedule. For instance, if x OLAS were accounted for in the inflation for top-ups during the inaugural tokenomics epoch but no

donator meets the veOLAS threshold, these top-ups cannot be utilized for subsequent epochs encoded in the 10-year inflation schedule.

A similar scenario can occur when OLAS top-ups and staking incentives are distributed. Due to the natural rounding behavior of Solidity and the division involved in calculating top-ups and staking emissions, it's possible that the actual sum of OLAS allocated to owners of agents and components referenced in donated services and the calculated staking emissions might be slightly less than the exact amount that can be extracted from the encoded inflation schedule in the tokenomics contract. In such cases, the difference between the exact amount and the actually allocated amount for top-up and staking is implicitly deducted from the inflation schedule.

This deferred inflation isn't lost; rather, it's postponed, as the OLAS token ensures that no more than 1 billion tokens are minted within a decade, with no more than 2% of the supply cap being minted annually, starting from 1 billion.

#### 7. Withheld tokens

Severity: Informative

The TargetStakingDispenser contract on L2 withholds some staking emissions sent by L1 (see the section "Verification on staking contract enabled by StakingVerifier" <a href="here">here</a> for details on the tokens withheld by the TargetStakingDispenser).

To prevent L1 from sending new emissions while there are still withheld emissions on the TargetStakingDispenser, we need to ensure regular synchronizations between L1 and L2. Specifically, if there is demand for emissions for a specific contract on L2, and L1 is synchronized with the withheld amount on the TargetStakingDispenser, L1 will only send a message without minting or sending new emissions to the L2 target contract until the withheld amount is fully utilized and additional demand arises.

Additionally, if there is no new demand for emissions from the L2 target dispenser and a withheld amount remains, the DAO can initiate a new staking campaign to utilize the withheld amount.

Finally, the DAO can employ the combination of the functions **migrate()**, **syncWithheldAmount()**, and **processDataMaintenance()** to transfer the withheld tokens to a DAO-controlled account.

8. changeManagers function (specifically - voteWeighting)

## Severity: Informative

The following function is implemented in the Dispenser contract:

```
function changeManagers(address _tokenomics, address _treasury,
address voteWeighting) external
```