

First-Come,First-Served CPU Scheduling Algorithm

Write a C program to implement the First-Come, First-Served (FCFS) CPU Scheduling Algorithm. The program should take the number of processes, their Arrival Times (AT), and Burst Times (BT) as input. Calculate and display the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process, along with the Average Turnaround Time and Average Waiting Time.

To evaluate the performance of the algorithm, we use the following formulas:

- **Completion Time (CT):** The time at which a process finishes execution.
- **Turnaround Time (TAT):** Total time taken from arrival to completion.
- $TAT = CT - AT$
- **Waiting Time (WT):** The time a process spends waiting in the ready queue.
- $WT = TAT - BT$

Input Format

1. The first input line contains an integer representing the number of processes.
2. The next lines contain two integers for each process, where the first integer represents the Arrival Time (AT) and the second integer represents the Burst Time (BT).

Output Format

The output displays the Average Turnaround Time and the Average Waiting Time.

Example 1

Sample Input 1

```
3
0 2
1 2
2 3
```

Sample Output 1

Enter number of processes:

Enter Arrival Time and Burst Time for P1:

Enter Arrival Time and Burst Time for P2:

Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33

Average Waiting Time: 1.00

Example 2

Sample Input 2

3

0 5

5 3

8 2

Sample Output 2

Enter number of processes:

Enter Arrival Time and Burst Time for P1:

Enter Arrival Time and Burst Time for P2:

Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33

Average Waiting Time: 0.00

SOURCE CODE:

```
Select Language: C (GCC 9.2.0)
1 #include <stdio.h>
2 int main(){
3     int n,i;
4     printf("Enter number of processes: \n");
5     scanf("%d",&n);
6     int at[n],bt[n],ct[n],tat[n],wt[n];
7     float total_tat = 0,total_wt = 0;
8     for(i=0;i<n;i++){
9         printf("Enter Arrival Time and Burst Time for P%d: \n",i+1);
10        scanf("%d %d",&at[i],&bt[i]);
11        ct[0]=at[0]+bt[0];
12        for(i=1;i<n;i++){
13            if(ct[i-1]<at[i])
14                ct[i]=at[i]+bt[i];
15            else
16                ct[i]=ct[i-1]+bt[i];
17        }for(i=0;i<n;i++){
18            tat[i]=ct[i]-at[i];
19            wt[i]=tat[i]-bt[i];
20        }
```

```
Select Language : C (GCC 9.2.0)
7 //float total_tat = 0, total_wt = 0;
8 for(i=0;i<n;i++){
9     printf("Enter Arrival Time and Burst Time for P%d: \n",i+1);
10    scanf("%d %d",&at[i],&bt[i]);
11    }ct[0]=at[0]+bt[0];
12    for(i=1;i<n;i++){
13        if(ct[i-1]<at[i])
14            ct[i]=at[i]+bt[i];
15        else
16            ct[i]=ct[i-1]+bt[i];
17    }for(i=0;i<n;i++){
18        tat[i]=ct[i]-at[i];
19        wt[i]=tat[i]-bt[i];
20        total_tat+=tat[i];
21        total_wt+=wt[i];
22    }printf("\nAverage Turnaround Time: %.2f\n",total_tat/n);
23    printf("Average Waiting Time: %.2f\n",total_wt/n);
24    return 0;
25 }
```

First-Come,First-Served CPU Scheduling Algorithm

Write a C program to implement the First-Come, First-Served (FCFS) CPU Scheduling Algorithm. The program should take the number of processes, their Arrival Times (AT), and Burst Times (BT) as input. Calculate and display the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process, along with the Average Turnaround Time and Average Waiting Time.

To evaluate the performance of the algorithm, we use the following formulas:

- **Completion Time (CT):** The time at which a process finishes execution.
- **Turnaround Time (TAT):** Total time taken from arrival to completion.
- $TAT = CT - AT$
- **Waiting Time (WT):** The time a process spends waiting in the ready queue.
- $WT = TAT - BT$

Input Format

1. The first input line contains an integer representing the number of processes.

Custom Test

Input :

```
3
0 2
1 2
2 3
```

Expected Output :

```
Enter number of processes:
Enter Arrival Time and Burst Time for P1:
Enter Arrival Time and Burst Time for P2:
Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33
Average Waiting Time: 1.00
```

Output :

```
Enter number of processes:
Enter Arrival Time and Burst Time for P1:
Enter Arrival Time and Burst Time for P2:
Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33
Average Waiting Time: 1.00
```

Sample Test Case

Success

FACE Prep

Operating System - Coding | REC | 3 Feb

Course Progress 89% [Go Back](#)

[Back To Practice](#) Q1 [Save](#)

First-Come,First-Served CPU Scheduling Algorithm

Write a C program to implement the First-Come, First-Served (FCFS) CPU Scheduling Algorithm. The program should take the number of processes, their Arrival Times (AT), and Burst Times (BT) as input. Calculate and display the Completion Time (CT), Turnaround Time (TAT), and Waiting Time (WT) for each process, along with the Average Turnaround Time and Average Waiting Time.

To evaluate the performance of the algorithm, we use the following formulas:

- **Completion Time (CT):** The time at which a process finishes execution.
- **Turnaround Time (TAT):** Total time taken from arrival to completion.
- $TAT = CT - AT$
- **Waiting Time (WT):** The time a process spends waiting in the ready queue.
- $WT = TAT - BT$

Input Format

1. The first input line contains an integer representing the number of processes.

```
3
0 5
5 3
8 2
```

```
Enter number of processes:
Enter Arrival Time and Burst Time for P1:
Enter Arrival Time and Burst Time for P2:
Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33
Average Waiting Time: 0.00
```

Output :

```
Enter number of processes:
Enter Arrival Time and Burst Time for P1:
Enter Arrival Time and Burst Time for P2:
Enter Arrival Time and Burst Time for P3:

Average Turnaround Time: 3.33
Average Waiting Time: 0.00
```

Test Cases Passed: 5 / 5