

```
# prn:23070521126 SANIYA GOUTAM
!pip install yfinance --quiet
```

```
import numpy as np
import pandas as pd
import yfinance as yf
from sklearn.preprocessing import MinMaxScaler
from sklearn.model_selection import train_test_split
from tensorflow.keras.models import Sequential
from tensorflow.keras.layers import LSTM, Dense
import matplotlib.pyplot as plt
```

```
# Define the stock ticker and date range
TICKER = 'AAPL' # Apple Inc.
START_DATE = '2010-01-01'
END_DATE = '2023-01-01'

# Download data
df = yf.download(TICKER, start=START_DATE, end=END_DATE)

# Display the first few rows of the data
print(f"Downloaded data for {TICKER} from {START_DATE} to {END_DATE}.")
display(df.head())

# Use only the 'Close' price for prediction
data = df['Close'].values.reshape(-1, 1)

# Scale the data to be between 0 and 1
scaler = MinMaxScaler(feature_range=(0, 1))
scaled_data = scaler.fit_transform(data)

print("\nScaled data snippet:")
display(scaled_data[:5])
```

```
/tmp/ipykernel_2095/1472712790.py:7: FutureWarning: YF.download() has changed argument aut
df = yf.download(TICKER, start=START_DATE, end=END_DATE)
[*****100%*****] 1 of 1 completedDownloaded data for AAPL
```

Price	Close	High	Low	Open	Volume	
Ticker	AAPL	AAPL	AAPL	AAPL	AAPL	
Date						
2010-01-04	6.400960	6.415616	6.352207	6.383612	493729600	
2010-01-05	6.412026	6.448217	6.378228	6.418607	601904800	
2010-01-06	6.310035	6.437450	6.303454	6.412027	552160000	
2010-01-07	6.298372	6.340845	6.252611	6.333367	477131200	
2010-01-08	6.340244	6.340843	6.252909	6.289996	447610800	

Scaled data snippet:
array([[0.00381775],
[0.00388208],
[0.00328925],
[0.00322146],
[0.00346484]])

```
# Function to create sequences for LSTM
def create_sequences(data, time_step=1):
    X, y = [], []
    for i in range(len(data) - time_step):
        X.append(data[i:(i + time_step), 0])
        y.append(data[i + time_step, 0])
    return np.array(X), np.array(y)

# Define time step (number of previous days to consider for prediction)
TIME_STEP = 60

# Create features (X) and target (y)
X, y = create_sequences(scaled_data, TIME_STEP)

# Split data into training and testing sets
# We'll use 80% for training and 20% for testing
train_size = int(len(X) * 0.8)
X_train, X_test = X[0:train_size], X[train_size:len(X)]
y_train, y_test = y[0:train_size], y[train_size:len(y)]

# Reshape input to be [samples, time_steps, features]
X_train = X_train.reshape(X_train.shape[0], X_train.shape[1], 1)
X_test = X_test.reshape(X_test.shape[0], X_test.shape[1], 1)

print(f"\nShape of X_train: {X_train.shape}")
print(f"Shape of y_train: {y_train.shape}")
print(f"Shape of X_test: {X_test.shape}")
print(f"Shape of y_test: {y_test.shape}")
```

```
Shape of X_train: (2569, 60, 1)
Shape of y_train: (2569,)
Shape of X_test: (643, 60, 1)
Shape of y_test: (643,)
```

```
# Build the LSTM model
model = Sequential()
model.add(LSTM(units=50, return_sequences=True, input_shape=(TIME_STEP, 1)))
model.add(LSTM(units=50, return_sequences=False))
model.add(Dense(units=25))
model.add(Dense(units=1))

# Compile the model
model.compile(optimizer='adam', loss='mean_squared_error')

# Train the model
history = model.fit(X_train, y_train, batch_size=32, epochs=50, validation_split=0.1, ver

print("Model training complete.")
```

```

Epoch 42/50
73/73 ————— 2s 28ms/step - loss: 1.4311e-05 - val_loss: 1.7415e-04
Epoch 43/50
73/73 ————— 2s 28ms/step - loss: 1.3479e-05 - val_loss: 1.2042e-04
Epoch 44/50
73/73 ————— 3s 37ms/step - loss: 1.6643e-05 - val_loss: 1.0969e-04
Epoch 45/50
73/73 ————— 2s 28ms/step - loss: 1.4765e-05 - val_loss: 1.0660e-04
Epoch 46/50
73/73 ————— 3s 28ms/step - loss: 1.6622e-05 - val_loss: 9.8476e-05
Epoch 47/50
73/73 ————— 2s 28ms/step - loss: 1.5090e-05 - val_loss: 1.5378e-04
Epoch 48/50
73/73 ————— 2s 29ms/step - loss: 1.3123e-05 - val_loss: 1.1239e-04
Epoch 49/50
73/73 ————— 3s 38ms/step - loss: 1.3694e-05 - val_loss: 1.0952e-04
Epoch 50/50
73/73 ————— 4s 29ms/step - loss: 1.6089e-05 - val_loss: 1.0063e-04
Model training complete

```

```

# Make predictions on the test set
test_predictions = model.predict(X_test)

# Inverse transform the predictions and y_test to get actual prices
test_predictions_rescaled = scaler.inverse_transform(test_predictions)
y_test_rescaled = scaler.inverse_transform(y_test.reshape(-1, 1))

# Prepare actual values for plotting (from the original DataFrame)
# The 'Close' prices used for testing start after the training data and TIME_STEP offset
# This variable was causing issues, removing it for a clearer approach.
# actual_prices_plot = df['Close'].values[len(df) - len(y_test_rescaled) - TIME_STEP + 1:]

# The dates for plotting should correspond to the actual y_test values.
# y_test corresponds to data[TIME_STEP + train_size:] in the original scaled_data.
# So, the dates should be from df.index starting at TIME_STEP + train_size.
dates_for_plot = df.index[TIME_STEP + train_size:]

# Visualize the results
plt.figure(figsize=(16, 8))
plt.title(f'{TICKER} Stock Price Prediction')
plt.xlabel('Date')
plt.ylabel('Close Price USD')

plt.plot(dates_for_plot, y_test_rescaled, label='Actual Price', color='green')
plt.plot(dates_for_plot, test_predictions_rescaled, label='Predicted Price', color='purple')
plt.legend()
plt.grid(True)
plt.show()

```

