

CS23334 Fundamentals of Data Science Lab

Experiment 10

Array Functions & Manipulations in Data Science using NumPy

Objective: To understand and perform NumPy array operations, dimensional checking, reshaping, flattening (`ravel`), and multi-dimensional slicing.

Methodology:

- 1 **Array Creation & Element-wise Operations:** Initialize NumPy arrays using `random.randint` and perform mathematical operations such as square root calculation (`np.sqrt`).
- 2 **Dimension Inspection:** Check array rank and dimensionality using the `.ndim` attribute.
- 3 **Reshaping & Flattening:** Re-structure 1D arrays into 2D matrices using `.reshape(3, 3)` and flatten multi-dimensional matrices back to 1D using `.ravel()`.
- 4 **Multi-dimensional Slicing & Indexing:** Perform 2D array slicing across rows and columns to extract sub-matrices and specific vector slices.

Code:

```
import numpy as np

array = np.random.randint(1, 100, 9)
array

np.sqrt(array)

array.ndim

new_array = array.reshape(3, 3)
new_array

new_array.ndim

new_array.ravel()

newm = new_array.reshape(3, 3)
newm

newm[2, 1:3]

newm[1:2, 1:3]

new_array[0:3, 0:0]

new_array[0:2, 0:1]

new_array[0:3, 0:1]

new_array[1:3]
```

OUTPUT: Array Operations, Reshaping & Slicing Results

```
In [1]: array = np.random.randint(1, 100, 9)
```

```
In [2]: array
```

```
Out[2]: array([83, 25, 19, 47, 62, 15, 96, 39, 51])
```

```
In [3]: np.sqrt(array)
```

```
Out[3]: array([9.11043358, 5.          , 4.35889894, 6.8556546 , 7.87400787,  
              3.87298335, 9.79795897, 6.244998  , 7.14142843])
```

```
In [4]: array.ndim
```

```
Out[4]: 1
```

```
In [5]: new_array = array.reshape(3, 3)
```

```
In [6]: new_array
```

```
Out[6]:
```

```
array([[83, 25, 19],  
       [47, 62, 15],  
       [96, 39, 51]])
```

```
In [7]: new_array.ndim
```

```
Out[7]: 2
```

```
In [8]: new_array.ravel()
```

```
Out[8]: array([83, 25, 19, 47, 62, 15, 96, 39, 51])
```

```
In [9]: newm = new_array.reshape(3, 3)
```

```
In [10]: newm[2, 1:3]
```

```
Out[10]: array([39, 51])
```

```
In [11]: newm[1:2, 1:3]
```

```
Out[11]: array([[62, 15]])
```

```
In [12]: new_array[0:3, 0:0]
```

```
Out[12]: array([], shape=(3, 0), dtype=int64)
```

```
In [13]: new_array[0:2, 0:1]
```

```
Out[13]:
```

```
array([[83],  
       [47]])
```

```
In [14]: new_array[0:3, 0:1]
```

```
Out[14]:
```

```
array([[83],  
       [47],  
       [96]])
```

```
In [15]: new_array[1:3]
```

```
Out[15]:
```

```
array([[47, 62, 15],  
       [96, 39, 51]])
```