

Python

▼ What is Python ?

→ Python is a **high-level, interpreted programming language** known for its simplicity and readability. It is widely used for web development, data science, artificial intelligence, machine learning, automation, scripting, and more. Python emphasizes code readability with its clean syntax and indentation-based structure.

Key Features of Python:

- **Interpreted** : Executes code line by line.
- **Dynamically Typed** : No need to declare variable types.
- **Extensive Libraries** : Has rich libraries like NumPy, Pandas, TensorFlow, Django, Flask, etc.

▼ Installation of Python ?

STEPS :

1. Go to the official Python website: <https://www.python.org/downloads/>
2. Click on **"Download Python [latest version]"** (e.g., Python 3.x.x).
3. The installer (`.exe` file) will be downloaded.
4. Open **Command Prompt (cmd)**:
5. Type `cmd` , and press **Enter**.
6. Type the following command and press **Enter** : If Python is installed correctly, it will display the installed version.

" python --version "

▼ What is Python Indentation ?

→ Indentation in Python refers to **the spaces or tabs at the beginning of a line of code** that define the structure of the program. Unlike other programming languages that use curly braces `{ }` to mark code blocks, Python **strictly enforces indentation** to indicate blocks of code.

→ The number of spaces is up to you as a programmer, the most common use is four, but it has to be at least one.

▼ Python Variables ?

→ A **variable** in Python is used to store data. It acts as a container that holds values, which can be changed during program execution.

▼ Declaring a Variable in Python :

- Python **automatically assigns** the data type based on the value.
- No need to specify `int` , `float` , `string` , etc.

```
x = 10 # Integer
y = "Sanjai" # String
z = 3.14 # Float
```

▼ Variable Names :

Rules for Naming Variables

✅ **Valid Variable Names:**

1. Must start with a **letter (a-z, A-Z) or an underscore** `_`, but not a number.
2. Can contain **letters, numbers (0-9), and underscores** `_`.
3. Variable names are **case-sensitive** (`age` and `Age` are different).
4. Should not use **Python keywords** (e.g., `if`, `else`, `class`, `def`, etc.).

```
name = "Sanjai" # Valid
_age = 22 # Valid
totalAmount = 500 # Valid
```

Best Practices for Naming Variables

- Use **descriptive** names (`student_name` instead of `s`).
- Follow **snake_case** (`first_name`, `total_amount`).
- Use **camelCase** if working with JavaScript-like syntax (`firstName`).

▼ ***Assign Multiple Values :***

→ Python allows assigning **multiple values** to multiple variables in one line.

Example : Assign Different Values

```
a, b, c = 10, 20, 30
print(a, b, c) # Output: 10 20 30
```

Example : Assign Same Value to Multiple Variables

```
x = y = z = 100
print(x, y, z) # Output: 100 100 100
```

Example : Unpacking a List or Tuple

```
fruits = ["apple", "banana", "cherry"]
x, y, z = fruits
print(x, y, z) # Output: apple banana cherry
```

▼ ***Output Variables :***

→ You can display the value of variables using `print()` .

Example : Printing Variables

```
name = "Sanjai"
age = 22
print(name)
print(age)
```

Example : Combining Strings and Variables

```
name = "Sanjai"
print("Hello, " + name) # Output: Hello, Sanjai
```

Example : Using `f-strings` (Recommended)

```
age = 22
print(f"I am {age} years old.") # Output: I am 22 years old.
```

Example : Using `format()`

```
name = "Sanjai"
age = 25
print("My name is {} and I am {} years old.".format(name, age))
```

▼ Global Variables :

→ A **global variable** is a variable declared outside of a function and can be accessed anywhere in the program.

Example : *Global Variable*

```
x = "Python" # Global variable

def my_function():
    print("I love " + x)

my_function() # Output: I love Python
```

Using the `global` Keyword

→ To modify a **global variable** inside a function, use the `global` keyword.

```
x = "Python" # Global variable

def my_function():
    global x
    x = "JavaScript" # Modify global variable

my_function()
print(x) # Output: JavaScript
```

▼ Python Data Types ?

→ A **data type** defines the type of value a variable holds. Python provides several built-in data types.

▼ Types of Data Types :

Text Type	<code>str</code>
Numeric Types	<code>int</code> , <code>float</code> , <code>complex</code>
Sequence Types	<code>list</code> , <code>tuple</code> , <code>range</code>
Mapping Type	<code>dict</code>
Set Types	<code>set</code> , <code>frozenset</code>
Boolean Type	<code>bool</code>
Binary Types	<code>bytes</code> , <code>bytearray</code> , <code>memoryview</code>
None Type	<code>NoneType</code>

▼ Setting the Specific Data Type :

Example	Data Type	OutPut
<code>x = str("Sanjai Kannan G")</code>	<code>str</code>	Sanjai Kannan G - str
<code>x = int(22)</code>	<code>int</code>	22 - int

x = float(22.5)	float	22.5 - float
x = complex(1j)	complex	1j - complex
x = list(("sanjai", "kannan", "gokul"))	list	["sanjai", "kannan", "gokul"] - list
x = tuple(("sanjai", "kannan", "gokul"))	tuple	("sanjai", "kannan", "gokul") - tuple
x = range(6)	range	range(0, 6) - range
x = dict("name" : "sanjai", "age" : 22)	dict	{'name': 'sanjai', 'age': 22} - dict
x = set(("apple", "banana", "cherry"))	set	{'apple', 'banana', 'cherry'} - set
x = frozenset(("apple", "banana", "cherry"))	frozenset	frozenset({'banana', 'apple', 'cherry'})
x = bool(5)	bool	True
x = bytes(5)	bytes	b'\x00\x00\x00\x00\x00'
x = bytearray(5)	bytearray	bytearray(b'\x00\x00\x00\x00\x00')
x = memoryview(bytes(5))	memoryview	<memory at 0x00D58FA0>

▼ **Python Casting (Type Conversion) ?**

→ Python allows you to convert data from one type to another using **casting functions**.

1. Casting to Integer (`int`) :

→ Converts values to an integer (removes decimals, converts strings if valid).

```
x = int(3.9)    # 3
y = int("10")   # 10
z = int(True)   # 1
```

2. Casting to Float (`float`) :

→ Converts values to a floating-point number.

```
x = float(5)    # 5.0
y = float("3.14") # 3.14
z = float(False) # 0.0
```

3. Casting to String (`str`) :

→ Converts values to a string.

```
x = str(100)    # "100"
y = str(3.14)   # "3.14"
z = str(True)   # "True"
```

4. Casting to Boolean (`bool`) :

→ Converts values to `True` or `False` .

- `0` , `None` , `""` , `[]` , `{}` → **False**
- Everything else → **True**

```
x = bool(0)     # False
y = bool(10)    # True
z = bool("Hello") # True
```

5. Casting to List (`list`) :

→ Converts an iterable (tuple, string, range) to a list.

```
x = list("hello")    # ['h', 'e', 'l', 'l', 'o']
y = list((1, 2, 3))  # [1, 2, 3]
z = list(range(3))   # [0, 1, 2]
```

6. Casting to Tuple (`tuple`) :

→ Converts an iterable to a tuple.

```
x = tuple([1, 2, 3]) # (1, 2, 3)
y = tuple("hello")   # ('h', 'e', 'l', 'l', 'o')
```

7. Casting to Set (`set`) :

→ Converts an iterable to a set (removes duplicates).

```
python
CopyEdit
x = set([1, 2, 2, 3]) # {1, 2, 3}
y = set("banana")    # {'a', 'b', 'n'}
```

8. Casting to Dictionary (`dict`) :

→ Converts a list of key-value pairs to a dictionary.

```
x = dict([("name", "Sanjai"), ("age", 25)])
# {'name': 'Sanjai', 'age': 25}
```

▼ Python Strings ?

▼ Strings :

→ A **string** in Python is a sequence of characters enclosed in **single**, **double**, or **triple quotes**.

```
print("Sanjai") #Double Quotes
print('Sanjai') #Single Quotes
```

▼ Slicing Strings :

→ Python allows **indexing** and **slicing** strings using `[]`.

```
text = "Sanjai Kannan G"

# Accessing characters
print(text[0])  # S (first character)
print(text[-1]) # G (last character)

# Slicing [start:end:step]
print(text[0:6]) # Python (0 to 5)
print(text[7:])  # Kannan G (from index 7 to end)
print(text[:6])  # Sanja (start to index 5)
print(text[::2]) # Sna annG (every second character)
print(text[::-1]) # G nannaK iajnaS (Reverse string)
```

▼ Modify Strings :

→ Python provides multiple string modification methods.

```
text = " Sanjai Kannan G"

# Changing case
print(text.upper()) # " HELLO WORLD "
print(text.lower()) # " hello world "
print(text.title()) # " Hello World "
print(text.capitalize()) # " Hello world "

# Removing spaces
print(text.strip()) # "hello world"
print(text.lstrip()) # "hello world " (removes left spaces)
print(text.rstrip()) # " hello world" (removes right spaces)

# Replacing
print(text.replace("hello", "Hi")) # " Hi world "
```

▼ **Concatenate Strings**

→ In Python, you can concatenate strings using the `+` operator or using the `join()` method.

```
# USING " + "

str1 = "sanjai"
str2 = "kannan"

result = str1 + " " + str2 # Concatenate with a space
print(result) # Output: sanjai kannan
```

```
# USING " JOIN "

str1 = "sanjai"
str2 = "kannan"

result = " ".join([str1, str2]) # Join with a space
print(result) # Output: sanjai kannan
```

▼ **Format Strings**

→ In 2 Methods we can format a string in python.

1. **Using f-strings** (Python 3.6+)

2. **Using** `.format()`

```
# Using f-strings

str1 = "sanjai"
```



```
result = f"my name is {str1}"
print(result)
```

```
# Using .format()

name = "sanjai"
age = 22

result = "my name is {} and my age is {}".format(name, age)
print(result)
```

▼ **Escape Characters**

→ Escape characters allow you to insert special characters into strings. For example:

- `\n` : Newline
- `\t` : Tab
- `\\` : Backslash
- `\'` : Single quote
- `\"` : Double quote

```
str1 = "Sanjai\nKannan" # Newline between Sanjai and Kannan
print(str1) # Output:
# Sanjai
# Kannan

str2 = "This is a \"quoted\" word."
print(str2) # Output: This is a "quoted" word.

str3 = "Backslash: \\"
print(str3) # Output: Backslash: \
```

▼ **String Methods**

PYTHON STRING METHODS

No	Method	Description	Example
1	capitalize()	Converts the first character to upper case	"hello".capitalize() → 'Hello'
2	casefold()	Converts string into lower case	"HELLO".casefold() → 'hello'
3	center()	Returns a centered string	"hello".center(10, "*") → '**hello**'
4	count()	Returns the number of times a specified value occurs	"hello".count('l') → 2
5	encode()	Returns an encoded version of the string	"hello".encode() → b'hello'
6	endswith()	Returns true if the string ends with the specified value	"hello".endswith('o') → True

No	Method	Description	Example
7	expandtabs()	Sets the tab size of the string	<code>"hello\tworld".expandtabs(4)</code> → <code>'hello world'</code>
8	find()	Searches the string for a specified value	<code>"hello".find('e')</code> → <code>1</code>
9	format()	Formats specified values in a string	<code>"My name is {}".format("Alice")</code> → <code>'My name is Alice'</code>
10	format_map()	Formats specified values in a string	<code>"My name is {name}".format_map({"name": "Alice"})</code> → <code>'My name is Alice'</code>
11	index()	Searches the string for a specified value	<code>"hello".index('e')</code> → <code>1</code>
12	isalnum()	Returns True if all characters are alphanumeric	<code>"hello123".isalnum()</code> → <code>True</code>
13	isalpha()	Returns True if all characters are in the alphabet	<code>"hello".isalpha()</code> → <code>True</code>
14	isascii()	Returns True if all characters are ascii characters	<code>"hello".isascii()</code> → <code>True</code>
15	isdecimal()	Returns True if all characters are decimals	<code>"123".isdecimal()</code> → <code>True</code>
16	isdigit()	Returns True if all characters are digits	<code>"123".isdigit()</code> → <code>True</code>
17	isidentifier()	Returns True if the string is an identifier	<code>"my_var".isidentifier()</code> → <code>True</code>
18	islower()	Returns True if all characters are lower case	<code>"hello".islower()</code> → <code>True</code>
29	isnumeric()	Returns True if all characters are numeric	<code>"123".isnumeric()</code> → <code>True</code>
20	isprintable()	Returns True if all characters in the string are printable	<code>"hello".isprintable()</code> → <code>True</code>
21	isspace()	Returns True if all characters are whitespaces	<code>" ".isspace()</code> → <code>True</code>
22	istitle()	Returns True if the string follows the rules of a title	<code>"Hello World".istitle()</code> → <code>True</code>
23	isupper()	Returns True if all characters are upper case	<code>"HELLO".isupper()</code> → <code>True</code>
24	join()	Joins the elements of an iterable to the end of the string	<code>"-".join(['hello', 'world'])</code> → <code>'hello-world'</code>
25	ljust()	Returns a left justified version of the string	<code>"hello".ljust(10, '*')</code> → <code>'hello*****'</code>
26	lower()	Converts a string into lower case	<code>"HELLO".lower()</code> → <code>'hello'</code>
27	lstrip()	Returns a left trim version of the string	<code>" hello".lstrip()</code> → <code>'hello'</code>
28	maketrans()	Returns a translation table to be used in translations	<code>"abc".maketrans("a", "z")</code> → <code>translation table</code>
29	partition()	Returns a tuple where the string is parted into three parts	<code>"hello world".partition(" ")</code> → <code>('hello', ' ', 'world')</code>
30	replace()	Returns a string where a specified value is replaced	<code>"hello".replace("e", "a")</code> → <code>'hallo'</code>
31	rfind()	Searches the string for a specified value (last occurrence)	<code>"hello".rfind('l')</code> → <code>3</code>
32	rindex()	Searches the string for a specified value (last occurrence)	<code>"hello".rindex('l')</code> → <code>3</code>
33	rjust()	Returns a right justified version of the string	<code>"hello".rjust(10, '*')</code> → <code>'*****hello'</code>
34	rpartition()	Returns a tuple where the string is parted into three parts (from right)	<code>"hello world".rpartition(" ")</code> → <code>('hello', ' ', 'world')</code>

No	Method	Description	Example
35	rsplit()	Splits the string at the specified separator, returns a list	"a,b,c".rsplit(',') → ['a', 'b', 'c']
36	rstrip()	Returns a right trim version of the string	"hello ".rstrip() → 'hello'
37	split()	Splits the string at the specified separator, returns a list	"a,b,c".split(',') → ['a', 'b', 'c']
38	splitlines()	Splits the string at line breaks and returns a list	"hello\nworld".splitlines() → ['hello', 'world']
39	startswith()	Returns true if the string starts with the specified value	"hello".startswith('h') → True
40	strip()	Returns a trimmed version of the string	" hello ".strip() → 'hello'
41	swapcase()	Swaps cases, lower case becomes upper case and vice versa	"Hello".swapcase() → 'hELLO'
42	title()	Converts the first character of each word to upper case	"hello world".title() → 'Hello World'
43	translate()	Returns a translated string	"abc".translate({97: 65}) → 'Abc'
44	upper()	Converts a string into upper case	"hello".upper() → 'HELLO'
45	zfill()	Fills the string with a specified number of 0 values at the beginning	"42".zfill(5) → '00042'

▼ **Python Operators ?**

→ Operators are used to perform operations on variables and values.

Python divides the operators in the following groups:

- Arithmetic operators
- Assignment operators
- Comparison operators
- Logical operators
- Identity operators
- Membership operators
- Bitwise operators

Python Arithmetic Operators

→ Arithmetic operators are used with numeric values to perform common mathematical operations:

Operator	Name	Example
+	Addition	x + y
-	Subtraction	x - y
*	Multiplication	x * y
/	Division	x / y
%	Modulus	x % y
**	Exponentiation	x ** y
//	Floor division	x // y

Python Assignment Operators

→ Assignment operators are used to assign values to variables:

Operator	Example	Same As
=	x = 5	x = 5
+=	x += 3	x = x + 3
-=	x -= 3	x = x - 3
*=	x *= 3	x = x * 3
/=	x /= 3	x = x / 3
%=	x %= 3	x = x % 3
//=	x //= 3	x = x // 3
**=	x **= 3	x = x ** 3
&=	x &= 3	x = x & 3
`	=`	`x
^=	x ^= 3	x = x ^ 3
>>=	x >>= 3	x = x >> 3
<<=	x <<= 3	x = x << 3
:=	x := 3	x = 3

Python Comparison Operators

→ Comparison operators are used to compare two values:

Operator	Name	Example
==	Equal	x == y
≠	Not equal	x != y
>	Greater than	x > y
<	Less than	x < y
≥	Greater than or equal to	x >= y
≤	Less than or equal to	x <= y

Python Logical Operators

→ Logical operators are used to combine conditional statements:

Operator	Description	Example
and	Returns "True" if both statements are true	x < 5 and x < 10
or	Returns "True" if at least one of the statements is true	x < 5 or x < 4
not	Reverses the result, returns "False" if the result is true	not(x < 5 and x < 10)

Python Identity Operators

→ Identity operators are used to compare the objects, not if they are equal, but if they are actually the same object, with the same memory location:

Operator	Description	Example
is	Returns "True" if both variables point to the same object	x is y
is not	Returns "True" if both variables do not point to the same object	x is not y

Python Membership Operators

→ Membership operators are used to test if a sequence is presented in an object:

Operator	Description	Example
in	Returns "True" if a sequence with the specified value is present in the object	x in y

Operator	Description	Example
not in	Returns "True" if a sequence with the specified value is not present in the object	x not in y

Python Bitwise Operators

→ Bitwise operators are used to compare (binary) numbers:

Operator	Name	Description	Example
&	AND	Sets each bit to 1 if both bits are 1	x & y
	OR	Sets each bit to 1 if one of two bits is 1	x y
^	XOR	Sets each bit to 1 if only one of two bits is 1	x ^ y
~	NOT	Inverts all the bits	~x
<<	Zero fill left shift	Shift left by pushing zeros in from the right and let the leftmost bits fall off	x << 2
>>	Signed right shift	Shift right by pushing copies of the leftmost bit in from the left, and let the rightmost bits fall off	x >> 2