

Computational Security and Pseudorandom Generators

CS 171: Cryptography

Sanjam Garg

September 8, 2026

Overview

- 1 Computationally Secure Encryption
- 2 Pseudorandom Generators
- 3 Pseudo One-Time Pad
- 4 Security Proof of the Pseudo OTP
- 5 Practice: Manipulating PRGs
- 6 Summary

Defining Computationally Secure Encryption (Syntax)

Definition 1 (Private-Key Encryption Scheme)

A **private-key encryption scheme** is a tuple of algorithms $(\text{Gen}, \text{Enc}, \text{Dec})$:

- $\text{Gen}(1^n)$: outputs a key k (we assume $|k| > n$).
- $\text{Enc}_k(m)$: takes key k and message $m \in \{0, 1\}^*$ as input; outputs ciphertext $c \leftarrow \text{Enc}_k(m)$.
- $\text{Dec}_k(c)$: takes key k and ciphertext c as input; outputs $m := \text{Dec}_k(c)$ or “error”.

Defining Computationally Secure Encryption (Syntax)

Definition 1 (Private-Key Encryption Scheme)

A **private-key encryption scheme** is a tuple of algorithms $(\text{Gen}, \text{Enc}, \text{Dec})$:

- $\text{Gen}(1^n)$: outputs a key k (we assume $|k| > n$).
- $\text{Enc}_k(m)$: takes key k and message $m \in \{0, 1\}^*$ as input; outputs ciphertext $c \leftarrow \text{Enc}_k(m)$.
- $\text{Dec}_k(c)$: takes key k and ciphertext c as input; outputs $m := \text{Dec}_k(c)$ or “error”.

Correctness

For all n , all k output by $\text{Gen}(1^n)$, and all $m \in \{0, 1\}^*$:

$$\text{Dec}_k(\text{Enc}_k(m)) = m.$$

Computational Indistinguishability

Game $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- 1 $\mathcal{A}$ is given the security parameter 1^n .
- 2 $\mathcal{A}$ outputs $m_0, m_1 \in \{0, 1\}^*$ with $|m_0| = |m_1|$.
- 3 $b \leftarrow \{0, 1\}$, $k \leftarrow \text{Gen}(1^n)$, $c \leftarrow \text{Enc}_k(m_b)$ is given to $\mathcal{A}$.
- 4 $\mathcal{A}$ outputs a guess b' .
- 5 Output 1 if $b = b'$, and 0 otherwise.

Computational Indistinguishability

Game $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$

- 1 $\mathcal{A}$ is given the security parameter 1^n .
- 2 $\mathcal{A}$ outputs $m_0, m_1 \in \{0, 1\}^*$ with $|m_0| = |m_1|$.
- 3 $b \leftarrow \{0, 1\}$, $k \leftarrow \text{Gen}(1^n)$, $c \leftarrow \text{Enc}_k(m_b)$ is given to $\mathcal{A}$.
- 4 $\mathcal{A}$ outputs a guess b' .
- 5 Output 1 if $b = b'$, and 0 otherwise.

Definition 2 (Indistinguishable Encryptions (eavesdropper))

$\Pi = (\text{Gen}, \text{Enc}, \text{Dec})$ with message space $\mathcal{M}$ has **indistinguishable encryptions in the presence of an eavesdropper** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

Computational Indistinguishability: Two Relaxations

- **Perfect** indistinguishability requires $\Pr[\dots] \leq \frac{1}{2}$ for *all* adversaries $\mathcal{A}$.
- **Computational** indistinguishability relaxes this in two ways:
 - Quantify only over **PPT** (efficient) adversaries $\mathcal{A}$.
 - Allow a **negligible** advantage: $\frac{1}{2} + \text{negl}(n)$.

Remark

This definition **does not hide the message length!**

Constructing Secure Encryption

A building block

To construct computationally secure encryption we will use
pseudorandom generators (PRGs).

What Does It Mean To Be Random?

Is this string random?

010101010101010101

010100010110101010

What Does It Mean To Be Random?

Is this string random?

010101010101010101

010100010110101010

- Uniformity is a property of a **distribution**, not of a specific **string**.

What Does It Mean To Be Random?

Is this string random?

010101010101010101

010100010110101010

- Uniformity is a property of a **distribution**, not of a specific **string**.

Definition 3 (Distribution / Uniform distribution)

A distribution on n -bit strings is a function $D : \{0, 1\}^n \rightarrow [0, 1]$ such that $\sum_x D(x) = 1$. For the **uniform** distribution on n -bit strings, denoted U_n , we set

$$\forall x \in \{0, 1\}^n : D(x) = 2^{-n}.$$

What About Pseudorandomness?

- Intuitively: a pseudorandom distribution should be **indistinguishable from uniform**.

What About Pseudorandomness?

- Intuitively: a pseudorandom distribution should be **indistinguishable from uniform**.
- As before: **pseudorandomness is a property of a distribution**, and not of a specific string.


Pseudorandom Generators

- Stretches a short uniform “seed” into a larger “uniform-looking” output.


Pseudorandom Generators

- Stretches a short uniform “seed” into a larger “uniform-looking” output.
- Useful when only a few random bits are available.

Pseudorandom Generators (Formally)



Pseudorandom Generators (Formally)



Syntax

Let $\ell(\cdot)$ be a polynomial with $\ell(n) > n$. A **pseudorandom generator** is a deterministic poly-time algorithm $G : \{0, 1\}^n \rightarrow \{0, 1\}^{\ell(n)}$ whose output on a uniform seed “looks uniform” to every PPT adversary.

- $\ell(\cdot)$ is the **stretch** of the generator.
- Next: make “looks uniform” precise via a game (as we did for encryption).

PRG (Predicting-Game Style)

Game $\text{PRG}_{\mathcal{A},G}(n)$

- ① $b \leftarrow \{0, 1\}$.
- ② If $b = 0$ set $x \leftarrow G(U_n)$; else set $x \leftarrow U_{\ell(n)}$.
- ③ Give x to $\mathcal{A}$, who outputs a guess b' .
- ④ Output 1 if $b = b'$, and 0 otherwise.

PRG (Predicting-Game Style)

Game $\text{PRG}_{\mathcal{A},G}(n)$

- 1 $b \leftarrow \{0, 1\}$.
- 2 If $b = 0$ set $x \leftarrow G(U_n)$; else set $x \leftarrow U_{\ell(n)}$.
- 3 Give x to $\mathcal{A}$, who outputs a guess b' .
- 4 Output 1 if $b = b'$, and 0 otherwise.

Definition 4 (PRG, game form)


G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

Remark

The seed must be kept **secret** — analogous to the secret key in an encryption scheme.

$\text{PRG}_{\mathcal{A},G}$: Challenger vs. Adversary




Definition 5 (PRG, game form)

G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

PRG_{A,G}: Challenger vs. Adversary

PRG_{A,G}(n)




Definition 5 (PRG, game form)

G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

PRG_{A,G}: Challenger vs. Adversary




Definition 5 (PRG, game form)

G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

PRG_{A,G}: Challenger vs. Adversary




Definition 5 (PRG, game form)

G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

PRG_{A,G}: Challenger vs. Adversary



Definition 5 (PRG, game form)

G is a **PRG** if for all PPT $\mathcal{A}$:

$$\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \leq \frac{1}{2} + \text{negl}(n).$$

Fixed-Length Encryption Scheme

Construction (Pseudo OTP)

Let $G : \{0, 1\}^n \rightarrow \{0, 1\}^{\ell(n)}$ be a PRG.

- $\text{Gen}(1^n)$: choose uniform $k \in \{0, 1\}^n$ and output it as the key.
- $\text{Enc}_k(m)$: on input a message $m \in \{0, 1\}^{\ell(n)}$, output the ciphertext

$$c := G(k) \oplus m.$$

- $\text{Dec}_k(c)$: on input a ciphertext $c \in \{0, 1\}^{\ell(n)}$, output the message

$$m := G(k) \oplus c.$$

- Like the one-time pad, but the pad is $G(k)$ instead of a truly random key.

Theorem 6

*If G is a PRG, then the construction above is a **fixed-length private-key encryption scheme** that has **indistinguishable encryptions** in the presence of an eavesdropper.*


Proof by Reduction (If X then Π)

Strategy: if X is hard, then Π is secure

To prove: *if no PPT adversary breaks X (here, the PRG G), then no PPT adversary breaks Π .*

- Assume there exists a PPT $\mathcal{A}$ that “breaks” Π .
- Then we construct a PPT $\mathcal{B}$ that “breaks” X .
- But such a $\mathcal{B}$ cannot exist.
- Thus the assumption that some $\mathcal{A}$ breaks Π must have been false. □

Proof by Reduction: The Picture



Important

- **View of $\mathcal{A}$:** no change (it is run exactly as in its own game).
- $\mathcal{B}$ is PPT, given $\mathcal{A}$ is PPT.
- $\mathcal{B}$'s success degrades w.r.t. $\mathcal{A}$'s by at most $1/\text{poly}(n)$.

Theorem 7

*If G is a PRG, then the construction above is a **fixed-length private-key encryption scheme** that has **indistinguishable encryptions** in the presence of an eavesdropper.*

Theorem 7

*If G is a PRG, then the construction above is a **fixed-length private-key encryption scheme** that has **indistinguishable encryptions** in the presence of an eavesdropper.*

Proof by reduction

Given a PPT adversary $\mathcal{A}$ “breaking” the encryption scheme, construct a PPT adversary $\mathcal{B}$ “breaking” the PRG.

Proof by Reduction (If PRG then Indistinguishable Encryption)

Reduction / Adversary $\mathcal{B}$


Adversary $\mathcal{A}$

Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A},\Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B},G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof by Reduction (If PRG then Indistinguishable Encryption)




Given / To prove

Given: $\Pr[\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, G}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Proof of Security: The Reduction $\mathcal{B}$



Reduction $\mathcal{B}$

- 1 Receive x .
- 2 Run $\mathcal{A}(1^n)$; receive m_0, m_1 .
- 3 Sample $b \leftarrow \{0, 1\}$, set $c = x \oplus m_b$; give c to $\mathcal{A}$.
- 4 Receive b' . Output 1 ("pseudorandom") if $b = b'$, else 0 ("uniform").

Proof of Security: Two Cases

Case $x \leftarrow U_{\ell(n)}$ (uniform)

Like a one-time pad, so $\mathcal{A}$ has no advantage:
 $\Pr[b = b'] = \frac{1}{2}.$

Case $x \leftarrow G(U_n)$ (pseudorandom)

$\mathcal{A}$'s view is the real scheme, so
 $\Pr[b = b'] \geq \frac{1}{2} + \epsilon(n).$

Proof of Security: Two Cases

Case $x \leftarrow U_{\ell(n)}$ (uniform)

Like a one-time pad, so $\mathcal{A}$ has no advantage:
 $\Pr[b = b'] = \frac{1}{2}$.

If x is uniform, then $c = x \oplus m_b$ is a one-time pad encryption of m_b : c is uniform and independent of b . So $\mathcal{A}$ learns nothing about b .

Case $x \leftarrow G(U_n)$ (pseudorandom)

$\mathcal{A}$'s view is the real scheme, so
 $\Pr[b = b'] \geq \frac{1}{2} + \epsilon(n)$.

Proof of Security: Two Cases

Case $x \leftarrow U_{\ell(n)}$ (uniform)

Like a one-time pad, so $\mathcal{A}$ has no advantage:
 $\Pr[b = b'] = \frac{1}{2}$.

If x is uniform, then $c = x \oplus m_b$ is a one-time pad encryption of m_b : c is uniform and independent of b . So $\mathcal{A}$ learns nothing about b .

Case $x \leftarrow G(U_n)$ (pseudorandom)

$\mathcal{A}$'s view is the real scheme, so
 $\Pr[b = b'] \geq \frac{1}{2} + \epsilon(n)$.

If $x = G(k)$ for a uniform seed k , then $c = G(k) \oplus m_b$ — exactly the Pseudo OTP. So the view of $\mathcal{A}$ is exactly as in $\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}(n)$.

Proof of Security: Putting It Together

Success probability of $\mathcal{B}$

$$\begin{aligned}\Pr[\mathcal{B} \text{ guesses correct}] &= \frac{1}{2} \Pr[\mathcal{B} \text{ correct} \mid x \leftarrow U_{\ell(n)}] + \frac{1}{2} \Pr[\mathcal{B} \text{ correct} \mid x \leftarrow G(U_n)] \\ &= \frac{1}{2} \left(\frac{1}{2} \right) + \frac{1}{2} \left(\frac{1}{2} + \epsilon(n) \right) = \frac{1}{2} + \frac{\epsilon(n)}{2}.\end{aligned}$$

If $\epsilon(n)$ is non-negligible, so is $\epsilon(n)/2$, contradicting that G is a PRG. □

Proof of Security: Putting It Together

Success probability of $\mathcal{B}$

$$\begin{aligned}\Pr[\mathcal{B} \text{ guesses correct}] &= \frac{1}{2} \Pr[\mathcal{B} \text{ correct} \mid x \leftarrow U_{\ell(n)}] + \frac{1}{2} \Pr[\mathcal{B} \text{ correct} \mid x \leftarrow G(U_n)] \\ &= \frac{1}{2} \left(\frac{1}{2} \right) + \frac{1}{2} \left(\frac{1}{2} + \epsilon(n) \right) = \frac{1}{2} + \frac{\epsilon(n)}{2}.\end{aligned}$$

If $\epsilon(n)$ is non-negligible, so is $\epsilon(n)/2$, contradicting that G is a PRG. □

Remark (running time)

$\mathcal{B}$ runs $\mathcal{A}$ once, performs one XOR, and a comparison — so $\mathcal{B}$ is PPT given $\mathcal{A}$ is PPT.

- **Pseudo OTP is secure** — assuming G is a PRG, with respect to our definition.
- **Gain**: Pseudo OTP has a **short key** — n bits instead of $\ell(n)$ bits.

- **Pseudo OTP is secure** — assuming G is a PRG, with respect to our definition.
- **Gain**: Pseudo OTP has a **short key** — n bits instead of $\ell(n)$ bits.
- Does the Pseudo OTP allow encryption of *multiple* messages?
 - We will need to **define** it first!

Practice Question

Question

Let $G : \{0, 1\}^n \rightarrow \{0, 1\}^{2n}$ be a PRG. Is $H : \{0, 1\}^n \rightarrow \{0, 1\}^{2n}$, defined by $H(s) = (s \parallel 0^n) \oplus G(s)$, also a PRG — for *any* G ? Yes? No?

Practice Question

Question

Let $G : \{0, 1\}^n \rightarrow \{0, 1\}^{2n}$ be a PRG. Is $H : \{0, 1\}^n \rightarrow \{0, 1\}^{2n}$, defined by $H(s) = (s \parallel 0^n) \oplus G(s)$, also a PRG — for *any* G ? Yes? No?

Answer: No! — a counterexample

Let $F : \{0, 1\}^{n/2} \rightarrow \{0, 1\}^{3n/2}$ be a PRG and define, with $s_0, s_1 \in \{0, 1\}^{n/2}$,

$$G(s = (s_0, s_1)) = s_0 \parallel F(s_1).$$

- **Step 1:** prove G is a PRG.
- **Step 2:** prove H is *not* a PRG (for this G).

Step 1: G is a PRG — Proof by Reduction

Reduction / Adversary $\mathcal{B}$ (against F)


Adversary $\mathcal{A}$ (against G)

Given / To prove

Given: $\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B},F}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Step 1: G is a PRG — Proof by Reduction




Given / To prove

Given: $\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B},F}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Step 1: G is a PRG — Proof by Reduction




Given / To prove

Given: $\Pr[\text{PRG}_{\mathcal{A},G}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B},F}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Step 1: G is a PRG — Proof by Reduction




Given / To prove

Given: $\Pr[\text{PRG}_{\mathcal{A}, G}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, F}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Step 1: G is a PRG — Proof by Reduction




Given / To prove

Given: $\Pr[\text{PRG}_{\mathcal{A}, G}(n) = 1] \geq \frac{1}{2} + \epsilon(n)$.

To prove: $\Pr[\text{PRG}_{\mathcal{B}, F}(n) = 1] \geq \frac{1}{2} + \delta(n)$.

Step 1: The Reduction $\mathcal{B}$



Reduction $\mathcal{B}$

- 1 Receive y .
- 2 Sample $s_0 \leftarrow U_{n/2}$; set $x = s_0 \parallel y \in \{0, 1\}^{2n}$.
- 3 Run $\mathcal{A}$ on x ; receive b' .
- 4 Output b' .

Step 1: Two Cases

Case $y \leftarrow U_{3n/2}$ (uniform)

Then $x = s_0 \parallel y$ is uniform in $\{0, 1\}^{2n}$ — exactly the $b = 1$ case of $\text{PRG}_{\mathcal{A}, G}$.

Case $y \leftarrow F(U_{n/2})$ (pseudorandom)

Then $x = s_0 \parallel F(s_1) = G(s_0 \parallel s_1)$ for a uniform seed — exactly the $b = 0$ case of $\text{PRG}_{\mathcal{A}, G}$.

Step 1: Two Cases

Case $y \leftarrow U_{3n/2}$ (uniform)

Then $x = s_0 \parallel y$ is uniform in $\{0, 1\}^{2n}$ — exactly the $b = 1$ case of $\text{PRG}_{\mathcal{A}, G}$.

Case $y \leftarrow F(U_{n/2})$ (pseudorandom)

Then $x = s_0 \parallel F(s_1) = G(s_0 \parallel s_1)$ for a uniform seed — exactly the $b = 0$ case of $\text{PRG}_{\mathcal{A}, G}$.

Putting it together

In both cases $\mathcal{A}$'s view is exactly $\text{PRG}_{\mathcal{A}, G}(n)$ with the *same* challenge bit b , and $\mathcal{B}$ outputs $\mathcal{A}$'s guess. So

$$\Pr[\text{PRG}_{\mathcal{B}, F}(n) = 1] = \Pr[\text{PRG}_{\mathcal{A}, G}(n) = 1] \geq \frac{1}{2} + \epsilon(n),$$

contradicting that F is a PRG. Thus G is a PRG. □

Step 1: Two Cases

Case $y \leftarrow U_{3n/2}$ (uniform)

Then $x = s_0 \parallel y$ is uniform in $\{0, 1\}^{2n}$ — exactly the $b = 1$ case of $\text{PRG}_{\mathcal{A}, G}$.

Case $y \leftarrow F(U_{n/2})$ (pseudorandom)

Then $x = s_0 \parallel F(s_1) = G(s_0 \parallel s_1)$ for a uniform seed — exactly the $b = 0$ case of $\text{PRG}_{\mathcal{A}, G}$.

Putting it together

In both cases $\mathcal{A}$'s view is exactly $\text{PRG}_{\mathcal{A}, G}(n)$ with the *same* challenge bit b , and $\mathcal{B}$ outputs $\mathcal{A}$'s guess. So

$$\Pr[\text{PRG}_{\mathcal{B}, F}(n) = 1] = \Pr[\text{PRG}_{\mathcal{A}, G}(n) = 1] \geq \frac{1}{2} + \epsilon(n),$$

contradicting that F is a PRG. Thus G is a PRG. □

Remark (running time)

$\mathcal{B}$ samples $n/2$ bits, concatenates, and runs $\mathcal{A}$ once — so $\mathcal{B}$ is PPT given $\mathcal{A}$ is PPT.

Step 2: H is not a PRG

Computation

For this G we have $G(s) = s_0 \parallel F(s_1)$, so (writing $s = (s_0, s_1)$)

$$\begin{aligned} H(s) &= (s \parallel 0^n) \oplus G(s) = ((s_0 \parallel s_1) \parallel 0^n) \oplus (s_0 \parallel F(s_1)) \\ &= 0^{n/2} \parallel ((s_1 \parallel 0^n) \oplus F(s_1)). \end{aligned}$$

- The first $n/2$ output bits of H are always $0^{n/2}$.
- A distinguisher that outputs 1 iff the first $n/2$ bits are zero succeeds with overwhelming advantage.
- Hence H is **not** a PRG.



Summary

- **Computational security:** relax perfect secrecy to PPT adversaries with negligible advantage ($\text{PrivK}_{\mathcal{A}, \Pi}^{\text{eav}}$).
- **Pseudorandomness** is a property of a *distribution*: indistinguishable from uniform by all PPT distinguishers.
- **PRG** $G : \{0, 1\}^n \rightarrow \{0, 1\}^{\ell(n)}$ stretches a short secret seed into a longer pseudorandom string.
- **Pseudo OTP** $\text{Enc}_k(m) = G(k) \oplus m$ has indistinguishable encryptions if G is a PRG — proved by **reduction**.
- **Gain:** a short (n -bit) key encrypts an $\ell(n)$ -bit message.
- PRGs do not compose naively: $H(s) = (s \parallel 0^n) \oplus G(s)$ need not be a PRG.