

ExpNo:8

NESTED QUERIES , JOIN QUERIES AND SET OPERATORS

AIM: To perform nested Queries , joining Queries and set operations using DML command

QUERIES

1. Display all employee names and salary whose salary is greater than minimum salary of the company

```
select Fname,Lname,Salary
from EMPLOYEE
where Salary>(select min(Salary) from EMPLOYEE);
```

2. Issue a query to display information about employees who earn more than any employee in dept no 5

```
select * from EMPLOYEE
where Salary>(select min(Salary) from EMPLOYEE where Dno=5);
```

3. Display the details of those who draw the salary greater than the average salary.

```
select distinct *
from EMPLOYEE
where Salary >= (select avg(Salary) from EMPLOYEE);
```

4. Write SQL Query which retrieves the name and address of every employee who works for the Research Department

```
select Fname, Lname, Address
from EMPLOYEE, DEPARTMENT
where Dno = Dnumber and Dname = 'Research';
```

5. Retrieve the name of each employee who has a dependent with the same first name and is the same sex as the employee.

```
Select E.Fname, E.Lname
From EMPLOYEE as E
where E.Ssn in ( Select Essn From DEPENDENT as D where
E.Fname=D.Dependent_Name and E.Sex=D.Sex );
```

6. Make a list of all project numbers for projects that involve an employee whose last name is 'Smith', either as a worker or as a manager of the department that controls the project.

```
select Pno from WORKS_ON, EMPLOYEE
where Essn = Ssn and Lname = 'Smith'
UNION
select Pnumber from PROJECT P, DEPARTMENT D, EMPLOYEE E where
P.Dnum = D.Dnumber and D.Mgr_ssn = E.Ssn and E.Lname = 'Smith';
```

7. Write a query to display the name for all employees who work in a department with any employee whose Fname contains the letter 'h'

Select Fname from EMPLOYEE where Dno IN (Select Dno from EMPLOYEE where Fname LIKE '%h%');

8 Retrieve all employees whose address Starts with Houston.

*select Fname, Lname, Address
from EMPLOYEE
where Address LIKE 'Houston%';*

9. Retrieve all employees whose address is Ends with Houston..

*select Fname, Lname, Address
from EMPLOYEE
where Address LIKE '%Houston';*

10. Find all employees who were born during the 1960s.

*select Fname, Lname
from EMPLOYEE
where Bdate LIKE '___6_____';*

11. Retrieve all employees in department 5 whose salary is between \$30,000 and \$40,000.

This is the use of in between

*SELECT * FROM EMPLOYEE
WHERE (Salary BETWEEN 30000 AND 40000) AND Dno = 5;*

this is equivalent to <= and > =

*SELECT * FROM EMPLOYEE
WHERE (Salary >= 30000 AND Salary <= 40000) AND Dno = 5;*

12. Write a SQL query to find those employees who work in the same department where 'Ramesh' works.

Exclude all those records where first name is 'Ramesh'. Return first name, last name.

select Fname, Lname, Dno from EMPLOYEE where dno = (select dno from EMPLOYEE where Fname = 'Ramesh') and Fname <> 'Ramesh';

13 Display all the dept numbers available in Emp and not in dept tables

Minus is no more supported in mysql

*select Dno
from EMPLOYEE left join DEPARTMENT on Dno = Dnumber
where Dnumber is NULL;*

14. Display all the dept numbers available in dept and not in Emp tables

*select Dnumber
from EMPLOYEE right join DEPARTMENT on Dno = Dnumber
where Dno is NULL;*

15. For every project located in 'Stafford', list the project number, the controlling department number, and the department manager's last name, address, and birth date.

```
select Pnumber, Dnum, Lname, Address, Bdate
from PROJECT, DEPARTMENT, EMPLOYEE
where Dnum=Dnumber and Mgr_ssn=Ssn and Plocation='Stafford';
```

16. For each employee, retrieve the employee's first and last name and the first and last name of his or her immediate supervisor.

only employees who have a supervisor are included in the result

this is SELF JOIN

```
select E.Fname, E.Lname, S.Fname, S.Lname
from EMPLOYEE AS E, EMPLOYEE AS S
where E.Super_ssn = S.Ssn;
```

17. For each employee, retrieve the employee's first and last name and the first and last name of his or her immediate supervisor, including those who have no immediate supervisors

```
select E.Fname, E.Lname, S.Fname, S.Lname
from EMPLOYEE AS E left join EMPLOYEE AS S on E.Super_ssn = S.Ssn;
```

18. List the details of employees having no immediate supervisor.

```
select *
from EMPLOYEE
where Super_ssn IS NULL;
```

19. Show the resulting salaries if every employee working on the 'ProductX' project is given a 10 percent raise.

#This is use of arithmetic expression in select clause

```
select E.Fname, E.Lname, 1.1 * E.Salary AS Increased_sal
from EMPLOYEE AS E, WORKS_ON AS W, PROJECT AS P
where E.Ssn=W.Essn AND W.Pno=P.Pnumber AND P.Pname='ProductX';
```

20. List the first name and last name of all employees who work in the same department as the manager with last name 'Wong',

```
select E.Fname, E.Lname from EMPLOYEE E where E.Dno = ( select D.Dnumber
from DEPARTMENT D where D.Mgr_ssn = (select E2.Ssn from EMPLOYEE E2
where E2.Lname = 'Wong'));
```

RESULT

The query was executed and output was successfully obtained.