RAJALAKSHMI ENGINEERING COLLEGE

Sanjana E 251001228-2025-IT S2

| | |
|---|---|
| **Started on** | Tuesday, 25 August 2026, 11:21 AM |
| **State** | Finished |
| **Completed on** | Tuesday, 25 August 2026, 11:22 AM |
| **Time taken** | 45 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs( 1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

**For example:**

| Input | Result |
|---|---|
| 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 |

**Answer:** (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int ascending(const void *a, const void *b)
{
    return (*(int *)a - *(int *)b);
}

int descending(const void *a, const void *b)
{
    return (*(int *)b - *(int *)a);
}

int main()
{
    int n;
    scanf("%d", &n);

    int A[n], B[n];

    for (int i = 0; i < n; i++)
        scanf("%d", &A[i]);

    for (int i = 0; i < n; i++)
        scanf("%d", &B[i]);

    qsort(A, n, sizeof(int), ascending);
    qsort(B, n, sizeof(int), descending);

    long long sum = 0;

    for (int i = 0; i < n; i++)
    {
        sum += (long long)A[i] * B[i];
    }

    printf("%lld", sum);

    return 0;
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | 3<br>1<br>2<br>3<br>4<br>5<br>6 | 28 | 28 | ✔ |
| ✔ | 4<br>7<br>5<br>1<br>2<br>1<br>3<br>4<br>1 | 22 | 22 | ✔ |
| ✔ | 5<br>20<br>10<br>30<br>10<br>40<br>8<br>9<br>4<br>3<br>10 | 590 | 590 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course