

## Skill – Week7

### Session 13:

1. To Parse Input Redirection, Open Files, Redirect stdin, Handle Missing Files, Restore Streams, Test File Inputs

```
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <unistd.h>
#include <fcntl.h>
#include <sys/wait.h>

#define MAX_INPUT 200
#define MAX_ARGS 20

int main() {
    char input[MAX_INPUT];
    char *args[MAX_ARGS];
    int fd;
    int saved_stdin;
    int count = 0;
    printf("Enter command with input redirection:\n");
    printf("Example: cat < sample.txt\n");
    fgets(input, MAX_INPUT, stdin);
    input[strcspn(input, "\n")] = '\0';
    /* Save original stdin */
    saved_stdin = dup(STDIN_FILENO);
    if (saved_stdin == -1) {
        perror("dup");
        return 1;
    }
    /* Parse command arguments */
    char *token = strtok(input, " ");
    while (token != NULL && count < MAX_ARGS - 1) {
        if (strcmp(token, "<") == 0) {
            /* Get input filename */
            token = strtok(NULL, " ");
            if (token == NULL) {
                printf("Error: Missing input filename\n");
                close(saved_stdin);
                return 1;
            }
        }
    }
}
```

```
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Hello from OSSP" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Input redirection test" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Linux system programming" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ ls sample.txt
sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Hello from OSSP
Input redirection test
Linux system programming
sanjay_dundra@Sanjay:~/OS_Lab$ nano input_redirect.c
sanjay_dundra@Sanjay:~/OS_Lab$ gcc input_redirect.c -o input_redirect
sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
cat < sample.txt
Input file opened successfully

Standard input restored successfully

sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -l < sample.txt
Input file opened successfully
3

Standard input restored successfully

sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -w < sample.txt
Input file opened successfully
9

Standard input restored successfully
```

```
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Hello from OSSP" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Input redirection test" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Linux system programming" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ ls sample.txt
sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Hello from OSSP
Input redirection test
Linux system programming

sanjay_dundra@Sanjay:~/OS_Lab$ nano input_redirect.c
sanjay_dundra@Sanjay:~/OS_Lab$ gcc input_redirect.c -o input_redirect
sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
cat < sample.txt
Input file opened successfully
Hello from OSSP
Input redirection test
Linux system programming

Standard input restored successfully

sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -l < sample.txt
Input file opened successfully
3

Standard input restored successfully

sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
wc -w < sample.txt
Input file opened successfully
9
```

```
sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
sort < sample.txt
Input file opened successfully
Hello from OSSP
Input redirection test
Linux system programming

sanjay_dundra@Sanjay:~/OS_Lab$ ./input_redirect
Enter command with input redirection:
Example: cat < sample.txt
grep Hello < sample.txt
Input file opened successfully
Hello from OSSP

Standard input restored successfully
```

**Report:** The program successfully parses input redirection, opens sample.txt, redirects standard input, executes the command, and restores the original standard input. File input is tested using cat, wc, sort, and grep.

2. To Parse Output Redirection, Create Output Files, Redirect stdout, Handle Permissions, Verify Output Data, Test Redirection

```
sanjay_dundra@Sanjay:~/OS_Lab$ nano output_redirect.c
sanjay_dundra@Sanjay:~/OS_Lab$ gcc output_redirect.c -o output_redirect
sanjay_dundra@Sanjay:~/OS_Lab$ ./output_redirect
```

Enter command with output redirection:

Example: ls > output.txt

```
ls > output.txt
```

Output file opened successfully

```
sanjay_dundra@Sanjay:~/OS_Lab$ ls
buildin.c          fork_example.c      pipeline
command_history    fork_example.c.save pipeline.c
command_history.c  grep                sample.txt
export_env         input_redirect      shell_dispatch
export_env.c       input_redirect.c    shell_dispatch.c
fifo_client        multi_pipe           signal_handler
fifo_client.c      multi_pipe.c         signal_handler.c
fifo_client_auto   output.txt           state_management
fifo_client_auto.c output_redirect       state_management.c
fifo_server        output_redirect.c    wc
fifo_server.c      pipe_demo
fork_example       pipe_demo.c
```

```

sanjay_dundra@Sanjay:~/OS_Lab$ cat output.txt
builtin.c
command_history
command_history.c
export_env
export_env.c
fifo_client
fifo_client.c
fifo_client_auto
fifo_client_auto.c
fifo_server
fifo_server.c
fork_example
fork_example.c.save
grep
input_redirect
input_redirect.c
multi_pipe
multi_pipe.c
output.txt
output_redirect
output_redirect.c
pipe_demo
pipe_demo.c
pipeline
pipeline.c
sample.txt
shell_dispatch
shell_dispatch.c
signal_handler
signal_handler.c
state_management
state_management.c
wc

sanjay_dundra@Sanjay:~/OS_Lab$ wc -l output.txt
34 output.txt

sanjay_dundra@Sanjay:~/OS_Lab$ ls -l output.txt
-rw-rw-r-- 1 sanjay_dundra sanjay_dundra 18 03:29 output.txt

```

**Report:** The program parses output redirection using `>`, creates an output file using `open()`, redirects standard output using `dup2()`, handles file permission errors, restores the original output stream, and verifies the redirected data using `cat` and `wc`.

#### Session 14:

1. To Parse Append Operator, Open Files in Append Mode, Redirect Streams, Preserve Existing Data, Validate Appends, Test Scenarios

```

sanjay_dundra@Sanjay:~/OS_Lab$ echo "First line" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Second line" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
First line
Second line
sanjay_dundra@Sanjay:~/OS_Lab$ touch sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Hello Linux" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
First line
Second line
Hello linux
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Line 1" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Line 2" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Line 3" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Line 1
Line 2
Line 3
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Old Data" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Old Data
sanjay_dundra@Sanjay:~/OS_Lab$ echo "New Data" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Old Data
New Data
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Apple" > sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Banana" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Mango" >> sample.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat sample.txt
Apple
Banana
Mango
sanjay_dundra@Sanjay:~/OS_Lab$ wc -l sample.txt
3

```

**Report:** The append operator >> adds new data to the end of a file while preserving existing content. The commands and C program demonstrate file appending, output redirection, and validation.

2. To Parse stderr Redirection, Redirect Error Streams, Capture Error Output, Verify File Contents, Handle Failures, Test Error Cases

```

#include <stdio.h>
#include <fcntl.h>
#include <unistd.h>
#include <string.h>

int main() {
    int fd;

    fd = open("error.txt",
              O_WRONLY | O_CREAT | O_APPEND, 0644);

    if (fd == -1) {
        perror("Error opening file");
        return 1;
    }

    dup2(fd, STDERR_FILENO);

    close(fd);

    fprintf(stderr, "Error: File not found\n");
    fprintf(stderr, "Error: Invalid command\n");

    return 0;
}

```

```

sanjay_dundra@Sanjay:~/OS_Lab$ nano stderr_redirect.c
sanjay_dundra@Sanjay:~/OS_Lab$ gcc stderr_redirect.c -o stderr_redirect
sanjay_dundra@Sanjay:~/OS_Lab$ ./stderr_redirect
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
First error
ls: cannot access '/wrong1': No such file or directory
ls: cannot access '/wrong2': No such file or directory
Error: File not found
Error: Invalid command

```

```

sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
cat: /wrong_file: No such file or directory
sanjay_dundra@Sanjay:~/OS_Lab$ echo "Old error" > error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ ls /missing_folder 2>> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
Old error
ls: cannot access '/missing_folder': No such file or directory
sanjay_dundra@Sanjay:~/OS_Lab$ ls /invalid_path 2> error.txt
if [ $? -ne 0 ]; then
    echo "Command failed"
else
    echo "Command succeeded"
fi
Command failed

sanjay_dundra@Sanjay:~/OS_Lab$ ls /not_found 2> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
ls: cannot access '/not_found': No such file or directory
sanjay_dundra@Sanjay:~/OS_Lab$ cat missing.txt 2> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
cat: missing.txt: No such file or directory
sanjay_dundra@Sanjay:~/OS_Lab$ cat /root/secret.txt 2> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
cat: /root/secret.txt: Permission denied

sanjay_dundra@Sanjay:~/OS_Lab$ echo "First error" > error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ ls /wrong1 2>> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ ls /wrong2 2>> error.txt
sanjay_dundra@Sanjay:~/OS_Lab$ cat error.txt
First error
ls: cannot access '/wrong1': No such file or directory
ls: cannot access '/wrong2': No such file or directory

```

**Report:** stderr redirection is used to capture error messages into a file using 2> and 2>>. The commands and C program demonstrate error handling, preserving previous data, and verifying error output.