

Muttprint – User's guide

Bernhard Walle

Bernhard.Walle@gmx.de

Version 0.60

Table of Contents

The Debian packages are created by Chanop Silpa-Anan <chanop@debian.org> and are normally available a few days after a new release of Muttprint. They could be installed by

```
# dpkg -i muttprint_[version]-[release]_noarch.deb
```

Take a look at the Debian “Developer’s Corner” (<http://www.debian.org/devel/>) for more information about Debian packages.

Another possibility to install Debian packages is **apt-get**.

2.3. Integration of Muttprint in mail clients

Muttprint was orgie90(.12_tion)-28i118(gie))(w)16(at)(gieusat)(gieto0 T3 Td[(w)1witht)(gie0.12t)(gieonr)165.87gieHo(a)-20(.12_

Muttprint – User'

Style	Description
border	rule after the headers (<i>default setting</i>)
fbox	simple box around the mailheaders
shadowbox	shadowbox around the header
ovalbox	box with rounded corners around around 22 8.966 Tf -107.596 -14 ovalbox

3.2. Command line options

4. Notes

4.1. Author, License

The script has been written by Bernhard Walle <Bernhard.Walle@gmx.de>.

This program is free software; you can redistribute it and/or modify it under the terms of the GNU General Public