Compositional Reasoning Depth Predicts Clinical AI Failure: Empirical Evidence Consistent with the Peng Impossibility Theorem in Electronic Health Record Question Answering

Anonymous Authors

Abstract

Aggregate accuracy benchmarks conceal a systematic structure in clinical AI failure: questions requiring more inferential steps produce disproportionately more errors. Motivated by the Peng impossibility theorem for transformer attention composition, we introduce a pre-registered *hop-count taxonomy*—the number of distinct reasoning steps required to answer a clinical question from an electronic health record (EHR)—as a principled predictor of model failure. We annotate 313 clinician-generated EHR question-answer pairs from MedAlign across four hop levels and evaluate 301 questions in a within-model ablation (`claude-sonnet-4-6`, zero-shot versus extended thinking) and a cross-architecture replication (`gpt-4o`, zero-shot). Both models exhibit monotone accuracy decline with hop count: Claude Sonnet zero-shot declines from 30.6% (hop=1) to 17.3% (hop=4) (Cochran–Armitage $z = -2.38$, $p = 0.009$; OR per hop $= 0.72$, 95% CI [0.56, 0.92], $p = 0.008$); GPT-4o independently replicates this pattern (37.8% to 14.7%; CA $z = -3.80$, $p < 0.0001$; OR $= 0.58$ [0.45, 0.75], $p < 0.001$). A pre-specified context sufficiency audit confirmed that higher-hop questions are not differentially disadvantaged by EHR truncation (answerability 93–95% at hops 2–4 vs. 79% at hop=1), establishing that the degradation reflects compositional reasoning difficulty. Extended thinking did not significantly flatten the accuracy-versus-depth curve across three reasoning conditions (internal extended thinking, structured four-step CoT, and 5$\times$ larger thinking budget), and thinking-token usage scaled with hop count ($r = 0.31$, $p < 0.0001$), consistent with the predicted $O(k)$ computational requirement. These findings establish hop count as a theoretically grounded, cross-architecture predictor of clinical AI failure with immediate implications for deployment risk stratification.

1 Introduction

Artificial intelligence systems based on transformer architectures are now embedded in clinical workflows ranging from automated chart summarization to real-time diagnostic support [Singhal et al., 2023, McDuff et al., 2025]. Despite rapidly improving benchmark performance on standardized medical examinations [Jin et al., 2021, Hendrycks et al., 2021], these systems exhibit inconsistent and sometimes dangerous failures when applied to real-world electronic health record (EHR) tasks [Wu et al., 2025]. A persistent challenge is that aggregate accuracy metrics conceal the structure of failure: researchers and clinicians typically observe *that* a model fails without understanding *why* or *when* it will fail.

Preprint. Under review.

We propose that compositional reasoning depth—the number of distinct inferential hops required to produce a correct answer—is a principled predictor of clinical AI failure, grounded in a formal theoretical result. Peng et al. [2024] prove an impossibility theorem for transformer self-attention: a single attention layer with H heads, head dimension d, and numerical precision p cannot solve the (n, k)-function-composition problem when $n \log n > H \cdot d \cdot p$. Informally, once the context length n exceeds a threshold determined by the model's architectural parameters, the attention mechanism lacks sufficient representational capacity to chain multiple inferential steps within a single forward pass. Three theoretical escape routes exist: multi-step chain-of-thought reasoning (which effectively adds layers), retrieval-augmented generation, and non-standard architectural choices such as state-space models or mixture-of-expert routing [Zhou et al., 2023, Yehudai et al., 2025]. While the theorem formally characterizes single-layer attention, practical transformers stack many such layers; we therefore treat it as a theoretical framework motivating *qualitative* predictions about compositional difficulty rather than applying it quantitatively to the multi-layer setting. The critical empirical question is whether accuracy degrades with hop count and whether test-time reasoning provides relief, predictions that hold regardless of whether the single-layer impossibility is the proximate mechanism.

Clinical EHR question answering is a natural testing ground for this theorem: retrieving a single fact (hop=1), computing a temporal overlap (hop=3), or synthesizing heterogeneous entries across domains (hop=4) constitute structurally distinct tasks predicted to exhibit qualitatively different error rates, with test-time reasoning predicted to selectively benefit higher-hop tasks.

This paper makes six contributions: (1) a pre-registered hop-count taxonomy for clinical EHR QA annotating 313 MedAlign questions across four hop levels; (2) first cross-architecture empirical evidence of hop-count-predicted failure in EHR QA (`claude-sonnet-4-6` and `gpt-4o`); (3) a context sufficiency audit ruling out EHR truncation as a confound; (4) mechanistic evidence of $O(k)$ computation scaling ($r = 0.31$, $p < 0.0001$); (5) characterization of error structure by hop level showing that structured decomposition converts hallucination to omission; and (6) question-type sensitivity analysis and truncation robustness ablation confirming the hop–accuracy relationship is not confounded (adjusted OR = 0.57, $p = 0.005$).

2 Background and Related Work

The Peng impossibility theorem. Peng et al. [2024] establish that for any single-layer transformer attention mechanism, the (n, k)-function-composition problem—which asks whether the model can compose k arbitrary functions over a context of length n—is unsolvable when $n \log n > H \cdot d \cdot p$. This is not an empirical observation but a formal impossibility result derived from communication complexity theory. The theorem applies to the softmax self-attention operation as standardized in modern transformers and does not depend on training procedure, model scale, or the specific clinical domain. Critically, the theorem identifies test-time chain-of-thought reasoning as a theoretically sound mitigation: by decomposing a k-hop problem into k sequential single-hop steps, each within the computability threshold, CoT reasoning should flatten the accuracy degradation curve. Yehudai et al. [2025] provide complementary analysis showing that recurrent architectures and chain-of-thought can solve compositional tasks that standard transformers cannot, independently corroborating the Peng escape route. Zhou et al. [2023] demonstrate architectural alternatives (non-uniform block structures) that can route around the attention bottleneck, though at engineering complexity cost.

Multi-hop reasoning benchmarks. The NLP community has extensively studied multi-hop reasoning in open-domain QA settings. HotpotQA [Yang et al., 2018] provides 113K questions requiring evidence synthesis from two Wikipedia paragraphs; MuSiQue [Trivedi et al., 2022] constructs up to 4-hop questions by composing single-hop questions with explicit bridge entities; 2WikiMultihopQA [Ho et al., 2020] adds cross-document coreference. Across these benchmarks, accuracy declines consistently with the number of required hops, attributed to error propagation and attention capacity limitations. However, no prior study has (a) grounded the hop–accuracy relationship in a formal theorem, (b) tested the theoretical CoT mitigation as a function of hop depth rather than on average, or (c) applied hop-count analysis to clinical EHR data.

Clinical AI benchmarks and EHR reasoning. MedQA [Jin et al., 2021] and MMLU Medical [Hendrycks et al., 2021] evaluate LLMs on medical licensing examinations—closed-book multiple-choice requiring medical knowledge but not EHR navigation. Med-PaLM [Singhal et al.,

2023] achieved expert-level performance on such benchmarks but was not evaluated on compositional EHR reasoning. emrQA [Pampari et al., 2018] provides a large EHR QA benchmark but questions are primarily single-hop slot-filling with no compositional depth taxonomy. Clinical TempEval [Bethard et al., 2016] establishes temporal relation extraction as a distinct challenging subtask in clinical NLP, consistent with the temporal arithmetic component of our hop=3 category. FDARxBench [Xiong et al., 2026] shows retrieval and long-context grounding remain bottlenecks in document-grounded biomedical QA—consistent with our finding that the hop–accuracy relationship is not resolved by more context. MedAlign [Fleming et al., 2024] provides clinician-generated, open-ended questions paired with EHR XML records and clinician reference answers, making it the most ecologically valid benchmark for testing compositional EHR reasoning. No prior study has stratified MedAlign performance by compositional depth.

Chain-of-thought and reasoning models. Wei et al. [2022] demonstrated that chain-of-thought prompting elicits multi-step reasoning in large models; Kojima et al. [2022] showed a zero-shot CoT trigger is sufficient. Nye et al. [2021] provided theoretical grounding through scratchpads as intermediate computation. Reasoning-specialized models—including OpenAI o1 [OpenAI, 2024] and DeepSeek R1 [DeepSeek-AI, 2025]—extend these ideas through reinforcement learning over extended thinking traces. Merrill and Sabharwal [2024] prove that transformers with polynomially many CoT tokens can solve problems inaccessible to direct inference, with required token count scaling with reasoning depth—a formal analog of the $O(k)$ computation scaling our P3 test examines empirically. No study has measured CoT benefit as a function of hop depth in clinical settings.

Safety and variance in clinical AI. Wu et al. [2025] document query-type-dependent hallucination rates in clinical LLMs without compositional depth stratification. Prior work on automation bias [Goddard et al., 2012, Lyell and Coiera, 2017] has not examined hop-count moderation. The error type structure—hallucination versus omission versus reasoning error—as a function of compositional depth has not been characterized.

3 Problem Formulation

The Peng theorem and clinical QA. Let $\mathcal{E}$ denote the EHR context of length n tokens, and let $\mathcal{Q}$ denote a clinical question requiring composition of k functions $f_1, \ldots, f_k$ over $\mathcal{E}$, where each f_i retrieves or transforms a specific subset of the EHR. The (n, k)-function-composition problem asks a model to produce a correct answer by sequentially applying these functions. By the Peng theorem [Peng et al., 2024], a single attention layer with parameters (H, d, p) cannot solve this problem when $n \log n > H \cdot d \cdot p$. For contemporary large-context models serving long EHRs, n is on the order of 10^3–10^4 tokens, making the left-hand side $n \log n \approx 10^4$–10^5. Typical model architectural parameters place $H \cdot d \cdot p$ in a range that, while large, is finite and potentially crossed by sufficiently complex EHR reasoning tasks.

The theorem generates three testable predictions: (P1) *Monotone degradation*: Accuracy should decrease monotonically with k under standard (non-CoT) inference. (P2) *CoT flattening*: Chain-of-thought reasoning, by decomposing k-hop problems into k sequential 1-hop steps, should flatten the accuracy-versus-hop curve, with greater absolute benefit at higher k. (P3) *Computation scaling*: The amount of reasoning computation (proxied by thinking token count in extended-thinking models) should scale with k, consistent with the theoretical requirement for $O(k)$ sequential computations.

Scope of the theoretical mapping. The Peng theorem characterizes a *single* attention layer; modern transformers stack many such layers, which can in principle decompose reasoning through depth. We interpret P1–P3 as qualitative predictions motivated by the theorem rather than strict corollaries. The empirical claims stand independently: compositional depth predicts accuracy, thinking tokens scale with depth, and test-time reasoning does not flatten the degradation curve at current budgets.

Hop-count taxonomy. We define a pre-registered four-level hop taxonomy (Table 1): hop=1 (single-fact retrieval), hop=2 (two-fact composition or threshold comparison), hop=3 (three-step inference chain: cross-domain retrieval, temporal reasoning, or guideline application), and hop=4 (multi-component synthesis or generation across $\geq$4 EHR sources or time spans).

Table 1: Pre-registered hop-count taxonomy for clinical EHR question answering, with operational definitions and representative examples from MedAlign.

Hop	Operational Definition	Representative Example
1	Direct retrieval of a single named fact from the EHR.	"What is the patient's current allergy list?"
2	Two-fact composition, threshold application, or binary temporal comparison.	"Did the patient have an elevated WBC on admission?"
3	Three-step reasoning chain; requires cross-domain lookup, temporal arithmetic, or contextual clinical guideline application.	"Is this patient eligible for supplemental breast cancer screening based on current guidelines?"
4	Multi-component synthesis or generation requiring integration of $\geq$4 EHR sources or time spans.	"Summarize all specialist consultations and flag unresolved recommendations."

4 Methods

Dataset: MedAlign. MedAlign [Fleming et al., 2024] consists of 983 clinician-generated instructions paired with EHR XML files from the Stanford STARR-OMOP database and clinician reference answers. We use the publicly released subset of 402 unique question-answer pairs for which clinician-reviewed model responses and source EHR files are available. After restricting to questions with a uniquely identifiable EHR file and valid clinician reference response, 313 questions were annotated and eligible; of these, 301 had complete model evaluations (API errors or timeouts accounted for 12 omissions), yielding the final analytic sample (hop=1: $n = 111$, hop=2: $n = 46$, hop=3: $n = 42$, hop=4: $n = 104$; 602 total evaluations across both conditions). EHR records were parsed from XML, chronologically structured, and truncated to 8,000 characters (approximately 1,600–2,000 tokens at 4–5 characters per token, well within the model's 200K-token context window) while retaining the full character count as a completeness covariate.

Context sufficiency analysis. To test whether EHR truncation differentially disadvantaged higher-hop questions, we computed evidential coverage for each question; full methodology and thresholds are in Appendix F.

Hop annotation. All 313 questions were annotated with hop count prior to any model evaluation (pre-registration; annotation log and timestamp available in supplementary materials). Each question was presented to an LLM annotator together with a structured rubric defining each hop level, with explicit examples and a chain-of-thought elicitation prompt. To assess annotation reliability, a second independent annotation pass was run on a stratified random sample of 50 questions (12–13 per hop level) using the same model and prompt (within-model reproducibility), and a cross-model validation was performed using `gpt-4o`. Within-model reproducibility was substantial ($\kappa = 0.787$, 95% CI [0.603, 0.970]; 84% exact agreement, 98% agreement within $\pm$1 hop). Cross-model agreement was moderate ($\kappa = 0.464$, 95% CI [0.292, 0.637]; 60% exact), reflecting divergent rubric calibration between model families. All annotations were finalized and locked before any model inference was run, precluding post-hoc adjustment.

Experimental design. We evaluate two conditions using `claude-sonnet-4-6`, a publicly available large language model with extended-thinking capability:

- **Condition A (Zero-Shot):** The model receives a patient EHR and question with the prompt "Answer concisely" and no explicit reasoning instructions. This is the dense baseline.
- **Condition B (Extended Thinking):** The same model receives the same prompt with extended thinking enabled (`thinking={"type":"enabled","budget_tokens":3000}`), allowing an internal chain-of-thought scratchpad before producing the visible response.

This within-model ablation design isolates the effect of test-time reasoning from confounds such as model capacity, training data, or architectural differences. Both conditions use identical weights, identical prompts, and identical context. The sole manipulation is whether reasoning is enabled. We pre-registered this design and judge prompt (see Section 4) before observing any experimental results.

Automated judge. Responses were evaluated by a pre-registered automated judge using `gpt-4o-mini` with the following system prompt: *"You are a clinical QA evaluator. Score model responses against clinician reference answers. Return ONLY valid JSON: {'correct': true or false, 'error_type': 'none' | 'omission' | 'hallucination' | 'reasoning_error', 'confidence': 0.0–1.0}. Correct means the model response substantially agrees with the clinician reference. Omission means the model failed to answer, refused, or gave an empty or irrelevant response. Hallucination means the model stated facts not present in the EHR or contradicting established medical knowledge. Reasoning_error means the model had the right facts but reached the wrong conclusion."* This binary scoring schema was adopted after an initial pilot with a 4-category schema revealed systematic under-scoring (models rated "partial" rather than "correct" were all coded as incorrect), collapsing true accuracy. Physician adjudication of 100 evaluations (16% sample) stratified by hop level and judge confidence was used to validate judge calibration. The sample size was determined by power analysis: to achieve a 95% confidence interval for Cohen's κ that excludes the "acceptable" threshold of 0.60 when true agreement is $\kappa = 0.80$, a minimum of 100 cases is required (estimated CI width $\approx \pm 0.13$ at $n = 100$ [Donner and Eliasziw, 1992]). Stratification allocates 25 cases per hop level, with oversampling of cases where judge confidence < 0.70 (the borderline stratum) within each hop stratum; both experimental conditions are represented. Physician adjudication was completed by two board-certified clinicians (P1, lenient criterion; P2, strict criterion) and validated the AI judge against the strict standard: $\kappa(\text{AI}, \text{P2}) = 0.957$ (95% CI [0.874, 1.000]), exceeding the pre-registered threshold of $\kappa \geq 0.70$ (see Appendix C).

Statistical analysis. The pre-registered primary analysis specified a generalized linear mixed model (GLMM) with logistic link and random intercepts per question. In implementation, MAP-based estimation via `BinomialBayesMixedGLM` (statsmodels) showed optimization instability across runs with 301 random-effect parameters each observed only twice—a known limitation of high-dimensional MAP inference with sparse data per group. As a pre-specified fallback, we report a generalized estimating equation (GEE) logistic regression with independence working correlation, which accounts for the within-question paired design through clustered robust standard errors and yields stable, consistent estimates. The model specification is $\text{logit}(P(\text{correct})) = \beta_0 + \beta_1 \cdot \text{hop} + \beta_2 \cdot \text{condition} + \beta_3 \cdot (\text{hop} \times \text{condition}) + \beta_4 \cdot \text{EHR_chars} + \beta_5 \cdot \text{q_tokens}$. The primary test of P1+P2 is the β_3 interaction term. We additionally report a Cochran–Armitage trend test for monotone accuracy decline across hop levels (one-tailed, $\alpha = 0.05$) and per-hop pairwise Fisher's exact tests with Bonferroni correction. For prediction P3, the pre-registered statistic is the individual-level Pearson correlation between hop count and thinking tokens in the extended-thinking condition. All analyses were finalized prior to model evaluation.

Question-type sensitivity analysis. To address question-type confounding, we extended the GEE model with reasoning-type dummies (factual/comparative/generative/computational; factual as reference) and ran a within-category Cochran–Armitage test for the comparative reasoning type (hops 2–4, $n = 16, 30, 20$; Appendix D).

Thinking-token computation. Extended-thinking token counts were obtained from the provider's API response as the sum of the `thinking` block lengths in each response, approximated as (word count) $\times 1.3$ to convert from approximate words to tokens. Raw thinking blocks are not retainable under the provider's terms of service; we release the token-count column in the public data release to enable cross-backend normalization by future investigators.

Truncation robustness ablation. To test whether P1 persists with larger EHR context, we run an additional zero-shot condition (*ZS-32K*) with an 8,000-character truncation limit replaced by 32,000 characters (a $4\times$ expansion), covering an estimated 6,400–8,000 tokens. All 301 questions are re-evaluated under this condition with identical prompting, judge, and scoring. Results are reported in Section 5 alongside the primary analyses.

Table 2: Error type distribution at hop=3 for zero-shot and CoT conditions in the pre-registered validation run ($n = 22$ questions per condition). CoT reduces hallucination but increases omission, consistent with the model learning to recognize its own uncertainty.

Condition	Correct	Hallucination	Omission	Reasoning Error	Accuracy
Zero-shot	5	13	3	1	22.7%
CoT	7	10	5	0	31.8%
Δ (CoT − ZS)	+2	−3	+2	−1	**+9.1 pp**

Table 3: Accuracy by condition and hop count ($n = 301$ questions). Cells show accuracy (%) with 95% Wilson confidence intervals. The GPT-4o replication used identical questions, EHR context, and judge. GEE per-hop OR quantifies accuracy degradation per additional reasoning hop in each condition.

	Hop Count					
Condition	**1** (n=111)	**2** (n=46)	**3** (n=42)	**4** (n=104)	**Overall**	**OR/hop**
Claude ZS	30.6 [22.8, 39.7]	28.3 [17.3, 42.5]	21.4 [11.7, 35.9]	17.3 [11.2, 25.7]	24.4 [19.9, 29.6]	0.72 [0.56, 0
Claude ET	34.2 [26.1, 43.5]	30.4 [19.1, 44.8]	19.0 [10.0, 33.3]	19.2 [12.8, 27.8]	26.4 [21.8, 31.6]	0.70 [0.55, 0
GPT-4o ZS*	37.8 [29.4, 47.1]	26.1 [15.6, 40.3]	23.8 [13.5, 38.5]	14.7 [9.1, 22.9]	26.2 [21.5, 31.5]	0.58 [0.45, 0
Δ GPT-4o − Claude ZS	+7.2 pp	−2.2 pp	+2.4 pp	−2.9 pp	+1.6 pp	—

Accuracy (%) with 95% Wilson CI in brackets. OR/hop from GEE logistic regression with independence working correlation (full interaction model; ET slope computed via delta method as $\hat{\beta}_{\text{hop}} + \hat{\beta}_{\text{interaction}}$).
*Independent replication on identical questions, EHR context, and judge.

5 Results

Preliminary validation (hop=3). A pre-registered validation run on 22 hop=3 questions found zero-shot accuracy 22.7% and CoT accuracy 31.8% (+9.1 pp; Table 2). CoT reduced hallucinations (13→10) but slightly increased omissions (3→5), consistent with the mechanism proposed by Nye et al. [2021]: explicit reasoning causes the model to recognize EHR insufficiency rather than confabulate. This hallucination-to-omission shift has favorable clinical safety implications.

Full experiment results. Across 602 evaluations, zero-shot accuracy declined monotonically from 30.6% (hop=1) to 17.3% (hop=4; Table 3, Figure 1). Extended thinking followed a similar slope (34.2%, 30.4%, 19.0%, 19.2%), with a marginal 2.0 pp overall advantage; at hop=3 extended thinking slightly underperformed zero-shot (19.0% vs. 21.4%).

Primary outcome: hop × condition interaction. Cochran–Armitage trend tests confirmed monotone accuracy decline for both conditions (ZS: $z = -2.38$, $p = 0.009$; ET: $z = -2.69$, $p = 0.004$). GEE logistic regression showed each additional hop associated with a 28% odds reduction under ZS (OR = 0.72, 95% CI [0.56, 0.92], $p = 0.008$) and 30% under ET (OR = 0.70 [0.55, 0.88], $p = 0.003$), confirming P1. The main effect of ET did not reach significance (OR = 1.18, 95% CI [0.85, 1.65], $p = 0.32$). The hop × condition interaction (P2 test) was not significant (OR = 0.97 [0.84, 1.13], $p = 0.72$), and EHR length covariates were non-significant ($p = 0.67$, $p = 0.24$).

Question-type sensitivity analysis. Adjusting for reasoning type strengthened the hop OR (0.72 unadjusted → 0.57, 95% CI [0.38, 0.84], $p = 0.005$), indicating question-type composition does not explain the hop effect. Within-comparative-type CA trend ($z = -1.90$, $p = 0.029$) confirmed P1 within a single reasoning category (hops 2–4, $n = 16$, 30, 20; Appendix D).

Computation scaling (P3). Mean thinking-token usage increased monotonically: 69.8 (hop=1), 83.0 (hop=2), 127.0 (hop=3), 135.1 (hop=4); individual-level Pearson $r = 0.31$ ($p < 0.0001$, $n = 301$, Figure 2), confirming P3. Mean usage (70–135 tokens) was far below the 3,000-token ceiling, ruling out budget exhaustion as an explanation for the P2 null result.



Figure 1: **(A)** Accuracy by compositional reasoning depth for three conditions, with 95% Wilson confidence intervals. Both Claude Sonnet zero-shot (blue circles) and GPT-4o zero-shot (green triangles) show monotone decline confirming cross-architecture generalizability of P1; extended thinking (orange squares) follows a similar slope. **(B)** Extended thinking minus zero-shot accuracy (percentage points) by hop count. Teal bars indicate positive CoT benefit; the coral bar at hop=3 indicates a small reversal. The near-zero differences across all hops are consistent with the null P2 result.

Error type profiles by hop. Figure 3 shows the error type distribution by condition and hop count. Omission errors dominate across all hops and increase sharply at hop=4: 52.3% (ZS) and 45.9% (ET) at hop=1, rising to 73.1% (ZS) and 72.1% (ET) at hop=4. Hallucination rates declined with hop count under zero-shot (12.6% at hop=1 to 5.9% at hop=4), with extended thinking producing consistently lower hallucination at hops 1–2. Reasoning errors peaked at hop=3 in both conditions (19.0%), consistent with the model having access to relevant facts but failing to compose them correctly; at hop=4 the model increasingly declines to answer (omission) rather than attempting synthesis.

Context sufficiency audit and truncation robustness. The pre-specified answerability analysis showed EHR truncation did not differentially disadvantage higher-hop questions: any-token answerability was 79.3% at hop=1 versus 93–95% at hops 2–4, with no monotone decline under the strict threshold ($H = 2.1$, Kruskal–Wallis $p = 0.55$), ruling out truncation as a confounder (Appendix F). The pre-specified ZS-32K ablation ($4\times$ context expansion, 32,000 characters) provides a behavioral test independent of any lexical metric: if truncation caused the accuracy decline, $4\times$ more context should attenuate P1, yet P1 strengthened (CA $z = -3.12$, $p < 0.001$; hop=1 31.5%, hop=2 19.6%, hop=3 14.3%, hop=4 14.4%), establishing that the degradation reflects compositional reasoning difficulty rather than context availability.

Additional reasoning conditions. Two further conditions confirmed the null P2 result. An explicit four-step structured CoT condition (*ExplicitCoT*, $n = 301$) showed no significant P2 flattening (OR $= 0.90$, 95% CI [0.71, 1.15], $p = 0.41$; overall accuracy 19.3%). An extended thinking condition



Figure 2: Mean thinking-token usage by hop count in the extended-thinking condition ($n = 301$). Error bars ± 1 SD. Pearson $r = 0.31$ ($p < 0.0001$) confirms proportionally more computation for higher-hop tasks; mean usage 70–135 tokens was far below the 3,000-token ceiling.



Figure 3: Error type distribution by condition and hop count ($n = 301$ questions per condition). **(A)** Zero-shot. **(B)** Extended thinking. Stack segments: green = correct, gray = omission, red/orange = hallucination, amber = reasoning error. Proportion labels shown for segments $> 5\%$. Omission errors dominate at hop=4 in both conditions; hallucination rates are modestly lower under extended thinking at hops 1–2.

with a $5\times$ larger budget (*ET-16K*, 16,000 tokens, $n = 179$ completions) also showed no P2 flattening (OR $= 1.03$, $p = 0.86$), and mean thinking-token usage scaled proportionally (83–190 tokens vs. 70–135 under the 3K budget). Importantly, ExplicitCoT shifted the error type profile: hallucination fell from 9.6% to 0.3% while omissions rose from 59.1% to 76.1%, consistent with explicit decomposition causing the model to recognise insufficient EHR evidence rather than confabulate. Full results and ET-16K selection bias analysis are in Appendix F.

Cross-architecture replication. To assess generalizability beyond a single model family, we ran a zero-shot replication on all 301 questions using `gpt-4o` (different provider, same EHR context, judge, and questions). GPT-4o accuracy declined monotonically from 37.8% [29.4, 47.1] at hop=1 to 14.7% [9.1, 22.9] at hop=4 (Table 3; CA $z = -3.80$, $p < 0.0001$; GEE OR per hop = 0.58 [0.45, 0.75],

$p < 0.001$), a steeper slope than Claude Sonnet (OR $= 0.72$). Error type profiles mirrored Claude's pattern: omissions escalated from 56.8% to 81.4% at hop=4. The hop–accuracy degradation is thus a cross-architecture property, not an artifact of a single model family; and the steeper GPT-4o slope against the same Claude-generated hop labels provides an implicit validity check on the taxonomy (a model-biased taxonomy would predict a *weaker* replication slope, not a stronger one).

6 Discussion

Empirical findings and theoretical alignment. Consistent with P1, zero-shot accuracy declines monotonically (OR = 0.72, $p = 0.008$), replicating cross-architecture (GPT-4o OR = 0.58, $p < 0.001$), and not attributable to EHR truncation or question-type composition (adjusted OR = 0.57, $p = 0.005$; ZS-32K CA $z = -3.12$, $p < 0.001$). These findings are consistent with—but not strictly derived from—the Peng single-layer impossibility, which we treat as motivating qualitative predictions in the multi-layer setting.

P3 is confirmed: thinking tokens scale with hop ($r = 0.31$, $p < 0.0001$) and mean usage (70–135 tokens) was far below the budget ceiling, indicating P2's null result reflects model behavior rather than budget exhaustion. P2 was not confirmed across three convergent conditions (ET-3K $p = 0.72$; ExplicitCoT $p = 0.41$; ET-16K $p = 0.86$). The ExplicitCoT hallucination-to-omission shift carries direct clinical safety implications: omission errors trigger escalation, whereas confabulated responses may not.

Clinical deployment implications. Current evaluation frameworks report aggregate accuracy without stratifying by compositional depth. A system achieving 80% overall on a hop=1-dominated benchmark may perform substantially worse on hop=3–4 queries that constitute the highest-stakes clinical decisions. Hop-count stratification provides a principled complement to existing safety frameworks [Wu et al., 2025], identifying tasks where reasoning-augmented inference is required and aggregate accuracy is an insufficient safety proxy.

Limitations. Several limitations qualify the present findings. First, the primary test of P2 was underpowered at hops 2–3 ($n = 46$ and $n = 42$); the interaction effect size (OR $\approx$ 0.90–1.03) is imprecisely estimated, and we cannot exclude small flattening effects. Convergent evidence across three conditions (ET-3K: $p = 0.72$; ExplicitCoT: $p = 0.41$; ET-16K: $p = 0.86$) mitigates but does not eliminate this concern. Second, the automated judge aligns with the strict physician reviewer ($\kappa = 0.957$) but shows moderate agreement with the lenient reviewer ($\kappa = 0.572$), indicating residual criterion sensitivity. Third, MedAlign represents a single institutional EHR environment (Stanford STARR-OMOP) and may not generalize to other EHR systems, clinical specialties, or international settings. Fourth, the theoretical framing derives predictions from the Peng single-layer impossibility result; multi-layer transformers can in principle decompose reasoning through depth, and we treat the theorem as motivating qualitative predictions rather than quantitative characterization. Additional limitations (hop annotation reliability, P2 untested in GPT-4o, MAP-based GLMM instability, answerability metric scope) are discussed in the supplementary materials.

Future directions. Three extensions follow directly from these findings. First, testing P2 in retrieval-augmented generation (RAG) systems would evaluate the Peng theoretical escape route most directly: explicit retrieval augmentation is predicted to flatten the accuracy–depth curve more effectively than internal CoT. Second, applying hop-count analysis to reasoning-specialized models (o1-class, DeepSeek R1) would determine whether reinforcement learning over extended thinking traces provides flattening that standard CoT does not. Third, integrating hop-count stratification into clinical AI evaluation frameworks as a standard safety dimension—complementing aggregate accuracy with task-complexity-stratified profiles—would operationalize the study's primary practical contribution.

7 Conclusion

Aggregate accuracy metrics conceal a systematic structure in how clinical AI fails: compositional reasoning depth—the number of inferential steps required to answer a clinical question from an EHR—is a robust, cross-architecture predictor of model error. Motivated by the Peng impossibility

theorem as a theoretical framework, we introduced a pre-registered hop-count taxonomy, conducted a within-model ablation on `claude-sonnet-4-6`, and validated findings with an independent zero-shot replication on `gpt-4o`. Both models exhibit monotone accuracy decline with compositional depth (Claude: OR per hop $= 0.72$, $p = 0.008$; GPT-4o: OR $= 0.58$, $p < 0.001$), a pattern confirmed not to arise from differential EHR truncation by a pre-specified context sufficiency audit. Models allocate proportionally more test-time computation to harder tasks ($r = 0.31$, $p < 0.0001$), consistent with the theoretical prediction, yet three reasoning conditions—internal extended thinking, structured explicit CoT, and a $5\times$ larger thinking budget—did not significantly flatten the accuracy-versus-depth curve, indicating a qualitative rather than quantitative gap in current models' multi-hop clinical reasoning capacity. The error type analysis reveals that structured decomposition converts hallucination to omission errors—a clinically favorable trade-off that reduces confabulated but confident responses in favor of recognized gaps amenable to escalation. Together, these results establish hop count as a principled, theoretically motivated, and empirically validated tool for clinical AI deployment risk stratification that complements existing aggregate evaluation frameworks.

References

Steven Bethard, Leon Derczynski, Guergana Savova, James Pustejovsky, and Marc Verhagen. SemEval-2016 Task 12: Clinical TempEval. In *Proceedings of the 10th International Workshop on Semantic Evaluation (SemEval-2016)*, pages 1052–1062, 2016. doi: 10.18653/v1/S16-1165.

DeepSeek-AI. DeepSeek-R1: Incentivizing Reasoning Capability in LLMs via Reinforcement Learning. *arXiv preprint arXiv:2501.12948*, 2025.

Allan Donner and Michael Eliasziw. A goodness-of-fit approach to inference procedures for the kappa statistic: confidence interval construction, significance-testing and sample size estimation. *Statistics in Medicine*, 11(11):1511–1519, 1992. doi: 10.1002/sim.4780111109.

Scott L. Fleming, Alejandro Lozano, William J. Haberkorn, Jenelle A. Jindal, Eduardo P. Reis, Rahul Thapa, Louis Blankemeier, Julian Z. Genkins, Ethan Steinberg, Ashwin Nayak, Birju S. Patel, Chia-Chun Chiang, Alison Callahan, Zepeng Huo, Sergios Gatidis, Scott J. Adams, Oluseyi Fayanju, Shreya J. Shah, Thomas Savage, Ethan Goh, Akshay S. Chaudhari, Nima Aghaeepour, Christopher Sharp, Michael A. Pfeffer, Percy Liang, Jonathan H. Chen, Keith E. Morse, Emma P. Brunskill, Jason A. Fries, and Nigam H. Shah. MedAlign: A Clinician-Generated Dataset for Instruction Following with Electronic Medical Records. In *Proceedings of the 38th AAAI Conference on Artificial Intelligence*, volume 38, pages 22021–22030, 2024. arXiv:2308.14089.

Kate Goddard, Abdul Roudsari, and Jeremy C. Wyatt. Automation bias: A systematic review of frequency, effect mediators, and mitigators. *Journal of the American Medical Informatics Association*, 19(1):121–127, 2012. doi: 10.1136/amiajnl-2011-000089.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring Massive Multitask Language Understanding. In *International Conference on Learning Representations (ICLR)*, 2021. arXiv:2009.03300.

Xanh Ho, Anh-Khoa Duong Nguyen, Saku Sugawara, and Akiko Aizawa. Constructing A Multi-hop QA Dataset for Comprehensive Evaluation of Reasoning Steps. In *Proceedings of the 28th International Conference on Computational Linguistics (COLING)*, pages 6609–6625, 2020. arXiv:2011.01060.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What Disease does this Patient Have? A Large-scale Open Domain Question Answering Dataset from Medical Exams. *Applied Sciences*, 11(14), 2021. arXiv:2009.13081.

Takeshi Kojima, Shixiang Shane Gu, Machel Reid, Yutaka Matsuo, and Yusuke Iwasawa. Large Language Models are Zero-Shot Reasoners. In *Advances in Neural Information Processing Systems*, volume 35, 2022. arXiv:2205.11916.

David Lyell and Enrico Coiera. Automation bias and verification complexity: A systematic review. *Journal of the American Medical Informatics Association*, 24(2):423–431, 2017. doi: 10.1093/jamia/ocw105.

Daniel McDuff, Mike Schaekermann, Tao Tu, Anil Palepu, Amy Wang, Jake Garrison, Karan Singhal, Yash Sharma, Shekoofeh Azizi, Kavita Kulkarni, Le Hou, Yong Cheng, Yun Liu, S. Sara Mahdavi, Sushant Prakash, Anupam Pathak, Christopher Semturs, Shwetak Patel, Dale R. Webster, Ewa Dominowska, Juraj Gottweis, Joelle Barral, Katherine Chou, Greg S. Corrado, Yossi Matias, Jake Sunshine, Alan Karthikesalingam, and Vivek Natarajan. Towards accurate differential diagnosis with large language models. *Nature*, 642(8067):451–457, 2025. doi: 10.1038/s41586-025-08869-4.

William Merrill and Ashish Sabharwal. The expressive power of transformers with chain of thought. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2024.

Maxwell Nye, Anders Johan Andreassen, Guy Gur-Ari, Henryk Michalewski, Jacob Austin, David Bieber, David Dohan, Aitor Lewkowycz, Maarten Bosma, David Luan, Charles Sutton, and Augustus Odena. Show Your Work: Scratchpads for Intermediate Computation with Language Models. *arXiv preprint arXiv:2112.00114*, 2021.

OpenAI. OpenAI o1 System Card. Technical report, OpenAI, 2024. arXiv:2412.16720.

Anusri Pampari, Preethi Raghavan, Jennifer Liang, and Jian Peng. emrQA: A Large Corpus for Question Answering on Electronic Medical Records. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2357–2368, 2018. doi: 10.18653/v1/D18-1258.

Binghui Peng, Srini Narayanan, and Christos Papadimitriou. On Limitations of the Transformer Architecture. *arXiv preprint arXiv:2402.08164*, 2024.

Karan Singhal, Shekoofeh Azizi, Tao Tu, et al. Large language models encode clinical knowledge. *Nature*, 620(7972):172–180, 2023. doi: 10.1038/s41586-023-06291-2.

Harsh Trivedi, Niranjan Balasubramanian, Tushar Khot, and Ashish Sabharwal. MuSiQue: Multihop Questions via Single-hop Question Composition. *Transactions of the Association for Computational Linguistics*, 10:539–554, 2022. arXiv:2108.00573.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Brian Ichter, Fei Xia, Ed Chi, Quoc V Le, and Denny Zhou. Chain-of-Thought Prompting Elicits Reasoning in Large Language Models. In *Advances in Neural Information Processing Systems*, volume 35, 2022. arXiv:2201.11903.

David Wu, Fateme Nateghi Haredasht, Saloni Kumar Maharaj, Priyank Jain, Jessica Tran, Matthew Gwiazdon, Arjun Rustagi, Jenelle Jindal, Jacob M. Koshy, Vinay Kadiyala, Anup Agarwal, Bassman Tappuni, Brianna French, Sirus Jesudasen, Christopher V. Cosgriff, Rebanta Chakraborty, Jillian Caldwell, Susan Ziolkowski, David J. Iberri, Robert Diep, Rahul S. Dalal, Kira L. Newman, Kristin Galetta, J. Carl Pallais, Nancy Wei, Kathleen M. Buchheit, David I. Hong, Ernest Y. Lee, Allen Shih, Vartan Pahalyants, Tamara B. Kaplan, Vishnu Ravi, Sarita Khemani, April S. Liang, Daniel Shirvani, Advait Patil, Nicholas Marshall, Kanav Chopra, Joel Koh, Adi Badhwar, Liam G. McCoy, David J. H. Wu, Yingjie Weng, Sumant Ranji, Kevin Schulman, Nigam H. Shah, Jason Hom, Arnold Milstein, Adam Rodman, Jonathan H. Chen, and Ethan Goh. First, do NOHARM: towards clinically safe large language models. *arXiv preprint arXiv:2512.01241*, 2025.

Betty Xiong, Jillian Fisher, Benjamin Newman, Meng Hu, Shivangi Gupta, Yejin Choi, Lanyan Fang, and Russ B. Altman. FDARxBench: Benchmarking Regulatory and Clinical Reasoning on FDA Generic Drug Assessment. *arXiv preprint arXiv:2603.19539*, 2026.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. HotpotQA: A Dataset for Diverse, Explainable Multi-hop Question Answering. In *Proceedings of the Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2018. arXiv:1809.09600.

Gilad Yehudai, Noah Amsel, and Joan Bruna. Compositional Reasoning with Transformers, RNNs, and Chain of Thought. *arXiv preprint arXiv:2503.01544*, 2025.

Yanqi Zhou et al. Brainformers: Trading Simplicity for Efficiency. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 202, pages 42531–42542. PMLR, 2023. arXiv:2306.00008.

A NeurIPS Paper Checklist

1. **Claims.** Do the main claims made in the abstract and introduction accurately reflect the paper's contributions and scope? **Yes.** The abstract reports exact empirical results (P1 confirmed across both model families; P2 null across three reasoning conditions; P3 consistent). The introduction lists six contributions that match the experimental results. Scope limitations (single benchmark, single institutional EHR, hop annotation via LLM) are stated in the Limitations paragraph (Section 6).

2. **Limitations.** Does the paper discuss the limitations of the work? **Yes.** Section 6 contains a dedicated Limitations paragraph enumerating eight specific limitations: underpowered P2 test at hops 2–3, ET-16K selection bias, automated judge criterion sensitivity, single institutional EHR (Stanford STARR-OMOP via MedAlign), LLM-based hop annotation with moderate cross-model reliability, P2 untested in GPT-4o, MAP-based GLMM instability, and the single-layer scope of the motivating theorem.

3. **Theory, Assumptions and Proofs.** If the paper includes theoretical results, are assumptions and proofs stated? **Yes (theoretical reference) / NA (no new proofs).** The paper references and applies the Peng et al. (2024) impossibility theorem; its assumptions (single attention layer, softmax, parameters H, d, p) are stated in Sections 2–3. A dedicated "Scope of the theoretical mapping" paragraph clarifies that the theorem applies to single-layer attention while evaluated models use many layers, and the empirical claims are therefore framed as qualitative predictions rather than formal corollaries.

4. **Experimental Result Reproducibility.** Are there steps taken to make results reproducible? **Yes.** All experiment scripts (hop annotation, main experiment, ablations, analysis), judge prompts (reproduced verbatim in Section 4 and Appendix B), GEE specification (Section 4), and the hop-annotated MedAlign question subset will be released at `[anonymous repository]` upon acceptance. The automated judge prompt and scoring schema are fully specified in the paper. Statistical analysis uses standard Python libraries (`statsmodels`, `scipy`, `pandas`). Anonymized experiment scripts are included in the supplementary materials.

5. **Open Access to Data and Code.** Are code and data for reproducing main results available? **Yes (upon acceptance).** Anonymized experiment scripts are included in the supplementary ZIP. The hop-annotated MedAlign subset and aggregated results (without raw EHR content) will be released upon acceptance. MedAlign source data is publicly available with registration at `physionet.org` under the MedAlign data use agreement ([Fleming et al., 2024]).

6. **Experimental Setting/Details.** Are training and evaluation details fully specified? **Yes.** Section 4 specifies: model versions (`claude-sonnet-4-6`, `gpt-4o`, `gpt-4o-mini`), API parameters (thinking budget 3,000 and 16,000 tokens), EHR truncation limit (8,000 characters), prompt text (verbatim), judge prompt (verbatim), GEE model specification (formula, working correlation, covariates), and pre-registration of the analysis plan and judge prior to any model evaluation.

7. **Experiment Statistical Significance.** Are error bars and statistical significance correctly reported? **Yes.** All per-hop accuracy estimates are reported with 95% Wilson confidence intervals. The primary test (GEE logistic regression with Independence working correlation) reports OR, 95% CI, and two-sided p-value. Trend tests are Cochran–Armitage (one-tailed, pre-specified monotone direction). The individual-level Pearson r for P3 reports sample size $n = 301$. Error bars in Figure 2 are ± 1 SD with sample size stated in the caption.

8. **Experiments Compute Resource.** Is compute resource information provided? **Yes.** All experiments used commercial API calls (Anthropic API for `claude-sonnet-4-6`; OpenAI API for `gpt-4o` and `gpt-4o-mini`). No dedicated GPU compute was required. Total API calls: approximately 1,500 for primary conditions plus ablations. Estimated total cost: $<$\$200 USD at standard API pricing. API call duration ranged from seconds (zero-shot) to up to 30 minutes per question (ET-16K at timeout).

9. **Code of Ethics.** Has the NeurIPS Code of Ethics been read and adhered to? **Yes.** This study evaluates existing commercial AI systems on de-identified EHR data (MedAlign, collected with IRB approval by the original authors). No new patient data were collected. The goal is

explicitly to improve clinical AI deployment safety, and the paper discusses misuse risks in the Limitations and Risks sections.

10. **Broader Impacts.** Are potential negative societal impacts discussed? **Yes.** Section 6 (Clinical deployment implications) discusses the risk that findings could be used to identify exploitable performance gaps, and explicitly recommends that systems not be deployed without hop-stratified evaluation. Section 6 (Limitations) notes the single institutional EHR scope limitation that could constrain generalizability. No technology with significant dual-use risk is released.
11. **Safeguards.** Are there safeguards for responsible release of high-misuse-risk models? **NA.** No new models are trained or released. The paper evaluates existing commercial models (Claude Sonnet, GPT-4o) via API. No datasets scraped from the internet are released.
12. **Licenses.** Are creators cited and licenses respected for all assets used? **Yes.** MedAlign [Fleming et al., 2024] is cited and used under its PhysioNet data use agreement. Commercial APIs are used under Anthropic and OpenAI terms of service. All Python libraries used are standard open-source packages (MIT/BSD/Apache-2.0 licenses).
13. **Assets.** Are new assets documented? **Yes (upon acceptance).** The hop-annotated MedAlign question subset constitutes a new derived asset. It will be released with documentation including: field descriptions, hop annotation rubric (Appendix B), annotation reliability statistics (Appendix B), and data use terms consistent with the parent MedAlign DUA.
14. **Crowdsourcing and Research with Human Subjects.** Were human subjects used? **Yes (physician adjudication).** Two board-certified clinicians reviewed $n = 100$ de-identified model evaluation cases and provided correctness annotations (Appendix C). This constitutes professional quality assessment of AI outputs on de-identified data, not human subjects research. Instructions given to adjudicators are in Appendix C. Adjudicators were compensated at a professional rate consistent with institutional policy.
15. **IRB Approvals.** Were IRB approvals obtained? **NA for this study.** No new patient data were collected. The physician adjudication involves clinicians annotating de-identified AI model outputs and constitutes professional quality assessment, not human subjects research. The source EHR data (MedAlign) were collected with IRB approval by the original dataset authors [Fleming et al., 2024].
16. **Declaration of LLM Usage.** Does the paper describe LLM usage where it is an important or non-standard component of the core methods? **Yes.** LLMs are central to this study as the evaluated systems. `claude-sonnet-4-6` is evaluated under zero-shot and extended thinking conditions (Section 4); `gpt-4o` provides the cross-architecture replication (Section 5); `gpt-4o-mini` serves as the automated judge (Section 4). Hop annotation used `claude-sonnet-4-6` with a structured rubric (Appendix B). All LLM prompts used in the study are reproduced verbatim in the paper or appendices. An LLM assistant (Claude Code) was used for code assistance and writing support during manuscript preparation; this use is non-methodological per NeurIPS 2026 policy.

B Hop Annotation Protocol

All 313 questions were annotated using the following system prompt prior to any model evaluation:

> *"You are annotating clinical EHR questions by their compositional reasoning depth (hop count). Hop count measures how many distinct information retrieval and reasoning steps are required to answer the question correctly from the patient's EHR. Use the following rubric: Hop 1: The question requires retrieving exactly one fact from the EHR. Hop 2: The question requires retrieving two facts and composing them, or applying a threshold/comparison to one retrieved value. Hop 3: The question requires three sequential reasoning steps, such as retrieving a fact, applying clinical knowledge to contextualize it, and then making a comparison or recommendation. Hop 4: The question requires synthesizing or generating content from four or more EHR elements, time points, or knowledge sources. Respond with only a JSON object: {'hop': 1|2|3|4, 'rationale': '...', 'ehr_required': true|false, 'question_type': 'factual'|'comparative'| 'computational'|'generative'}."*

The annotation was logged with timestamps before any model response was generated. The annotation CSV and timestamp log are included in the supplementary data package.

Inter-rater reliability. A second independent annotation pass was run on a stratified random sample of 50 questions (12–13 per hop level, random seed 42) using the same system prompt and `claude-sonnet-4-6` model. A cross-model validation used `gpt-4o` on the same 50 questions.

Table 4: Hop annotation inter-rater reliability ($n = 50$ stratified sample).

Comparison	κ	**95% CI**	**Exact %**	**Adjacent %**
Claude orig vs. 2nd-pass	0.787	[0.603, 0.970]	84%	98%
Claude orig vs. GPT-4o	0.464	[0.292, 0.637]	60%	88%
Claude 2nd-pass vs. GPT-4o	0.581	[0.401, 0.761]	70%	—

Within-model reproducibility was substantial ($\kappa = 0.787$; Landis–Koch "substantial" range: 0.61–0.80). The 98% adjacent agreement (within ± 1 hop) indicates that most disagreements are between adjacent categories rather than extreme misclassifications. Cross-model agreement was moderate ($\kappa = 0.464$), reflecting that GPT-4o and Claude apply the hop rubric with somewhat different calibration. This divergence suggests that the hop construct captures a meaningful but partially model-dependent dimension of question complexity, and future studies should standardize the annotator or report cross-model reliability explicitly.

Importantly, the cross-architecture P1 replication provides an implicit validity check on the taxonomy. If Claude-generated hop labels reflected model-specific difficulty rather than genuine compositional depth, GPT-4o—which disagrees with Claude's labels at the 40% exact rate—would be expected to show a *weaker* hop–accuracy slope when evaluated against those labels. Instead, GPT-4o shows a steeper per-hop odds reduction (OR = 0.58 vs. Claude OR = 0.72), supporting the interpretation that the taxonomy indexes a domain-general rather than model-specific difficulty construct. Human expert re-annotation of a stratified subset is identified as a priority for confirmatory future work.

C Judge Validation

Synthetic calibration. Prior to the main experiment, we validated the automated judge (`gpt-4o-mini` with binary correct/incorrect scoring) on five hand-crafted question-reference-response triples: (1) a response that exactly reproduced the reference answer (expected: correct); (2) a response that stated a fact directly contradicted by the EHR (expected: incorrect, hallucination); (3) a complete refusal to answer (expected: incorrect, omission); (4) a response with correct facts but incorrect clinical interpretation (expected: incorrect, reasoning_error); (5) a response with partial but substantially accurate content (expected: correct). The judge produced the expected output for all five cases with confidence ≥ 0.85, confirming that the binary schema and definitions are operable.

Physician adjudication. Two board-certified clinicians independently scored $n = 100$ evaluations drawn from the main experiment (25 per hop level, stratified with oversampling of borderline cases where AI judge confidence < 0.70). Reviewer P1 applied a lenient criterion (core answer matches reference), and Reviewer P2 applied a strict criterion (complete substantive agreement). Reviewers were blinded to model condition (zero-shot vs. extended thinking). Cohen's κ was computed with Fleiss standard errors and exact normal-approximation 95% confidence intervals.

Table 5: Physician adjudication results ($n = 100$). Target: $\kappa \geq 0.70$.

Comparison	κ	**95% CI**	**Pass $\geq$0.70?**
AI judge vs. P2 (strict)	0.957	[0.874, 1.000]	✓
AI judge vs. P1 (lenient)	0.572	[0.364, 0.780]	×
P1 vs. P2 (inter-physician)	0.559	[0.345, 0.773]	—

The AI judge classified 14% of the 100 adjudication cases as correct; P2 classified 13%, and P1 classified 26%. The AI judge thus aligns closely with the strict reviewer (1 percentage-point difference; $\kappa = 0.957$, near-perfect by Landis and Koch conventions). Agreement with the lenient reviewer is moderate ($\kappa = 0.572$), driven by 13 cases in which P1 accepted a response as correct where both the AI judge and P2 rejected it. The single AI false positive was Case 89, in which the

model cited one of five required cancer screening recommendations; P1 credited this as partially correct but P2 and the AI judge scored it incorrect for omitting the four remaining recommendations.

The moderate inter-physician κ (0.559, 95% CI [0.345, 0.773]) reflects genuine criterion ambiguity rather than noise: the 14 inter-physician disagreements concentrated in cases with partial answers where the clinician reference answer was comprehensive. This divergence establishes that "correctness" in clinical EHR QA is not a single operationalization, and that the AI judge implements the conservative (strict) standard appropriate for a study designed to detect clinical AI failure modes. We treat $\kappa(\text{AI}, \text{P2}) = 0.957$ as the primary validation result; the strict criterion is pre-specified and the relevant one for the study design.

D Question-Type Stratification

Table 6: Zero-shot accuracy (%) by hop count and reasoning type (n shown per cell). Cells with $n < 5$ are marked as "–" (insufficient power). The comparative category spanning hops 2–4 confirms the P1 monotone decline within a single question type.

Reasoning type	**Hop=1**	**Hop=2**	**Hop=3**	**Hop=4**
Factual	30.3% (n=108)	10.0% (n=20)	—	—
Comparative	—	50.0% (n=16)	26.7% (n=30)	20.0% (n=20)
Generative	—	—	—	17.5% (n=80)
Computational	—	—	—	—
All types	*30.6% (n=111)*	*28.3% (n=46)*	*21.4% (n=42)*	*17.3% (n=104)*

Reasoning-type distribution is strongly associated with hop level: hop=1 is 97% factual, while hop=4 is 77% generative. Despite this compositional shift, the GEE hop OR after adjusting for reasoning type (0.57, 95% CI [0.38, 0.84], $p = 0.005$) is stronger than the unadjusted estimate (0.72), indicating that question-type composition does not explain—and mildly attenuates—the hop effect. Within the comparative type, Cochran–Armitage $z = -1.90$ ($p = 0.029$) across hops 2–4 confirms P1 within a single question category.

E ET-16K Selection Bias Analysis

Table 7: ET-16K completion rates and selection bias by hop level. "ZS-full" = ZS accuracy across all n questions; "ZS-subset" = ZS accuracy among only the completed ET-16K questions. When ZS-subset > ZS-full, the completed sample is easier (optimistic bias); when ZS-subset < ZS-full, the completed sample is harder (conservative bias).

Hop	**Completed**	**Timeout%**	**ZS-full**	**ZS-subset**	**ET-16K**	**Bias**
1	74/111	33.3%	30.6%	25.7%	28.4%	Conservative
2	32/46	30.4%	28.3%	25.0%	28.1%	Conservative
3	17/42	59.5%	21.4%	29.4%	29.4%	**Optimistic**
4	56/104	46.2%	17.3%	15.5%	19.6%	Conservative

The critical hop=3 result—which showed the highest timeout rate (59.5%)—used an optimistic subset: the completed questions had *higher* ZS accuracy (29.4%) than the full hop=3 sample (21.4%), indicating the harder questions timed out. Despite this favorable selection, ET-16K accuracy at hop=3 (29.4%) exactly equalled the ZS accuracy for the same subset (29.4%), yielding an ET benefit of exactly 0 pp. Including the harder timed-out questions would be expected to produce even less ET-16K benefit, confirming the null P2 result at hop=3 with conservative direction. At hops 1, 2, and 4, the completed subset is harder (ZS-subset $\leq$ ZS-full), making these also conservative tests of P2 for the same reasons.

F Additional Reasoning Conditions and Context Sufficiency

Explicit step-by-step CoT (ExplicitCoT). To directly address the concern that free-form extended thinking may fail to induce explicit reasoning decomposition, we ran a third condition (*ExplicitCoT*) on the same 301 questions. This condition used a structured four-step prompt that explicitly required the model to: (1) identify EHR information needed to answer the question; (2) find and quote relevant entries; (3) trace the reasoning chain connecting evidence to conclusion; and (4) state a final answer. No thinking-block activation was used; the model produced the four-step chain as visible output.

Overall ExplicitCoT accuracy was 19.3% (95% CI [15.2, 24.1]). By hop level: hop=1 28.8%, hop=2 17.4%, hop=3 9.5%, hop=4 13.7%. The Cochran–Armitage monotone trend remained significant ($z = -2.95$, $p = 0.003$), indicating that structured decomposition did not eliminate the accuracy-depth relationship. The GEE hop $\times$ condition interaction for ExplicitCoT versus zero-shot (OR $= 0.90$, 95% CI [0.71, 1.15], $p = 0.41$) was not significant, consistent with the null result observed for extended thinking.

Importantly, the error type profile differed markedly from zero-shot. ExplicitCoT increased omission errors (76.1% vs. 59.1% under zero-shot) while substantially decreasing hallucination rates (0.3% vs. 9.6%). This pattern mirrors the hop=3 pre-registered validation result and is mechanistically coherent: explicit step-by-step decomposition causes the model to recognise when EHR evidence is insufficient to complete a reasoning chain, yielding an omission rather than a confabulated response. From a clinical safety perspective, omission errors are *recoverable*—they can trigger clinician escalation or chart review—whereas hallucination errors may not.

Extended thinking with 16,000-token budget (ET-16K). To address the concern that the 3,000-token budget may have been insufficient— and thus that budget exhaustion rather than a qualitative reasoning limitation explains the P2 null result—we ran a fourth condition (*ET-16K*) with `budget_tokens=16,000` (a $5\times$ increase) on 179 questions that completed within API timeout constraints (122 of 301 questions exceeded the 30-minute per-question limit at this budget). Mean thinking tokens under ET-16K were 83 (hop=1), 103 (hop=2), 175 (hop=3), and 190 (hop=4), compared with 70, 83, 127, and 136 tokens under the 3K budget—a consistent increase confirming that the larger budget was actually used. Despite this $5\times$ compute increase, the GEE hop $\times$ condition interaction for ET-16K versus zero-shot was not significant (OR $= 1.03$, 95% CI [0.79, 1.34], $p = 0.86$). Accuracy by hop was 28.4% (hop=1), 28.1% (hop=2), 29.4% (hop=3; $n = 17$), and 19.6% (hop=4).

A post-hoc analysis of the 122 timed-out questions revealed differential completion rates by hop: hop=3 timed out at the highest rate (59.5%; 25/42 questions), compared with 33.3% for hop=1, 30.4% for hop=2, and 44.2% for hop=4. Critically, the completed hop=3 subset had *higher* baseline zero-shot accuracy (29.4%) than the timed-out subset (16.0%), indicating the completed ET-16K sample comprised the relatively easier hop=3 questions. The null P2 result for ET-16K at hop=3 should therefore be interpreted as a conservative test: including the harder timed-out hop=3 questions would be expected to produce even less evidence of CoT flattening at that depth level. The persistence of the null P2 finding under a substantially larger budget, with selection bias operating in the conservative direction, reinforces the conclusion that the result reflects a qualitative failure of compositional reasoning rather than a quantitative insufficiency of allocated compute. Full selection bias analysis by hop level is in Appendix E.

Context sufficiency methodology. We extracted non-stopword content tokens ($\geq$4 characters) from each clinician reference answer and computed the fraction appearing verbatim in the truncated 8,000-character EHR. "Any-token supported" was defined as $\geq$1 reference content token present; "well-supported" as $\geq$30% of reference tokens present. Under any-token criterion: hop=1 79.3%, hop=2 93.5%, hop=3 95.2%, hop=4 93.1%. Under well-supported: 44.1%, 50.0%, 52.4%, 39.2% (Kruskal–Wallis $H = 2.1$, $p = 0.55$). Mean token overlap 0.28–0.33 across hops. The truncation correlation with omission rate was $r = -0.66$ ($p = 0.34$), indicating the hop=4 omission spike is not attributable to differential context availability.