PipelineParameter display update

Old processing, new behavior, and verification notes

1. How the old processing worked

The old code treated a column with the key **allAssets** as a special case. This behavior was separate from the normal lookup for a user-selected PipelineParameter.

Automatic parameter choice: In the **potoodev** project, it tried **testAllAssets** before **allAssets**. In other projects, it tried them in the opposite order. A value could therefore come from an automatically substituted parameter.

Extra lookup route: The legacy path tried PipelineParameterDelivery and then a local database fallback. If no value was found, that special column could display a hyphen (**-**).

Value flattening: Lists and dictionaries were joined into ordinary text. For example, a one-item list appeared without its brackets. Boolean values were converted to Python-style text such as **False**.

2. How the new processing works

The selected **parameter_index** identifies which PipelineParameter to read. The code then matches that parameter to the current asset or shot location. It no longer substitutes **allAssets** and **testAllAssets** based on the project.

Values are read from the configured repository source. Strings retain their contents; non-empty lists and dictionaries retain their structure as JSON. Booleans display as **true** or **false**.

Stored value	Old display	New display
["fxTestDustA"]	fxTestDustA	["fxTestDustA"]
["taskA", "taskB"]	taskA, taskB	["taskA", "taskB"]
{"enabled": false}	enabled: False	{"enabled": false}
Boolean false	False	false
Plain text camAim	camAim	camAim

The normal Shots Number generation remains in place. The update removes the legacy PipelineParameter special handling, rather than changing unrelated shot-number behavior.

Configuration note: A column that relied on the former automatic allAssets lookup must be configured as a PipelineParameter column with the desired parameter selected explicitly. Saved server column definitions were not automatically migrated.

Display rules and verification

What to expect in Assets, Shots, and exported CSV files

3. Empty values and valid values

After the first implementation, an additional display preference was requested: show empty values as blank instead of showing empty brackets or a hyphen.

Value returned by the repository	Display
Missing value or null / None	Blank
Empty string, empty list [], or empty dictionary {}	Blank
Boolean false or true	false or true
Number 0	0
Non-empty list or dictionary	JSON structure is preserved
Non-empty string	Original text is preserved

Important: A valid **false** value is not missing data. A list containing a value, such as **[false]** or **[0]**, is also not empty. Literal text such as the string **"[]"** is preserved as text.

4. What was checked

Office screenshots were compared with CentralWeb for project **potoodev**. With **testMultiTasks** selected, these Assets values matched:

Asset	Expected / observed value
testAssetA	["fxTestDustA"]
testAssetB	["fxTestSparksA"]
testAssetD	["cfxTestDust"]

The office screenshots also confirmed blank display for empty entries and **false** display for **toCfx**. The supervisor's missing-value issue was not reproduced in these specific Assets examples; this does not establish that every parameter and location is correct.

During implementation, **20 isolated local regression checks passed**, using the actual display and worker methods with test repositories. The display and CSV paths share the selected-parameter lookup and formatting. A complete office application run, Shots verification, and office CSV comparison were not independently performed.

5. Summary to share with the supervisor

I removed the legacy project-specific allAssets/testAllAssets substitution and its delivery/local database fallback route. PipelineParameter columns now use the parameter explicitly selected in Column Manager. List and dictionary structures are preserved instead of being flattened. As an additional display adjustment, empty values appear blank, while valid false and zero values remain visible. I verified the testMultiTasks Assets examples against CentralWeb; the reported missing-value issue was not reproduced in those cases.