

General Specifications

- Dimensions 110mm(L)x110mm(W)x46mm(H)
- Weight 350 g
- Power supply voltage 12 Vdc $\pm$ 5%
- Operating temperature 0 - 40 °C
- Storage temperature 0 - 70 °C

User Interfaces

- 1x Unlock button
- 1x LAN interface
- 1x Power connector
- 1x LED dim button

LAN interface(s)

- Compliant with IEEE802.3 Clause 40 (1000/100/10BASE-T)
- LED indicators for link and activity

WAN interface

- 1x GPON interface
- Compliant ITU-T G.984.x
- Compliant ITU-T G.988
- SC/APC connector
- Class B+ optics
- Interoperable with major OLT brands in triple-play configurations
- 256 GEM ports
- 32 T-CONT

Emission and safety regulations

- CE, FCC approved
- Safety:
 - IEC 60950
 - IL94HB flammability class
- Laser safety
 - IEC EN 60825 class 1
 - FDA 21 CFR 1040.10/.11 Class 1
- Emission & Immunity:
 - EN 55022/CISPR 22:2008, Class B
 - EN 61000
 - EN 55024
- RoHS/WEEE marking:
Compliant with 2002/95/EC



Status LEDs

- Power
- Fiber uplink status
- Alarm