

Niurix SOLT33-16P OLT

Specifications Sheet



Product Features

- Compact 1RU 19inch design
- 16 GPON ports
- 4 GE Optical/Electrical uplink ports
- 2 x 10G ports
- Support B+ and C+ SFP
- ONT Broadcast and loop protection
- Hot Dual power supply

General Specifications

- Dimensions 445mm(L)x383mm(W)x44mm(D)
- Weight ≤ 2.8 kg
- Power supply AC 90 - 264 V, 47/63 Hz DC -36 - -72 V
- Power Consumption ≤ 65 W
- Switching Capacity 128 Gbps
- Forward Capacity 95.2 Mbps (IPV4/IPV6)

Environmental Requirements

- Operating Temperature -10 - 65 °C
- Storage Temperature -40 - 70 °C
- Relative humidity 10% - 90%, non-condensing

Ports

- 16 GPON ports
- 4 GE Optical/Electrical uplink ports
- 2 x 10G expansion slots

GPON

- ITU - T G.984.x compliant
- Supports up to 128 x ONTs
- Max. transmission distance 20km
- Uplink and downlink triple churning encrypted function with 128Bits
- ONU Terminal legitimacy certification report illegal ONU registration
- DBA algorithm, the particle is 1Kbit/s
- Standard OMCI management function
- ONU batch software upgrade, fixed time upgrade, real time upgrade
- PON port optical power detection

Service Features - Layer 3

QOS

- Rate-limit to packet sending/receiving speed of port
- Priority remark to port or self defined flow and provide 802.1P, DSCP priority and Remark
- CAR (Committed Access Rate), Traffic shaping & flow statisticst
- Packet mirror and redirection of interface & self defined flow

IPv4

- ARP Proxy
- DHCP Relay
- DHCP Server
- Static Route

IPv6

- ICMPv6
- ICMPv6 Redirection
- DHCPv6

Multicast

- IGMPv1/v2/v3
- IGMPv1/v2/v3 Snooping
- IGMP Filter
- MLDv2/MLDv2 Snooping

Layer 2

MAC

- MAC Black Hole
- Port MAC Limit
- 64K MAC (packet exchange chip cache 2MB, external 720 MB)

VLAN

- 4K VLAN entries
- Port/MAC/IP subnet-based VLAN
- QinQ and Flexible QinQ (Stack VLAN)
- VLAN swap and remark

Spanning Tree Protocol (STP)

- IEEE 802.1D /W/S STP/RSTP/MSTP
- ONU remote loop detect alarm

Ports

- Bi-directional bandwidth control
- Static link aggregation
- LACP
- Port mirroring

Security

User Security

- Anti-ARP-spoofing
- Anti-ARP-flooding
- IP Source Guard
- IEEE 802.1x & AAA/Radius authentication
- IP Source Guard create IP, VLAN MAC and Port binding
- Port Isolation
- MAC address binding to the port and MAC address filtering

Device Security

- Anti-DOS attack(such as ARP, Synflood, Smurf, ICMP attack), ARP
- Detection, worm and Msblaster worm attack
- SSHv2 Secure Shell
- SNMP v3 encrypted management
- Security IP login through Telnet

Network Security

- User based MAC & ARP traffic examination
- Restrict ARP traffic of each user and force-out user with abnormal ARP traffic
- Dynamic ARP table-based binding
- IP, VLAN, MAC and Port binding

Reliability

Loop Protection

- ERPP (recover-time <50ms)
- Loopback-detection

Link Protection

- RSTP/MSTP (recover-time <1s)
- LACP (recover-time <10ms)

Device Protection

- 1+1 power hot backup backup maintenance

Network Maintenance

- GPON OMCI
- Ping and Traceroute
- Port real-time, utilization and transmit/ receive statistic based on Telnet

Device Management

- CLI, Console port, Telnet
- SNMPv1/v2/v3
- RMON (Remote Monitoring) 1,2,3,9 groups MIB
- NTP

About the Company

At Niurix we work to engineer devices that will usher a new era in computer networking. As large scale network deployments are steadily moving from copper to fiber for faster, reliable and secure data connectivity, many smaller network setups remain outside this shift in the connected world. To bring these smaller networks closer to cutting edge technology, our engineers have developed a range of modern, reliable and cost-effective hardware products. Our versatile range of products use the Gigabit Passive Optical Network (GPON) technology to deliver data, voice and video services to each node in a network, thus making it the ideal solution for hospitality, assisted living, student living and other campus based network