

Niurix-P4200R

- 4 POE Gigabit Ethernet
- 2 Analog Phones
- 1 CATV



Product Description

The P4200R Optical Network Terminal (ONT) is the most feature rich CPE for a GPON based network architecture in the USA. Built to deliver high quality triple play services (data, video and phone), It is the ideal device for a Fiber to the Room (FTTR) solution in hospitality, assisted living, student living, and other campus networks.

Product Features

- Supports Gigabit Data, Quality Voice Services, Cable TV, and IPTV.
- Can be configured to support IP phones and analog phones.
- Designed with advanced fiber termination for easy installation.
- Ethernet ports support PoE standards IEEE 802.3af/at.
- Zero-touch provisioning and advanced management over TR-069.
- GPON uplink with 1.244Gbps/2.488Gbps link speed.

The perfect accessory for your move to fiber

The benefits of a move from copper based data networks to fiber based ones is no longer a debate. Internet Service Providers have for long been migrating their trunk infrastructure to fiber to enhance data speeds, create a reliable network, and bring triple play services over one cable to the home. As the adoption of fiber technology picks up pace, small scale network deployments in hospitality, student living and assisted living can now take advantage of this technology in their network setups. The Niurix P4200R has been specially designed to provide an efficient and cost-effective solution for such projects.

Niurix-P4200R ONT

Specifications Sheet



General Specifications

- Dimensions 210mm(L)x135mm(W)x30mm(H)
- Weight < 400 g
- Power supply voltage 52 Vdc, 1.8A
- Relative Humidity 5% - 95%
- Storage Humidity 5% - 95%
- Operating temperature 0 - 50 °C
- Storage temperature -40 - 70 °C

User Interfaces

- 4x 10/100/1000 Mbps Lan Port
- 2x FXS Port
- 1x SC/APC GPON Port
- 1x RF Port

Standards

- PoE IEEE 802.3af, IEEE 802.3at
- SIP RFC3261, ITU - T G.711/G.729
- GPON ITU - T G.984.2 Amd1, Class B+
- VLAN 802.1Q/P
- ACS TR069

CATV

- Light reflection loss: >45dB
- Input optical power: -15dBm ~ 0dBm
- RF bandwidth: 45MHz ~ 1000MHz
- RF output level: 75±2dBuV

VOIP

- SIP Client
- SIP Phones for Hospitality - Message Waiting Indicator (MWI)

L2/L3 Features

- IPv4, IPv6 support
- Dynamic IP/Static IP/PPPoE WAN
- DHCP Server
- DHCP Client
- Port Triggering
- UPnP
- Port based VLANs
- Bridged Networks
- NAT

Security

- DoS Attack Prevention
- SPI Firewall
- IP Address/MAC Address/Domain Filtering
- IP and MAC Address Binding

Management

- TR-069 supported
- Advanced GUI



Status LEDs

- Power
- Fiber uplink status, PON
- Telephony status 1-2
- CATV status
- Connectivity status, Internet
- LAN1-4 status
- Fiber uplink status, LOS