



Welcome to Ubuntu 22.04.3 LTS (GNU/Linux 5.15.153.1-microsoft-standard-WSL2 x86\_64)

- \* Documentation: <https://help.ubuntu.com>
- \* Management: <https://landscape.canonical.com>
- \* Support: <https://ubuntu.com/advantage>

This message is shown once a day. To disable it please create the  
/home/manikandan/.hushlogin file.

manikandan@HPVICTUSMANI61:~\$ cat /etc/passwd

```
root:x:0:0:root:/root:/bin/bash
daemon:x:1:1:daemon:/usr/sbin:/usr/sbin/nologin
bin:x:2:2:bin:/bin:/usr/sbin/nologin
sys:x:3:3:sys:/dev:/usr/sbin/nologin
sync:x:4:65534:sync:/bin:/bin/sync
games:x:5:60:games:/usr/games:/usr/sbin/nologin
man:x:6:12:man:/var/cache/man:/usr/sbin/nologin
lp:x:7:7:lp:/var/spool/lpd:/usr/sbin/nologin
mail:x:8:8:mail:/var/mail:/usr/sbin/nologin
news:x:9:9:news:/var/spool/news:/usr/sbin/nologin
uucp:x:10:10:uucp:/var/spool/uucp:/usr/sbin/nologin
proxy:x:13:13:proxy:/bin:/usr/sbin/nologin
www-data:x:33:33:www-data:/var/www:/usr/sbin/nologin
backup:x:34:34:backup:/var/backups:/usr/sbin/nologin
list:x:38:38:Mailing List Manager:/var/list:/usr/sbin/nologin
irc:x:39:39:ircd:/run/ircd:/usr/sbin/nologin
gnats:x:41:41:Gnats Bug-Reporting System (admin):/var/lib/gnats:/usr/sbin/nologin
nobody:x:65534:65534:nobody:/nonexistent:/usr/sbin/nologin
systemd-network:x:100:102:systemd Network Management,,,:/run/systemd:/usr/sbin/nologin
systemd-resolve:x:101:103:systemd Resolver,,,:/run/systemd:/usr/sbin/nologin
messagebus:x:102:105:,:/nonexistent:/usr/sbin/nologin
systemd-timesync:x:103:106:systemd Time Synchronization,,,:/run/systemd:/usr/sbin/nologin
syslog:x:104:111:,:/home/syslog:/usr/sbin/nologin
_apt:x:105:65534:,:/nonexistent:/usr/sbin/nologin
uidd:x:106:112:,:/run/uidd:/usr/sbin/nologin
tcpdump:x:107:113:,:/nonexistent:/usr/sbin/nologin
manikandan:x:1000:1000:,,,:/home/manikandan:/bin/bash
manikandan@HPVICTUSMANI61:~$
```

manikandan@HPVICTUSMANI61:~\$ cat /etc/passwd

manikandan@HPVICTUSMANI61:~\$ awk -F':' '{ print \$1}' /etc/passwd

root  
daemon  
bin  
sys  
sync  
games  
man  
lp  
mail  
news  
uucp  
proxy  
www-data  
backup  
list  
irc  
gnats  
nobody  
systemd-network  
systemd-resolve  
messagebus  
systemd-timesync  
syslog  
\_apt  
uidd  
tcpdump  
manikandan  
manikandan@HPVICTUSMANI61:~\$

manikandan

manikandan@HPVICTUSMANI61:~\$ sudo adduser coderacer

[sudo] password for manikandan:

Adding user `coderacer' ...

Adding new group `coderacer' (1001) ...

Adding new user `coderacer' (1001) with group `coderacer' ...

Creating home directory `/home/coderacer' ...

Copying files from `/etc/skel' ...

New password:

Retype new password:

passwd: password updated successfully

Changing the user information for coderacer

Enter the new value, or press ENTER for the default

Full Name []: coderacer

Room Number []: 45

Work Phone []: 8838509909

Home Phone []: 8838509909

Other []:

Is the information correct? [Y/n] Y

manikandan@HPVICTUSMANI61:~\$



```
Other []:
Is the information correct? [Y/n] Y
manikandan@HPVICTUSMANI61:~$ pwd
/home/manikandan
manikandan@HPVICTUSMANI61:~$ cd ../
manikandan@HPVICTUSMANI61:/home$ pwd
/home
manikandan@HPVICTUSMANI61:/home$ ls
coderacer  manikandan
manikandan@HPVICTUSMANI61:/home$ cd coderacer/
-bash: cd: coderacer/: Permission denied
manikandan@HPVICTUSMANI61:/home$ cd coderacer
-bash: cd: coderacer: Permission denied
manikandan@HPVICTUSMANI61:/home$ pwd
/home
manikandan@HPVICTUSMANI61:/home$ cd coderacer/
-bash: cd: coderacer/: Permission denied
manikandan@HPVICTUSMANI61:/home$ cd manikandan
manikandan@HPVICTUSMANI61:~$ ls
manikandan@HPVICTUSMANI61:~$ pwd
/home/manikandan
manikandan@HPVICTUSMANI61:~$ cd ../
manikandan@HPVICTUSMANI61:/home$ ls
coderacer  manikandan
manikandan@HPVICTUSMANI61:/home$ cd coderacer
-bash: cd: coderacer: Permission denied
manikandan@HPVICTUSMANI61:/home$ whoami
manikandan
manikandan@HPVICTUSMANI61:/home$ cd
manikandan@HPVICTUSMANI61:~$ whoami
manikandan
manikandan@HPVICTUSMANI61:~$ sudo su
root@HPVICTUSMANI61:/home/manikandan#
root@HPVICTUSMANI61:/home/manikandan#
root@HPVICTUSMANI61:/home/manikandan# sudo su
root@HPVICTUSMANI61:/home/manikandan# pwd
/home/manikandan
root@HPVICTUSMANI61:/home/manikandan# cd ../
root@HPVICTUSMANI61:/home# pwd
/home
root@HPVICTUSMANI61:/home# ls
coderacer  manikandan
root@HPVICTUSMANI61:/home# cd coderacer/
```

```
manikandan@HPVICTUSMANI61:~$ sudo su
root@HPVICTUSMANI61:/home/manikandan#
root@HPVICTUSMANI61:/home/manikandan#
root@HPVICTUSMANI61:/home/manikandan# sudo su
root@HPVICTUSMANI61:/home/manikandan# pwd
/home/manikandan
root@HPVICTUSMANI61:/home/manikandan# cd ../
root@HPVICTUSMANI61:/home# pwd
/home
root@HPVICTUSMANI61:/home# ls
coderacer  manikandan
root@HPVICTUSMANI61:/home# cd coderacer/
root@HPVICTUSMANI61:/home/coderacer# whoami
root
root@HPVICTUSMANI61:/home/coderacer# su coderacer
coderacer@HPVICTUSMANI61:~$ whoami
coderacer
coderacer@HPVICTUSMANI61:~$ pwd
/home/coderacer
coderacer@HPVICTUSMANI61:~$
```





## Package configuration

## Postfix Configuration

Please select the mail server configuration type that best meets your needs.

No configuration:

Should be chosen to leave the current configuration unchanged.

Internet site:

Mail is sent and received directly using SMTP.

Internet with smarthost:

Mail is received directly using SMTP or by running a utility such as fetchmail. Outgoing mail is sent using a smarthost.

Satellite system:

All mail is sent to another machine, called a 'smarthost', for delivery.

Local only:

The only delivered mail is the mail for local users. There is no network.

General mail configuration type:

No configuration

Internet Site

Internet with smarthost

Satellite system

Local only

<Ok>

<Cancel>

## Package configuration

## Postfix Configuration

The 'mail name' is the domain name used to 'qualify' `_ALL_` mail addresses without a domain name. This includes mail to and from `<root>`: please do not make your machine send out mail from `root@example.org` unless `root@example.org` has told you to.

This name will also be used by other programs. It should be the single, fully qualified domain name (FQDN).

Thus, if a mail address on the local host is `foo@example.org`, the correct value for this option would be `example.org`.

System mail name:

HPVICTUSMANI61.

<Ok>

<Cancel>

```
manikandan@HPVICTUSMANI61:~$ sudo su
root@HPVICTUSMANI61:/home/manikandan# cd /etc/postfix
root@HPVICTUSMANI61:/etc/postfix# cp main.cf main.cf.bkp
root@HPVICTUSMANI61:/etc/postfix# hostname
HPVICTUSMANI61
root@HPVICTUSMANI61:/etc/postfix#
```



```
# See http://www.postfix.org/COMPATIBILITY\_README.html -- default to 3.6 on
# fresh installs.
compatibility_level = 3.6

# TLS parameters
smtpd_tls_cert_file=/etc/ssl/certs/ssl-cert-snakeoil.pem
smtpd_tls_key_file=/etc/ssl/private/ssl-cert-snakeoil.key
smtpd_tls_security_level=may

smtp_tls_CApath=/etc/ssl/certs
smtp_tls_security_level=may
smtp_tls_session_cache_database = btree:${data_directory}/smtp_scache

smtpd_relay_restrictions = permit_mynetworks permit_sasl_authenticated defer
_unauth_destination
myhostname = HPVICTUSMANI61.localdomain
alias_maps = hash:/etc/aliases
alias_database = hash:/etc/aliases
myorigin = /etc/mailname
mydestination = $myhostname, HPVICTUSMANI61., localhost., , localhost
relayhost = [smtp.gmail.com]:587
mynetworks = 127.0.0.0/8 [::ffff:127.0.0.0]/104 [::1]/128
mailbox_size_limit = 0
recipient_delimiter = +
inet_interfaces = all
inet_protocols = all
# Location of sasl_passwd
# Going to that ^ directry
smtp_sasl_password_maps = hash:/etc/postfix/sasl/sasl_passwd

# SASL authentication for postfix
# Giving authentication status YES and ENCRYPT IT
smtp_sasl_auth_enable = yes
smtp_tls_security_level = encrypt

# Disallow methods that allow anonymous authentication
# So no one can get in anonymously
smtp_sasl_security_options = noanonymous
```

```
manikandan@HPVICTUSMANI61:~$ sudo su
root@HPVICTUSMANI61:/home/manikandan# cd /etc/postfix
root@HPVICTUSMANI61:/etc/postfix# cp main.cf main.cf.bkp
root@HPVICTUSMANI61:/etc/postfix# hostname
HPVICTUSMANI61
root@HPVICTUSMANI61:/etc/postfix# ls
dynamicmaps.cf      main.cf.bkp      master.cf.proto  postfix-files.d
dynamicmaps.cf.d    main.cf.proto    post-install      postfix-script
main.cf             master.cf        postfix-files     sasl
root@HPVICTUSMANI61:/etc/postfix# vim main.cf
root@HPVICTUSMANI61:/etc/postfix# cd sasl
root@HPVICTUSMANI61:/etc/postfix/sasl# ls
root@HPVICTUSMANI61:/etc/postfix/sasl# vim sasl_passwd
root@HPVICTUSMANI61:/etc/postfix/sasl# postmap sasl_passwd
postmap: warning: /etc/postfix/main.cf, line 55: overriding earlier entry: s
mtp_tls_security_level=may
root@HPVICTUSMANI61:/etc/postfix/sasl# chmod 600 sasl_passwd
root@HPVICTUSMANI61:/etc/postfix/sasl# ls
sasl_passwd  sasl_passwd.db
root@HPVICTUSMANI61:/etc/postfix/sasl# |
```



```
manikandan@HPVICTUSMANI61:~$ echo "why it so tough to get this mail" | mail  
-s "am i an idiot" manikandan2982004@gmail.com  
manikandan@HPVICTUSMANI61:~$ |
```





## THE FIRST MAIL

Inbox x



**manikandan2982004@gmail.com**

to me ▼

i have sent a mail through my terminal(running via wsl).which is nice!



Reply



Forward

