Diabetes Risk Prediction Using Health and Lifestyle Indicators

Course: AIMLCZG549 — API-Driven Cloud-Native Solutions **Assignment:** Assignment I **Group:** 49 **Institution:** BITS Pilani, Work Integrated Learning Programmes

This report documents the design, implementation, and verification of a cloud-based, API-accessible data pipeline for diabetes-risk screening from health and lifestyle indicators, delivered as four work packages:

1. Business understanding, dataset selection, and ingestion.
2. Data-quality validation, preprocessing, and scheduled pipeline automation.
3. Exploratory data analysis and an optional predictive-model comparison.
4. Dashboard, APIs, and demonstration.

Team Contribution and Equal Workload Allocation

Each member is listed once below, with their contribution across the full project scope, reflecting the team's agreed equal-effort rebalancing (including work already completed). Effort points are a relative planning unit, not a recorded hour.

Team member	Student email / ID	Contribution
Person 1: Pushadapu Sanjay Kumar	2025ae05898@wilp.bits-pilani.ac.in	Developed the business understanding, verified an
Person 2: Sathish Krishnan V	2025ae05425@wilp.bits-pilani.ac.in	Implemented data-quality checks, preprocessing ar
Person 3: Chezrla Raga Suma	2025ae05828@wilp.bits-pilani.ac.in	Completed EDA interpretation and visual analysis,
Person 4: Bhuvnesh Mishra	2025ae05391@wilp.bits-pilani.ac.in	Implemented and deployed the dashboard and API
Total		**40 pts**

Project and Platform Details

Confirmed project details

- **Approved dataset:** Kaggle Diabetes Health Indicators Dataset (source)
- **Selected cloud platform:** Google Cloud Platform (GCP) — Cloud Composer (managed Apache Airflow) for orchestration and the required two-minute schedule.
- **API documentation/testing tool:** Swagger/OpenAPI
- **Prediction model:** the Random Forest produces the feature-importance results included in the EDA. Section 3.8 also compares it with a Logistic Regression baseline; neither model is deployed as a prediction service.
- **Dashboard and API implementation:** activity 1.5 is supported by the execution information shown on the cloud dashboard. The FastAPI interface documents application details; Composer and Cloud Storage-backed routes retrieve platform data or stored pipeline artifacts as described in Section 4.1.
- **Video submission mechanism:** per the assessment PDF, no length or format is specified; delivery is a shared Google Drive link, not the assignment portal.

The items above summarize the selected implementation and assessment scope.

Platform selection

The platform had to support public dataset ingestion, raw/processed data storage, preprocessing, automated EDA generation, workflow automation on a two-minute schedule, execution logging, cloud dashboarding, at least four application APIs testable through Swagger/OpenAPI or an equivalent client, student/university access, and secure authentication without exposing credentials. The team selected **Google Cloud Platform (GCP)** to meet these requirements.

Detail	Value
Required services	Cloud Composer (managed Apache Airflow), Cloud Storage, Cloud Logging/Monitoring
Cloud Storage bucket	`diabetes-risk-group49-pipeline`
Two-minute scheduling	Cloud Composer DAG (`dags/diabetes_risk_pipeline.py`), `schedule="*/2 * * * *"`; observed task ru
Authentication	Cloud Run runtime service account and Application Default Credentials in production; user ADC for local develo
Failure handling	One retry with a one-minute retry delay; `max_active_runs=1` prevents overlapping runs (Section 2.9)

GCP project, region, and Composer environment details are recorded in the deployment verification table in Section 2.9. BITS also offers an optional AWS ”Virtual Lab Session” for this course; it does not apply here, since the team selected GCP for this deployment.

Continuous deployment (CI/CD)

Deployment of the API and dashboard is automated through `.github/workflows/deploy-gcp.yml`, triggered on every push (and manually via `workflow_dispatch`), running as three dependent GitHub Actions jobs:

1. **`ci`** — installs dependencies, runs the automated test suite (`pytest -q`), and compiles all Python sources (`compileall`) as a quality gate.

2. **build** — runs only if `ci` succeeds and the branch is `main`; builds the Docker image from the repository `Dockerfile` and pushes it to Google Artifact Registry, tagged with the commit SHA.
3. **deploy** — runs only if `build` succeeds; deploys the same image to both Cloud Run services (`diabetes-risk-api`, `diabetes-risk-dashboard`) under the configured runtime service account, then checks that both deployed `/health` endpoints respond successfully with `curl --fail --retry 5` before the workflow is considered successful.


Authentication uses GitHub OIDC via Workload Identity Federation (`google-github-actions/auth`) rather than a long-lived service-account key stored as a GitHub secret — the workflow exchanges a short-lived, GitHub-issued token for GCP credentials at run time. This automates the deployment of the application layer itself, not just the data pipeline's Composer schedule.

Containerization

A single `Dockerfile` (`python:3.11-slim` base) builds one image containing the FastAPI application; the API and dashboard run from that same image, started with different commands (the dashboard container overrides the default `uvicorn` entrypoint to serve `diabetes_risk.dashboard.app:app` instead). This is the same image the CI/CD pipeline above builds and pushes to Artifact Registry. It is also validated locally through `docker-compose.yml`, which runs both services together (API on port `8082`, dashboard on `8083`) with a container health check polling `/health` every 10 seconds, and the dashboard container configured to start only after the API container reports healthy.

Architecture Overview

The solution separates platform-neutral data processing from cloud orchestration and presentation. The same Python pipeline can run locally for development or inside Apache Airflow on Cloud Composer for scheduled execution. Pipeline outputs are written to local folders during development and to the corresponding Cloud Storage locations in the deployed environment.



Execution steps

1. **Select the source:** use the immutable BRFSS CSV from `data/raw/` locally or the matching `data/raw/` object in Cloud Storage when running on Composer.
2. **Run ingestion locally:** the CLI validates the schema and row count, then appends a timestamped SHA-256 record to the ingestion manifest.
3. **Schedule the cloud path:** Cloud Composer hosts the Airflow DAG, configured with `*/2 * * * *`, `catchup=False`, and `max_active_runs=1`; actual runs can take longer than the configured schedule interval, as recorded in Section 2.9.
4. **Execute Task 1:** download the raw object to the task workspace, run data quality, preprocessing, and EDA, then upload processed datasets, reports, and execution logs.
5. **Execute Tasks 2 and 3:** Task 2 trains the Random Forest from the model-ready dataset; Task 3 evaluates the models and uploads comparison artifacts to Cloud Storage. Their measured runtime is included in the overall DAG execution details in Section 2.9.
6. **Serve results:** the FastAPI layer reads pipeline artifacts and GCP runtime details, while the dashboard calls the FastAPI endpoints. The dashboard does not access Cloud Storage directly or hard-code pipeline results.

Component boundaries

Component	Responsibility
`src/diabetes_risk/pipeline/`	Ingestion, validation, preprocessing, EDA, modeling, and logging

Component	Responsibility
`dags/diabetes_risk_pipeline.py`	Task ordering, retries, cadence, and overlap policy
Cloud Storage	Raw, processed, report, model, and execution-log objects
`src/diabetes_risk/api/`	FastAPI routes and built-in API clients
`src/diabetes_risk/dashboard/`	Activity and result presentation through API calls
`tests/`	Automated test suite (pytest) covering ingestion, quality, preprocessing, models, and API routes

The API and dashboard are intentionally downstream of the pipeline outputs. They do not change the raw dataset or run preprocessing themselves. Credentials and project settings are supplied through environment configuration or Application Default Credentials; they are not embedded in the DAG or committed to the repository.

Implementation status: the pipeline, DAG, Cloud Storage hand-off, and Composer schedule are implemented and evidenced in Section 2.9, which also documents the observed run history and end-to-end runtime. The API and dashboard are implemented, deployed, and tested; live API and dashboard evidence is recorded in Section 4. The demonstration video link is included in Section 4.2.

---

1. Business Understanding, Dataset, and Ingestion

1.1 Introduction

This section covers the business problem, dataset selection, and data ingestion that the rest of the pipeline (Sections 2-4) builds on. The pipeline ingests a public health survey snapshot, validates and preprocesses it, runs exploratory data analysis, and re-executes on a fixed schedule. Results are exposed through the cloud dashboard and documented REST API (Swagger/OpenAPI, Section 4). Scheduled reruns use the same 2015 source file unless that input is replaced.

1.2 Project topic

Diabetes Risk Prediction Using Health and Lifestyle Indicators

1.3 Business problem

Healthcare organizations collect large volumes of patient health and lifestyle data — clinical measurements, lifestyle habits, and demographic indicators — but converting that data into early diabetes-risk screening is difficult in practice. Manual chart-by-chart review does not scale across thousands of patient records, so at-risk individuals are often identified only after symptoms are already present or during unrelated visits, rather than through proactive screening.

This can delay preventive action and make consistent review across large populations difficult.

An automated, data-driven risk-screening pipeline addresses this by analyzing health and lifestyle indicators (e.g., BMI, blood pressure, cholesterol, physical activity, general health status) at the population level and surfacing which factors and sub-groups are associated with diabetes prevalence. This project analyzes aggregated survey records; it does not score individual patients.

Who uses the results: primarily healthcare providers and care coordinators, who can use the risk-screening output to prioritize outreach and preventive care for higher-risk patients, and secondarily program administrators, who can use the aggregated dashboard view to understand risk distribution across a patient population. The output is explicitly a **risk-screening signal**, not a diagnosis — final clinical decisions remain with a qualified provider.

1.4 Current and proposed states

Current state

Health and lifestyle data is collected by healthcare organizations and public health surveys. This project uses an existing public survey snapshot to demonstrate population-level analysis; it does not ingest individual patient records or identify specific people for outreach. Without an automated workflow, repeating the same validation and analysis requires manual execution.

Proposed state

The selected BRFSS 2015 dataset flows through an automated cloud pipeline that validates and preprocesses the file and analyzes diabetes indicators on the configured schedule. Each run refreshes results from that same source snapshot; the schedule demonstrates repeatable DataOps execution, not ingestion of new survey data. Pipeline activity and aggregated analysis outputs are available through a cloud dashboard and API.

1.5 Objectives and benefits

Objectives

- Ingest and validate a real, sufficiently large public health dataset (BRFSS 2015 diabetes indicators) with automated checks on schema, target column, and row count.
- Preprocess and clean the data (missing-value handling, encoding, normalization) so it is ready for repeatable analysis.

- Run exploratory data analysis (distribution, correlation, binning, feature importance) to summarize diabetes-risk indicators in the selected dataset.
- Automate the pipeline on a fixed (2-minute) schedule with execution logging, demonstrating repeatable runs against the configured source file.
- Expose pipeline results and at least four application operations through a documented, testable REST API (Swagger/OpenAPI), and visualize them on a cloud dashboard.

Benefits


- **For healthcare providers/care coordinators:** an aggregated view of factors and population segments associated with diabetes prevalence, to inform preventive-care planning.
- **For program administrators:** an aggregated dashboard view of risk distribution across a patient population, supporting resource and program planning.

1.6 Dataset profile

- **Filename:** `diabetes_012_health_indicators_BRFSS2015.csv`
- **Source:** Kaggle — Diabetes Health Indicators Dataset (https://www.kaggle.com/datasets/alexteboul/diabetes-health-indicators-dataset)
- **Row count:** 253,680
- **Column count:** 22
- **Target column:** `Diabetes_012` (0 = no diabetes, 1 = prediabetes, 2 = diabetes)
- **Feature columns:** `HighBP`, `HighChol`, `CholCheck`, `BMI`, `Smoker`, `Stroke`, `HeartDiseaseorAttack`, `PhysActivity`, `Fruits`, `Veggies`, `HvyAlcoholConsump`, `AnyHealthcare`, `NoDocbcCost`, `GenHlth`, `MentHlth`, `PhysHlth`, `DiffWalk`, `Sex`, `Age`, `Education`, `Income`
- **Data types:** All 22 columns are stored as numeric (float64); several are binary flags (0/1) or ordinal codes (e.g. `GenHlth` 1–5, `Age` bucketed 1–13, `Income` 1–8) rather than free-form categories.
- **Missing values:** 0 across all columns (independently verified against the raw CSV).
- **Target-value distribution:** 0.0 → 213,703 (84.2%), 1.0 → 4,631 (1.8%), 2.0 → 35,346 (13.9%) — notably imbalanced, especially the prediabetes class.

Why this is sufficient: At 253,680 rows, even the smallest class (prediabetes, 4,631 rows) comfortably supports EDA (correlation analysis, binning, feature importance) and, if a model is included, a held-out test split — a standard 80/20 split still leaves roughly 900+ minority-class examples for evaluation. The dataset's scale also means a full preprocessing + EDA pass is fast enough to comfortably fit inside the assignment's every-2-minute scheduled run.

Evidence — raw dataset source (Kaggle):



1.7 Data dictionary

All columns are stored as numeric (float64); ”Role” marks the prediction target vs. feature. Ranges below are confirmed against the raw CSV, not assumed.

Column	Business meaning	Values
Diabetes_012	Diabetes status	0 = no diabetes, 1 = prediabetes, 2 = diabe
HighBP	Diagnosed with high blood pressure	0 = no, 1 = yes
HighChol	Diagnosed with high cholesterol	0 = no, 1 = yes
CholCheck	Cholesterol checked in past 5 years	0 = no, 1 = yes
BMI	Body Mass Index	12–98 (continuous)
Smoker	Smoked ≥100 cigarettes in lifetime	0 = no, 1 = yes
Stroke	Ever told had a stroke	0 = no, 1 = yes
HeartDiseaseorAttack	Coronary heart disease or myocardial infarction	0 = no, 1 = yes
PhysActivity	Physical activity in past 30 days (excl. job)	0 = no, 1 = yes
Fruits	Consumes fruit ≥1×/day	0 = no, 1 = yes
Veggies	Consumes vegetables ≥1×/day	0 = no, 1 = yes
HvyAlcoholConsump	Heavy alcohol consumption (men >14, women >7 drinks/week)	0 = no, 1 = yes
AnyHealthcare	Has any healthcare coverage	0 = no, 1 = yes
NoDocbcCost	Needed a doctor but couldn't afford it (past 12 mo.)	0 = no, 1 = yes
GenHlth	Self-rated general health	1 = excellent … 5 = poor (ordinal)
MentHlth	Days of poor mental health, past 30 days	0–30 (count)
PhysHlth	Days of poor physical health, past 30 days	0–30 (count)
DiffWalk	Serious difficulty walking/climbing stairs	0 = no, 1 = yes
Sex	Sex	0 = female, 1 = male
Age	13-level age bracket	1 = 18–24 … 13 = 80+ (ordinal)
Education	Education level	1 = none/kindergarten … 6 = college 4+ ye
Income	Household income bracket	1 = <$10k … 8 = $75k+ (ordinal)

1.8 Suitability and limitations

Why this dataset suits the assignment

- **Scale:** 253,680 rows is large enough for statistically meaningful correlation analysis, binning, and feature importance, and still leaves a workable minority-class sample (4,631 rows) if a held-out model evaluation is added.
- **Feature mix:** binary flags (`HighBP`, `Smoker`, …), ordinal scales (`GenHlth`, `Age`, `Education`, `Income`), and continuous counts (`BMI`, `MentHlth`, `PhysHlth`) together give real material for every required EDA activity — correlation, univariate/bivariate analysis, and, once binned (Section 3.4), encoding.
- **Target:** a 3-class label (`Diabetes_012`) supports the required feature-importance work (Section 3.8) and, given its imbalance, gives the EDA and model evaluation a genuine class-imbalance problem to analyze rather than an artificially clean one.
- **Automation-friendly:** no missing values and a manageable file size (~23 MB) mean a full preprocessing + EDA pass runs quickly — important for the every-2-minute scheduled workflow.

Source and licensing

Derived from the CDC's public **Behavioral Risk Factor Surveillance System (BRFSS) 2015** survey, cleaned and republished on Kaggle by Alex Teboul (https://www.kaggle.com/datasets/alexteboul/diabetes-health-indicators-dataset) and also mirrored on the UCI Machine Learning Repository. The original 2015 BRFSS survey collected responses from 441,455 individuals across 330 features; this cleaned file keeps 253,680 responses and 21 feature variables plus the target.

License: CC0: Public Domain (confirmed directly on the Kaggle dataset page). No attribution or usage restriction applies; the CDC's original BRFSS data is credited as the underlying source in the References section.

Limitations

- **Self-report bias:** all fields are self-reported survey answers (smoking, alcohol use, activity, etc.), which are known to be subject to recall error and social-desirability bias (e.g., under-reporting alcohol consumption or over-reporting physical activity).
- **Dataset age:** collected in 2015 — over a decade old, so absolute rates (e.g., smoking, obesity) may not reflect current populations.
- **Generalization:** BRFSS is a U.S.-only telephone survey; findings should not be generalized to non-U.S. populations, and telephone-survey methodology can under-represent some demographic groups.
- **Bias and fairness:** `Income`, `Education`, and `AnyHealthcare`/`NoDocbcCost` reflect healthcare-access disparities as much as biological risk — correlations involving these fields should be discussed as access/equity signals, not purely clinical ones. `Sex` is recorded as a binary field only, per the original survey design.
- **Not a diagnosis:** all outputs remain a **risk-screening signal**, not a clinical diagnosis, as established in Section 1.3.

1.9 Data ingestion evidence

Implemented as `src/diabetes_risk/pipeline/ingestion.py` (`ingest()`), covering the required checks: file opens successfully, all 21 expected feature columns plus the `Diabetes_012` target are present, and the row count is recorded and compared against the verified profile (253,680). The raw CSV is never modified or duplicated — each ingestion run instead

appends a timestamped, SHA-256-hashed entry to `data/raw/ingestion_manifest.json`, so the exact file used stays verifiable and any future drift (a different file swapped in under the same name) would be visible immediately as a hash or row-count change.

Run with:

```
python -m diabetes_risk.pipeline ingest --source data/raw/diabetes_012_health_indicators_BRFSS2015.csv --ma
```

(The screenshot shows an equivalent earlier CLI form; the underlying ingestion logic is unchanged.)

Verified result (first import):


```
{
  "source_path": "data/raw/diabetes_012_health_indicators_BRFSS2015.csv",
  "sha256": "a971809d0786d2d7d7f6070f83dfe8af9d860ea33a79e0e2701c8a49f78f9861",
  "row_count": 253680,
  "column_count": 22,
  "columns_match_expected": true,
  "target_present": true,
  "row_count_matches_expected": true
}
```


Processed output (the preprocessing stage in Section 2) is written to `data/processed/`, kept separate from `data/raw/` so the original file is always preserved untouched. Covered by 5 automated tests in `tests/test_ingestion.py` (valid file, manifest append behavior, missing target column, missing feature column, missing file).

Evidence — terminal run:



The tests shown passing are the ingestion suite; the full current suite (Section 2.11) passes 34 tests with 1 skipped. The ingestion run against the real dataset matches the result recorded above exactly (same SHA-256 hash, same row/column counts), confirming it is reproducible outside the verification environment too.

In summary, the business problem, dataset profile, and data dictionary are established and verified against the real file, suitability and limitations are documented with a confirmed CC0 license, and the raw data has been ingested, validated, and logged, providing a verified foundation for the preprocessing stage in Section 2.

---

2. Data Quality, Preprocessing, and Pipeline Automation

2.1 Scope

This section covers **data-quality validation, preprocessing, automated EDA generation, DataOps execution, two-minute scheduling, execution logging, verification, and handoff to the EDA and modeling stage (Section 3)**. The implementation is deliberately platform-neutral so that the same Python processing code can run locally or under Apache Airflow, with Google Cloud Composer as the deployed production orchestration environment (Section 2.9).

The raw dataset from Section 1 remains immutable. All transformed datasets, analytical artifacts, and execution logs are written to separate `data/processed/` and `data/outputs/` locations.

2.2 Data-quality validation

A reusable validation module is implemented in `src/diabetes_risk/pipeline/data_quality.py`. The module validates the approved dataset before preprocessing and produces machine-readable quality results.

The implemented checks include:

- Schema and target-column validation
- Row and column counts
- Pandas data types
- Summary statistics
- Missing-value counts and percentages
- Exact duplicate-record detection
- Target-value validation (`Diabetes_012` must contain only 0, 1, or 2)
- Known numeric-range validation
- Binary indicator validation (0/1)

Verified source dataset: `data/raw/diabetes_012_health_indicators_BRFSS2015.csv`

Quality check	Verified result
Input records	253,680
Input columns	22
Missing values	0
Exact duplicate records	23,899 (9.42%)
Invalid target values	0
Invalid known numeric-range values	0
Invalid binary values	0
Quality status	PASS_WITH_WARNINGS

The duplicate records are treated as a **non-fatal quality warning**, rather than a schema or data-validity failure. The raw file is preserved unchanged, while exact duplicates are removed during preprocessing.

Summary statistics and data types (verified against the real 229,781-row cleaned dataset; all 22 columns are stored as `float64`):

Column	Mean	Std	Min	25%	Median	75%	Max
Diabetes_012	0.33	0.72	0	0	0	0	2
HighBP	0.45	0.50	0	0	0	1	1
HighChol	0.44	0.50	0	0	0	1	1
CholCheck	0.96	0.20	0	1	1	1	1
BMI	28.69	6.79	12	24	27	32	98
Smoker	0.47	0.50	0	0	0	1	1
Stroke	0.04	0.21	0	0	0	0	1
HeartDiseaseorAttack	0.10	0.30	0	0	0	0	1
PhysActivity	0.73	0.44	0	0	1	1	1
Fruits	0.61	0.49	0	0	1	1	1
Veggies	0.79	0.40	0	1	1	1	1
HvyAlcoholConsump	0.06	0.24	0	0	0	0	1
AnyHealthcare	0.95	0.23	0	1	1	1	1
NoDocbcCost	0.09	0.29	0	0	0	0	1
GenHlth	2.60	1.06	1	2	3	3	5
MentHlth	3.51	7.71	0	0	0	2	30
PhysHlth	4.68	9.05	0	0	0	4	30
DiffWalk	0.19	0.39	0	0	0	0	1
Sex	0.44	0.50	0	0	0	1	1
Age	8.09	3.09	1	6	8	10	13
Education	4.98	0.99	1	4	5	6	6
Income	5.89	2.09	1	5	6	8	8

This table gives concrete values for the ”Pandas data types” and ”Summary statistics” checks listed above, rather than naming them as checklist items only; it was computed directly from `data/processed/diabetes_cleaned.csv` for this report.

Quality artifacts generated by the pipeline are:

```
data/outputs/quality/data_quality.json
data/outputs/quality/missing_values.csv
```

2.3 Preprocessing and cleaned-data generation

The transformation contract is implemented in `src/diabetes_risk/pipeline/preprocessing.py`. The preprocessing flow is applied consistently on every pipeline execution:

1. Normalize column names to lowercase snake case for downstream processing consistency.
2. Detect and remove exact duplicate records, retaining the first occurrence.
3. Median-impute numeric missing values where required.
4. Mode-impute non-numeric values where required.
5. One-hot encode non-numeric categorical fields where required.
6. Preserve existing binary and ordinal indicators in interpretable form.
7. Keep the target separate from feature standardization.
8. Write an analytical cleaned dataset for the EDA stage (Section 3).
9. Write a separate standardized model-ready dataset for optional downstream model work.

For the current approved dataset, no imputation was required because the raw file contains **zero missing values**. Likewise, no one-hot categorical encoding was required in the current run because the dataset fields are already represented as numeric, binary, or ordinal values.

The current execution produced:

Output	Result
Input rows	253,680
Exact duplicates removed	23,899
Cleaned analytical rows	229,781
Cleaned columns	22
Model-ready rows	229,781
Model-ready columns	22

2.4 Analytical cleaned dataset vs. model-ready dataset

Two processed datasets are intentionally maintained rather than applying the same transformation to both analytical and modeling use cases.

`data/processed/diabetes_cleaned.csv` is the primary handoff to the EDA stage (Section 3). It retains the original, interpretable feature scales so that BMI, health-day counts, age groups, and other indicators remain meaningful in EDA charts and tables.

`data/processed/diabetes_model_ready.csv` is a separate downstream modeling output. Z-score standardization is applied to the continuous/count fields `BMI`, `MentHlth`, and `PhysHlth`, while binary and ordinal indicators remain interpretable and the target is not scaled.

This separation satisfies the assignment's normalization/standardization requirement without making the EDA outputs harder to interpret. It also leaves the optional model-comparison stage (Section 3.8) free to use the model-ready dataset.

The preprocessing module writes its transformation summary to:

`data/processed/preprocessing_report.json`

2.5 Automated EDA artifact generation

This section automates the **generation** of the EDA artifacts in `src/diabetes_risk/pipeline/eda.py`. Section 3 remains responsible for the analytical interpretation and final EDA narrative.

Each successful pipeline run refreshes the following outputs:

- Summary statistics
- Missing-value summary
- Target-distribution table and chart
- Feature-distribution charts
- Correlation matrix
- Selected bivariate tables and charts
- Age/BMI binned features
- EDA metadata

The automated feature-distribution outputs cover eight selected indicators:

- BMI
- Age
- General Health
- High Blood Pressure
- High Cholesterol
- Physical Activity
- Cholesterol Check
- Smoking

The automated bivariate outputs cover six selected relationships against the diabetes target:

- BMI vs. target
- Age vs. target
- High Blood Pressure vs. target
- High Cholesterol vs. target
- Physical Activity vs. target
- General Health vs. target

This design allows the EDA artifacts to be refreshed automatically without requiring manual notebook reruns or chart regeneration downstream.

2.6 End-to-end DataOps runner

`src/diabetes_risk/pipeline/runner.py` provides the single end-to-end execution path used for both local execution and Airflow orchestration:

```
Raw CSV
  ↓
Data-quality validation
  ↓
Preprocessing
  ├── diabetes_cleaned.csv
  └── diabetes_model_ready.csv
  ↓
Automated EDA artifact generation
  ↓
Structured execution log
```

The runner records the status of each execution and writes outputs to predictable locations. A verified full-dataset local execution finished in **5.10 seconds**. It read all **253,680** raw records and produced the expected 229,781-row processed outputs.

2.7 Verified full-dataset execution result

This table documents a successful end-to-end run against the complete raw CSV. Its input and output counts match the quality-validation results in Section 2.2 and the preprocessing results in Section 2.3.

Execution metric	Verified result
Input file	`data/raw/diabetes_012_health_indicators_BRFSS2015.csv`
Execution status	SUCCESS
Quality status	PASS_WITH_WARNINGS
Runtime	**5.10 seconds**

The post-duplicate-removal target distribution produced by this run is interpreted in Section 3.3 (distinct from the raw, pre-deduplication distribution in Section 1.6).

The execution record is stored at:

`data/outputs/execution/run_<run_id>.json`
`data/outputs/execution/latest_run.json`

The generated EDA artifacts, quality report, cleaned dataset, and model-ready dataset all correspond to this same full-dataset execution.

2.8 Execution logging and monitoring information

`src/diabetes_risk/pipeline/logging_utils.py` implements structured JSON execution logging. Each pipeline run records:

- Unique run ID
- Start timestamp
- End timestamp
- Runtime duration
- Execution status
- Number of input/processed records
- Number of output records
- Duplicate count
- Errors
- Warnings
- Quality status
- Processed-output locations
- EDA-output locations

Execution artifacts are written under:

`data/outputs/execution/run_<run_id>.json`
`data/outputs/execution/latest_run.json`

A trimmed excerpt of the measured counts and status from an execution log:


```
{
  "duration_seconds": 9.623993,
  "status": "SUCCESS",
  "input_rows": 253680,
  "output_rows": 229781,
  "duplicates_detected": 23899,
  "errors": [],
  "warnings": [
```

```
    "One or more non-fatal data-quality checks require review."
  ]
}
```

2.9 Airflow orchestration and two-minute schedule

`dags/diabetes_risk_pipeline.py` implements the orchestration layer using **Apache Airflow**. Each task invokes the same platform-neutral Python runner and pipeline modules used for local execution.

The core pipeline logic in `src/diabetes_risk/pipeline/` contains no GCP SDK imports, GCS-specific operators, Vertex AI operators, or cloud credentials, so the same code runs unchanged locally or under Airflow. The orchestration wrapper in `dags/diabetes_risk_pipeline.py` is the one GCP-specific layer — it uses the Google Cloud Storage client to move data between tasks, detailed below — and it contains no Vertex AI operators and no credentials embedded in the repository.

The configured schedule is:

`*/2 * * * *`

The DAG schedule is configured to trigger every two minutes. Each run performs data-quality checks, preprocessing, automated EDA generation, and the optional Random Forest/model-evaluation tasks described in Section 3.8. The observed total task runtime is recorded separately below; the schedule interval and task runtime describe different aspects of execution.


The reliability configuration includes:

- `catchup=False` to avoid replaying historical schedules during deployment.
- `max_active_runs=1` to prevent overlapping pipeline executions.
- One retry with a one-minute retry delay for transient task failures.

The production deployment target is **Google Cloud Composer**, which provides managed Apache Airflow, and is deployed and verified below. The Python processing modules remain platform-neutral, while `dags/diabetes_risk_pipeline.py` uses the Google Cloud Storage client to download raw inputs and upload processed datasets, reports, models, and execution logs between Composer tasks. Deployment and architecture details are documented in this report and the root README.


Cloud Composer deployment verification The DAG was deployed to a live **Google Cloud Composer** environment to verify the configured schedule under managed-orchestration infrastructure, separate from local Airflow unit testing.

Deployment detail	Value
GCP project	`diabetes-risk-group49`
Composer environment	`diabetes-risk-env`
Location	`us-central1`
Airflow version	`2.11.1`
Confirmed schedule interval (Composer console)	`*/2 * * * *`



The Cloud Storage bucket managed by the environment is used as the data hand-off between Airflow tasks: the raw dataset is read from `data/raw/`, and processed/EDA/model outputs are written back to `data/processed/` and `data/outputs/`.

A selected Composer run completed successfully across all three tasks: `data_quality_preprocessing_and_eda`, `random_forest`, and `model_evaluation`.



The deployed `/api/v1/schedule` endpoint also returns the Composer environment state. The Cloud Console page is available at https://console.cloud.google.com/managed-airflow/environments/detail/us-central1/diabetes-risk-env/dags?project=diabetes-risk-group49.

Schedule and runtime observations: the DAG's configured schedule is `*/2 * * * *`, which defines a two-minute trigger interval. The times shown in the Composer job history (9:48, 9:50, 9:54, 9:58, 10:00, and 10:04) are job completion times, not scheduled trigger times; they therefore should not be used to infer the schedule interval. For the selected successful run, the three tasks took 17.7 s + 64.0 s + 79.1 s, or about 2 minutes 41 seconds end to end. This is the measured runtime of that job, separate from its configured trigger interval. Most of the runtime came from Random Forest training and model evaluation; the required data-quality/preprocessing/EDA work alone completes locally in about 5–10 seconds (Section 2.6).

2.10 Configuration and local execution

Environment-driven configuration is provided through `src/diabetes_risk/pipeline/config.py`, along with a unified command-line entry point through `src/diabetes_risk/pipeline/cli.py`.

The pipeline can therefore be executed locally without GCP dependencies. The main commands are:

```
python -m diabetes_risk.pipeline ingest
python -m diabetes_risk.pipeline run
```

The default configuration uses the repository's raw dataset and separates processed and reporting outputs. Environment variables can override the dataset, target column, processed-output directory, and report-output directory when the same code is deployed to another environment.

2.11 Verification and test results

This implementation was verified using both automated tests and an end-to-end run against the real repository dataset.

Automated verification (full current suite, independently rerun for this report):

```
34 passed, 1 skipped
```

The one skipped test is Airflow-specific because an Airflow runtime is not installed in the local development environment. Airflow is intentionally kept outside the core Python dependency set because it is expected to be supplied by the orchestration runtime, such as Cloud Composer.

Additional validation completed successfully:

- Python source compilation using `compileall`
- End-to-end execution against the actual 253,680-row raw CSV
- Generated processed datasets and EDA artifacts verified at the expected output locations

2.12 Evidence summary

This report records local validation and Cloud Composer evidence.

The verified local evidence includes:

- Dataset validation
- Summary statistics and data types
- Missing-value results
- Duplicate-record results
- Invalid-value results
- Preprocessing results
- Cleaned dataset output
- Model-ready output
- Automated EDA outputs
- Structured execution log
- Airflow DAG configuration

Deployment evidence: the Composer screenshots in Section 2.9 confirm the `*/2 * * * *` schedule on an Active DAG and show a selected run with all three tasks successful. The history and task runtime are included as execution details.

2.13 Summary

The selected dataset has been validated, quality checks and preprocessing are automated, cleaned and model-ready datasets are generated, EDA artifacts are refreshed by the workflow, and structured execution logging is implemented. The Airflow DAG is configured for a two-minute schedule with an explicit overlapping-run policy; measured task runtime and Composer run history are reported in Section 2.9. The available automated verification suite passed at the time documented above. Dashboard and API details are covered in Section 4.

---

3. Exploratory Data Analysis and Optional Model

3.1 Scope

This section covers interpretation of the automated EDA outputs from Section 2, plus an additional predictive-model comparison built on top of the model-ready dataset. Dashboard and API details are covered in Section 4.

Source: the EDA interpretation and feature/correlation charts in Sections 3.2-3.7 are drawn from `Diabetes_EDA_Person3.pptx`, included in the assignment project. The target-distribution chart below was refreshed from the automated EDA run against the raw CSV after exact-duplicate removal; its values match the 229,781-row analytical dataset documented in this report. Section 3.8's model implementation, evaluation, and evidence were rerun for this report (see Section 3.9 for the reproducibility distinction between the two).

3.2 Dataset overview and completeness

The interpretation is based on the analytical dataset produced in Section 2 after exact-duplicate removal:

Metric	Value
Analyzed records	**229,781**
Variables	**22**
Target classes	**3** (`Diabetes_012`)
Missing values	**0** (0.0% across every field)


The 21 features (plus the `Diabetes_012` target) group into five categories: clinical (high BP, high cholesterol, cholesterol check, stroke, heart disease), lifestyle (physical activity, smoking, fruit/vegetable intake, heavy alcohol consumption), healthcare access (any healthcare coverage, cost-related doctor avoidance), health status (BMI, general/mental/physical health, mobility), and demographic (age band, education, income, sex).

Because the missing-value summary reports zero missing observations across all 22 analyzed variables, no rows required exclusion for missingness at this stage; this conclusion applies specifically to the processed analytical dataset used for these outputs.

3.3 Target distribution

The target is strongly imbalanced, particularly for the prediabetes class. Figures below are **post-duplicate-removal** (229,781 rows); see Section 1.6 for the raw, pre-deduplication distribution:


`Diabetes_012`	Records	Percentage
0 — No diabetes	190,055	82.71%
1 — Prediabetes	4,629	2.01%
2 — Diabetes	35,097	15.27%



Modeling implication: with this degree of imbalance, accuracy alone is not a reliable measure of model quality. Class-level precision, recall, and F1-score must be reported alongside it — this is confirmed empirically in Section 3.8 below.

3.4 Feature distribution analysis

The population combines high cardiometabolic exposure with widespread reported physical activity:



Selected distribution statistics:

Feature	Mean	Median	Range / Scale
BMI	28.69	27	12 to 98
Age band	8.09	8	1 to 13
General health	2.60	3	1 to 5

High BP and high cholesterol each affect nearly half of respondents (45.4% and 44.2% respectively), while 73.3% report physical activity, 46.6% have smoked at least 100 cigarettes in their lifetime (the `Smoker` field's definition — not current smoking), 10.3% report heart disease/attack, and 4.5% report a prior stroke.

Binned features

The pipeline also generates two categorical binnings of continuous/ordinal features on every run, written to `data/outputs/eda/binned_fe` a 4-level `AgeGroup` derived from the existing 13-level age bracket (Section 1.7: level 1 = 18–24, level 13 = 80+), and a 4-level `BMIGroup` using standard clinical BMI categories (Underweight < 18.5, Normal 18.5–25, Overweight 25–30, Obese ≥ 30).

AgeGroup (age-bracket levels)	Records	Share	Diabetes rate (class 2)
1-4	34,839	15.16%	3.32%
5-7	54,489	23.71%	10.76%
8-10	86,205	37.52%	19.03%
11-13	54,248	23.61%	21.52%


BMIGroup	Records	Share	Diabetes rate (class 2)
Underweight	3,053	1.33%	5.54%
Normal	73,736	32.09%	7.26%
Overweight	81,555	35.49%	14.00%
Obese	71,437	31.09%	25.42%

Diabetes prevalence rises with both bins: from 3.32% in the youngest age-bracket group to 21.52% in the oldest, and from 5.54% among underweight respondents to 25.42% among the obese — both consistent with the positive BMI and age correlations reported in Section 3.5. These counts were independently recomputed for this report by running the pipeline against the real 229,781-row cleaned dataset, to verify the binning output empirically rather than describing it from the artifact list alone.

Encoding. `generate_eda()` now one-hot encodes the two binned categorical features as part of every scheduled run — `AgeGroup` into 4 indicator columns and `BMIGroup` into 4 indicator columns — by passing `bin_frame` through the same `preprocessing.encode_features()` used elsewhere in the codebase, and writes the result to `binned_features_encoded.csv` alongside a `binned_features_encoding_report` entry in `eda_metadata.json`. Re-run directly against the real 229,781-row cleaned dataset for this report, the encoded sums reproduce the binning tables above exactly (`AgeGroup_8–10` sums to 86,205; `BMIGroup_Obese` sums to 71,437). No categorical encoding was needed for the pipeline's other 21 features, since they arrive already numeric, binary, or ordinal (Section 2.3); the binned age/BMI groups are the dataset's only genuinely categorical (non-ordinal) fields, so this is where the assignment's encoding activity (1.4) applies.

3.5 Correlation analysis

Associations with `Diabetes_012` are modest; no single feature dominates:




Strongest positive	r	Strongest negative	r
General health	+0.285	Income	−0.147
High BP	+0.262	Education	−0.108
BMI	+0.212	Physical activity	−0.103
Difficulty walking	+0.211	Heavy alcohol consumption	−0.067
High cholesterol	+0.203		

Correlation indicates association, not causation.

3.6 Bivariate analysis

Six priority features were compared against the ordered diabetes outcome:



General health has the strongest of the six associations (+0.285). High BP (+0.262), BMI (+0.212), and high cholesterol (+0.203) all rise with the ordered target, and age is positively associated (+0.185). Physical activity is inversely associated (−0.103).

Interpretation boundary: these values summarize linear association; they do not prove a causal effect or substitute for group-level significance tests.

3.7 Consolidated EDA findings

- **Data quality:** 229,781 complete records; zero missing values across all 22 analyzed fields.
- **Target risk:** 82.71% of records are class 0; prediabetes is only 2.01%, creating severe class imbalance.
- **Health signals:** general health, high BP, BMI, mobility difficulty, and high cholesterol show the largest positive associations with the target.
- **Negative associations:** income, education, and physical activity show the largest negative correlations with the target — read as access/equity signals for income and education (Section 1.8), not purely protective clinical effects, and as association rather than a causal claim (Section 3.5).


3.8 Optional model implementation and evaluation

A Random Forest is trained to produce the feature-importance evidence required by activity 1.4; it is then compared against a Logistic Regression baseline on accuracy, precision, recall, and F1 as additional, non-required analysis — the assessment PDF does not ask for a model comparison or a deployed prediction service.

Implementation: `src/diabetes_risk/pipeline/randomforestclassifier.py` trains a Random Forest (200 trees, `random_state=42`, no `class_weight` argument set, i.e. classes are left unweighted) on an 80/20 stratified train/test split (183,824 train / 45,957 test records) and saves feature importances. `src/diabetes_risk/pipeline/model_evaluation.py` reproduces the same split, trains a Logistic Regression model (`class_weight="balanced"`, all 21 feature columns `StandardScaler`-normalized — including the binary/ordinal fields that Section 2.4's model-ready dataset otherwise leaves unscaled, since Logistic Regression benefits from uniformly scaled inputs while Random Forest does not need it), and evaluates both models side by side. Because only Logistic Regression is trained with class-weight balancing, the comparison below reflects both the algorithm difference and this imbalance-handling difference, not the algorithm alone. Both are exposed as CLI subcommands (`python -m diabetes_risk.pipeline randomforestclassifier` and `python -m diabetes_risk.pipeline model_evaluation`) and as separate Cloud Composer DAG tasks (Section 2.9).

Verified local run result (executed against the real 229,781-row model-ready dataset):

Model	Accuracy	Balanced Accuracy	Precision (weighted)	Recall (weighted)	F1 (weighted)
Logistic Regression	62.92%	**51.35%**	83.69%	62.92%	70.33%
Random Forest	**82.47%**	38.39%	77.42%	82.47%	78.74%



Random Forest has the higher raw accuracy but the lower balanced accuracy — this is the class-imbalance effect flagged in Section 3.3, and it shows up directly in the per-class results. Random Forest's classification report scores 0.0 recall and F1 for class 1 (prediabetes): it never *correctly* predicts a prediabetes case (0 of 926 true prediabetes cases). It does output class 1 sixty-one times in total, all of them wrong, so its class-1 precision is also 0.0. Logistic Regression, trained with `class_weight="balanced"`, trades off overall accuracy for materially better minority-class **recall**: 30.3% on class 1 and 59.3% on class 2 — but that recall comes at a steep **precision** cost, not a class-0-precision cost as such trade-offs are sometimes assumed to work: only 3.2% of Logistic Regression's class-1 predictions are actually correct (281 of 8,659), and its class-0 **recall** drops to 64.4% (vs. 96.2% for Random Forest), even though its class-0 **precision** is actually slightly *higher* than Random Forest's (94.3% vs. 84.9%).

Random Forest confusion matrix	Pred 0	Pred 1	Pred 2
True 0	36,568	55	1,389
True 1	820	**0**	106
True 2	5,682	6	1,331

Logistic Regression confusion matrix	Pred 0	Pred 1	Pred 2
True 0	24,469	6,729	6,814
True 1	265	281	380
True 2	1,206	1,649	4,164


Per-class precision and recall (recomputed directly from the confusion matrices above, since the weighted metrics in the summary table mask class-1 performance entirely):

Model	Class	Precision	Recall
Random Forest	0 — No diabetes	84.90%	96.20%
Random Forest	1 — Prediabetes	0.00%	0.00%
Random Forest	2 — Diabetes	47.10%	18.96%
Logistic Regression	0 — No diabetes	94.33%	64.37%
Logistic Regression	1 — Prediabetes	3.25%	30.35%
Logistic Regression	2 — Diabetes	36.66%	59.32%

Conclusion: neither model is production-ready for the minority prediabetes class, and accuracy alone would have hidden this — Random Forest's 82.5% accuracy looks strong until the per-class breakdown shows it never correctly identifies a prediabetes case, and Logistic Regression's "materially better" 30.3% recall on that same class still means fewer than 1 in 30 of its prediabetes predictions are right. This confirms the EDA's own modeling-implication warning (Section 3.3) with actual model results rather than assumption. Note also that this comparison mixes two differences at once — the algorithm (Random Forest vs. Logistic Regression) and the imbalance handling (`class_weight="balanced"` was applied only to Logistic Regression) — so it should be read as "a balanced linear baseline vs. an unweighted ensemble," not as a clean like-for-like algorithm comparison.

Covered by automated tests in `tests/test_randomforestclassifier.py` (verifies the model artifact, feature-importance CSV/plot, and that the target column is excluded from feature importances) and `tests/test_model_evaluation.py` (verifies both models train, all comparison/report/confusion-matrix artifacts are written, and that evaluation fails clearly if the Random Forest model has not been trained first). Both use synthetic fixtures via pytest's `tmp_path`; the full current suite passes 34 tests with 1 skipped (Section 2.11).

Feature importance (Random Forest, top 10 of 21):



Feature	Importance
BMI	0.183
Age	0.124
Income	0.102
Physical health (days)	0.085
Education	0.073
General health	0.065
Mental health (days)	0.065
High BP	0.040
Fruits	0.035
Smoker	0.034

Note that Random Forest's feature-importance ranking (BMI, age, income) differs from the EDA's linear-correlation ranking (general health, high BP, BMI). Some of this is genuine: impurity-based feature importance captures non-linear and interaction effects that Pearson correlation (Section 3.5) does not. But this importance metric (mean decrease in impurity, the scikit-learn default) is also known to be biased toward high-cardinality and continuous features over low-cardinality binary ones — which is a more parsimonious explanation for why continuous/wide-range fields (`BMI`, `Age`, `Income`, `PhysHlth`) rank above binary fields like `HighBP` here, despite `HighBP` having a stronger linear correlation with the target. A permutation-importance or SHAP analysis was not run for this report and would be needed to separate the two effects conclusively.

3.9 Known limitations

- The feature-distribution, correlation, and bivariate charts in Sections 3.4-3.6 remain static images from the Person 3 analysis deck; no checked-in script regenerates those exact presentation charts. The target-distribution chart in Section

3.3 and the binned-feature table in Section 3.4 were refreshed from the automated EDA pipeline. The model-evaluation charts and metrics in Section 3.8 were independently regenerated and are reproducible via the two CLI commands listed above.
- The optional model (Section 3.8) is not integrated into the automated `run()` pipeline; it runs as separate CLI commands and Composer DAG tasks, consistent with its optional, additive analysis scope.
- The Composer schedule is configured for every two minutes; measured task runtime and observed run history are documented in Section 2.9.
- Logistic Regression's ”materially better” minority-class recall (Section 3.8) comes with very low precision (3.25% for class 1); neither model would be usable in a real screening tool without further tuning, threshold adjustment, or a different modeling approach.
- The deployed API (Section 4) is intentionally public and unauthenticated for grading convenience; it is read-only and exposes no write operations or secrets beyond a project ID and a service-account email, but this is not the authentication posture a production deployment would use.
- Every scheduled run reprocesses the same static, immutable 2015 survey file rather than new incoming data; the two-minute automation demonstrates the required DataOps mechanics, not a live data-ingestion pipeline reacting to new records.

---

4. Dashboard, APIs, and Demonstration

4.1 Dashboard and application APIs

The public dashboard is served by `src/diabetes_risk/dashboard/app.py` and obtains data from the separate FastAPI service. Its activity view contains:

- **Latest Completed Composer Workflow Status** and **Latest Completed DAG Duration**, selected from the newest completed Composer DAG run (`success` or `failed`). A currently running run stays visible in history and does not replace these summary values.
- **Composer DAG Run History**, showing up to 10 runs from the Composer Airflow REST API. It displays run ID, state, UTC start/end timestamps, whole-DAG duration, and a control to retrieve that run's task-instance details.
- **Processed Records**, duplicate removals, quality status, processing errors, and processing warnings. These values come from GCS pipeline manifests and quality/preprocessing reports. The record total shown is the input count (253,680); the cleaned output count is 229,781 and is returned by the dataset endpoint.
- **Composer Environment**, which displays the environment name, state, and Airflow version from the Composer Environments API. The `*/2 * * * *` cadence shown beside it is the DAG's configured schedule, not a field returned by that API.

A model-comparison chart is also shown when model artifacts are available; it is additional analysis. All displayed run and task timestamps use UTC. Composer DAG run history and GCS pipeline execution history are separate: the dashboard's 10-row history is Composer-backed, while `/api/v1/pipeline/history` returns processing manifests from GCS and is not the dashboard's run-history table.

Public services: Dashboard · Swagger/OpenAPI

The dashboard reads the API base URL from `DIABETES_API_BASE_URL`. In production the API uses its Cloud Run runtime service account and Application Default Credentials to access Cloud Storage, the Composer Environments API, the Composer-hosted Airflow REST API, and Cloud Monitoring. The account must have the corresponding GCP permissions and Composer web-server/Airflow access. If configuration or access is unavailable, GCP-backed dashboard values can show an error even while the public page itself loads.

The four dashboard detail calls and their sources are:

Application detail	API route	Underlying source	What it returns
Composer workflow	`GET /api/v1/workflow`	Composer-hosted Airflow REST API	Up to 10 recent DAG runs, inc
Latest pipeline execution	`GET /api/v1/runs/latest`	GCS execution manifest	Latest processing status, dura
Dataset and data quality	`GET /api/v1/dataset`	GCS quality and preprocessing reports	Input/output dimensions, dupli
Composer deployment details	`GET /api/v1/schedule`	Cloud Composer Environments API	Environment state, Airflow ver

The dashboard's task expansion calls `GET /api/v1/workflow/{dag_run_id}/tasks`, which reads task states and timings from Composer's Airflow REST API. `GET /api/v1/pipeline/history` reads GCS processing manifests. `GET /api/v1/model` reads model-comparison and feature-importance artifacts from GCS. `GET /api/v1/health/environment` reads Composer health metrics from Cloud Monitoring. `/health` and `/api/v1/metadata` provide supporting service information. The FastAPI endpoints are the application's documented interface; their underlying data is retrieved from the GCP APIs or stored pipeline artifacts identified above.

4.2 Deployed evidence and demonstration


The screenshots below document the deployed Cloud Run dashboard and Swagger/OpenAPI responses. The dashboard and Swagger UI loaded, and the four detail routes shown below returned HTTP 200 in the captured responses. The Composer

workflow response contains 10 DAG runs. In the captured view, the newest run is in progress while the summary cards continue to show the latest completed run and its duration.


Deployed services:

- Dashboard: diabetes-risk-dashboard
- Swagger/OpenAPI: diabetes-risk-api/docs


1. Composer workflow history — `GET /api/v1/workflow` returned 10 Composer DAG runs (HTTP 200). The screenshot shows the workflow request and response.




2. Latest processing execution — `GET /api/v1/runs/latest` returned the latest GCS processing manifest (HTTP 200), including `SUCCESS` status and 253,680 input records. This is processing-run information and is distinct from Composer DAG run history.




3. Dataset and quality — `GET /api/v1/dataset` returned HTTP 200 with 253,680 input rows, 229,781 output rows, 23,899 duplicates removed, no missing values after preprocessing, and `PASS_WITH_WARNINGS` quality status. The warning reflects duplicates detected in the source, which preprocessing removes; the raw file remains unchanged.



4. Composer environment details — `GET /api/v1/schedule` returned HTTP 200 with the environment state and Airflow version. The two-minute cadence is configured in the DAG and is displayed separately from the environment API response.



The dashboard screenshot shows the Composer DAG Run History table with an expanded run and its task instances:



Demonstration video: Watch the Group 49 project demonstration

---

5. Conclusion and Limitations

Conclusion. The repository implements the business understanding, ingestion, preprocessing, EDA (including binning, encoding, and feature importance), a DataOps workflow configured on a two-minute schedule, a cloud dashboard, and four documented API details. Section 2.9 reports the configured schedule, observed run history, and measured task runtime. The deployed dashboard uses Composer DAG history with expandable task details and a completed-run summary, and retains GCS processing manifests through separate endpoints. Live API and dashboard responses and refreshed screenshots are included in Section 4.2. The optional model comparison is reported with its limitations. The demonstration video link is included in Section 4.2.

Cross-cutting limitations, consolidating the per-section notes in Sections 2.9, 3.9, and 4.1:

- Neither comparison model is precise enough on the minority prediabetes class to be usable in a real screening tool (Section 3.8).

References

1. Centers for Disease Control and Prevention (CDC). *Behavioral Risk Factor Surveillance System (BRFSS) 2015.* Original survey data underlying the dataset used in this project.
2. Teboul, A. *Diabetes Health Indicators Dataset.* Kaggle, cleaned and republished from CDC BRFSS 2015 data. https://www.kaggle.com/datasets/alexteboul/diabetes-health-indicators-dataset (CC0: Public Domain).
3. UCI Machine Learning Repository. *CDC Diabetes Health Indicators* (mirror of the same underlying BRFSS 2015 data).
4. Pedregosa, F. et al. *Scikit-learn: Machine Learning in Python.* Journal of Machine Learning Research, 12, 2011. (Random Forest and Logistic Regression implementations, Section 3.8.)
5. Apache Software Foundation. *Apache Airflow Documentation.* https://airflow.apache.org/docs/ (DAG orchestration, Section 2.9.)
6. Google Cloud. *Cloud Composer, Cloud Storage, Cloud Run, and Cloud Monitoring Documentation.* https://cloud.google.com/docs (platform services used throughout Sections 2 and 4.)