

Many To One XML

(Advised to do it by your own)

Many To One Annotation

QueryN1.java

```
package hibernatemapping;

import javax.persistence.CascadeType;
import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;
import javax.persistence.ManyToOne;

@Entity
public class QueryN1 {
    @Id
    @GeneratedValue(strategy=GenerationType.AUTO)
    @Column(length = 10)
    private int id;
    @Column(length = 20)
    private String qname;
    @ManyToOne(cascade = CascadeType.ALL)
    private ResponseN1 responses;
    public int getId() {
        return id;
    }
    public String getQname() {
        return qname;
    }
    public ResponseN1 getResponses() {
        return responses;
    }
    public void setId(int id) {
        this.id = id;
    }
    public void setQname(String qname) {
        this.qname = qname;
    }
    public void setResponses(ResponseN1 responses) {
        this.responses = responses;
    }
}
```

```
}
```

ResponseN1.java

```
package hibernatemapping;

import javax.persistence.Column;
import javax.persistence.Entity;
import javax.persistence.GeneratedValue;
import javax.persistence.GenerationType;
import javax.persistence.Id;

@Entity
public class ResponseN1 {
    @Id
    @GeneratedValue(strategy=GenerationType.AUTO)
    @Column(length = 10)
    private int id;

    @Column(length = 30)
    private String responsestr;

    @Column(length = 15)
    private String postedby;

    public int getId() {
        return id;
    }

    public String getResponsestr() {
        return responsestr;
    }

    public String getPostedby() {
        return postedby;
    }

    public void setId(int id) {
        this.id = id;
    }

    public void setResponsestr(String responsestr) {
        this.responsestr = responsestr;
    }

    public void setPostedby(String postedby) {
```

```

        this.postedby = postedby;
    }
}

```

hibernate.cfg.xml

```

<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE hibernate-configuration PUBLIC
    "-//Hibernate/Hibernate Configuration DTD 3.0//EN"
    "http://www.hibernate.org/dtd/hibernate-configuration-
3.0.dtd">
<hibernate-configuration>
    <session-factory>
<property
name="hibernate.current_session_context_class">thread</property>
        <property
name="hibernate.connection.driver_class">oracle.jdbc.driver.OracleDriv
er</property>
        <property
name="hibernate.connection.password">oracle</property>
        <property
name="hibernate.connection.url">jdbc:oracle:thin:@localhost:1521:xe</p
roperty>
        <property
name="hibernate.connection.username">system</property>
        <property
name="hibernate.dialect">org.hibernate.dialect.Oracle10gDialect</prope
rty>
        <property name="hbm2ddl.auto">create</property>
        <property name="show_sql">true</property>

    </session-factory>
</hibernate-configuration>

```

AppQRN1.java

```

package hibernatemapping;

import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.Transaction;
import org.hibernate.cfg.Configuration;
import org.hibernate.service.ServiceRegistry;
import org.hibernate.service.ServiceRegistryBuilder;

```

```

public class AppQRN1 {
    public static void main(String[] args) {

        QueryN1 query1 = new QueryN1();
        query1.setQname("Query1");

        QueryN1 query2 = new QueryN1();
        query2.setQname("Query2");

        ResponseN1 r = new ResponseN1();
        r.setResponsestr("Response");
        r.setPostedby("John");

        query1.setResponses(r);
        query2.setResponses(r);

        Configuration conf = new
Configuration().configure("hibernate.cfg.xml")
                .addAnnotatedClass(QueryN1.class)
                .addAnnotatedClass(ResponseN1.class);

        ServiceRegistry sr = new ServiceRegistryBuilder()
                                .applySettings(conf.getProperties())
                                .buildServiceRegistry();
        SessionFactory sf1 = conf.buildSessionFactory(sr);
        Session s1 = sf1.openSession();
        Transaction txn1 = s1.beginTransaction();

        s1.save(query1);
        s1.save(query2);

        txn1.commit();
    }
}

```

```
SQL Plus

SQL> select * from QueryN1;

   ID QNAME      RESPONSES_ID
-----
    1 Query1         2
    3 Query2         2

SQL> select * from ResponseN1;

   ID POSTEDBY      RESPONSESTR
-----
    2 John          Response

SQL>
```

QueryN1.java

```
@ManyToOne(cascade = CascadeType.DETACH)
```

AppQRN1Delete.java

```
package hibernatemapping;

import org.hibernate.Session;
import org.hibernate.SessionFactory;
import org.hibernate.cfg.Configuration;
import org.hibernate.service.ServiceRegistry;
import org.hibernate.service.ServiceRegistryBuilder;

public class AppQRN1Delete {
public static void main(String[] args) {
    Configuration conf = new
Configuration().configure("hibernate.cfg.xml")
                .addAnnotatedClass(QueryN1.class)
                .addAnnotatedClass(ResponseN1.class);

    ServiceRegistry sr = new ServiceRegistryBuilder()
                        .applySettings(conf.getProperties())
                        .buildServiceRegistry();
```

```
SessionFactory sf1 = conf.buildSessionFactory(sr);
Session s1 = sf1.openSession();
s1.beginTransaction();
```

```
Object query = s1.get(QueryN1.class, 3);
```

```
if(query != null) {
    s1.delete(query);
    System.out.println("Query deleted");
}
```

```
s1.getTransaction().commit();
}
}
```

SQL Plus

SQL> select * from QueryN1;

ID	QNAME	RESPONSES_ID
1	Query1	2

SQL> select * from ResponseN1;

ID	POSTEDBY	RESPONSESTR
2	John	Response

SQL>