

Spring Boot RESTful API Learning Guide

Response: Masterclass: Spring Boot RESTful API (Part 1: Beginner Level)

Welcome, future Full-Stack Engineers! Over my 20+ years of training thousands of B.Tech, MCA, and M.Tech students, I've learned one universal truth: **Mastering the fundamentals is 90% of the battle**. This guide breaks down every core concept of Spring Boot and RESTful web services into digestible, real-world pieces. Let's dive in!

1. Introduction to REST Architecture

Definition

REST stands for **RE**presentational **S**tate **T**ransfer. It is an architectural style (not a protocol or programming language) proposed by Roy Fielding in 2000 for designing networked applications.


Purpose

REST allows two different systems (e.g., a React frontend and a Java backend) to communicate over HTTP using standard formats like **JSON** or **XML** without needing to know each other's internal implementation details.

How It Works

1. The **Client** sends an HTTP request specifying an action and a Resource URI (e.g., GET /api/v1/students).
2. The **Server** processes the request, fetches data from the database, converts it into a representation (usually JSON), and returns it with an HTTP status code.

Architecture & Flow Diagram



+-----+

Real-World Example

Think of a **Restaurant Menu**:

- **Client:** You (the customer).
- **Server:** The Kitchen.
- **REST API / Waiter:** Takes your order from the menu (URI), brings it to the kitchen, and delivers your food (JSON representation) back to your table.

Advantages & Disadvantages

- **Advantages:** Decoupled client-server structure, highly scalable, light payload (JSON), language-agnostic.
- **Disadvantages:** No built-in security standards (relies on HTTP/TLS), no built-in messaging state across calls.

Best Practices & Common Mistakes

- **Best Practice:** Use plural nouns for resource endpoints (e.g., /users, not /getUser).
- **Common Mistake:** Putting actions in the URI (e.g., /deleteUser/101 instead of using DELETE /users/101).

Interview Questions

1. *What does REST stand for, and is it a protocol or an architectural style?*
 - **Answer:** Architectural style that uses HTTP protocols.
2. *Can a REST API return XML instead of JSON?*
 - **Answer:** Yes, REST is format-agnostic, though JSON is the industry standard.

2. REST vs SOAP

Definition & Comparison

- **REST:** Lightweight architectural style using standard HTTP protocols and flexible formats (JSON/XML).
- **SOAP (Simple Object Access Protocol):** Rigid, strict protocol relying exclusively on XML and formal WSDL contracts.

Feature	REST	SOAP
Type	Architectural Style	Formal Protocol
Data Format	JSON, XML, Plain Text, HTML	XML Only

Feature	REST	SOAP
Protocol	HTTP / HTTPS	HTTP, SMTP, TCP, etc.
Bandwidth	Lightweight (Fast)	Heavy XML wrappers (Slower)
Stateful/Stateless	Strictly Stateless	Supports Stateful operations
Security	HTTPS, OAuth2, JWT	WS-Security, HTTPS

When to Use What?

- Use **REST** for web apps, mobile apps, and modern microservices.
- Use **SOAP** for legacy enterprise systems, financial networks, and strict contract banking applications.

3. HTTP Protocol

Definition

HTTP (Hypertext Transfer Protocol) is an application-layer protocol that powers data communication on the World Wide Web.

Purpose

It provides a standardized rulebook for clients (browsers/apps) and servers to structure request messages and response messages.

Anatomy of HTTP Communication

An HTTP message consists of:

1. **Request Line / Status Line:** HTTP Method + URI + Version (or Status Code).
2. **Headers:** Metadata (e.g., Content-Type: application/json, Authorization: Bearer <token>).
3. **Body:** Payload data (used in POST, PUT, PATCH).

Key HTTP Status Codes

- **2xx Success:** 200 OK, 201 Created, 204 No Content
- **3xx Redirection:** 301 Moved Permanently
- **4xx Client Errors:** 400 Bad Request, 401 Unauthorized, 403 Forbidden, 404 Not Found
- **5xx Server Errors:** 500 Internal Server Error, 503 Service Unavailable

4. HTTP Methods

HTTP methods specify the **action** to perform on a resource.

Method	Action	Request Payload?	Success Code	Status
GET	Retrieve resource(s)	No	200 OK	
POST	Create a new resource	Yes	201 Created	
PUT	Replace an existing resource completely	Yes	200 OK / 204 No Content	
PATCH	Update part of an existing resource	Yes	200 OK	
DELETE	Remove a resource	No	200 OK / 204 No Content	

Code Analogy (Spring Boot Mapping)

- GET → @GetMapping
- POST → @PostMapping
- PUT → @PutMapping
- PATCH → @PatchMapping
- DELETE → @DeleteMapping

5. Idempotent vs Non-Idempotent Methods

Definition

An HTTP method is **idempotent** if making multiple identical requests leaves the server in the exact same state as making a single request.

Effect(N requests)=Effect(1 request)for $N \geq 1$

HTTP Method Idempotency		
Method	Idempotent?	Explanation
GET	YES	Only reads data; state never changes.
PUT	YES	Replaces resource; multiple calls produce the same final state.
DELETE	YES	Deleting ID 5 once or 10 times results in ID 5 being gone.
PATCH	VARIES	Can be idempotent, but can also increment

		values if implemented dynamically.
POST	NO	Calling POST 5 times creates 5 separate records in the DB.

6. REST Constraints

To qualify as a true RESTful API, an application must follow **6 core constraints**:

graph TD

```

A[REST Constraints] --> B[Client-Server]
A --> C[Stateless]
A --> D[Cacheable]
A --> E[Uniform Interface]
A --> F[Layered System]
A --> G[Code-on-Demand Optional]

```


1. **Client-Server Separation:** UI and database concerns are isolated.
2. **Statelessness:** Every HTTP request must contain **all** the context necessary to process it. Server stores no client session context.
3. **Cacheability:** Responses must define themselves as cacheable or non-cacheable to improve efficiency.
4. **Uniform Interface:** Standardized URIs, HTTP methods, and payload representations.
5. **Layered System:** The client cannot tell whether it is connected directly to the end server or an intermediate proxy/load balancer.
6. **Code-on-Demand (Optional):** Server can temporarily extend client functionality by transferring executable code (e.g., JavaScript scripts).

7. Spring Boot Architecture

Definition

Spring Boot is an extension of the Spring Framework that eliminates boiler-plate configuration through **Auto-Configuration** and embedded servers.

Architectural Layers



8. Spring Boot Project Structure

Standard Maven/Spring layout follows a strict hierarchy:

```
student-management-system/
├── pom.xml
├── src/
│   ├── main/
│   │   ├── java/
│   │   │   ├── com/
│   │   │   │   ├── edtech/
│   │   │   │   │   └── studentapp/
│   │   │   │   │       └── StudentApplication.java    <-- Entry Point
│   │   │   │   │       (@SpringBootApplication)
│   │   │   │   ├── controller/                <-- REST Endpoints
│   │   │   │   │   └── StudentController.java
│   │   │   │   ├── service/                    <-- Business Logic
│   │   │   │   │   └── StudentService.java
│   │   │   │   └── repository/                 <-- Data Access (Spring
│   │   │   │       └── StudentRepository.java
│   │   │   │       └── model/                  <-- Entities/DB Models
│   │   │   │           └── Student.java
│   │   └── resources/
│   │       ├── application.properties          <-- App Config
│   │       ├── static/                       <-- Static Assets
│   │       └── templates/                     <-- UI Templates (if any)
│   └── test/
│       └── java/                             <-- Unit / Integration
└── Tests
```

9. Maven Dependencies (pom.xml)

What is Maven?

Maven is a build automation tool that manages project dependencies, libraries, and compilation lifecycles using XML.

Key pom.xml Snippet for Web & JPA:

```
<project xmlns="http://maven.apache.org/POM/4.0.0"
  xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
  xsi:schemaLocation="http://maven.apache.org/POM/4.0.0
https://maven.apache.org/xsd/maven-4.0.0.xsd">
  <modelVersion>4.0.0</modelVersion>

  <parent>
    <groupId>org.springframework.boot</groupId>
    <artifactId>spring-boot-starter-parent</artifactId>
```

```

        <version>3.2.2</version>
        <relativePath/>
    </parent>

    <groupId>com.edtech</groupId>
    <artifactId>studentapp</artifactId>
    <version>0.0.1-SNAPSHOT</version>
    <name>studentapp</name>

    <properties>
        <java.version>17</java.version>
    </properties>

    <dependencies>
        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-web</artifactId>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-data-jpa</artifactId>
        </dependency>

        <dependency>
            <groupId>com.h2database</groupId>
            <artifactId>h2</artifactId>
            <scope>runtime</scope>
        </dependency>

        <dependency>
            <groupId>org.springframework.boot</groupId>
            <artifactId>spring-boot-starter-test</artifactId>
            <scope>test</scope>
        </dependency>
    </dependencies>
</project>

```

10. Spring Initializr

Definition

start.spring.io is a web-based bootstrap generator provided by the Spring team to spin up new Spring Boot projects instantly.

Steps to Bootstrap

1. Select Project Type: **Maven**
2. Language: **Java**
3. Spring Boot Version: **3.x.x (Stable)**

4. Fill Packaging Metadata (Group, Artifact, Packaging: Jar, Java: 17)
5. Add Dependencies: Spring Web, Spring Data JPA, H2 Database.
6. Click **Generate** → Download ZIP → Unzip and import into IntelliJ IDEA / Eclipse.

11. application.properties

Purpose

Used to configure application settings such as server port, database connectivity, and logging behavior without touching Java source code.

Example Configuration (src/main/resources/application.properties)

```
# Server Port Configuration
server.port=8080


# H2 Database Settings
spring.datasource.url=jdbc:h2:mem:studentdb
spring.datasource.driverClassName=org.h2.Driver
spring.datasource.username=sa
spring.datasource.password=password

# Enable H2 Web Console at http://localhost:8080/h2-console
spring.h2.console.enabled=true

# Hibernate SQL Generation Options (create-drop, update, validate)
spring.jpa.hibernate.ddl-auto=update
spring.jpa.show-sql=true
spring.jpa.properties.hibernate.format_sql=true
```

12. Layered Architecture

Layered architecture separates concerns so components remain modular and unit-testable.



13. Spring Data JPA

Definition

JPA (Java Persistence API / Jakarta Persistence) is an ORM (Object-Relational Mapping) specification. **Spring Data JPA** is an abstraction layer on top of ORM providers (like Hibernate) that eliminates repetitive SQL query code.

Standard Repository Abstraction

By extending `JpaRepository<EntityClass, PrimaryKeyType>`, you automatically gain built-in methods like `save()`, `findById()`, `findAll()`, `deleteById()`, without writing a single SQL query!

14. End-to-End CRUD Operations (Complete Code Example)

Let's build a functional **Student Management REST API**.

1. Entity (Student.java)

```
package com.edtech.studentapp.model;

import jakarta.persistence.*;

@Entity
@Table(name = "students")
public class Student {

    @Id
    @GeneratedValue(strategy = GenerationType.IDENTITY)
    private Long id;

    @Column(name = "first_name", nullable = false)
    private String firstName;

    @Column(name = "email", nullable = false, unique = true)
    private String email;

    // Constructors
    public Student() {}

    public Student(String firstName, String email) {
        this.firstName = firstName;
        this.email = email;
    }

    // Getters and Setters
    public Long getId() { return id; }
    public void setId(Long id) { this.id = id; }

    public String getFirstName() { return firstName; }
    public void setFirstName(String firstName) { this.firstName = firstName; }

    public String getEmail() { return email; }
    public void setEmail(String email) { this.email = email; }
}
```

2. Repository (StudentRepository.java)

```
package com.edtech.studentapp.repository;

import com.edtech.studentapp.model.Student;
import org.springframework.data.jpa.repository.JpaRepository;
import org.springframework.stereotype.Repository;
```

```

@Repository
public interface StudentRepository extends JpaRepository<Student, Long> {
    // Custom finder methods can be defined here if needed
}

```

3. Service Layer (StudentService.java)

```

package com.edtech.studentapp.service;

import com.edtech.studentapp.model.Student;
import com.edtech.studentapp.repository.StudentRepository;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.stereotype.Service;

import java.util.List;

@Service
public class StudentService {

    private final StudentRepository studentRepository;

    // Constructor Injection (Best Practice)
    @Autowired
    public StudentService(StudentRepository studentRepository) {
        this.studentRepository = studentRepository;
    }

    public Student createStudent(Student student) {
        return studentRepository.save(student);
    }

    public List<Student> getAllStudents() {
        return studentRepository.findAll();
    }

    public Student getStudentById(Long id) {
        return studentRepository.findById(id)
            .orElseThrow(() -> new RuntimeException("Student not found with
ID: " + id));
    }

    public Student updateStudent(Long id, Student updatedStudent) {
        Student existing = getStudentById(id);
        existing.setFirstName(updatedStudent.getFirstName());
        existing.setEmail(updatedStudent.getEmail());
        return studentRepository.save(existing);
    }

    public void deleteStudent(Long id) {
        Student existing = getStudentById(id);

```

```

        studentRepository.delete(existing);
    }
}

```

4. Controller Layer (StudentController.java)

```

package com.edtech.studentapp.controller;

import com.edtech.studentapp.model.Student;
import com.edtech.studentapp.service.StudentService;
import org.springframework.beans.factory.annotation.Autowired;
import org.springframework.http.HttpStatus;
import org.springframework.http.ResponseEntity;
import org.springframework.web.bind.annotation.*;

import java.util.List;

@RestController
@RequestMapping("/api/v1/students")
public class StudentController {

    private final StudentService studentService;

    @Autowired
    public StudentController(StudentService studentService) {
        this.studentService = studentService;
    }

    // CREATE - POST
    @PostMapping
    public ResponseEntity<Student> createStudent(@RequestBody Student student)
    {
        Student savedStudent = studentService.createStudent(student);
        return new ResponseEntity<>(savedStudent, HttpStatus.CREATED);
    }

    // READ ALL - GET
    @GetMapping
    public ResponseEntity<List<Student>> getAllStudents() {
        return ResponseEntity.ok(studentService.getAllStudents());
    }

    // READ BY ID - GET
    @GetMapping("/{id}")
    public ResponseEntity<Student> getStudentById(@PathVariable Long id) {
        return ResponseEntity.ok(studentService.getStudentById(id));
    }

    // UPDATE - PUT
    @PutMapping("/{id}")
    public ResponseEntity<Student> updateStudent(@PathVariable Long id,

```

```

@RequestBody Student studentDetails) {
    Student updated = studentService.updateStudent(id, studentDetails);
    return ResponseEntity.ok(updated);
}

// DELETE - DELETE
@DeleteMapping("/{id}")
public ResponseEntity<String> deleteStudent(@PathVariable Long id) {
    studentService.deleteStudent(id);
    return ResponseEntity.ok("Student deleted successfully!");
}
}

```

5. Main Class (StudentApplication.java)

```

package com.edtech.studentapp;

import org.springframework.boot.SpringApplication;
import org.springframework.boot.autoconfigure.SpringBootApplication;

@SpringBootApplication
public class StudentApplication {
    public static void main(String[] args) {
        SpringApplication.run(StudentApplication.class, args);
    }
}

```

Testing API Endpoints (cURL / Postman Commands)

1. Create Student (POST)

- **URL:** `http://localhost:8080/api/v1/students`
- **Headers:** `Content-Type: application/json`
- **Body:**

```

{
  "firstName": "Rahul",
  "email": "rahul@example.com"
}

```

- **Status Response:** 201 Created

2. Get All Students (GET)

- **URL:** `http://localhost:8080/api/v1/students`
- **Response Body:**

```

[
  {
    "id": 1,
    "firstName": "Rahul",
    "email": "rahul@example.com"
  }
]

```

```
}  
]
```

Best Practices & Common Mistakes

Common Pitfalls to Avoid

1. **Field Injection Pitfall:** Avoid using `@Autowired` on fields directly (`@Autowired private StudentRepository repo;`). Always prefer **Constructor Injection** to ensure immutability and ease of unit testing.
2. **Returning Entities Directly:** Returning Database Entities directly to API clients leaks internal DB schemas. (In Part 2, we will introduce DTOs - Data Transfer Objects).
3. **Ignoring HTTP Status Codes:** Don't return 200 OK for resource creation (use 201 Created) or resource deletion failures (use 404 Not Found).

Key Takeaways & Summary

1. **REST Architecture** decouples client and server using standardized HTTP methods over stateless endpoints.
 2. **Spring Boot** automates configuration via spring-boot-starter dependencies and embedded containers (Tomcat).
 3. **Layered Architecture** separates responsibilities: **Controller** handles web requests, **Service** holds business rules, **Repository** handles database interactions, and **Entity** models database records.
 4. **Spring Data JPA** provides out-of-the-box database operations, removing the need for manual SQL writing for standard CRUD operations.
-