

Status	Finished
Started	Sunday, 2 November 2025, 1:50 PM
Completed	Sunday, 2 November 2025, 3:20 PM
Duration	1 hour 30 mins

Question **1**

Correct

A single line L with a set of space separated values indicating distance travelled and time taken is passed as the input. The program must calculate the average speed S (with precision upto 2 decimal places) and print S as the output.

Note: The distance and time taken will follow the format DISTANCE@TIMETAKEN. DISTANCE will be in kilometers and TIMETAKEN will be in hours.

Input Format:

The first line contains L.

Output Format:

The first line contains the average speed S.

Boundary Conditions:

Length of L will be from 3 to 100.

Example Input/Output 1:

Input:

60@2 120@3

Output:

36.00 kmph

Explanation:

Total distance = $60+120 = 180$ km.

Total time taken = $2+3 = 5$ hours.

Hence average speed = $180/5 = 36.00$ kmph

For example:

Input	Result
60@2 120@3	36.00 kmph

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int d,t;
4     double D=0,T=0;
5     while(scanf("%d@d",&d,&t)==2){ D+=d;T+=t;}
6     if(T) printf("%.2f kmph",D/T);
7     return 0;
8 }
```

	Input	Expected	Got	
✓	60@2 120@3	36.00 kmph	36.00 kmph	✓

Passed all tests! ✓

Question **2**

Correct

The program must accept two numbers X and Y and then print their HCF/GCD.

Input Format:

The first line denotes the value of X.
The second line denotes the value of Y.

Output Format:

The first line contains the HCF of X and Y.

Boundary Conditions:

$1 \leq X \leq 999999$
 $1 \leq Y \leq 999999$

Example Input/Output 1:

Input:

30
40

Output:

10

Example Input/Output 2:

Input:

15
10

Output:

5

For example:

Input	Result
30 40	10

Answer: (penalty regime: 0 %)

```
1 | #include<stdio.h>
2 | int main() {
```

```

2 | int main() {
3 |     int x,y;
4 |     scanf("%d %d",&x,&y);
5 |     while(x!=y){
6 |         if(x>y)x-= y;
7 |         else y-=x;
8 |     }
9 |     printf("%d",x);
10 |    return 0;
11 | }

```

	Input	Expected	Got	
✓	30 40	10	10	✓

Passed all tests! ✓

Question **3**

Correct

A string S is passed as input. S will contain two integer values separated by one of these alphabets - A, S, M, D where

- A or a is for addition
- S or s is for subtraction
- M or m is for multiplication
- D or d is for division

The program must perform the necessary operation and print the result as the output. (Ignore any floating point values just print the integer result.)

Input Format:

The first line contains S.

Output Format:

The first line contains the resulting integer value.

Boundary Conditions:

Length of S is from 3 to 100.

Example Input/Output 1:

Input:

5A11

Output:

16

Explanation:

As the alphabet is A, 5 and 11 are added giving 16.

Example Input/Output 2:

Input:

120D6

Output:

20

Example Input/Output 3:

Input:

1405d10

Output:

140

For example:

Input	Result
5A11	16
120D6	20
1405d10	140

Answer: (penalty regime: 0 %)

```
1  #include <stdio.h>
2  #include <ctype.h>
3  int main() {
4      int a,b;
5      char op;
6      scanf("%d%c%d",&a,&op,&b);
7      op=toupper(op);
8      if(op=='A')
9          printf("%d",a+b);
10     else if(op=='S')
11         printf("%d",a-b);
12     else if(op=='M')
13         printf("%d",a*b);
14     else if(op=='D')
15         printf("%d",a/b);
16     return 0;
17 }
18
19
```

	Input	Expected	Got	
✓	5A11	16	16	✓
✓	120D6	20	20	✓
✓	1405d10	140	140	✓

Passed all tests! ✓