RAJALAKSHMI ENGINEERING COLLEGE

Sanjeev Kanna R 251801292-2025-AIDS S2

Started on	Thursday, 6 August 2026, 10:07 AM
State	Finished
Completed on	Thursday, 6 August 2026, 10:26 AM
Time taken	19 mins
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
```

```
    int s =1;
```

```
    while(s <= n)
    {
         i++;
         s += i;
     }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

Ace editor not ready. Perhaps reload page?

Falling back to raw text area.

```
#include<stdio.h>
int main(){
    int n;
    int s=1;
    int i=1;
    int c=2;
    scanf("%d",&n);
    while(s<=n){
        c++;
        i++;
        c++;
        s+=i;
        c++;
    }
    c++;
    printf("%d",c);

}
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Sanjeev Kanna R 251801292-2025-AIDS S2

Started on	Thursday, 6 August 2026, 10:26 AM
State	Finished
Completed on	Thursday, 6 August 2026, 10:33 AM
Time taken	7 mins 1 sec
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

```
#include<stdio.h>
int main(){
    int n;
    scanf("%d",&n);
    int c=0;
    if(n==1){
        c++;
        //printf("*");
        c++;
    }
    else
    {
        c++;
     for(int i=1; i<=n; i++)
     {
         c++;
       for(int j=1; j<=n; j++)
       {
          c++;
          //printf("*");
          c++;
          //printf("*");
          c++;
          break;
       }
       c++;
     }
     c++;
```

```
29    }
30    printf("%d",c);
31  }
32
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Sanjeev Kanna R 251801292-2025-AIDS S2

Started on	Thursday, 6 August 2026, 10:34 AM
State	Finished
Completed on	Thursday, 6 August 2026, 11:17 AM
Time taken	42 mins 57 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```
#include<stdio.h>
int main(){
    int num;
    scanf("%d",&num);
    int c=0;

    int i;
    for (i = 1; i <= num;++i)
    {
        c++;//i<=num;
        c++;
     if (num % i== 0)
        {
            c++;
          //printf("%d ", i);

        }
     }
     c++;
     printf("%d",c);
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Sanjeev Kanna R 251801292-2025-AIDS S2

Started on	Thursday, 6 August 2026, 11:27 AM
State	Finished
Completed on	Tuesday, 25 August 2026, 12:44 PM
Time taken	19 days 1 hour
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

void function(int n)
{
    int c = 0;

    c++;  // count the initial execution

    for (int i = n / 2; i < n; i++)
    {
        c++;  // i < n condition

        for (int j = 1; j < n; j = 2 * j)
        {
            c++;  // j < n condition

            for (int k = 1; k < n; k = k * 2)
            {
                c++;  // k < n condition
                c++;  // c++ statement
            }

            c++;  // final k < n check
        }

        c++;  // final j < n check
    }

    c++;  // final i < n check

    printf("%d", c);
}

int main()
{
    int n;
    scanf("%d", &n);
```

```
39      function(n);
40
41      return 0;
42  }
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Sanjeev Kanna R 251801292-2025-AIDS S2

Started on	Thursday, 17 September 2026, 10:06 AM
State	Finished
Completed on	Thursday, 17 September 2026, 10:18 AM
Time taken	12 mins 23 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

```c
#include <stdio.h>

void reverse(int n)
{
    int rev = 0, remainder;
    int count = 0;

    count++;

    while (n != 0)
    {
        count++;
        remainder = n % 10;

        count++;
        rev = rev * 10 + remainder;

        count++;
        n /= 10;

        count++;
    }

    count++;
    count++;

    printf("%d", count);
}

int main()
{
    int n;
    scanf("%d", &n);
    reverse(n);
    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course