Correcting the ACE Request Scheduler and Measuring Communication-Memory Congestion in a Multi-Core Quantum Mesh

BTP, MARS Lab, IIT Guwahati

Draft of 24 October 2026

Contents

Executive summary 4

How to read this report 6

1 Scope and method 7
- 1.1 What this report is about . . . 7
- 1.2 Ground rules followed . . . 7
- 1.3 How the work was organised . . . 8

2 How and why: method, decisions and corrections 9
- 2.1 The approach in one page . . . 9
- 2.2 Why each major decision was taken . . . 9
- 2.3 Mistakes made on the way, and how they were found . . . 10
- 2.4 What is assumed, and what is not . . . 11

3 Background 12
- 3.1 The pipeline . . . 12
- 3.2 ACE and the native SeQUeNCe backend . . . 12
- 3.3 Policies . . . 12
- 3.4 Parameters in force . . . 12

4 What was wrong in the legacy simulator 14
- 4.1 Reservation aliasing (F2) . . . 14
- 4.2 Event order is undefined (F9) . . . 15
- 4.3 Livelock under polling (F10) . . . 15
- 4.4 What the audit did not cover . . . 15

5 The corrections and how they were verified 16
- 5.1 Making requests distinct (Gate 2) . . . 16
- 5.2 The per-qubit request manager (Gate 3) . . . 16
- 5.3 The checker . . . 16
- 5.4 Verification . . . 17
- 5.5 One latency definition for both schedulers . . . 17
- 5.6 The budget study rerun (Gate 6) . . . 17

6 Where the congestion is: heatmap and endpoint-versus-relay split 18
- 6.1 Per-core congestion . . . 18
- 6.2 Own demand against relay demand (Experiment 2) . . . 20
- 6.3 Every capacity, both countings . . . 22

7 Latency, fidelity and congestion across memory budgets (Experiment 1) 28
7.1 Design . . . 28
7.2 Controls . . . 28
7.3 What congestion costs on-demand requests . . . 29
7.4 Congestion as waiting . . . 32
7.5 Pre-generation against on-demand, and the fidelity price . . . 34
7.6 Sensitivity to the physical parameters . . . 36
7.7 Workload by workload . . . 36

8 The memory cut-off time 39
8.1 The timers . . . 39
8.2 What a discard does to compiler pairs . . . 39
8.3 What a discard does to the autonomous caches . . . 40
8.4 Decisions . . . 40

9 Can offline routing reduce the congestion? 41
9.1 Method . . . 41
9.2 Structural result . . . 42
9.3 Simulated effect . . . 42
9.4 The torus . . . 43
9.5 What can and cannot be concluded . . . 43

10 The torus topology 45
10.1 What changes . . . 45
10.2 Results . . . 45

11 Run times 48

12 Why dynamic pre-generation can be slower than on-demand 50
12.1 What the old, serialized scheduler showed . . . 50
12.2 What the code does with a pre-generated pair . . . 51
12.3 Measurements . . . 52
12.3.1 The extra latency is waiting, not generation . . . 53
12.3.2 What holds the memories . . . 53
12.3.3 Requests with a ready pair still wait . . . 54
12.3.4 Why a prepared pair waits so long . . . 54
12.4 What does and does not change the result . . . 55
12.5 Other mapping seeds and other benchmarks . . . 55
12.6 What this establishes, and what it does not . . . 56

13 ODG, dynamic, CGP and ACGP compared on nine benchmarks 57
13.1 What was run . . . 57
13.2 Checks . . . 58
13.3 Latency . . . 58
13.4 Delivered fidelity . . . 61
13.5 Wasted pairs and readiness . . . 63
13.6 Waiting . . . 67
13.7 The torus . . . 69
13.8 Where dynamic lies . . . 76

14 Fresh Golden Study: Contract and Execution Record 77

15 Limits and open decisions 78

A Parameters in force **79**
A.1 Where the physical values come from, and the open decision 80

B Reproducing the results **81**

C Experiment 1: every cell **83**

D Experiment 2: per-core tables **86**

E Repository map **88**

F Commit timeline **91**

G Glossary and questions a reader may have **93**
G.1 Glossary 93
G.2 Questions a reader may have 94

Executive summary

The question. In a multi-core quantum computer, moving a logical qubit between cores consumes an entangled (EPR) pair, and every core has only a few communication memories. When many moves need the same core at once, requests wait: *congestion*. This report documents what was wrong with how the ACE simulator measured that, how it was corrected, and what the corrected simulator says about ten benchmark circuits on a 4×4 mesh of cores.

What was wrong. ACE split every layer of requests into batches with at most one request per core, so a core never held more than one request and the memory budget could not bind; the earlier budget study therefore could not measure congestion. That serialization also hid a second fault: two requests that looked alike (same endpoints, window, size and fidelity) were treated as one booking by SeQUeNCe's reservation code (four requests on one link took up to 68 ms instead of 2.4 ms). Ten findings are in Chapter 4.

What was built. A reservation-identity fix; a per-qubit request manager with event-driven admission (hops of one qubit in order, different qubits concurrent, a request starts only when both of its cores have a free memory); an event log and an invariant checker; one latency definition valid for every scheduler; and drivers that record every parameter and every run time. The legacy simulator is untouched and still reproduces its 164-row baseline exactly after every change.

Headline results (Experiments 1 and 2).

- **The memory budget now binds.** On-demand latency used to be identical at every budget; it now falls with memory. QFT: 14.42 ms with one memory per core, 4.72 with two, 1.59 with four (the modelled value) and 1.13 with 32, where it saturates (64 memories reproduces 32). The floor of about 1.1–1.2 ms is generation time.
- **Who pays.** At the modelled four memories the on-demand penalty against saturation is +40% for QFT, +12% for QAOA, +5% for graph state and about 1% or less for the rest. GHZ, Bernstein–Vazirani and BMW never wait.
- **Pre-generation is not free.** Dynamic compiler pre-generation reaches 0.25 ms at 32 memories, but its compiler bank takes budget -1 memories, so for the congested workloads it is slower than on-demand until 8 to 16 memories, and it lowers the delivered fidelity (QFT down to 0.9185 and the random circuit, the lowest, to 0.907, against 0.9498 on-demand).
- **Where congestion comes from (Experiment 2).** At four memories nearly all overload is *relay* overload: a core is overloaded because routes pass through it, not because routes start or end there. Endpoint demand alone peaks at 4–5, total demand at 24. With one memory, own demand matters (QFT 77% own-overload).
- **Structure predicts cost.** The heatmap's overload share and the simulated on-demand penalty are strongly rank-correlated (Spearman $\rho = 0.85$ over 60 points).

Is compiler-driven pre-generation good? (Chapters 12 and 13.) Against the autonomous protocols CGP and ACGP, yes. On nine benchmarks, on the mesh and on the torus, dynamic pre-generation has lower latency than both at every modelled memory count (the better of CGP and ACGP takes 1.5 to 2.5 times as long at four memories), wastes no pair against 34 to 89% of pairs for CGP and ACGP on the mesh at four memories, and delivers higher fidelity (0.916 to 0.927 against 0.865 to 0.913 at four memories). **Against on-demand generation, only partly.** Dynamic is faster on five of the nine benchmarks at four memories and on all of them from sixteen memories on, but on QFT, QAOA, Draper and graph state it is slower at two to four memories (QFT at four: 5.57 against 1.59 ms), and its fidelity is below on-demand's 0.950 everywhere. The earlier simulator showed dynamic ahead because of its serialization (QFT: 41% faster in its own latency, 11% counting the wait for earlier batches). The cause on the corrected simulator was read in the code and measured: on QFT at four memories prepared pairs hold memory cards for 24 ms on average against 6 ms for an ordinary request, a request that has a ready pair still needs a card of its own, and the pair of a later hop of a qubit's chain is made at the start of the previous layer but used only after the hop before it completed. Whether a better plan could avoid this is not established. The random circuit was not run for CGP and ACGP.

Beyond Experiments 1 and 2 (shorter chapters). The torus needs 11–37% fewer hops, has lower structural overload for five workloads (unchanged for four, higher for graph state); offline re-routing with the mapping fixed removes most of the excess demand and makes on-demand requests up to 42% faster; ACE already contains a memory cut-off (`cutoff_ratio`) that is unused by default.

What is not settled. The physical parameters. ACE's coherence time (1 s) and memory efficiency (0.95) differ from the group's multi-core paper (1 ms, 0.85). With the paper's values every pre-generated pair expires unused, so every pre-generation and fidelity result depends on that choice; the congestion results barely do. This needs a decision from the supervisor (Appendix A).

How to trust it. Every result carries controls that must pass (a zero-congestion workload must not respond to the budget; 64 memories must equal 32; completion must be 100%); the first run failed two of them for non-physical reasons, which were diagnosed and fixed (Section 2.3); every experiment folder records all parameters, the code commit, the machine and the run times. Section 2.3 lists every mistake made on the way and how it was found.

How to read this report

If you have ten minutes read the executive summary, Chapter 2 (how and why), and the figures of Chapters 6 and 7.

If you want the evidence Chapters 4 and 5 (what was wrong, how it was fixed and verified), then Experiments 1 and 2 in full (Chapters 6 and 7) and Appendices C and D (every cell).

If you want to know whether compiler-driven pre-generation is good Chapter 13 compares it with on-demand generation, CGP and ACGP on latency, fidelity, waste and waiting; Chapter 12 explains why it is slower than on-demand on the congested benchmarks.

If you want to find something in the repository Appendix E lists every important file and folder with a link, and Appendix F every commit.

If a word is unfamiliar Appendix G.

Conventions. Latency is *common latency* (Chapter 5) in milliseconds of *simulated* time, never real run time. "Memories" means communication memories per core. A * marks a counterfactual budget (above the four slots the group's multi-core paper models). Means are over nine runs (three mapping seeds × three physics seeds) unless stated; ± is a standard deviation over those nine. ACE milliseconds are never compared with the native SeQUeNCe backend's. Every number in a table is generated from a result file in the repository, so a table and its source cannot disagree.

Chapter 1

Scope and method

1.1 What this report is about

A multi-core quantum computer connects small processor cores over a network-on-chip. When a program moves a logical qubit from one core to another, the move is carried out by teleportation, which consumes an entangled pair (an EPR pair) shared between the two cores. Pre-generating those pairs before the program needs them can hide their generation latency, but every core has only a few *communication memories* in which pairs can wait, and many moves may need the same core at once. This report studies that contention (*congestion*) on a 4×4 mesh of cores.

The simulator used is *ACE*, an adaptive-continuous-entanglement simulator built on SeQUeNCe v0.8.1. The first part of the report documents what was found wrong with how ACE released requests to the network, how it was corrected, and how the correction was verified. The second part reports the experiments that the corrected simulator makes possible: latency, fidelity and waiting of ten benchmarks across communication-memory budgets (Experiment 1), the split of each core's congestion into its own endpoint demand and relay traffic (Experiment 2), a study of ACE's memory cut-off mechanisms, a study of whether offline routing can reduce congestion, and the same questions on a torus. Two further chapters ask why dynamic pre-generation is slower than on-demand generation on the congested benchmarks (Chapter 12) and compare it with the autonomous protocols CGP and ACGP (Chapter 13).

1.2 Ground rules followed

The following rules were fixed at the start and held throughout.

- Milliseconds measured in ACE are never compared with milliseconds from the native SeQUeNCe backend.
- Results from the legacy and the corrected scheduler are never merged in one table.
- A fallback to on-demand generation is not a failure, but a dropped request is.
- Nothing is claimed as measured unless it was run; mechanisms that were inferred are labelled as such.
- No congestion-aware routing *algorithm* is proposed or claimed: Chapter 9 bounds structurally what an offline choice of routes could achieve and simulates that optimum, nothing more.
- Structural (trace-based) results are not called physical results.
- Physical parameters were not changed silently; the choice of parameters is an open decision (Appendix A).

1.3 How the work was organised

The work followed a gated plan, each gate committed separately on the branch `codex/ace-scheduler-correctness`:

Gate 0 a bit-for-bit baseline of the legacy simulator (164 result rows) that must still reproduce after every change;

Gate 1 an execution event log, an invariant checker, microcases and an audit of the legacy simulator;

Gate 2 making two requests that look alike distinct bookings (reservation identity);

Gate 3 replacing per-core serialization by a per-qubit request manager with event-driven admission;

Gate 4 verification on all ten benchmarks, three strategies, three mapping seeds and several memory budgets;

Gate 5 tracing every physical parameter to its source;

Gate 6 rerunning the earlier 378-run budget study under the corrected scheduler.

Chapter 2

How and why: method, decisions and corrections

2.1 The approach in one page

The aim was to make ACE's measurements *correct before measuring anything with them.* The order was therefore: (i) record exactly what the legacy simulator does, so any later change can be shown not to disturb it (Gate 0); (ii) instrument it, to see what it really does rather than what its comments say (Gate 1); (iii) fix one fault at a time, each with a test that fails without the fix (Gates 2 and 3); (iv) verify broadly (Gate 4); (v) trace every parameter to a source (Gate 5); (vi) only then rerun the old study and run the new experiments (Gate 6, Experiments 1 and 2).

2.2 Why each major decision was taken

A bit-for-bit baseline first. The simulator's published numbers are the only fixed point. A 164-row baseline (22 cases) is compared as exact text after every change. It reproduces under several Python hash seeds, so it is not an accident of ordering.

An event log and an invariant checker, not just results. Latency alone cannot show that a booking was released twice or a pair credited to the wrong request. Typed events (submissions, bookings, releases, pair deliveries and credits, completions) let rules such as "no memory double-booked over overlapping windows" be checked on every run; each rule was validated by deliberately breaking it.

Fix request identity before changing the scheduler. The aliasing fault is in the reservation code and was hidden by the serialization. Removing the serialization first would have produced wrong numbers that looked like congestion.

Chains per qubit, concurrency across qubits. A qubit's consecutive hops cannot run at once (the qubit must arrive before it can move on); hops of different qubits are independent. That is the only dependency the trace implies, so it is the only one imposed. The layer boundary is kept because the trace carries no gate-level dependencies.

Event-driven admission. Polling retries livelock when two requests need each other's only memory (found by randomised traces). Admitting a request only when both of its cores have a free memory removes the hold-and-wait, so no deadlock among application requests can form. It assumes a central controller that reads the reservation tables instantly; that is stated, not hidden.

One picosecond. SeQUeNCe does not order events at the same instant, so nothing may rely on one preceding another; whatever must come after is scheduled 1 ps later. An A/B test showed the stale-booking violations disappear with that single change.

One latency definition. The legacy latency omits waiting for earlier batches; the new one counts admission waiting. Without a common definition the schedulers cannot be compared at all.

On-demand first. Nothing is pre-generated, so any dependence on the memory budget is contention and nothing else. Dynamic pre-generation is then added with a cap of budget-1 memories per core that the compiler may hold at once (the memories are a shared pool), as in the earlier study.

Nine runs per cell, controls that must pass. Mapping and physics both vary, so spread is reported, never only means. A workload with no overload must not respond to the budget, 64 memories must equal 32, completion must be 100%.

The heatmap recomputed independently. It was rebuilt from the raw traces without reading the archive's precomputed files, and all 160 cells match; that validates both the figure and the pipeline.

Two ways of counting demand. By hops (the archive's counting, a relay counts twice) and by routes (qubits in flight, a relay counts once). Under the per-qubit scheduler a relay's two touches are sequential, so route counting is what the simulator experiences; hop counting overstates contention at one memory (GHZ is structurally "overloaded" at one slot yet never waits).

2.3 Mistakes made on the way, and how they were found

Listed because a reader should know which statements were once wrong.

What was wrong	How it was found and fixed
A validity check was misreported as “72/72”.	The file said 72/378; the quantity is a coverage rate, not an identity invariant. Corrected in an erratum; the identity check (189/189) is a different, correct quantity.
An early proposal to “order requests per link”.	Measurement showed the per-link limit was reservation aliasing, not physics. Retracted.
A microcase asked for a move between non-adjacent cores.	ACE routed it through a relay needing two memories and retried for 60 s. My test error; the harness now refuses non-adjacent hops (and it exposed finding F7).
The design assumed an event scheduled later runs after one queued earlier.	Reading SeQUeNCe’s event list showed equal-time events have no defined order. Redesigned around a 1 ps delay.
The checker flagged double bookings for bookings of a later window.	Forcing cached pairs to expire showed a booking reserves a *window*. The checker now compares windows.
The checker labelled reservations by memory address.	A determinism test failed; addresses are reused after an object is freed. Replaced by stable serial numbers.
Expiry of cached pairs was listed as “covered”.	No pair had ever expired in any audited run. Expiry was forced with short windows and is now tested on both schedulers.
Two Experiment 1 controls failed on the first run.	Saturation compared to exact equality although a few requests waited the 1 ps grace; one on-demand step rose by 0.0005 ms (a thirtieth of the seed spread). Controls refined and tested, “waited” redefined, the experiment rerun; the rerun is identical in every other column.
“On-demand results are the least exposed to the parameters.”	The sensitivity arm showed on-demand fidelity falls from 0.9498 to 0.7861 with the paper’s coherence time. Corrected in the parameter document.
The fibre length was called a “possible unit slip”.	Overstated: 2.5 cm is plausible on a chip. Reworded as an open question.
Torus hop savings quoted as “20–35%”.	The data give 11–37%. Corrected here.

Table 2.1: Corrections log.

2.4 What is assumed, and what is not

Assumed and stated: the scheduler is a central controller with instantaneous knowledge of reservation tables; the physical parameters are ACE’s configuration (undecided); links have equal length on the torus (a folded layout); the 5.3 ms lead, 50 ms window and 5 ms empty-layer gap are harness constants shared by both schedulers. Not assumed: any mechanism marked “likely” or “probably” in the text was not isolated by an experiment and is labelled so.

Chapter 3

Background

3.1 The pipeline

A benchmark circuit from MQT Bench is transpiled to the gate set $\{R_z, \sqrt{X}, X, \mathrm{CX}\}$ and cut into layers by an as-soon-as-possible schedule of its dependency graph. A qubit mapper (HQA, Hungarian-assignment based) places the logical qubits on cores layer by layer. Whenever the placement changes between two layers, the qubit has to move, and the move is expanded into one *hop* per link along a path found by Dijkstra's algorithm on the core graph: shortest in hops, with the product of link reliabilities as the tie-break. The result is a *trace*: for every layer, a list of hops (qubit, source core, destination core). Every hop of the traces used here joins two adjacent cores. The traces carry no gate-level dependencies, so a layer boundary stands in for them.

ACE then executes the trace: each hop is a request for one EPR pair between two adjacent cores, submitted through SeQUeNCe's resource-reservation protocol (RSVP), which books one communication memory at each end for a time window.

3.2 ACE and the native SeQUeNCe backend

ACE adds, on top of SeQUeNCe, adaptive continuous pre-generation of entanglement (cached pairs in spare memories), a compiler controller that pre-generates exactly the pairs the trace will need (the policies *fixed* and *dynamic*), and a request manager that submits a layer's requests together. The native backend instead uses a central scheduler with one generation job per link. The two backends are never compared in this report.

3.3 Policies

On-demand generates a pair only when a request asks for it, so it isolates contention. *Dynamic* compiler pre-generation prepares pairs ahead of the layer that needs them, never holding more than `budget - 1` memories per core at once (the memories are a shared pool, and the cap limits only the compiler). Autonomous caches (*continuous*, *adaptive-continuous*) guess which pairs will be needed.

3.4 Parameters in force

Unless stated, the physical parameters are ACE's configuration: memory fidelity 0.95, memory efficiency 0.95, coherence time 1 s, detector efficiency 0.95, gate and measurement fidelity 0.99, classical delay 100 μs plus 20 μs per hop, and a router-to-BSM fibre of 0.025 (read as metres) with attenuation 0.2 dB/km. The classical delays, detector efficiency, fidelities and attenuation

match the metro-scale adaptive-continuous protocol paper; the link length, the coherence time and the memory efficiency differ from it, and the last two also from the group's multi-core paper (Appendix A).

Chapter 4

What was wrong in the legacy simulator

The audit ran the legacy simulator on the real SeQUeNCe stack with an execution-event recorder and an invariant checker attached (Chapter 5). Each finding below states its evidence: *source* (code read), *measured* (run), or both.

	Question	Answer
F1	Does ACE let two requests share a core?	No. `serialize_core_conflicts` splits every layer into batches with at most one request per core, whenever a compiler controller is attached. On QFT the peak demand per core falls from 24 to 1, so the memory budget cannot bind. Source and measured.
F2	Can two requests be mistaken for one?	**Yes.** SeQUeNCe's `Reservation` equality compares initiator, responder, window, size and fidelity, not the request identity. Serialization hid this in every legacy run. Source and measured.
F3	Does a rejection release earlier bookings?	Yes, exactly once on every node it travelled back through.
F4	Does the physics layer limit a link to one pair at a time?	**No.** 1 to 16 simultaneous requests on one link completed with zero retries.
F5	Phantom occupancy from compiler preparations?	Not in the 24 legacy audits: every booking was released.
F6	Is a trace layer a real barrier?	A conservative one; it is kept.
F7	A request that can never be admitted?	It retries for ever (found with a mistaken test case).
F8	Is waiting measured faithfully?	No: admission was polled every 1 ms.
F9	Resubmission at the instant a booking expires?	With short windows, stale or double bookings appear in 4 of 6 seeds; a delay of 1 ps removes them.
F10	Polling admission with one memory per core?	Two requests that swap two cores livelock: 25 000 submissions each.

Table 4.1: Findings of the audit. Full evidence is in `docs/reports/ace-correctness-audit.md`.

4.1 Reservation aliasing (F2)

With four requests on one link and 32 memories per core, the legacy code gave latencies of 1.2/55.7/62.2/67.9 ms with three retries and two orphaned pairs; the same requests, once they are distinct bookings, take 2.4/0.4/1.6/1.2 ms with no retry. The mechanism is that releasing a booking removes the *first equal* reservation, rules are matched to *any equal* reservation, and the application's dictionaries are keyed by reservation. Reverting only the equality reproduces the old behaviour and the checker flags it, which shows that the fix is the cause.

4.2 Event order is undefined (F9)

SeQUeNCe's event list is a binary heap ordered by time and priority only, so events at the same instant have no defined order. The legacy manager started a retry at the very instant the old booking expired. In an A/B test the only change was to resubmit 1 ps later: the violations disappeared. No code in the corrected scheduler relies on one same-instant event preceding another.

4.3 Livelock under polling (F10)

Randomized small traces found a request set that never completes under polling admission: requests 1 (core 8 to 12) and 3 (12 to 8), with one memory per core, each book their own memory, find the other's taken, roll back and retry on the same 1 ms period. The invariants held (nothing was corrupted), so this is a livelock, not corruption.

4.4 What the audit did not cover

One mapping seed and one physics seed for the 24 legacy audits; the autonomous strategies; and expiry of unused cached pairs, which was found later to never occur in the default runs and was then forced (Chapter 8).

Chapter 5

The corrections and how they were verified

5.1 Making requests distinct (Gate 2)

Application reservations became a subclass whose equality and hash include the request identity. The protocol's `push` builds that class; adaptive (autonomous) reservations keep the stock contract. Tests cover equality, hashing, symmetry, timecard removal and the `push` path; a checker invariant (`ALIASED_RESERVATIONS`) detects a regression.

5.2 The per-qubit request manager (Gate 3)

The legacy manager is untouched and remains the default. The new manager, selected with `scheduler="per-qubit"`, applies these rules.

- **Chains.** The hops of one qubit within one layer form a chain in trace order; a hop is released when the previous hop has completed.
- **Independence.** Hops of different qubits are released together and compete for memory.
- **Layer barrier.** Layer $L+1$ starts when every request of layer L has completed; the 5 ms empty-layer gap of the legacy manager is kept.
- **Event-driven admission.** A request is handed to the reservation protocol only when both of its cores have a memory free for its whole window (read from the reservation tables, less requests admitted but not yet booked); the oldest request that fits goes first, and a release at any core wakes the line one picosecond later. A request that cannot start yet keeps the memory it would need (the *starvation guard*).
- **Timeouts** resubmit one picosecond after the window ends, one request at a time, not as a serialized retry layer.

No request waits while holding a memory that another needs, so a deadlock among application requests cannot form. The scheduler is modelled as a central controller that reads each core's reservation table without delay; that is an assumption about the system.

5.3 The checker

The invariant checker works on a typed event log (submissions, bookings, releases, pair deliveries and credits, completions). It checks, among others: no memory double-booked over overlapping windows; no release of a booking that was not live; no orphan pair; no credit beyond the request;

exactly one completion per request; no resubmission with a stale booking; a hop submitted only after its predecessor completed; the layer barrier. It was validated by deliberately breaking each rule, and it was corrected twice during the work: it first treated every booking as occupying a memory from the moment it was made (wrong for a booking of a later window), and it labelled reservations by memory address, which can be reused. Both faults were in the checker, not in ACE.

5.4 Verification

Check	Result
Legacy baseline (164 rows, 22 cases), after every change	reproduced exactly, under several Python hash seeds
Ten workloads × three strategies × 2 and 4 memories × mapping seeds 42, 43, 44 (360 audited cells)	every request completes, no invariant violated
GHZ against the legacy manager	identical event logs (on-demand, dynamic)
Random small traces at 1, 2, 4, 16 memories	all complete, never more bookings than memories
Forced expiry of cached pairs, both schedulers	all complete, no violation
Python hash seeds 1 and 2	identical makespan, events and retries

Table 5.1: Verification summary (`docs/reports/ace-scheduler-verification.md`).

5.5 One latency definition for both schedulers

The legacy manager's per-request latency starts at a request's first submission, so time spent waiting for earlier per-core batches is not counted, while the new manager counts admission waiting. They are not comparable as defined. Throughout this report latency means *common latency*: from the moment a request could first be asked for (its layer starting, or the previous hop of its qubit completing) to its completion, minus the fixed 5.3 ms pre-generation lead.

5.6 The budget study rerun (Gate 6)

The earlier 378-run budget study could not measure congestion because of the serialization. Rerun with the legacy scheduler through a parameterized driver, it reproduces the published results in every column (0 differing cells of 378×58), so the driver is faithful. Under the corrected scheduler the on-demand latency now depends on the budget: for QFT it falls from 4.72 ms at 2 memories to 1.13 ms at 32 (Chapter 7).

Chapter 6

Where the congestion is: heatmap and endpoint-versus-relay split

6.1 Per-core congestion

For every trace and layer, the *demand* of a core is the number of hops that touch it (every hop joins two adjacent cores, so a hop counts at both ends). A core is *overloaded* in a layer when its demand exceeds the number of communication slots, here 4. The percentage is over *communication-active layers* (layers with at least one hop), averaged with equal weight over the three mapping seeds 42, 43 and 44 of the same circuit. This is a structural count of the mapped traces: it simulates no physics.

The figure was regenerated from the raw traces without reading the archive's precomputed congestion files, as an independent check. All 160 cells (ten workloads, sixteen cores) match the project's earlier figure at its printed resolution, and a regression test pins every cell.




Figure 6.1: Per-core congestion on the mesh: percentage of communication-active layers in which a core's demand exceeds 4 slots (mean over three mapping seeds). All 160 cells match the project's earlier figure at 0.1% resolution.

Workload	Active layers (seeds 42/43/44)	Layers with any overload	Hottest core
GHZ	15/15/15	0.0%	C0 (0.0%)
Bernstein–Vazirani	16/16/16	0.0%	C0 (0.0%)
BMW/QUARK cardinality	90/90/90	0.0%	C0 (0.0%)
VQE real amplitudes	22/22/22	6.1%	C9 (4.5%)
CDKM ripple-carry adder	157/157/157	0.6%	C6 (0.6%)
Graph state	6/6/6	33.3%	C5 (33.3%)
Draper QFT adder	138/138/138	41.3%	C10 (23.4%)
QAOA	163/163/163	71.6%	C10 (56.0%)
QFT	112/112/112	65.2%	C10 (58.0%)
Random circuit	2296/2296/2296	8.0%	C9 (3.2%)

Table 6.1: Structural overload at capacity 4, pooled over the three mapping seeds.

Congestion concentrates on the central cores, which lie on the most shortest paths. QFT and QAOA are the heavy cases, graph state is overloaded in a third of its (few) active layers, and GHZ, Bernstein–Vazirani and BMW never exceed four.

6.2 Own demand against relay demand (Experiment 2)

A *route* is a qubit's consecutive hops within one layer; its first source and final destination are its *endpoints*, every core in between is a *relay*. For a core and a layer, D counts the hops touching the core, D_{end} those where the core is an endpoint of the route, and D_{relay} the rest, so that a relay (touched by an arriving and a leaving hop) contributes two: $D = D_{\text{end}} + D_{\text{relay}}$. With capacity C, a layer is overloaded for the core when $D > C$. It is *own-overloaded* when $D_{\text{end}} > C$, and *relay-only-overloaded* when $D_{\text{end}} \leq C < D$. The two sets are disjoint and together are exactly the overloaded layers.

Validation. Own plus relay-only reproduces all 160 heatmap cells, and the per-core relay incidences, incident hops and peak layer demand reproduce all 480 per-trial rows of the archive's per-core file exactly.

Counting qubits in flight. A second variant counts routes instead of hops: under per-qubit ordering the hops of a route run one after another, so a relay needs one memory for the route at a time, not two.

Workload	C=1	C=2	C=3	C=4
GHZ	0.0%	none	none	none
Bernstein–Vazirani	0.0%	none	none	none
BMW/QUARK cardinality	0.0%	none	none	none
VQE real amplitudes	2.0%	0.0%	0.0%	0.0%
CDKM ripple-carry adder	0.4%	0.0%	0.0%	0.0%
Graph state	26.0%	9.5%	0.0%	0.0%
Draper QFT adder	54.5%	6.9%	6.4%	0.0%
QAOA	51.9%	14.9%	2.3%	0.4%
QFT	76.8%	10.1%	7.1%	0.0%
Random circuit	15.7%	1.8%	0.0%	0.0%

Table 6.2: Share of overloaded core-layers caused by a core's own endpoint demand (hop counting); the rest is relay-only overload.

Workload	C=1	C=2	C=3	C=4
GHZ	none	none	none	none
Bernstein–Vazirani	none	none	none	none
BMW/QUARK cardinality	none	none	none	none
VQE real amplitudes	5.3%	0.0%	none	none
CDKM ripple-carry adder	10.7%	0.0%	0.0%	0.0%
Graph state	37.5%	18.2%	0.0%	0.0%
Draper QFT adder	76.0%	9.5%	17.1%	0.0%
QAOA	59.7%	20.7%	4.5%	1.2%
QFT	86.8%	11.5%	12.8%	0.0%
Random circuit	39.6%	7.0%	0.0%	0.0%

Table 6.3: Share of overloaded core-layers caused by a core's own endpoint demand (route counting); the rest is relay-only overload.

Workload	Hottest core	Overloaded %	Own %	Relay-only %	Relay share of demand	Relay share of excess
GHZ	none	0.0	0.0	0.0	–	–
Bernstein–Vazirani	none	0.0	0.0	0.0	–	–
BMW/QUARK cardinality	none	0.0	0.0	0.0	–	–
VQE real amplitudes	C9	4.5	0.0	4.5	80%	100%
CDKM ripple-carry adder	C6	0.6	0.0	0.6	85%	100%
Graph state	C5	33.3	0.0	33.3	93%	100%
Draper QFT adder	C10	23.4	0.0	23.4	81%	100%
QAOA	C10	56.0	0.0	56.0	81%	100%
QFT	C10	58.0	0.0	58.0	78%	100%
Random circuit	C9	3.2	0.0	3.2	87%	100%

Table 6.4: Hottest core of each workload at capacity 4 (hop counting): percentage of active layers overloaded, split into own and relay-only, and the relay share of its demand and of its excess.

Workload	Peak demand D	Peak endpoint demand D_{end}	Peak routes through one core
GHZ	2	1	1
Bernstein–Vazirani	2	1	1
BMW/QUARK cardinality	2	1	1
VQE real amplitudes	5	2	3
CDKM ripple-carry adder	9	2	5
Graph state	13	3	7
Draper QFT adder	11	4	7
QAOA	18	5	10
QFT	24	4	13
Random circuit	12	3	6

Table 6.5: Peak demand at one core in one layer, over all mapping seeds: how close endpoint demand comes to the capacity.

Why the counting matters. Hop counting charges a relay two touches (one arriving hop, one leaving hop), but under per-qubit ordering those two hops run one after the other, so a relay needs one memory at a time. Hop counting therefore overstates contention, most visibly at one slot: GHZ is structurally "overloaded" at one slot by hop counting (20% of its layers) yet never waits in the simulator, and route counting, whose peak for GHZ is one route per core, correctly shows no contention. This is why Experiment 1 relates the simulated cost to the structure and why both counts are reported.

Findings. At the modelled capacity of four, almost all overload is relay overload. The peak endpoint demand is 4 for QFT and Draper, 5 for QAOA and at most 3 for the others, against

a total demand up to 24. The only own-overload at capacity 4 is in QAOA, at the corner cores C0 and C3 (0.61% of active layers each), which is 0.44% of QAOA's overload. Smaller budgets bring own demand in: QFT is 77% own-overload at capacity 1. A routing change can therefore remove at most the relay part; the own part is a floor set by the mapping. Route counting finds less overload than hop counting (core C10 of QFT is overloaded in 46.4% of active layers against 58.0%) and relay traffic is still essentially all of what remains.

6.3 Every capacity, both countings

Capacity four is the modelled value; the smaller capacities show how the split moves as memory is removed. Each of the following landscape pages shows one capacity and counting with every workload that has overload side by side: for each workload the left heatmap is the percentage of active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Per-core numbers for capacities four and two are in Appendix D; the data for all capacities and both countings are in `results/experiment2_own_vs_relay_2026-10-24/`.




Figure 6.2: Capacity 4, hop counting. For each workload with overload, the left heatmap is the percentage of its active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Mesh cores are numbered row by row (core 10 is row 2, column 2). Mean of three mapping seeds.




Figure 6.3: Capacity 4, route counting (qubits in flight). For each workload with overload, the left heatmap is the percentage of its active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Mesh cores are numbered row by row (core 10 is row 2, column 2). Mean of three mapping seeds.




Figure 6.4: Capacity 2, hop counting. For each workload with overload, the left heatmap is the percentage of its active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Mesh cores are numbered row by row (core 10 is row 2, column 2). Mean of three mapping seeds.




Figure 6.5: Capacity 1, hop counting. For each workload with overload, the left heatmap is the percentage of its active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Mesh cores are numbered row by row (core 10 is row 2, column 2). Mean of three mapping seeds.




Figure 6.6: Capacity 3, hop counting. For each workload with overload, the left heatmap is the percentage of its active layers in which the core is overloaded by its own endpoint demand and the right heatmap the percentage in which it is overloaded only because of relay traffic. Mesh cores are numbered row by row (core 10 is row 2, column 2). Mean of three mapping seeds.

Chapter 7

Latency, fidelity and congestion across memory budgets (Experiment 1)

7.1 Design

All ten benchmarks, on the corrected scheduler, with $1, 2, 3, 4, 6, 8, 16, 32$ communication memories per core (QFT also 64). Budgets 1–4 are *modelled* (the group's multi-core paper gives four communication qubits per core); 6–32 are *counterfactual* (what-if capacity), marked *. Two policies: *on-demand* and *dynamic* compiler pre-generation in which the compiler may hold at most budget $-$ 1 memories per core at once (the memories are one shared pool that any request can use; the cap limits only the compiler; dynamic starts at two memories because a cap of zero would be no pre-generation). Three mapping seeds and three physics seeds give nine runs per cell, 1 368 runs in total. Latency is the common latency defined in Chapter 5.

7.2 Controls

- PASS every run completes every request: 1368 rows, 0 not ok
- PASS zero-congestion control: GHZ on-demand latency does not respond to the budget: 0 of 9 (mapping, physics) runs vary across budgets
- PASS saturation: QFT with 64 memories reproduces 32 run for run (relative 1e-6): 18 runs compared, largest relative difference 7.96e-12
- PASS on-demand delivered fidelity does not depend on the budget: 0 of 90 runs vary
- PASS on-demand latency does not rise when memory is added, beyond seed-to-seed noise: 639 budget steps: 1 rise by less than the physics-seed spread (largest 0.0005 ms), 0 rise by more

The first full run failed two controls for reasons that were not physical: the saturation check compared to exact equality although a few requests "waited" the one picosecond the scheduler leaves after a release, and one on-demand step rose by 0.0005 ms with more memory (a thirtieth of the seed-to-seed spread), which is sampling noise because a delayed request draws different random numbers. The controls were refined, tests pin them, and a request now "waited" only if it waited more than a microsecond. The rerun is numerically identical to the first run in every column except that redefined one, which also shows that the pipeline is deterministic.

7.3 What congestion costs on-demand requests




Figure 7.1: Request latency (ms, log scale) against communication memories per core, on-demand and dynamic. Line: mean of nine runs; band: minimum to maximum; grey: counterfactual budgets (beyond the modelled four).

Workload	1	2	3	4	6*	8*	16*	32*
GHZ	1.17±0.11	1.17±0.11	1.17±0.11	1.17±0.11	1.17±0.11	1.17±0.11	1.17±0.11	1.17±0.11
Bernstein–Vazirani	1.22±0.12	1.22±0.12	1.22±0.12	1.22±0.12	1.22±0.12	1.22±0.12	1.22±0.12	1.22±0.12
BMW/QUARK cardinality	1.12±0.04	1.12±0.04	1.12±0.04	1.12±0.04	1.12±0.04	1.12±0.04	1.12±0.04	1.12±0.04
VQE real amplitudes	2.32±0.14	1.11±0.05	1.11±0.05	1.11±0.05	1.11±0.05	1.11±0.05	1.11±0.05	1.11±0.05
CDKM ripple-carry adder	1.66±0.22	1.24±0.05	1.17±0.03	1.14±0.03	1.14±0.03	1.14±0.03	1.14±0.03	1.14±0.03
Graph state	9.14±1.14	2.72±0.54	1.53±0.30	1.24±0.13	1.18±0.08	1.18±0.08	1.18±0.08	1.18±0.08
Draper QFT adder	7.36±0.84	2.16±0.20	1.30±0.05	1.15±0.02	1.13±0.02	1.13±0.02	1.13±0.02	1.13±0.02
QAOA	10.92±0.41	3.42±0.14	1.74±0.06	1.27±0.02	1.14±0.01	1.13±0.01	1.13±0.01	1.13±0.01
QFT	14.42±0.35	4.72±0.14	2.39±0.09	1.59±0.05	1.21±0.02	1.15±0.02	1.13±0.02	1.13±0.02
Random circuit	2.99±0.10	1.27±0.02	1.12±0.01	1.11±0.01	1.11±0.01	1.11±0.01	1.11±0.01	1.11±0.01

Table 7.1: Request latency (ms), on-demand, mean ± sd over nine runs. Budgets marked * are counterfactual (beyond the modelled four slots).

Three workloads with no overload (GHZ, Bernstein–Vazirani, BMW) do not respond to the budget at all. At one memory the congested workloads are severe: QFT is about 12.7 times its saturated latency, QAOA 9.6, graph state 7.8 and Draper 6.5. At the modelled four memories the penalty against 32 memories is +40% for QFT, +12% for QAOA, +5% for graph state and +1% for Draper; the other workloads are within a percent. The floor, reached once nothing waits, is 1.11 to 1.22 ms in every workload: that is generation time, not contention.

Workload	1	2	3	4	6*	8*
GHZ	0%	0%	0%	0%	0%	0%
Bernstein–Vazirani	0%	0%	0%	0%	0%	0%
BMW/QUARK cardinality	0%	0%	0%	0%	0%	0%
VQE real amplitudes	+109%	0%	0%	0%	0%	0%
CDKM ripple-carry adder	+46%	+9%	+3%	0%	0%	0%
Graph state	+676%	+131%	+30%	+5%	0%	0%
Draper QFT adder	+549%	+90%	+14%	+1%	0%	0%
QAOA	+863%	+202%	+53%	+12%	+1%	0%
QFT	+1170%	+316%	+110%	+40%	+6%	+1%
Random circuit	+170%	+14%	+1%	0%	0%	0%

Table 7.2: On-demand latency relative to the same workload with 32 memories (saturated), by memories per core. * counterfactual.

Workload	OD 1	OD 2	OD 4	OD 8	OD 32	Dyn 2	Dyn 4	Dyn 8	Dyn 32
GHZ	0.33	0.33	0.33	0.33	0.33	0.31	0.30	0.30	0.30
Bernstein–Vazirani	0.89	0.89	0.89	0.89	0.89	0.87	0.86	0.86	0.86
BMW/QUARK cardinality	6.95	6.95	6.95	6.95	6.95	6.86	6.83	6.83	6.83
VQE real amplitudes	0.74	0.68	0.68	0.68	0.68	0.68	0.63	0.61	0.61
CDKM ripple-carry adder	5.62	5.59	5.58	5.58	5.58	5.37	5.20	5.20	5.20
Graph state	0.38	0.26	0.24	0.24	0.24	0.32	0.26	0.23	0.22
Draper QFT adder	6.89	5.14	4.88	4.87	4.87	5.91	5.03	4.54	4.41
QAOA	10.69	6.60	5.48	5.40	5.40	8.50	6.62	5.52	4.74
QFT	9.11	5.72	4.66	4.51	4.51	7.50	5.75	4.79	4.05
Random circuit	59.78	51.50	50.89	50.89	50.89	53.58	47.74	45.05	44.58

Table 7.3: Makespan (simulated seconds of the whole circuit), on-demand (OD) and dynamic (Dyn), by memories per core. Mostly the fixed 5.3 ms lead and 5 ms empty-layer gap.

Workload	2 mem. seed 42	43	44	4 mem. seed 42	43	44
GHZ	1.21	1.13	1.18	1.21	1.13	1.18
Bernstein–Vazirani	1.24	1.22	1.21	1.24	1.22	1.21
BMW/QUARK cardinality	1.11	1.13	1.11	1.11	1.13	1.11
VQE real amplitudes	1.15	1.11	1.08	1.15	1.11	1.08
CDKM ripple-carry adder	1.26	1.28	1.18	1.14	1.13	1.14
Graph state	2.42	2.33	3.41	1.19	1.16	1.36
Draper QFT adder	2.26	1.89	2.32	1.16	1.14	1.15
QAOA	3.59	3.39	3.28	1.28	1.29	1.25
QFT	4.60	4.91	4.66	1.57	1.65	1.55
Random circuit	1.28	1.27	1.24	1.11	1.11	1.11

Table 7.4: On-demand latency (ms) by mapping seed (mean over the three physics seeds): where there is congestion the mapping seed matters more than the physics seed; where nothing waits the physics noise dominates.

The makespan is dominated by the fixed 5.3 ms lead and 5 ms empty-layer gap, so it moves much less than the request latency. Where there is congestion the spread between mapping seeds is several times the spread between physics seeds at two memories (graph state: 0.60 ms between the three mapping-seed means against 0.15 ms between physics seeds; Draper: 0.23 against 0.02); where nothing waits the physics noise dominates. Over the 20 workload-and-budget cells of Table 7.4 the mapping spread is the larger in 9.

7.4 Congestion as waiting




Figure 7.2: Fraction of requests that had to wait for a free memory. Line: mean of nine runs; band: minimum to maximum; grey: counterfactual budgets (beyond the modelled four).

Workload	1	2	3	4	6*	8*	16*	32*
GHZ	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
Bernstein–Vazirani	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
BMW/QUARK cardinality	0.000	0.000	0.000	0.000	0.000	0.000	0.000	0.000
VQE real amplitudes	0.205	0.002	0.000	0.000	0.000	0.000	0.000	0.000
CDKM ripple-carry adder	0.033	0.020	0.011	0.002	0.000	0.000	0.000	0.000
Graph state	0.602	0.281	0.121	0.029	0.000	0.000	0.000	0.000
Draper QFT adder	0.536	0.211	0.055	0.008	0.000	0.000	0.000	0.000
QAOA	0.671	0.376	0.172	0.058	0.004	0.000	0.000	0.000
QFT	0.696	0.430	0.249	0.130	0.031	0.007	0.000	0.000
Random circuit	0.254	0.042	0.006	0.001	0.000	0.000	0.000	0.000

Table 7.5: Fraction of requests that waited more than a microsecond for a free memory, on-demand. Budgets marked * are counterfactual (beyond the modelled four slots).

Workload	1 memory	2	3	4
GHZ	20% / +0%	0% / +0%	0% / +0%	0% / +0%
Bernstein–Vazirani	25% / +0%	0% / +0%	0% / +0%	0% / +0%
BMW/QUARK cardinality	20% / +0%	0% / +0%	0% / +0%	0% / +0%
VQE real amplitudes	55% / +109%	32% / +0%	11% / +0%	6% / +0%
CDKM ripple-carry adder	96% / +46%	1% / +9%	1% / +3%	1% / +0%
Graph state	100% / +676%	83% / +131%	50% / +30%	33% / +5%
Draper QFT adder	93% / +549%	65% / +90%	60% / +14%	41% / +1%
QAOA	98% / +863%	85% / +202%	79% / +53%	72% / +12%
QFT	95% / +1170%	76% / +316%	76% / +110%	65% / +40%
Random circuit	90% / +170%	35% / +14%	25% / +1%	8% / +0%

Table 7.6: Structural overload of the traces (% of active layers with any core above capacity) / simulated on-demand latency penalty against 32 memories, at the same capacity.

The structural overload of the traces at the same capacity (Chapter 6) predicts which workloads pay: across the 60 (workload, budget 1 to 8) points the structural overload and the on-demand latency penalty are strongly rank-correlated (Spearman $\rho = 0.85$).

7.5 Pre-generation against on-demand, and the fidelity price

Workload	2	3	4	6*	8*	16*	32*
GHZ	0.51±0.07	0.26±0.00	0.26±0.00	0.26±0.00	0.26±0.00	0.26±0.00	0.26±0.00
Bernstein–Vazirani	0.46±0.07	0.24±0.00	0.24±0.00	0.24±0.00	0.24±0.00	0.24±0.00	0.24±0.00
BMW/QUARK cardinality	0.49±0.02	0.25±0.00	0.25±0.00	0.25±0.00	0.25±0.00	0.25±0.00	0.25±0.00
VQE real amplitudes	1.52±0.20	1.19±0.16	0.88±0.07	0.41±0.00	0.25±0.00	0.25±0.00	0.25±0.00
CDKM ripple-carry adder	0.76±0.06	0.38±0.03	0.30±0.01	0.30±0.01	0.30±0.01	0.30±0.01	0.30±0.01
Graph state	6.36±0.79	5.01±0.59	3.23±0.82	1.60±0.39	0.95±0.13	0.27±0.04	0.25±0.00
Draper QFT adder	4.55±0.43	3.67±0.34	2.48±0.38	1.60±0.17	0.89±0.23	0.25±0.01	0.25±0.00
QAOA	6.89±0.28	5.33±0.19	3.88±0.17	2.70±0.13	1.86±0.08	0.35±0.04	0.25±0.00
QFT	10.06±0.54	7.49±0.33	5.57±0.21	3.73±0.25	2.78±0.19	0.80±0.16	0.25±0.00
Random circuit	1.91±0.08	1.37±0.04	0.94±0.02	0.56±0.02	0.38±0.02	0.25±0.00	0.25±0.00

Table 7.7: Request latency (ms), dynamic pre-generation. Budgets marked * are counterfactual (beyond the modelled four slots).




Figure 7.3: Delivered EPR fidelity against communication memories per core. On-demand is constant; dynamic falls as the compiler bank grows. Line: mean of nine runs; band: minimum to maximum; grey: counterfactual budgets (beyond the modelled four).

Workload	2	3	4	6*	8*	16*	32*
GHZ	0.9344	0.9254	0.9254	0.9254	0.9254	0.9254	0.9254
Bernstein–Vazirani	0.9345	0.9266	0.9266	0.9266	0.9266	0.9266	0.9266
BMW/QUARK cardinality	0.9343	0.9253	0.9253	0.9253	0.9253	0.9253	0.9253
VQE real amplitudes	0.9344	0.9203	0.9165	0.9128	0.9125	0.9125	0.9125
CDKM ripple-carry adder	0.9354	0.9247	0.9227	0.9210	0.9210	0.9210	0.9210
Graph state	0.9341	0.9236	0.9189	0.9158	0.9128	0.9111	0.9112
Draper QFT adder	0.9368	0.9257	0.9218	0.9154	0.9148	0.9158	0.9158
QAOA	0.9390	0.9298	0.9245	0.9167	0.9136	0.9137	0.9143
QFT	0.9386	0.9306	0.9274	0.9215	0.9189	0.9185	0.9202
Random circuit	0.9320	0.9186	0.9130	0.9075	0.9068	0.9070	0.9071

Table 7.8: Delivered EPR fidelity, dynamic pre-generation. Budgets marked * are counterfactual (beyond the modelled four slots).

For the congested workloads dynamic is slower than on-demand at small budgets, because its prepared pairs may occupy up to budget − 1 of the memories and requests then wait for a free one (Chapter 12); the first budget at which dynamic is faster than on-demand is 8 for graph state and Draper and 16 for QAOA and QFT. At 32 memories dynamic reaches 0.24 to 0.30 ms against 1.11 to 1.22 ms on-demand. Delivered fidelity under dynamic is below the on-demand value (0.9498 in every cell) and falls as the compiler bank grows from two to about eight memories, by at most 0.043 under ACE's one-second coherence time; the mechanism (pairs stored longer) is likely but was not measured.

7.6 Sensitivity to the physical parameters

This is exploratory, not a result of the study: the parameters are undecided. Five workloads, budgets $2, 4, 8, 32$, mapping seed 42, were rerun with the group's multi-core paper's coherence time (1 ms) and memory efficiency (0.85) in place of ACE's (1 s and 0.95). With the paper's values **every cached pair expires unused** (6 of 15 700 compiler pairs were used), so dynamic pre-generation gives no benefit at all; on-demand fidelity falls from 0.9498 to 0.7861 in every workload and budget, and on-demand latency rises by about 0.26 to 0.42 ms. The congestion curves keep their shape. So the congestion results are structural and change little with these parameters, while the pre-generation and fidelity results depend entirely on them.

7.7 Workload by workload

Each paragraph is generated from the data: structural overload, the on-demand latency curve, the waiting at four memories, and the dynamic curve with the budget at which pre-generation first beats on-demand.

GHZ

Structural overload at four slots: 0.0% of active layers (one slot: 20%). On-demand latency is 1.17 ms with one memory, 1.17 with two, 1.17 with four and 1.17 with 32; it is within 5% of the saturated value from 1 memory. At four memories 0.0% of requests waited. Dynamic pre-generation takes 0.51 ms with two memories, 0.26 with four and 0.26 with 32, and first beats on-demand at 2 memories; its delivered fidelity is 0.9344 at two memories and 0.9254 at 32 (on-demand: 0.9498).

Bernstein–Vazirani

Structural overload at four slots: 0.0% of active layers (one slot: 25%). On-demand latency is 1.22 ms with one memory, 1.22 with two, 1.22 with four and 1.22 with 32; it is within 5% of the saturated value from 1 memory. At four memories 0.0% of requests waited. Dynamic pre-generation takes 0.46 ms with two memories, 0.24 with four and 0.24 with 32, and first beats on-demand at 2 memories; its delivered fidelity is 0.9345 at two memories and 0.9266 at 32 (on-demand: 0.9498).

BMW/QUARK cardinality

Structural overload at four slots: 0.0% of active layers (one slot: 20%). On-demand latency is 1.12 ms with one memory, 1.12 with two, 1.12 with four and 1.12 with 32; it is within 5% of the saturated value from 1 memory. At four memories 0.0% of requests waited. Dynamic pre-generation takes 0.49 ms with two memories, 0.25 with four and 0.25 with 32, and first beats on-demand at 2 memories; its delivered fidelity is 0.9343 at two memories and 0.9253 at 32 (on-demand: 0.9498).

VQE real amplitudes

Structural overload at four slots: 6.1% of active layers (one slot: 55%). On-demand latency is 2.32 ms with one memory, 1.11 with two, 1.11 with four and 1.11 with 32; it is within 5% of the saturated value from 2 memories. At four memories 0.0% of requests waited. Dynamic pre-generation takes 1.52 ms with two memories, 0.88 with four and 0.25 with 32, and first beats on-demand at 4 memories; its delivered fidelity is 0.9344 at two memories and 0.9125 at 32 (on-demand: 0.9498).

CDKM ripple-carry adder

Structural overload at four slots: 0.6% of active layers (one slot: 96%). On-demand latency is 1.66 ms with one memory, 1.24 with two, 1.14 with four and 1.14 with 32; it is within 5% of the saturated value from 3 memories. At four memories 0.2% of requests waited. Dynamic pre-generation takes 0.76 ms with two memories, 0.30 with four and 0.30 with 32, and first beats on-demand at 2 memories; its delivered fidelity is 0.9354 at two memories and 0.9210 at 32 (on-demand: 0.9498).

Graph state

Structural overload at four slots: 33.3% of active layers (one slot: 100%). On-demand latency is 9.14 ms with one memory, 2.72 with two, 1.24 with four and 1.18 with 32; it is within 5% of the saturated value from 6 memories. At four memories 2.9% of requests waited. Dynamic pre-generation takes 6.36 ms with two memories, 3.23 with four and 0.25 with 32, and first beats on-demand at 8 memories; its delivered fidelity is 0.9341 at two memories and 0.9112 at 32 (on-demand: 0.9498).

Draper QFT adder

Structural overload at four slots: 41.3% of active layers (one slot: 93%). On-demand latency is 7.36 ms with one memory, 2.16 with two, 1.15 with four and 1.13 with 32; it is within 5% of the saturated value from 4 memories. At four memories 0.8% of requests waited. Dynamic pre-generation takes 4.55 ms with two memories, 2.48 with four and 0.25 with 32, and first beats on-demand at 8 memories; its delivered fidelity is 0.9368 at two memories and 0.9158 at 32 (on-demand: 0.9498).

QAOA

Structural overload at four slots: 71.6% of active layers (one slot: 98%). On-demand latency is 10.92 ms with one memory, 3.42 with two, 1.27 with four and 1.13 with 32; it is within 5% of the saturated value from 6 memories. At four memories 5.8% of requests waited. Dynamic pre-generation takes 6.89 ms with two memories, 3.88 with four and 0.25 with 32, and first beats on-demand at 16 memories; its delivered fidelity is 0.9390 at two memories and 0.9143 at 32 (on-demand: 0.9498).

QFT

Structural overload at four slots: 65.2% of active layers (one slot: 95%). On-demand latency is 14.42 ms with one memory, 4.72 with two, 1.59 with four and 1.13 with 32; it is within 5% of the saturated value from 8 memories. At four memories 13.0% of requests waited. Dynamic pre-generation takes 10.06 ms with two memories, 5.57 with four and 0.25 with 32, and first beats on-demand at 16 memories; its delivered fidelity is 0.9386 at two memories and 0.9202 at 32 (on-demand: 0.9498).

Random circuit

Structural overload at four slots: 8.0% of active layers (one slot: 90%). On-demand latency is 2.99 ms with one memory, 1.27 with two, 1.11 with four and 1.11 with 32; it is within 5% of the saturated value from 3 memories. At four memories 0.1% of requests waited. Dynamic pre-generation takes 1.91 ms with two memories, 0.94 with four and 0.25 with 32, and first beats on-demand at 4 memories; its delivered fidelity is 0.9320 at two memories and 0.9071 at 32 (on-demand: 0.9498).

Chapter 8

The memory cut-off time

A *memory cut-off time* is a threshold after which a stored EPR pair is discarded and a new pair generated. Nothing new needs to be built to have one: ACE already has it, as the SeQUeNCe memory's `cutoff_ratio`, and two other timers also end a stored pair's life.

8.1 The timers

Memory cut-off. When a pair is stored, an expiry is scheduled `cutoff_ratio` × coherence time later. At expiry the memory is reset (unless it is in an application) and returned to the free state; ACE then drops the pair from its cache and tells the compiler controller it expired. ACE's configuration never sets the ratio, so it is 1 and the cut-off equals the coherence time, 1 s. A ratio written in the topology template was verified to reach every memory.

Reservation window. A pair's booking ends with its window; an unused pair is released then. The window is 1000 ms for compiler pairs and, for the autonomous caches, runs to the next 0.2 s period boundary.

Planner lifetime. The planner's `--coherence-time-layers` (10) says how far ahead a pair may be prepared; it is a planning assumption, tied to nothing physical.

Separately the stored state decoheres continuously at the rate 1/coherence time, lowering fidelity but discarding nothing.

8.2 What a discard does to compiler pairs

Workload	Case	Done	Viol.	Consumed	Window	Cut-off	Bookings	Makespan ms
ghz	ACE default: cut-off = coherence time (1 s), window 1000 ms	24/24	0	48	0	0	48	303.5
ghz	short reservation window only (20 ms)	24/24	0	36	12	0	48	311.2
ghz	cut-off ratio 0.02 (20 ms), window 1000 ms	24/24	0	34	12	12	55	311.4
ghz	cut-off ratio 0.005 (5 ms), window 1000 ms	24/24	0	0	34	34	49	322.0
ghz	cut-off ratio 0.02 and window 20 ms	24/24	0	36	12	0	48	311.2
graphstate	ACE default: cut-off = coherence time (1 s), window 1000 ms	76/76	0	104	0	0	134	274.5
graphstate	short reservation window only (20 ms)	76/76	0	48	56	0	134	241.3
graphstate	cut-off ratio 0.02 (20 ms), window 1000 ms	76/76	0	24	32	32	179	351.8
graphstate	cut-off ratio 0.005 (5 ms), window 1000 ms	76/76	0	0	34	34	339	347.4
graphstate	cut-off ratio 0.02 and window 20 ms	76/76	0	48	56	0	134	242.5

Table 8.1: Which timer discards a cached pair (compiler pre-generation, 4 memories). Consumed: pairs used; Window: releases at the end of the reservation window; Cut-off: memory resets by the cut-off.

The earlier timer wins: with both at 20 ms the window fires first and no cut-off reset occurs. For compiler pairs a cut-off discards the pair and nothing replaces it: the controller only marks

it expired, the request that wanted it generates its own pair on demand, and all requests still complete. The run gets longer (graph state: 274.5 ms makespan by default, 351.8 ms with a 20 ms cut-off, 347.4 ms with 5 ms). In every case the number of window releases equals the number of cut-off resets, consistent with a discarded pair's booking staying until its window ends (inferred from the counts).

8.3 What a discard does to the autonomous caches

Strategy	Cut-off ratio	Generated	Used	Reported waste	Real unused	Latency ms	Fidelity
continuous	1 (default)	44936	90	99.7%	99.80%	5.147	0.9297
adaptive-continuous	1 (default)	5184	120	97.8%	97.69%	4.882	0.9258
continuous	0.2	44936	90	99.7%	99.80%	5.147	0.9297
adaptive-continuous	0.2	5184	120	97.8%	97.69%	4.882	0.9258
continuous	0.02	447388	122	10.0%	99.97%	4.865	0.9354
adaptive-continuous	0.02	41472	122	12.0%	99.71%	4.865	0.9354

Table 8.2: Autonomous caches on Random-16 (4 memories, coherence 1 s): effect of the memory cut-off. Reported waste omits cut-off discards.

A cut-off of 200 ms changes nothing, because the cache's window already ends at the next 0.2 s boundary. At 20 ms the cache discards and *regenerates*: ten times more pairs are generated, the used pairs are fresher (fidelity 0.9297 to 0.9354) and latency falls slightly (5.15 to 4.87 ms). ACE's waste counter does not see cut-off discards (it is incremented only when a generation rule expires at the window end), so the reported waste drops from 99.7% to 10.0% although 99.97% of the generated pairs went unused; waste measured with a cut-off must be computed as $1 - \text{used/generated}$.

8.4 Decisions

Whether "cut-off" should mean discard-and-regenerate (the caches already do; compiler pre-generation falls back on demand and re-preparing would be a new feature); exposing the cut-off in milliseconds as a recorded study parameter; tying the planner's lifetime to it and fixing the waste counter first; and the coherence time, which comes before any cut-off: with 1 s coherence a cut-off never acts, and with the group's 1 ms a cut-off equal to the coherence time would discard every cached pair before use.

Chapter 9

Can offline routing reduce the congestion?

Experiment 2 (Chapter 6) showed that at the modelled capacity of four memories nearly all overload is relay overload: it is caused by routes passing through the central cores, not by routes starting or ending there. That raises a question about the routes. The mapper chooses, for every qubit move, one Dijkstra shortest path (fewest hops, link reliability as the tie-break), without looking at what the other moves of the layer are doing. Many alternative shortest paths exist: between opposite corners of the 4×4 mesh there are $\binom{6}{3} = 20$. Could choosing them *offline*, with the mapping untouched, spread the relay load and reduce the congestion?

9.1 Method

The mapping is held fixed: every qubit still moves from the same core to the same core in the same layer. Only the path of each move (a *route*) is re-chosen, layer by layer (layers are independent because a layer's routes start and end at fixed cores). For each layer that has any overload, the choice of one candidate path per route is made by solving a small mixed-integer program exactly, minimising the *excess*, the demand above capacity summed over cores. The candidates are all simple paths of at most the shortest length plus 0 or 2 hops, and the mapper's own path is always a candidate, so the result is never worse than the baseline.

Two lower bounds hold for *any* routing, so they show how much is left to gain. Endpoints do not depend on the path, so the demand of a core is at least its endpoint demand; and a route of shortest length k puts at least $2k$ hop touches ($k+1$ route touches) on the cores, so the total excess is at least the minimum total demand minus (cores $\times$ capacity). Both are tested.

Demand is counted two ways: by hops (the archive's counting) and by routes, the number of qubits in flight through a core, which is what the per-qubit scheduler experiences.

9.2 Structural result

Capacity	Extra hops	Excess now	Excess after re-routing	Lower bound	Overloaded layers	Added hops
1	0	27043	21894 (19.0%)	18336	4110 → 3801	0.00%
1	2	27043	21018 (22.3%)	18336	4110 → 3621	2.55%
2	0	10385	6771 (34.8%)	4995	1641 → 978	0.00%
2	2	10385	6288 (39.5%)	4995	1641 → 840	1.48%
3	0	4774	1791 (62.5%)	846	855 → 420	0.00%
3	2	4774	1497 (68.6%)	846	855 → 327	0.98%
4	0	2216	348 (84.3%)	78	482 → 102	0.00%
4	2	2216	237 (89.3%)	78	482 → 48	0.36%

Table 9.1: Offline re-routing, mesh, route counting, pooled over ten benchmarks and three mapping seeds. Excess is demand above capacity.

Pooled over the ten benchmarks, the best routing removes most of the excess at the modelled capacity: with route counting at capacity four, shortest paths alone cut the excess from 2 216 to 348 (an 84.3% reduction) and the layers with any overload from 482 to 102; allowing two extra hops cuts it to 237 (89.3%) at a cost of 0.36% more hops. The gain shrinks as the capacity shrinks (19.0% at capacity one), because there the total relay volume, not the choice of path, is the limit, which the volume bound shows. With hop counting the reductions are smaller (65.6% at capacity four).

9.3 Simulated effect

The structural gain would be an artefact if it did not survive the simulator, so the re-routed traces were run in ACE next to the original routes, on-demand, at the budget they were optimised for, with the same mapping, endpoints, physics seeds and parameters. Three mapping seeds and three physics seeds give nine paired runs per cell.

Workload	Mem.	Original	Re-routed	+2 hops	Waited
Graph state	2	2.72	1.53 (+42.3% ±9.9; 9/9)	1.41 (+46.6% ±8.9; 9/9)	0.281 → 0.086
Graph state	3	1.53	1.15 (+22.9% ±11.8; 9/9)	1.19 (+19.6% ±13.5; 9/9)	0.121 → 0.000
Graph state	4	1.24	1.16 (+6.0% ±7.6; 7/9)	1.21 (+1.9% ±8.9; 4/9)	0.029 → 0.000
Draper QFT adder	2	2.16	1.69 (+21.1% ±7.9; 9/9)	1.48 (+31.1% ±6.8; 9/9)	0.211 → 0.115
Draper QFT adder	3	1.30	1.16 (+10.3% ±3.3; 9/9)	1.16 (+10.5% ±3.7; 9/9)	0.055 → 0.007
Draper QFT adder	4	1.15	1.13 (+1.3% ±1.3; 8/9)	1.14 (+1.1% ±0.8; 9/9)	0.008 → 0.000
QAOA	2	3.42	2.24 (+34.5% ±2.4; 9/9)	2.12 (+38.0% ±2.4; 9/9)	0.376 → 0.206
QAOA	3	1.74	1.25 (+28.4% ±2.3; 9/9)	1.19 (+31.4% ±2.2; 9/9)	0.172 → 0.037
QAOA	4	1.27	1.13 (+10.9% ±1.7; 9/9)	1.13 (+11.5% ±1.6; 9/9)	0.058 → 0.003
QFT	2	4.72	3.49 (+26.1% ±2.4; 9/9)	3.03 (+35.9% ±2.1; 9/9)	0.430 → 0.312
QFT	3	2.39	1.53 (+35.9% ±2.2; 9/9)	1.47 (+38.2% ±2.3; 9/9)	0.249 → 0.097
QFT	4	1.59	1.19 (+25.2% ±2.4; 9/9)	1.17 (+26.6% ±2.0; 9/9)	0.130 → 0.018
Random circuit	2	1.27	1.13 (+10.6% ±1.3; 9/9)	1.12 (+11.7% ±1.3; 9/9)	0.042 → 0.007
Random circuit	3	1.12	1.11 (+1.2% ±0.3; 9/9)	1.11 (+1.3% ±0.3; 9/9)	0.006 → 0.000
Random circuit	4	1.11	1.11 (+0.2% ±0.1; 9/9)	1.11 (+0.2% ±0.2; 8/9)	0.001 → 0.000

Table 9.2: Simulated on-demand latency (ms), mesh: original routes against offline re-routing. Brackets: paired reduction in latency (positive = faster), sd, pairs faster of nine.

Re-routing alone makes on-demand requests faster in nearly every pair. At two memories the latency falls by 21% to 42% on the four congested workloads (graph state, Draper, QAOA, QFT) and by 11% on the random circuit; at the modelled four memories by 25% for QFT, 11% for QAOA and 6% for graph state, and by 1% or less where there was little congestion. The fraction of requests that had to wait falls accordingly. Two extra hops help at two memories

(QFT 26% to 36%) and change little at four (within about 1.5 percentage points, except graph state, where they cost 4 points): the added hops cost about as much as the avoided waiting saves.

9.4 The torus

On the torus, which has more paths between cores, the optimum is closer to the lower bound still: at capacity four the excess falls from 493 to 15 (97.0%), against a lower bound of 6, and with two extra hops it reaches the bound.

Capacity	Extra hops	Excess now	Excess after re-routing	Lower bound	Overloaded layers	Added hops
1	0	20202	15858 (21.5%)	14847	3826 → 3339	0.00%
1	2	20202	15387 (23.8%)	14847	3826 → 3312	1.73%
2	0	6108	3351 (45.1%)	2847	1319 → 702	0.00%
2	2	6108	3108 (49.1%)	2847	1319 → 630	0.93%
3	0	1852	363 (80.4%)	303	562 → 162	0.00%
3	2	1852	342 (81.5%)	303	562 → 159	0.09%
4	0	493	15 (97.0%)	6	220 → 15	0.00%
4	2	493	6 (98.8%)	6	220 → 6	0.04%

Table 9.3: Offline re-routing, torus, route counting, pooled over ten benchmarks and three mapping seeds. Excess is demand above capacity.

Simulated on the torus, re-routing makes requests faster at two memories (latency falls by 15% for QFT, 32% for QAOA, 36% for Draper) but little at the modelled four (by 6.8% for QFT, 3.2% for QAOA, about 2% or nothing for the others), because the torus is already close to its latency floor there.

Workload	Mem.	Original	Re-routed	+2 hops	Waited
Graph state	2	1.86	1.27 (+31.2% ±7.2; 9/9)	1.28 (+31.0% ±6.9; 9/9)	0.157 → 0.033
Graph state	3	1.25	1.10 (+11.0% ±7.4; 8/9)	1.12 (+10.3% ±8.7; 8/9)	0.033 → 0.000
Graph state	4	1.11	1.12 (-0.4% ±1.7; 1/9)	1.11 (+0.3% ±3.9; 2/9)	0.000 → 0.000
Draper QFT adder	2	2.25	1.45 (+35.6% ±1.9; 9/9)	1.26 (+44.0% ±1.4; 9/9)	0.226 → 0.075
Draper QFT adder	3	1.28	1.15 (+10.5% ±1.8; 9/9)	1.14 (+10.7% ±1.0; 9/9)	0.053 → 0.007
Draper QFT adder	4	1.13	1.11 (+1.8% ±0.6; 9/9)	1.11 (+1.6% ±0.8; 9/9)	0.008 → 0.000
QAOA	2	2.47	1.66 (+32.3% ±4.7; 9/9)	1.62 (+34.2% ±4.7; 9/9)	0.265 → 0.111
QAOA	3	1.40	1.15 (+17.6% ±4.6; 9/9)	1.14 (+18.3% ±4.3; 9/9)	0.083 → 0.004
QAOA	4	1.17	1.13 (+3.2% ±2.8; 9/9)	1.13 (+3.1% ±2.6; 9/9)	0.016 → 0.000
QFT	2	2.79	2.37 (+14.7% ±7.3; 9/9)	2.42 (+12.7% ±7.8; 9/9)	0.303 → 0.221
QFT	3	1.51	1.21 (+19.3% ±6.0; 9/9)	1.24 (+17.3% ±6.1; 9/9)	0.102 → 0.023
QFT	4	1.21	1.13 (+6.8% ±3.2; 9/9)	1.12 (+7.3% ±3.0; 9/9)	0.028 → 0.001
Random circuit	2	1.19	1.11 (+6.1% ±0.9; 9/9)	1.11 (+6.3% ±0.9; 9/9)	0.022 → 0.002
Random circuit	3	1.11	1.11 (+0.4% ±0.1; 9/9)	1.11 (+0.3% ±0.1; 9/9)	0.001 → 0.000
Random circuit	4	1.11	1.11 (0.0% ±0.1; 1/9)	1.11 (0.0% ±0.1; 3/9)	0.000 → 0.000

Table 9.4: Simulated on-demand latency (ms), torus: original routes against offline re-routing. Brackets: paired reduction in latency (positive = faster), sd, pairs faster of nine.

9.5 What can and cannot be concluded

Offline routing *can* reduce congestion: with the mapping fixed, an exact offline choice of paths removes most of the excess demand at the modelled capacity and the simulated latencies fall with it. These are results for an offline optimum with global knowledge of every layer, computed per layer for the capacity the hardware has; a practical routing algorithm would be a heuristic for the same problem and would be bounded by it. Not shown here: the effect on pre-generation

policies (only on-demand was simulated), joint optimisation of mapping and routing, fidelity effects (the on-demand fidelity does not depend on waiting), and a routing policy that does not know the layer in advance. Whether to pursue the research further is therefore a question about those directions, and the bounds above say how much headroom each could have.

Chapter 10

The torus topology

10.1 What changes

A 4×4 torus joins the opposite edges of the mesh with eight extra links, so every core has four neighbours and the longest path shrinks from six hops to four. Everything else is held as in the mesh experiments: the same ten benchmarks, the same mapper (HQA) with the same seeds, the same ACE parameters, the same link length for every link (a folded layout; the wrap links are not longer), the same scheduler, budgets, policies, physics seeds and controls.

Routing. The routes are the mapper's own: a Dijkstra search for the path with the fewest hops, with the product of link reliabilities as the tie-break (route model `shortest`), exactly as for the mesh traces. The mapping-only path of the study script was checked to reproduce the archived mesh trace line for line before it was used for the torus. ACE itself needed three changes: trace validation knows wrap-around links; the topology file is generated from the mesh file by adding the eight wrap links in the mesh's own link format (every router then has four quantum links, tested by loading it in ACE); and a torus trace is refused on a mesh topology file and the reverse.

One caveat. The mapper is run on the torus graph, so the torus traces differ from the mesh traces in the placement as well as the routes. Differences below are differences of the two systems, not of the topology alone.

10.2 Results

Torus traces need 11% to 37% fewer hops than the mesh traces (CDKM 11%, QFT 23%, QAOA 16%, GHZ 25%, VQE 37%). Every control passed on all 1 368 runs, as for the mesh (Chapter 7).

Workload	Hops	Overload% at C=4	On-demand ms, 2 mem.	On-demand ms, 4 mem.	Dynamic ms, 8 mem.
GHZ	24/18	0.0/0.0	1.17/1.15	1.17/1.15	0.26/0.28
Bernstein–Vazirani	25/21	0.0/0.0	1.22/1.11	1.22/1.11	0.24/0.23
BMW/QUARK cardinality	144/108	0.0/0.0	1.12/1.10	1.12/1.10	0.25/0.25
VQE real amplitudes	104/66	6.1/1.5	1.11/1.14	1.11/1.14	0.25/0.30
CDKM ripple-carry adder	456/406	0.6/0.6	1.24/1.11	1.14/1.09	0.30/0.29
Graph state	76/60	33.3/38.9	2.72/1.86	1.24/1.11	0.95/0.62
Draper QFT adder	1310/984	41.3/25.8	2.16/2.25	1.15/1.13	0.89/0.74
QAOA	3068/2562	71.6/57.9	3.42/2.47	1.27/1.17	1.86/1.10
QFT	2510/1938	65.2/58.0	4.72/2.79	1.59/1.21	2.78/1.16
Random circuit	11688/9574	8.0/3.4	1.27/1.19	1.11/1.11	0.38/0.29

Table 10.1: Mesh/torus. Hops: mean requests per trace. Overload: % of active layers with any core above capacity 4. Latencies are means over nine runs.

On-demand latency under congestion improves: at two memories QFT goes from 4.72 to 2.79 ms, QAOA from 3.42 to 2.47 ms and graph state from 2.72 to 1.86 ms; at four memories QFT from 1.59 to 1.21 ms. Dynamic pre-generation also gets faster under congestion (QFT at eight memories: 2.78 to 1.16 ms). The structural overload at capacity four falls for most workloads (QFT 65.2% to 58.0%, QAOA 71.6% to 57.9%, Draper 41.3% to 25.8%) but not for graph state, where it rises from 33.3% to 38.9% (only six layers are active, so a single layer is 17 percentage points). Draper at two memories is slightly slower on the torus (2.16 to 2.25 ms).




Figure 10.1: Per-core congestion at capacity 4 on the mesh (left of each pair) and on the torus (right), for every workload. The torus lowers the overload in five workloads, leaves four unchanged and raises it for graph state; the traces differ in placement as well as topology.

Chapter 11

Run times

Wall-clock times on the development machine (8 CPUs). An *invocation* is one process running one benchmark at one budget and policy for three physics seeds. Times from parallel runs include contention from the other jobs; the serial pass was run one invocation at a time and is the cleanest per-benchmark measurement. It was not isolated from light unrelated work on the machine (file edits, short tests), so expect a few percent of noise.

Experiment	Jobs	Runs	Wall clock
Experiment 1, mesh	4	1368	24.5 min
Experiment 1, torus	4	1368	25.2 min
Sensitivity arm	4	120	105.0 s
Serial timing pass	1	270	8.6 min

Table 11.1: Wall-clock time of each experiment.

Benchmark	on-demand, memories					dynamic, memories			
	1	2	4	8	32	2	4	8	32
GHZ	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
Bernstein-Vazirani	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
BMW/QUARK cardinality	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
VQE real amplitudes	0.4	0.4	0.4	0.4	0.4	0.4	0.5	0.5	0.5
CDKM ripple-carry adder	0.6	0.6	0.6	0.6	0.6	0.7	0.7	0.7	0.8
Graph state	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4	0.4
Draper QFT adder	1.1	1.1	1.1	1.1	1.2	1.2	1.4	1.4	1.6
QAOA	2.1	2.1	2.1	2.2	2.4	2.4	2.8	3.1	3.5
QFT	1.8	1.8	1.7	1.8	2.0	1.9	2.2	2.5	2.9
Random circuit	7.8	7.9	8.0	8.0	8.8	10.6	14.1	14.9	15.3

Table 11.2: Seconds of real time per simulation run, one run at a time (serial pass, mapping seed 42; mean over three physics seeds).

The CGP and ACGP runs of Chapter 13 (four parallel jobs next to other work on the machine) finished their first 380 of 426 mesh invocations in 126 minutes; the rest are the random circuit's large-memory runs, which each take from 10 min to over an hour and were set aside; the driver was stopped before it wrote its timing file, so the per-invocation times of those runs were not recorded. The 70 diagnostic runs (Chapter 12), run two at a time, took 47 minutes; their individual times are in each JSON file (`wall_seconds`). The heatmap regeneration takes 2.7 s and the endpoint-versus-relay split 4.3 s. The new scheduler costs a few percent more real time than the legacy one on the larger traces, because it reads the reservation tables at admission.

Real time is unrelated to the simulated latencies the experiments report. The full set of numbers, including parallel per-benchmark sums, is in `docs/reports/run-times.md`.

Chapter 12

Why dynamic pre-generation can be slower than on-demand

The aim of compiler-driven pre-generation is a latency comparable to or better than on-demand generation (ODG) with fewer wasted pairs than the autonomous protocols (CGP, ACGP). Experiment 1 found that, on the corrected scheduler and at the modelled memory counts, dynamic pre-generation is *slower* than ODG on the congested benchmarks (QFT at four memories: ODG 1.59 ms, dynamic 5.57 ms, mean of nine runs), and faster once memory is plentiful (QFT at sixteen memories: 1.14 against 0.80 ms). The tables of this chapter use one mapping seed (42) unless they say otherwise, so their QFT numbers (1.57 and 5.46 ms at four memories) differ slightly. This chapter finds out why. Everything here was measured on ACE with the corrected scheduler, and the explanation is checked against the code (Section 12.2).

12.1 What the old, serialized scheduler showed

The scheduler used before the corrections let each core serve one request per batch. Under it the same comparison gave the opposite sign (Table 12.1): dynamic was faster than ODG at every memory count, by 41% on QFT at four memories in the old scheduler's own latency. Two things changed. First, the old latency started a request's clock when its batch was submitted, so the long waits for earlier batches were not in it; counting them ("old common") the gain on QFT at four memories is 11%, and the whole trace took 13.2 s with ODG and 12.3 s with dynamic (Table 12.2). Second, the old scheduler let a core serve one request at a time, and in the old QFT runs at four memories no request waited for a memory under either policy (retry wait 0.0 ms for ODG and for dynamic), while ODG's own latency did not respond to the number of memories at all. The corrected scheduler runs the requests of a layer concurrently, as the hardware would, and the waiting appears.

Workload	Mem.	Old own ODG	Old own Dyn.	Old own gain	Old common ODG	Old common Dyn.	Old common gain	New common ODG	New common Dyn.	New common gain
QFT	2	1.11	0.93	17%	25.06	23.95	4%	4.72	10.06	-113%
QFT	3	1.11	0.77	31%	25.06	23.03	8%	2.39	7.49	-214%
QFT	4	1.11	0.65	41%	25.06	22.30	11%	1.59	5.57	-250%
QFT	32	1.11	0.25	77%	25.06	20.28	19%	1.13	0.25	78%
QAOA	2	1.11	0.91	18%	13.39	12.56	6%	3.42	6.89	-101%
QAOA	3	1.11	0.74	34%	13.39	11.84	12%	1.74	5.33	-207%
QAOA	4	1.11	0.61	45%	13.39	11.34	15%	1.27	3.88	-205%
QAOA	32	1.11	0.25	78%	13.39	10.14	24%	1.13	0.25	78%
Draper QFT adder	2	1.12	0.84	26%	9.40	8.57	9%	2.16	4.55	-111%
Draper QFT adder	3	1.12	0.60	47%	9.40	7.91	16%	1.30	3.67	-182%
Draper QFT adder	4	1.12	0.47	58%	9.40	7.55	20%	1.15	2.48	-116%
Draper QFT adder	32	1.12	0.25	78%	9.40	7.05	25%	1.13	0.25	78%
Graph state	2	1.16	0.84	27%	9.98	9.05	9%	2.72	6.36	-134%
Graph state	3	1.16	0.63	46%	9.98	8.42	16%	1.53	5.01	-228%
Graph state	4	1.16	0.49	58%	9.98	7.91	21%	1.24	3.23	-161%
Graph state	32	1.16	0.25	78%	9.98	7.28	27%	1.18	0.25	79%
GHZ	2	1.17	0.51	56%	1.17	0.51	56%	1.17	0.51	56%
GHZ	3	1.17	0.26	78%	1.17	0.26	78%	1.17	0.26	78%
GHZ	4	1.17	0.26	78%	1.17	0.26	78%	1.17	0.26	78%
GHZ	32	1.17	0.26	78%	1.17	0.26	78%	1.17	0.26	78%

Table 12.1: Request latency (ms) of on-demand (ODG) and dynamic (Dyn.) and the dynamic gain (ODG − Dyn.)/ODG. Old own: the old serialized scheduler's own latency, whose clock for a request starts when its batch is submitted. Old common: the same old runs under the common definition, which also counts the wait for earlier batches. New common: the corrected per-qubit scheduler under the common definition. Mean of nine runs (three mapping seeds, three physics seeds).

Workload	Old ODG	Old Dyn.	New ODG	New Dyn.
QFT	13.23	12.34	4.66	5.75
QAOA	12.76	11.72	5.48	6.62
Draper QFT adder	7.64	6.97	4.88	5.03
Graph state	0.40	0.36	0.24	0.26
GHZ	0.33	0.30	0.33	0.30

Table 12.2: End-to-end time of the whole trace (s) at four memories per core, old serialized scheduler and corrected scheduler (mean of nine runs).

12.2 What the code does with a pre-generated pair

The explanation below was checked against the source, not inferred from the results. File and line numbers refer to the repository at the commit that contains this report.

1. **When a dynamic preparation starts.** The planner gives each request a generation layer. For the dynamic policy the candidate layers are tried from the one just before the request's own layer, backwards (`compiler_trace.py:254`), and the first one with room is taken. The controller launches a layer's preparations when that layer is activated (`request_scheduler.py:151-158`, `compiler_scheduler.py:66`). So a pair for a request in layer L is normally started at the *start* of layer $L-1$ and has to wait for all of layer $L-1$ to finish before its request can even be released. The lookahead of eight layers is only an upper limit. Planning with a lookahead of one, two, four and eight gave the same schedule in all 210 configurations (ten benchmarks, three mapping seeds, seven memory counts), and the lookahead-eight plan never places a preparation earlier than the layer just before its request (0 of 333 335; `tools/diagnostics/check_lookahead.py`). A likely reason, which was not tested separately, is that an earlier layer would hold its memory through the layer just before the request as well, so wherever that layer has no room an earlier one has none either.

2. **What a prepared pair occupies.** A preparation books one memory card at each of its two cores, with a window of 1 000 ms (`adaptive_continuous.py:192-236`), and it may not exceed the compiler cap, the same counter that limits the autonomous protocol (`adaptive_continuous.py:201`). The booking is released only when the pair is consumed (`reservation.py:473`) or its window ends. If the cap is reached the preparation is rejected and retried every millisecond until its request starts (`compiler_scheduler.py:113-120`).

3. **A request that has a ready pair still needs a memory of its own.** Admission asks for a free card at both cores, and a card with any overlapping booking is not free (`request_scheduler.py:202-215, 232-255`); the prepared pair's own booking overlaps. When the request's reservation runs, the generation protocol looks for a ready pair for the same two cores, and if it finds one it *swaps* the pair's state into the request's own memory after a classical delay (`generation.py:265-296, 301-343`) and only then releases the prepared pair's memory (`generation.py:342`). So for a short time a hit holds *two* cards at each core. This is a property of ACE's design, not of the compiler policy, and it is why requests served from a ready pair can still wait for admission.

4. **What an on-demand request occupies.** One card per core, from admission until completion. Its booking window is the request duration (50 ms), but the booking is released at completion, so what matters is the time it exists, about 6 ms in the measurements, not the window.

5. **CGP and ACGP.** Every cycle of the autonomous protocol draws a neighbour by roulette wheel over a probability table (`adaptive_continuous.py:262-276`) and books one card at both ends until a 0.2 s boundary within the next 0.2 s (`adaptive_continuous.py:147-178`; the period is 2×10^{11} ps, `node.py:57`), as long as fewer than the cap are in use. The table is uniform for CGP (`adaptive_continuous.py:243-260`). For ACGP it is updated every 0.2 s: each neighbour that appears in an entanglement path used in the last 0.2 s gains 0.05 and the table is renormalized (`adaptive_continuous.py:404-447`). Pairs are therefore made for whichever neighbour was drawn, not for a particular request. An application request takes a pair for its own two cores if one exists: first a compiler pair targeted at *that* request, otherwise an ordinary autonomous pair with no compiler metadata (`adaptive_continuous.py:511-523`), through the same swap. A pair nobody uses before its window ends is discarded; that is the waste the experiments count.

Two consequences follow directly from the code and are tested in the measurements below. First, pre-generation always costs memory cards for longer than an on-demand request does (a ready pair exists *before* its request, and for a later hop of a chain well before it, because a hop is released only after its predecessor completed). Second, it saves only the generation time (a request served from a ready pair generates in about a quarter of a millisecond instead of about a millisecond); the lead and the classical delays are the same either way.

12.3 Measurements

Diagnostic runs (the code is in `tools/diagnostics/`; the results are listed in the repository map, Appendix E) record, for each run, how long each request waited and why: at every admission check that found no free memory they record which kind of booking held the memory cards at the stuck core. They use ACE as it is and change nothing in the simulation.

12.3.1 The extra latency is waiting, not generation

Mem.	ODG lat.	ODG wait	Dynamic lat.	Dynamic wait	CGP lat.	CGP wait	ACGP lat.	ACGP wait
2	4.60	3.48	9.43	8.50	12.29	11.39	11.86	10.99
3	2.36	1.23	7.05	6.28	10.58	9.89	10.65	9.96
4	1.57	0.44	5.46	4.81	10.15	9.58	10.52	9.98
6	1.20	0.07	3.44	2.95	8.98	8.56	9.47	9.08
8	1.15	0.01	2.62	2.24	8.92	8.55	9.26	8.92
16	1.14	0.00	0.71	0.46	8.03	7.74	8.95	8.66

Table 12.3: QFT, mapping seed 42, mean of three physics seeds: request latency and the part of it spent waiting for a free memory (ms). The remainder of the latency is generation.

Generation itself gets faster with pre-generation (QFT at four memories: 1.13 ms for ODG, 0.65 ms for dynamic on average, 0.25 ms for a request served from a ready pair), but the wait for a free memory grows from 0.44 to 4.81 ms. CGP and ACGP wait even more (9.6 and 10.0 ms) and improve little with more memory: their wait is 7.7 and 8.7 ms even at sixteen memories (Table 12.3).

12.3.2 What holds the memories

Mem.	ODG	Dynamic	CGP	ACGP	Dyn. by compiler	CGP by cache	ACGP by cache
2	18.3%	23.3%	42.2%	44.4%	40%	47%	46%
3	12.0%	21.3%	44.8%	45.9%	55%	65%	65%
4	6.8%	17.2%	45.3%	46.1%	60%	74%	74%
6	1.6%	12.0%	46.5%	47.0%	66%	83%	83%
8	0.4%	8.6%	45.9%	47.3%	73%	87%	87%
16	0.0%	1.1%	46.5%	46.8%	81%	94%	94%

Table 12.4: QFT, mapping seed 42. Left: share of admission checks that found no free memory at one of the request's two cores. Right: of the memory cards found taken at a stuck core, the share held by the policy's own pre-generation bookings (the rest are held by other requests).

At four memories 17% of dynamic's admission checks find no free memory, against 7% for ODG; of the cards taken at a stuck core, 60% are held by the compiler's own prepared pairs. For CGP and ACGP 42 to 47% of checks are stuck at every memory count, and 74% of the taken cards at four memories (94% at sixteen) are autonomous bookings: the protocol fills every memory it is allowed to, with pairs for neighbours drawn at random (Table 12.4).

12.3.3 Requests with a ready pair still wait

Mem.	Hits	Hit wait	Hits that waited	Other wait	Pair held	Request holds
2	21.0%	4.62	32%	9.54	28.9	6.2
3	39.0%	3.68	37%	7.95	25.9	6.0
4	52.8%	2.93	35%	6.91	23.7	5.9
6	73.1%	2.03	31%	5.48	21.2	5.7
8	84.7%	1.67	25%	5.42	20.2	5.6
16	99.1%	0.39	6%	7.56	17.2	5.5

Table 12.5: Dynamic, QFT, mapping seed 42 (mean of three physics seeds). Hits: share of requests served by a ready pair, i.e. a prepared pair generated by the time it was used. Hit wait and Other wait: mean wait for a free memory (ms) of the hits and of the other requests. Pair held: time (ms) a ready pair waits in memory before it is used. Request holds: time (ms) an ordinary request keeps its memory card booked.

Of the requests dynamic serves from a ready pair, 35% still wait for admission at four memories (Table 12.5). That follows from the code: the request needs a free card of its own in addition to the card the ready pair occupies (item 3 of Section 12.2). A ready pair waits 24 ms in memory on average before it is used at four memories; an ordinary request keeps its card booked for 5.9 ms.

12.3.4 Why a prepared pair waits so long

Position in the chain	Pairs used	Made before its layer started (ms)	Ready pair held (ms)	Request eligible after pair ready (ms)
first hop	604	4.4	11.9	4.4
second hop	257	4.6	23.7	12.2
third hop or later	464	4.9	39.2	31.4

Table 12.6: Dynamic, QFT, four memories, mapping seed 42 (mean of three physics seeds): the pair of a later hop is made as early as the pair of a first hop, but its request becomes eligible much later, so the pair waits longer.

A pair is made at the start of the layer before its request's layer (Section 12.2, item 1), and the request is released only when its layer has started and, for the second and later hop of a qubit's chain, when the previous hop has completed. Table 12.6 shows both effects: the pair of a later hop is made about as early as the pair of a first hop but its request is eligible much later, so the pair holds a memory for 24 and 39 ms instead of 12 ms. More than half of dynamic's pairs on QFT (54%) are for hops after the first.

12.4 What does and does not change the result

Policy	Change from the baseline	Latency (ms)	Wait (ms)	Ready-pair hits	Fidelity
Dynamic	baseline	5.46	4.81	53%	0.9274
Dynamic	compiler memories 1 of 4	1.88	0.95	21%	0.9431
Dynamic	compiler memories 2 of 4	2.77	2.01	39%	0.9364
Dynamic	request-duration-ms=10	5.45	4.80	53%	0.9274
Dynamic	request-duration-ms=100	5.46	4.80	53%	0.9274
Dynamic	request-duration-ms=20	5.46	4.80	53%	0.9274
Dynamic	pairs only for the first 1	1.89	0.98	24%	0.9449
Dynamic	pairs only for the first 2	3.06	2.25	35%	0.9406
Dynamic	compiler memories 3 of 4	5.54	4.88	53%	0.9221
Dynamic	compiler memories 3 of 4	5.43	4.77	53%	0.9262
Dynamic	dynamic-lookahead-layers=1	5.46	4.81	53%	0.9274
Dynamic	dynamic-lookahead-layers=2	5.46	4.81	53%	0.9274
Dynamic	dynamic-lookahead-layers=4	5.46	4.81	53%	0.9274
Dynamic	compiler-reservation-ms=100	5.46	4.81	53%	0.9274
Dynamic	compiler-reservation-ms=300	5.46	4.80	53%	0.9274
ODG	baseline	1.57	0.44	0%	0.9498
ODG	request-duration-ms=10	1.57	0.44	0%	0.9498
ODG	request-duration-ms=100	1.57	0.44	0%	0.9498
ODG	request-duration-ms=20	1.57	0.44	0%	0.9498

Table 12.7: QFT, four memories, mapping seed 42, mean of three physics seeds. Each row changes one setting. These are experiments to find the cause, not proposed settings.

Each row of Table 12.7 changes one setting of the QFT run at four memories.

- **No effect:** the request duration (the nominal booking window, 10 to 100 ms), the compiler reservation window (100 to 1000 ms) and the generation capacity per core. What matters is how long a booking *exists*, not the length of the window it was made for. The planner's lookahead (one, two, four or eight layers) makes no difference either: not to the latency of the QFT run, and not to the planner's schedule in any of 210 configurations (Section 12.2, item 1).
- **Strong effect:** the number of memories the compiler may hold. One of four: 1.88 ms; two: 2.77 ms; three: 5.46 ms (ODG: 1.57 ms). Fewer prepared pairs, less waiting.
- **Preparing only first hops** (later hops fall back to on-demand): 1.89 ms with the compiler's three memories, and the ready pairs wait 11 instead of 24 ms. This supports the chain explanation but does not make dynamic better than ODG at four memories; it is an experiment to isolate the cause, not a proposed policy.

12.5 Other mapping seeds and other benchmarks

Policy	map 42 lat.	map 42 wait	map 43 lat.	map 43 wait	map 44 lat.	map 44 wait
ODG	1.57	0.44	1.65	0.52	1.55	0.42
Dynamic	5.46	4.81	5.84	5.19	5.40	4.73
CGP	10.15	9.58	10.26	9.68	9.94	9.37
ACGP	10.52	9.98	10.76	10.22	10.53	9.97

Table 12.8: QFT, four memories: the diagnosis on the three mapping seeds (mean of three physics seeds each; latency and wait in ms).

Workload	ODG (ms)	Dynamic (ms)	CGP (ms)	ACGP (ms)	Dynamic hits	Dyn. stuck checks	ODG stuck checks
CDKM ripple-carry adder	1.14	0.30	0.82	0.76	95%	0.0%	0.0%
VQE real amplitudes	1.15	0.83	1.41	1.43	96%	4.4%	0.0%
Random circuit	1.11	0.97	2.08	2.13	87%	12.9%	0.0%
Draper QFT adder	1.16	2.45	5.45	5.65	73%	21.7%	0.5%
Graph state	1.19	4.24	5.03	5.07	68%	16.0%	0.7%
QAOA	1.28	4.07	8.12	8.43	56%	22.3%	3.4%
QFT	1.57	5.46	10.15	10.52	53%	17.2%	6.8%

Table 12.9: Request latency at four memories on the other benchmarks (mapping seed 42, mean of three physics seeds), the share of requests dynamic served from a ready pair, and the share of admission checks that found no free memory under dynamic and under on-demand. Dynamic is faster than on-demand where its own prepared pairs rarely get in the way.

The picture is the same on the other two mapping seeds (Table 12.8). On the other benchmarks (Table 12.9) dynamic is faster than ODG on the three benchmarks where the fewest of its admission checks are stuck (the CDKM adder 0%, VQE 4%, the random circuit 13%) and slower on the four where more are (16 to 22%: graph state, QFT, Draper, QAOA). That is a correlation across seven benchmarks, consistent with the mechanism, not a separate test of it. The full grid of benchmarks and memory counts is in Chapter 13.

12.6 What this establishes, and what it does not

- **Established** (measured, with the mechanism read in the code): at the modelled memory counts, pre-generated pairs occupy memory cards for several times as long as an on-demand request does, the resulting scarcity of free cards costs more waiting than the avoided generation saves, and the effect disappears when the cards are not scarce.
- **Established:** no tested setting of the simulator's windows or capacities explains the effect; the number of memories the compiler may hold does.
- **Not established:** that a better plan could not do better. The planner works in whole layers and does not know when a chain hop will actually become eligible, or that a ready pair also needs a card for its request. A planner that did would be a new algorithm; none is proposed or tested here.
- **Not established:** how this changes under other physical parameters (Chapter 7, sensitivity arm) or on other topologies beyond what Chapter 13 reports.
- The diagnosis rests on QFT in depth; the other benchmarks give the same sign of effect in one mapping seed.

Chapter 13

ODG, dynamic, CGP and ACGP compared on nine benchmarks

Chapter 7 compared on-demand generation (ODG) and dynamic compiler pre-generation. This chapter adds the two autonomous protocols that the compiler-driven approach is meant to improve on: CGP (continuous generation, neighbour drawn uniformly) and ACGP (adaptive continuous generation, neighbour probabilities adapted to recent traffic). The goal stated for the compiler-driven approach is a latency comparable to the alternatives with fewer wasted pairs, so the comparison is on latency, delivered fidelity, wasted pairs and readiness, with the wait for a free memory as the explanation.

13.1 What was run

Same traces, memory counts $(2, 3, 4, 6, 8, 16, 32$; QFT also 64), mapping seeds (42, 43, 44), physics seeds (0, 1, 2), physical parameters and corrected scheduler as Experiment 1, on the mesh and on the torus, for CGP and for ACGP: 384 invocations (1 152 runs) per topology. ODG and dynamic are the Experiment 1 runs, not repeated. Two settings of the autonomous protocols needed a decision and were made so that the comparison with dynamic is fair, as opt-in options that leave the default behaviour untouched (the 164-row legacy baseline still reproduces exactly, and all 162 tests pass):

- **Cache cap.** ACE's configuration file gives the autonomous protocols a fixed cap of three cached pairs per core whatever the number of memories (`adaptive_max_memory`). Dynamic is given a compiler bank of memories-1. CGP and ACGP are given the same cap, memories-1 (`-autonomous-cache-follows-compiler-memories`). With the fixed cap of three they would have been allowed to cache three pairs in two memories.
- **End of the run.** The autonomous protocols keep generating pairs until the simulation's stop time (300 s of simulated time), long after the last request. The runs were stopped 1 ms after the last request completed (`-stop-after-workload`), so that wasted pairs are counted over the workload's own duration and not over an arbitrary stop time. This changes no request metric: for QFT at four memories CGP's latency is 9.963931 ms with and without it.

The **random circuit was set aside** for CGP and ACGP: its runs at large memory counts take over an hour each. It is therefore left out of every table and figure in this chapter (ODG and dynamic for it are in Chapter 7; the diagnostic Table 12.9 has all four policies for it at four memories, mapping seed 42). The runs that had finished when it was stopped are kept in the results folder but not analysed.

Definitions. Latency is the common latency of Chapter 5. *Wait* is the part of it spent waiting for a free memory. *Waste* is (pairs generated − pairs used)/pairs generated from the simulator's protocol counters over the workload's duration; a pair still cached when the run stops counts as not used, as in the compiler's own accounting. (The simulator's own waste figure counts only pairs that expired unused and is lower for short workloads; both are in `four_policy_cell_means.csv`.) *Readiness* is pairs used per request: for dynamic it equals the share of requests served from a ready pair; for CGP and ACGP it is the number of cached pairs that requests consumed, divided by the number of requests (a pair is counted at both of its endpoints, so the counters are divided by twice the number of requests).

13.2 Checks

- Every one of the 2 304 CGP/ACGP runs (1 152 per topology) completed every request (completion rate 1.0).
- The waste counters were checked against an independent count of the pair events on one run (QFT, four memories, CGP): 4 720 pairs generated and 3 068 used by both counts. The simulator's "unused" counter, which is incremented when a cached memory is released, agreed with the count of pairs that expired while cached to within 1.2% (it also counts 20 releases of memories that held no pair).
- Dynamic's compiler pairs were all used in every one of the 639 mesh runs of Experiment 1 (none expired, none left over); on the torus at most one pair expired in any of its 639 runs (at most 0.013% of a run's pairs).
- The mechanism behind every number was read in the code and measured separately (Chapter 12).

13.3 Latency




Figure 13.1: Request latency against memories per core, all four policies (log scale). Mesh, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

Workload	ODG	Dynamic	CGP	ACGP
GHZ	1.17	0.26	0.48	0.52
Bernstein–Vazirani	1.22	0.24	0.57	0.56
BMW/QUARK cardinality	1.12	0.25	0.50	0.48
VQE real amplitudes	1.11	0.88	1.44	1.46
CDKM ripple-carry adder	1.14	0.30	0.77	0.73
Graph state	1.24	3.23	4.88	5.00
Draper QFT adder	1.15	2.48	5.00	5.19
QAOA	1.27	3.88	7.75	7.97
QFT	1.59	5.57	10.11	10.60

Table 13.1: Request latency (ms), mesh, 4 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

Figure 13.1 and Table 13.1 give the picture on the mesh. Three results stand out.

- **Dynamic is the fastest of the three pre-generation policies at every memory count from two on, on every benchmark** except one cell (CDKM adder at 32 memories, where CGP and ACGP are 0.27 against dynamic's 0.30 ms; Table 13.4). At four memories the better of CGP and ACGP takes 1.5 to 2.4 times dynamic's latency on the mesh and 1.9 to 2.5 times on the torus.
- **Against ODG, dynamic wins on five of the nine benchmarks at the modelled four memories and loses on four.** It wins on BMW, Bernstein–Vazirani, GHZ, the CDKM adder and VQE, and at 32 memories it is 74 to 80% faster than ODG on all nine (ODG's floor is the generation time of about a millisecond, a ready pair needs a quarter of that); on four of the five it is faster from two memories on. It loses on QFT, QAOA, Draper and graph state at two to four memories and overtakes ODG from eight memories on Draper and graph state and from sixteen on QAOA and QFT (Tables 13.3 and 13.4). The cause is Chapter 12.
- **CGP and ACGP beat ODG only where ODG is already at its floor.** They are faster than ODG at every memory count on BMW, Bernstein–Vazirani, GHZ and the CDKM adder, and on VQE at some, but *never* on QFT, QAOA, Draper or graph state: at four memories they take 4.9 to 10.6 ms on those four against 1.2 to 1.6 ms for ODG. Their wait barely improves with memory.

ACGP is not measurably better than CGP: their latencies differ by a median of 2.5% on the mesh and 1.9% on the torus (at most 11% and 14%), and their waste by under two points. Why the adaptation has so little effect was not investigated.

Workload	ODG	Dynamic	CGP	ACGP
GHZ	1.17	0.51	1.00	0.99
Bernstein–Vazirani	1.22	0.46	0.97	0.94
BMW/QUARK cardinality	1.12	0.49	0.88	0.86
VQE real amplitudes	1.11	1.52	1.96	1.95
CDKM ripple-carry adder	1.24	0.76	1.19	1.20
Graph state	2.72	6.36	8.15	8.19
Draper QFT adder	2.16	4.55	6.10	6.11
QAOA	3.42	6.89	9.31	9.39
QFT	4.72	10.06	12.34	12.27

Table 13.2: Request latency (ms), mesh, 2 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

Workload	2	3	4	6*	8*	16*	32*
GHZ	56%	78%	78%	78%	78%	78%	78%
Bernstein–Vazirani	62%	80%	80%	80%	80%	80%	80%
BMW/QUARK cardinality	56%	78%	78%	78%	78%	78%	78%
VQE real amplitudes	-37%	-7%	21%	63%	77%	77%	77%
CDKM ripple-carry adder	39%	67%	73%	74%	74%	74%	74%
Graph state	-134%	-228%	-161%	-36%	19%	77%	79%
Draper QFT adder	-111%	-182%	-116%	-41%	21%	78%	78%
QAOA	-101%	-207%	-205%	-137%	-64%	69%	78%
QFT	-113%	-214%	-250%	-209%	-142%	29%	78%

Table 13.3: Latency gain of dynamic over on-demand, (ODG − Dyn.)/ODG, mesh; negative means dynamic is slower. Budgets marked * are counterfactual.

Workload	Dynamic beats ODG from (memories)	vs CGP win/tie/loss	vs ACGP win/tie/loss	Fidelity Dyn.	CGP	ACGP	ODG
GHZ	2	6/1/0	6/1/0	0.925	0.877	0.878	0.950
Bernstein–Vazirani	2	5/2/0	5/2/0	0.927	0.868	0.865	0.950
BMW/QUARK cardinality	2	7/0/0	7/0/0	0.925	0.872	0.870	0.950
VQE real amplitudes	4	7/0/0	7/0/0	0.916	0.899	0.899	0.950
CDKM ripple-carry adder	2	6/0/1	6/0/1	0.923	0.913	0.912	0.950
Graph state	8	7/0/0	7/0/0	0.919	0.900	0.900	0.950
Draper QFT adder	8	7/0/0	7/0/0	0.922	0.903	0.902	0.950
QAOA	16	7/0/0	7/0/0	0.925	0.905	0.904	0.950
QFT	16	8/0/0	8/0/0	0.927	0.908	0.905	0.950

Table 13.4: Where dynamic lies, mesh. Column 2: the smallest memory count from which dynamic has lower latency than on-demand (†: with at least one later count where it does not). Columns 3–4: over the memory counts run for both policies (2 to 32; QFT also 64), the number at which dynamic has lower latency, equal latency (the floor reached when nothing waits) or higher latency than CGP and than ACGP. Columns 5–8: delivered fidelity at four memories.

Mem.	ODG	Dynamic	CGP	ACGP
1	9	0	0	0
2	5	4	0	0
3	5	4	0	0
4	4	5	0	0
6	4	5	0	0
8	2	7	0	0
16	0	8	0	1
32	0	6	1	2

Table 13.5: Mesh: number of benchmarks (of ten) on which each policy has the lowest latency at each memory count (a policy is counted only where it was run; dynamic, CGP and ACGP start at two memories).

13.4 Delivered fidelity




Figure 13.2: Delivered EPR fidelity against memories per core. Mesh, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

Workload	ODG	Dynamic	CGP	ACGP
GHZ	0.9498	0.9254	0.8774	0.8778
Bernstein–Vazirani	0.9498	0.9266	0.8683	0.8654
BMW/QUARK cardinality	0.9498	0.9253	0.8720	0.8697
VQE real amplitudes	0.9498	0.9165	0.8993	0.8989
CDKM ripple-carry adder	0.9498	0.9227	0.9127	0.9123
Graph state	0.9498	0.9189	0.9000	0.8997
Draper QFT adder	0.9498	0.9218	0.9034	0.9022
QAOA	0.9498	0.9245	0.9054	0.9041
QFT	0.9498	0.9274	0.9084	0.9055

Table 13.6: Delivered EPR fidelity, mesh, 4 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

ODG delivers 0.950 always. Dynamic's pairs wait in memory and decohere: its fidelity is 0.911 to 0.939 over all budgets (0.916 to 0.927 at four memories) and falls from two to 32 memories on every benchmark, as the compiler bank grows. CGP and ACGP are lower and more variable, 0.838 to 0.935 over all budgets (0.865 to 0.913 at four memories), presumably because their pairs age longer before use (the age of CGP and ACGP pairs was not measured). Dynamic's pairs are better by 0.01 to 0.06 at four memories, but never as good as on-demand pairs. (These figures use ACE's coherence time of one second; under the group's multi-core paper's 1 ms every cached pair would expire, Chapter 7.)

13.5 Wasted pairs and readiness




Figure 13.3: Pairs generated and not used by the end of the run, as a percentage of pairs generated (dynamic, CGP, ACGP). Mesh, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

Workload	Dynamic	CGP	ACGP
GHZ	0.0	71.3	71.3
Bernstein–Vazirani	0.0	86.4	86.0
BMW/QUARK cardinality	0.0	88.6	88.2
VQE real amplitudes	0.0	56.4	56.3
CDKM ripple-carry adder	0.0	67.1	66.1
Graph state	0.0	47.7	47.4
Draper QFT adder	0.0	43.9	43.2
QAOA	0.0	34.0	33.6
QFT	0.0	35.4	34.3

Table 13.7: Pairs generated and never used (%), mesh, 4 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

Dynamic wastes no pair on the mesh (every prepared pair is used). CGP and ACGP waste 34 to 89% of their pairs at four memories on the mesh, and more with more memory (31% on QFT at two memories, 78% at 32): they make pairs for neighbours drawn at random, and a pair nobody uses before its window ends is lost. The percentage depends on the size of the workload: at four memories it is highest on BMW, Bernstein–Vazirani, GHZ and the CDKM adder (24 to 456 requests) and lowest on QAOA, QFT and Draper (1 310 to 3 068 requests), so it is comparable only within a benchmark. Cached pairs, used or not, are also what block requests (Chapter 12).




Figure 13.4: Pre-generated pairs consumed per request (pairs are counted at both endpoints, so the unit is pairs used divided by twice the requests). Mesh, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

Readiness differs less than one would expect. At four memories dynamic serves 100% of the requests of BMW, Bernstein–Vazirani and GHZ from a ready pair, 94 to 95% on VQE and the CDKM adder, but only 53 to 74% on the four congested circuits, where the planner could not place a preparation for the rest within the compiler's memories (for QFT it placed 1 330 of 2 510 requests). CGP and ACGP find a cached pair for 62 to 76% of the requests at four memories — more than dynamic on QFT and QAOA — because a cached pair for a link serves any request on that link, yet they are slower, because a request that has such a pair still has to wait for a memory of its own (Section 12.2).

13.6 Waiting




Figure 13.5: Average wait for a free memory (log scale). Mesh, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

Workload	ODG	Dynamic	CGP	ACGP
GHZ	0.00	0.00	0.00	0.00
Bernstein–Vazirani	0.00	0.00	0.00	0.00
BMW/QUARK cardinality	0.00	0.00	0.00	0.00
VQE real amplitudes	0.00	0.58	0.88	0.90
CDKM ripple-carry adder	0.00	0.00	0.21	0.21
Graph state	0.06	2.73	4.33	4.46
Draper QFT adder	0.02	2.01	4.46	4.67
QAOA	0.14	3.27	7.20	7.42
QFT	0.46	4.91	9.54	10.06

Table 13.8: Wait for a free memory (ms), mesh, 4 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

Waiting for a free memory is where the policies differ. On the congested circuits at four memories ODG waits 0.02 to 0.46 ms on average, dynamic 2.0 to 4.9 ms and CGP and ACGP 4.3 to 10.1 ms; on the other five circuits nobody waits more than about a millisecond. The cause is the number of memory cards held by pre-generated pairs (Chapter 12).

13.7 The torus

Workload	ODG	Dynamic	CGP	ACGP
GHZ	1.15	0.28	0.72	0.77
Bernstein–Vazirani	1.11	0.23	0.50	0.43
BMW/QUARK cardinality	1.10	0.25	0.61	0.54
VQE real amplitudes	1.14	0.48	1.00	1.02
CDKM ripple-carry adder	1.09	0.31	0.74	0.69
Graph state	1.11	1.99	4.06	4.05
Draper QFT adder	1.13	2.71	5.81	6.01
QAOA	1.17	3.00	6.49	6.37
QFT	1.21	3.38	7.46	7.62

Table 13.9: Request latency (ms), torus, 4 memories per core (modelled), mean of three mapping seeds of the mean of three physics seeds.

Workload	2	3	4	6*	8*	16*	32*
GHZ	68%	75%	75%	75%	75%	75%	75%
Bernstein–Vazirani	67%	79%	79%	79%	79%	79%	79%
BMW/QUARK cardinality	66%	77%	77%	77%	77%	77%	77%
VQE real amplitudes	43%	55%	58%	66%	74%	76%	76%
CDKM ripple-carry adder	40%	66%	72%	73%	73%	73%	73%
Graph state	-98%	-131%	-79%	-21%	44%	77%	77%
Draper QFT adder	-119%	-224%	-141%	-37%	33%	77%	77%
QAOA	-110%	-193%	-157%	-65%	2%	77%	78%
QFT	-125%	-219%	-179%	-85%	-3%	77%	78%

Table 13.10: Latency gain of dynamic over on-demand, (ODG − Dyn.)/ODG, torus; negative means dynamic is slower. Budgets marked * are counterfactual.

Workload	Dynamic beats ODG from (memories)	vs CGP win/tie/loss	vs ACGP win/tie/loss	Fidelity Dyn.	CGP	ACGP	ODG
GHZ	2	5/2/0	5/2/0	0.931	0.878	0.879	0.950
Bernstein–Vazirani	2	6/1/0	6/1/0	0.930	0.871	0.870	0.950
BMW/QUARK cardinality	2	7/0/0	7/0/0	0.931	0.880	0.879	0.950
VQE real amplitudes	2	7/0/0	7/0/0	0.929	0.902	0.906	0.950
CDKM ripple-carry adder	2	7/0/0	7/0/0	0.925	0.919	0.916	0.950
Graph state	8	7/0/0	7/0/0	0.919	0.894	0.894	0.950
Draper QFT adder	8	7/0/0	7/0/0	0.925	0.910	0.908	0.950
QAOA	8	7/0/0	7/0/0	0.925	0.906	0.906	0.950
QFT	16	8/0/0	8/0/0	0.928	0.910	0.909	0.950

Table 13.11: Where dynamic lies, torus. Column 2: the smallest memory count from which dynamic has lower latency than on-demand (†: with at least one later count where it does not). Columns 3–4: over the memory counts run for both policies (2 to 32; QFT also 64), the number at which dynamic has lower latency, equal latency (the floor reached when nothing waits) or higher latency than CGP and than ACGP. Columns 5–8: delivered fidelity at four memories.

Mem.	ODG	Dynamic	CGP	ACGP
1	9	0	0	0
2	4	5	0	0
3	4	5	0	0
4	4	5	0	0
6	4	5	0	0
8	1	8	0	0
16	0	8	0	1
32	0	7	0	2

Table 13.12: Torus: number of benchmarks (of ten) on which each policy has the lowest latency at each memory count (a policy is counted only where it was run; dynamic, CGP and ACGP start at two memories).

The ordering is the same on the torus: dynamic is faster than the better of CGP and ACGP on every benchmark at every memory count except ties at the floor (Table 13.11); against ODG it wins on the same five benchmarks at four memories, loses on QFT, QAOA, Draper and graph state at two to four, and overtakes ODG from eight memories on Draper, graph state and QAOA and from sixteen on QFT. CGP and ACGP beat ODG on BMW, Bernstein–Vazirani, GHZ and the CDKM adder at every memory count and on VQE from three or four, and never on the other four. Waste is higher on the torus (34 to 92% at four memories). The figures for the torus follow.




Figure 13.6: Request latency against memories per core, all four policies (log scale). Torus, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.




Figure 13.7: Delivered EPR fidelity against memories per core. Torus, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.




Figure 13.8: Pairs generated and not used by the end of the run, as a percentage of pairs generated (dynamic, CGP, ACGP). Torus, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.




Figure 13.9: Average wait for a free memory (log scale). Torus, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.




Figure 13.10: Pre-generated pairs consumed per request (pairs are counted at both endpoints, so the unit is pairs used divided by twice the requests). Torus, corrected scheduler, mean of three mapping seeds of the mean of three physics seeds; CGP and ACGP cache at most memories−1 pairs per core.

13.8 Where dynamic lies

- **Against the autonomous protocols (the stated goal): yes.** At every modelled memory count (two to four) dynamic has lower latency than CGP and ACGP on every one of the nine benchmarks, wastes none of its pairs against 34 to 89%, and delivers higher fidelity on every benchmark (0.916 to 0.927 against 0.865 to 0.913 at four memories). This holds on the mesh and on the torus.
- **Against on-demand generation: only partly.** Dynamic matches or beats ODG's latency on the benchmarks where requests rarely compete for memory (five of nine at four memories), and on all of them once the memory count reaches eight to sixteen. On the congested benchmarks at the modelled two to four memories it is slower than ODG, by a factor of 2.0 to 3.5 on the mesh and 1.8 to 3.2 on the torus, because prepared pairs occupy memory that requests need. It never matches ODG's fidelity.
- **What would change this** is not established here. The plan does not account for the memory a ready pair's own request also needs, nor for when a chain hop becomes eligible (Chapter 12); a planner that did is a possible direction, not a result.

Limits. Nine benchmarks (the random circuit was not run for CGP and ACGP); three mapping seeds; ACE's physical parameters, which are undecided (Appendix A); the autonomous protocols are configured with a cache cap of memories−1, which is my choice for fairness and is not ACE's default; the waste of the autonomous protocols depends on the length of the workload and is only comparable within a benchmark.

Chapter 14

Fresh Golden Study: Contract and Execution Record

This chapter is the living record for the consolidated experiment program. It is kept separate from historical ACE results so that a result cannot be promoted merely because it exists in an older output directory. Every accepted observation must have an immutable trace hash, a configuration manifest, paired seeds, complete requests, and a source CSV listed in the study registry.

The cross-policy headline metric is request eligibility-to-EPR-delivery latency. It includes admission wait, reservation, retry, and generation time. It excludes time before eligibility during which a cached pair was merely stored. Whole-program cost is reported separately as makespan.

Table 14.1: Golden-study contract at report build time.

Study identifier	`golden-ace-2026-10-25`
Memory capacities/core	2, 3, 4, 6, 8, 16, 32, 64
Policies registered	ODG, CGP, ACGP, Dynamic-full-chain, Dynamic-first-hop, Dynamic-congestion-adaptive
Torus routing	Dijkstra only

The planned capacity study includes constrained settings and deliberately labelled architecture-scaling settings. Capacities greater than the current four-memory model are sensitivity points, not claims about the baseline hardware. The torus arm uses Dijkstra routing only. Mesh routing comparisons hold a placement contract fixed.

At report build time, this chapter contains no performance conclusion until the contract has been made run-ready and the corresponding registry rows, raw CSV files, and validation records exist.

Chapter 15

Limits and open decisions

- **Physical parameters are undecided.** ACE's coherence time (1 s), memory efficiency (0.95) and 2.5 cm link differ from the group's multi-core paper (1 ms, 0.85). Congestion conclusions are largely structural; pre-generation and fidelity conclusions depend entirely on them (Chapter 7).
- **The scheduler is modelled as a central controller** that reads each core's reservation table instantly. A distributed scheduler would see stale tables.
- **Budgets above four are counterfactual.** They say what more memory would buy, not what the hardware has.
- **One machine, one parameter set, nine runs per cell.** Standard deviations pool mapping and physics seeds.
- **Experiment 1 ran on-demand and dynamic;** CGP and ACGP were added in Chapter 13 for nine benchmarks (the random circuit was set aside for them: its runs at large memory counts take over an hour each). Fixed pre-generation was audited for correctness but not swept.
- **The autonomous protocols' cache cap is my choice.** CGP and ACGP were allowed to hold at most memories−1 pairs per core, as dynamic is, instead of ACE's fixed cap of three; their runs end 1 ms after the last request so that waste covers the workload only. Waste depends on the length of the workload and is comparable only within a benchmark.
- **The diagnosis of Chapter 12 is deep on QFT** (three mapping and three physics seeds at four memories); on the other benchmarks it is one mapping seed.
- **CGP and ACGP pair ages were not measured,** so the lower fidelity of their pairs is not attributed to a measured cause.
- **Harness constants** (5.3 ms lead, 50 ms window, 5 ms empty-layer gap) dominate makespan on short traces and are identical for both schedulers.
- **No routing algorithm is proposed.** Chapter 9 bounds what offline routing could achieve structurally and then simulates the optimal offline choice of routes; it does not claim a practical congestion-aware routing algorithm.
- Mechanisms marked "likely" or "probably" in the text were not isolated by an experiment.

Appendix A

Parameters in force

The tables below are generated from the parameter record written by the Experiment 1 driver, which reads the physics from the configuration file and the other constants from the source, so they cannot drift from what ran.

Physical parameter	Value
Memory fidelity	0.95
Memory efficiency	0.95
Memory coherence time	1 s
Memory cut-off ratio (cut-off / coherence)	1 (SeQUeNCe default; not set in the file)
BSM detector efficiencies	0.95, 0.95
Gate / measurement fidelity	0.99 / 0.99
Router-to-BSM fibre	0.025 m, 0.0002 dB/m
Classical delay	distance/c + 20 μs per hop + 100 μs
Configuration file	config/final_config/grid_4x4_ace_3.json

Table A.1: Physical parameters in force (read from the run's parameter record).

Harness constant	Value
Pre-generation lead (request submitted this long before its window)	5.3 ms
Request reservation window	50 ms
Empty-layer gap	5 ms
Retry period after a physical rejection	1 ms
Admission grace after a release or timeout	1 ps
A "wait" means more than	0.001 ms
Compiler reservation window	1000 ms
Planner: delta / lookahead / coherence layers	6 / 8 / 10
Fidelity threshold of a request	0.01
Simulation stop time	300 s
Scheduler	per-qubit, admission event, starvation guard on
Seeds	mapping [42, 43, 44], physics [0, 1, 2]

Table A.2: Harness and scheduler constants (not physical).

A.1 Where the physical values come from, and the open decision

The values were traced to the two neighbouring papers' Table I. ACE's classical delays, detector efficiency, memory and gate fidelities and fibre attenuation match the metro-scale adaptive-continuous protocol paper (arXiv 2502.01964), which also gives a 10 km link, a 2 s coherence time and a memory efficiency of 0.6. ACE's link is 0.025 (read as metres), its coherence time 1 s and its memory efficiency 0.95. The group's multi-core paper (arXiv 2607.14592) states coherence 1 ms and memory efficiency 0.85. The sensitivity arm of Experiment 1 shows that this choice decides every pre-generation and fidelity conclusion; it is the most important open decision, and the question for the supervisor is written in `docs/reports/ace-physical-parameters.md`.

Appendix B

Reproducing the results

All commands are run from the repository root with the project's Python environment. Result folders are dated 2026-10-24.

```
# legacy baseline (must pass after any change to ACE)
python tools/ace_correctness/baseline.py check \
    --golden results/ace_correctness_baseline_2026-10-24/legacy --strict

# tests
python -B -m unittest discover -s test -p 'test_*.py'

# heatmap, Experiment 2
python tools/heatmap/regenerate_heatmap.py --output out/heatmap
python tools/experiment2/make_report.py

# Experiment 1 (mesh), then its analysis
python tools/experiment1/run_experiment1.py --output out --jobs 4
python tools/experiment1/analyze.py --results out/results.csv --output out

# offline routing
python tools/routing_research/run_routing_study.py --output out/routing
python tools/routing_research/simulate_rerouted.py --output out/reroute

# torus: map, then run the experiments
python tools/congestion_study/run_study.py --mapper-dir mapper \
    --topology torus --mapping-only --seeds 42 43 44 --workloads <ten names>
sh tools/torus/run_torus_experiments.sh WORKDIR

# CGP and ACGP on the Experiment 1 grid (mesh; for the torus add
# --topology torus --traces-dir <torus traces>)
python tools/experiment1/run_experiment1.py \
    --policies continuous adaptive-continuous \
    --output out/cgp_acgp --jobs 4
# only if the driver was stopped before it wrote results.csv:
python tools/experiment1/assemble_results.py out/cgp_acgp \
    out/cgp_acgp/results.csv
python tools/experiment1/four_policies.py \
    --base results/experiment1_ten_benchmarks_2026-10-24/results.csv \
    --extra out/cgp_acgp/results.csv --output out/four \
    --label mesh --exclude randomcircuit

# diagnosis of dynamic against on-demand (70 diagnostic runs)
python tools/diagnostics/run_diagnostics.py --output out/diag --jobs 4
python tools/diagnostics/summarise.py out/diag
python tools/latex/make_policy_comparison.py
```

```
python tools/diagnostics/make_report.py

# memory cut-off
python tools/cutoff_study/mechanism.py --output out/mechanism.csv

# this report
python tools/latex/make_tables.py
python tools/latex/make_full_tables.py
python tools/latex/make_big_figures.py
tectonic docs/latex/ace_report/main.tex
```

Every experiment folder contains `run_parameters.json` (all parameters, trace hashes, code commit, machine) and, where timed, `timings.csv`.

Appendix C

Experiment 1: every cell

All workloads, both policies and every budget, with the nine runs behind each cell summarised. The same data are in `results/experiment1_ten_benchmarks_2026-10-24/results.csv` (one row per run) and `cell_summary.csv`.

Table C.1: Experiment 1, every cell: nine runs (three mapping × three physics seeds). Latency in ms (mean, standard deviation, minimum–maximum); makespan in seconds; Waited is the fraction of requests that waited more than a microsecond; Retries the mean number of physical rejections per run. * counterfactual budget.

Workload	Policy	Mem.	Latency ms	sd	min–max	Fidelity	Makespan s	Waited	Retries
GHZ	on-demand	1	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	2	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	3	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	4	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	6*	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	8*	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	16*	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	on-demand	32*	1.171	0.112	1.029–1.342	0.9498	0.33	0.000	0.00
GHZ	dynamic	2	0.512	0.066	0.396–0.600	0.9344	0.31	0.000	0.00
GHZ	dynamic	3	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
GHZ	dynamic	4	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
GHZ	dynamic	6*	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
GHZ	dynamic	8*	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
GHZ	dynamic	16*	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
GHZ	dynamic	32*	0.263	0.000	0.263–0.263	0.9254	0.30	0.000	0.00
Bernstein–Vazirani	on-demand	1	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	2	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	3	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	4	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	6*	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	8*	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	16*	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	on-demand	32*	1.221	0.115	1.120–1.404	0.9498	0.89	0.000	0.00
Bernstein–Vazirani	dynamic	2	0.464	0.067	0.372–0.584	0.9345	0.87	0.000	0.00
Bernstein–Vazirani	dynamic	3	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
Bernstein–Vazirani	dynamic	4	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
Bernstein–Vazirani	dynamic	6*	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
Bernstein–Vazirani	dynamic	8*	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
Bernstein–Vazirani	dynamic	16*	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
Bernstein–Vazirani	dynamic	32*	0.244	0.000	0.244–0.244	0.9266	0.86	0.000	0.00
BMW/QUARK cardinality	on-demand	1	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	2	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	3	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	4	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	6*	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	8*	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	16*	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	on-demand	32*	1.120	0.041	1.056–1.183	0.9498	6.95	0.000	0.00
BMW/QUARK cardinality	dynamic	2	0.488	0.016	0.458–0.510	0.9343	6.86	0.000	0.00
BMW/QUARK cardinality	dynamic	3	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00
BMW/QUARK cardinality	dynamic	4	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00
BMW/QUARK cardinality	dynamic	6*	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00

Workload	Policy	Mem.	Latency ms	sd	min–max	Fidelity	Makespan s	Waited	Retries
BMW/QUARK cardinality	dynamic	8*	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00
BMW/QUARK cardinality	dynamic	16*	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00
BMW/QUARK cardinality	dynamic	32*	0.250	0.000	0.250–0.250	0.9253	6.83	0.000	0.00
VQE real amplitudes	on-demand	1	2.324	0.139	2.121–2.568	0.9498	0.74	0.205	0.00
VQE real amplitudes	on-demand	2	1.112	0.047	1.043–1.175	0.9498	0.68	0.002	0.00
VQE real amplitudes	on-demand	3	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	on-demand	4	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	on-demand	6*	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	on-demand	8*	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	on-demand	16*	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	on-demand	32*	1.112	0.047	1.043–1.174	0.9498	0.68	0.000	0.00
VQE real amplitudes	dynamic	2	1.524	0.205	1.251–1.829	0.9344	0.68	0.184	0.00
VQE real amplitudes	dynamic	3	1.195	0.161	0.954–1.433	0.9203	0.65	0.176	0.00
VQE real amplitudes	dynamic	4	0.878	0.072	0.821–0.994	0.9165	0.63	0.141	0.00
VQE real amplitudes	dynamic	6*	0.413	0.000	0.413–0.413	0.9128	0.62	0.032	0.00
VQE real amplitudes	dynamic	8*	0.253	0.000	0.253–0.253	0.9125	0.61	0.000	0.00
VQE real amplitudes	dynamic	16*	0.253	0.000	0.253–0.253	0.9125	0.61	0.000	0.00
VQE real amplitudes	dynamic	32*	0.253	0.000	0.253–0.253	0.9125	0.61	0.000	0.00
CDKM ripple-carry adder	on-demand	1	1.658	0.221	1.362–1.979	0.9498	5.62	0.033	0.00
CDKM ripple-carry adder	on-demand	2	1.242	0.054	1.160–1.311	0.9498	5.59	0.020	0.00
CDKM ripple-carry adder	on-demand	3	1.165	0.033	1.119–1.215	0.9498	5.58	0.011	0.00
CDKM ripple-carry adder	on-demand	4	1.138	0.027	1.100–1.178	0.9498	5.58	0.002	0.00
CDKM ripple-carry adder	on-demand	6*	1.137	0.027	1.099–1.178	0.9498	5.58	0.000	0.00
CDKM ripple-carry adder	on-demand	8*	1.137	0.027	1.099–1.178	0.9498	5.58	0.000	0.00
CDKM ripple-carry adder	on-demand	16*	1.137	0.027	1.099–1.178	0.9498	5.58	0.000	0.00
CDKM ripple-carry adder	on-demand	32*	1.137	0.027	1.099–1.178	0.9498	5.58	0.000	0.00
CDKM ripple-carry adder	dynamic	2	0.764	0.059	0.656–0.838	0.9354	5.37	0.021	0.00
CDKM ripple-carry adder	dynamic	3	0.380	0.027	0.350–0.417	0.9247	5.22	0.014	0.00
CDKM ripple-carry adder	dynamic	4	0.303	0.008	0.293–0.315	0.9227	5.20	0.003	0.00
CDKM ripple-carry adder	dynamic	6*	0.298	0.006	0.292–0.307	0.9210	5.20	0.000	0.00
CDKM ripple-carry adder	dynamic	8*	0.298	0.006	0.292–0.307	0.9210	5.20	0.000	0.00
CDKM ripple-carry adder	dynamic	16*	0.298	0.006	0.292–0.307	0.9210	5.20	0.000	0.00
CDKM ripple-carry adder	dynamic	32*	0.298	0.006	0.292–0.307	0.9210	5.20	0.000	0.00
Graph state	on-demand	1	9.138	1.141	7.970–10.778	0.9498	0.38	0.602	0.00
Graph state	on-demand	2	2.722	0.541	2.268–3.708	0.9498	0.26	0.281	0.00
Graph state	on-demand	3	1.528	0.304	1.197–2.051	0.9498	0.24	0.121	0.00
Graph state	on-demand	4	1.239	0.131	1.053–1.472	0.9498	0.24	0.029	0.00
Graph state	on-demand	6*	1.177	0.080	1.040–1.278	0.9498	0.24	0.000	0.00
Graph state	on-demand	8*	1.177	0.080	1.040–1.278	0.9498	0.24	0.000	0.00
Graph state	on-demand	16*	1.177	0.080	1.040–1.278	0.9498	0.24	0.000	0.00
Graph state	on-demand	32*	1.177	0.080	1.040–1.278	0.9498	0.24	0.000	0.00
Graph state	dynamic	2	6.360	0.793	5.193–7.251	0.9341	0.32	0.488	0.00
Graph state	dynamic	3	5.011	0.592	4.329–5.909	0.9236	0.30	0.444	0.00
Graph state	dynamic	4	3.234	0.817	2.336–4.361	0.9189	0.26	0.374	0.00
Graph state	dynamic	6*	1.603	0.389	1.324–2.272	0.9158	0.24	0.224	0.00
Graph state	dynamic	8*	0.951	0.131	0.783–1.125	0.9128	0.23	0.173	0.00
Graph state	dynamic	16*	0.274	0.036	0.250–0.322	0.9111	0.22	0.004	0.00
Graph state	dynamic	32*	0.250	0.000	0.250–0.250	0.9112	0.22	0.000	0.00
Draper QFT adder	on-demand	1	7.355	0.840	6.208–8.013	0.9498	6.89	0.536	0.00
Draper QFT adder	on-demand	2	2.157	0.204	1.863–2.329	0.9498	5.14	0.211	0.00
Draper QFT adder	on-demand	3	1.298	0.053	1.213–1.357	0.9498	4.90	0.055	0.00
Draper QFT adder	on-demand	4	1.150	0.022	1.126–1.188	0.9498	4.88	0.008	0.00
Draper QFT adder	on-demand	6*	1.134	0.020	1.108–1.165	0.9498	4.87	0.000	0.00
Draper QFT adder	on-demand	8*	1.134	0.020	1.108–1.165	0.9498	4.87	0.000	0.00
Draper QFT adder	on-demand	16*	1.134	0.020	1.108–1.165	0.9498	4.87	0.000	0.00
Draper QFT adder	on-demand	32*	1.134	0.020	1.108–1.165	0.9498	4.87	0.000	0.00
Draper QFT adder	dynamic	2	4.546	0.426	3.947–4.915	0.9368	5.91	0.459	0.33
Draper QFT adder	dynamic	3	3.666	0.341	3.195–4.017	0.9257	5.46	0.417	1.22
Draper QFT adder	dynamic	4	2.481	0.376	2.062–2.947	0.9218	5.03	0.317	2.44
Draper QFT adder	dynamic	6*	1.599	0.169	1.375–1.746	0.9154	4.75	0.227	2.78
Draper QFT adder	dynamic	8*	0.893	0.228	0.593–1.088	0.9148	4.54	0.118	4.44
Draper QFT adder	dynamic	16*	0.254	0.006	0.250–0.263	0.9158	4.41	0.000	1.00
Draper QFT adder	dynamic	32*	0.250	0.000	0.250–0.250	0.9158	4.41	0.000	0.00
QAOA	on-demand	1	10.925	0.405	10.452–11.462	0.9498	10.69	0.671	0.00
QAOA	on-demand	2	3.421	0.140	3.248–3.620	0.9498	6.60	0.376	0.00
QAOA	on-demand	3	1.740	0.057	1.665–1.818	0.9498	5.71	0.172	0.00
QAOA	on-demand	4	1.273	0.022	1.231–1.299	0.9498	5.48	0.058	0.00
QAOA	on-demand	6*	1.141	0.011	1.127–1.159	0.9498	5.41	0.004	0.00
QAOA	on-demand	8*	1.134	0.011	1.118–1.149	0.9498	5.40	0.000	0.00
QAOA	on-demand	16*	1.134	0.011	1.119–1.149	0.9498	5.40	0.000	0.00
QAOA	on-demand	32*	1.134	0.011	1.119–1.149	0.9498	5.40	0.000	0.00

Workload	Policy	Mem.	Latency ms	sd	min–max	Fidelity	Makespan s	Waited	Retries
QAOA	dynamic	2	6.887	0.280	6.584–7.252	0.9390	8.50	0.576	1.00
QAOA	dynamic	3	5.334	0.191	5.147–5.657	0.9298	7.43	0.519	5.67
QAOA	dynamic	4	3.879	0.165	3.659–4.088	0.9245	6.62	0.454	5.67
QAOA	dynamic	6*	2.705	0.132	2.587–2.900	0.9167	5.98	0.353	9.33
QAOA	dynamic	8*	1.857	0.085	1.787–1.974	0.9136	5.52	0.262	10.89
QAOA	dynamic	16*	0.355	0.036	0.307–0.380	0.9137	4.78	0.020	11.89
QAOA	dynamic	32*	0.250	0.000	0.250–0.250	0.9143	4.74	0.000	0.00
QFT	on-demand	1	14.417	0.352	13.954–14.870	0.9498	9.11	0.696	0.00
QFT	on-demand	2	4.721	0.145	4.572–4.936	0.9498	5.72	0.430	0.00
QFT	on-demand	3	2.386	0.085	2.267–2.506	0.9498	4.91	0.249	0.00
QFT	on-demand	4	1.589	0.046	1.548–1.665	0.9498	4.66	0.130	0.00
QFT	on-demand	6*	1.205	0.017	1.185–1.228	0.9498	4.53	0.031	0.00
QFT	on-demand	8*	1.148	0.017	1.124–1.171	0.9498	4.51	0.007	0.00
QFT	on-demand	16*	1.135	0.015	1.113–1.160	0.9498	4.51	0.000	0.00
QFT	on-demand	32*	1.135	0.015	1.113–1.160	0.9498	4.51	0.000	0.00
QFT	on-demand	64*	1.135	0.015	1.113–1.160	0.9498	4.51	0.000	0.00
QFT	dynamic	2	10.056	0.537	9.410–10.752	0.9386	7.50	0.636	0.44
QFT	dynamic	3	7.489	0.330	7.002–7.730	0.9306	6.50	0.593	1.33
QFT	dynamic	4	5.566	0.214	5.347–5.921	0.9274	5.75	0.513	0.89
QFT	dynamic	6*	3.726	0.246	3.425–4.015	0.9215	5.12	0.414	0.56
QFT	dynamic	8*	2.783	0.190	2.613–3.061	0.9189	4.79	0.328	0.44
QFT	dynamic	16*	0.803	0.156	0.683–1.011	0.9185	4.19	0.082	0.00
QFT	dynamic	32*	0.250	0.000	0.250–0.250	0.9202	4.05	0.000	0.00
QFT	dynamic	64*	0.250	0.000	0.250–0.250	0.9202	4.05	0.000	0.00
Random circuit	on-demand	1	2.989	0.104	2.889–3.134	0.9498	59.78	0.254	0.00
Random circuit	on-demand	2	1.265	0.019	1.238–1.294	0.9498	51.50	0.042	0.00
Random circuit	on-demand	3	1.123	0.007	1.115–1.134	0.9498	50.93	0.006	0.00
Random circuit	on-demand	4	1.110	0.007	1.103–1.122	0.9498	50.89	0.001	0.00
Random circuit	on-demand	6*	1.109	0.006	1.101–1.120	0.9498	50.89	0.000	0.00
Random circuit	on-demand	8*	1.109	0.006	1.101–1.120	0.9498	50.89	0.000	0.00
Random circuit	on-demand	16*	1.109	0.006	1.101–1.120	0.9498	50.89	0.000	0.00
Random circuit	on-demand	32*	1.109	0.006	1.101–1.120	0.9498	50.89	0.000	0.00
Random circuit	dynamic	2	1.910	0.075	1.836–2.021	0.9320	53.58	0.193	16.89
Random circuit	dynamic	3	1.368	0.041	1.325–1.426	0.9186	50.11	0.164	23.78
Random circuit	dynamic	4	0.940	0.024	0.911–0.970	0.9130	47.74	0.117	25.56
Random circuit	dynamic	6*	0.555	0.020	0.530–0.576	0.9075	45.89	0.057	79.67
Random circuit	dynamic	8*	0.381	0.015	0.368–0.404	0.9068	45.05	0.025	53.22
Random circuit	dynamic	16*	0.251	0.000	0.251–0.252	0.9070	44.58	0.000	1.33
Random circuit	dynamic	32*	0.251	0.000	0.250–0.251	0.9071	44.58	0.000	0.00

Appendix D

Experiment 2: per-core tables

Cores are numbered row by row on the 4×4 mesh (core 0 top left, core 15 bottom right; core 10 is row 2, column 2). Values are the percentage of a workload's communication-active layers in which the core is overloaded, mean of three mapping seeds.

Workload	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15
VQE real amplitudes	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
CDKM ripple-carry adder	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Graph state	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Draper QFT adder	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
QAOA	0.6	0.0	0.0	0.6	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
QFT	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Random circuit	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0

Table D.1: Per core, % of active layers overloaded by own endpoint demand, capacity 4, hop counting (mean of three mapping seeds). Workloads with no overload are omitted.

Workload	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15
VQE real amplitudes	0.0	0.0	0.0	0.0	0.0	0.0	1.5	0.0	0.0	4.5	4.5	0.0	0.0	0.0	0.0	0.0
CDKM ripple-carry adder	0.0	0.0	0.0	0.0	0.2	0.4	0.6	0.0	0.0	0.4	0.6	0.0	0.0	0.0	0.0	0.0
Graph state	0.0	5.6	5.6	0.0	5.6	33.3	16.7	0.0	5.6	22.2	27.8	0.0	0.0	5.6	5.6	0.0
Draper QFT adder	0.0	4.8	2.9	1.0	0.5	11.6	6.5	0.2	1.0	15.2	23.4	11.1	0.0	1.9	5.8	1.2
QAOA	0.8	15.7	21.3	2.9	20.4	38.7	37.6	8.8	8.2	48.7	56.0	8.8	0.0	5.5	4.5	0.2
QFT	0.3	20.2	24.1	0.3	11.0	50.6	44.3	10.1	21.4	52.4	58.0	4.8	0.0	2.7	1.8	0.0
Random circuit	0.0	0.4	0.5	0.0	0.6	2.0	2.6	0.2	0.6	3.2	3.0	0.1	0.0	0.1	0.1	0.0

Table D.2: Per core, % of active layers overloaded by relay traffic only, capacity 4, hop counting (mean of three mapping seeds). Workloads with no overload are omitted.

Workload	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15
VQE real amplitudes	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
CDKM ripple-carry adder	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0
Graph state	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	16.7	16.7	0.0
Draper QFT adder	0.0	0.0	2.2	0.0	0.0	0.0	0.0	0.0	0.0	0.0	2.9	1.4	1.4	4.3	1.4	1.4
QAOA	7.4	3.7	6.7	6.7	7.4	8.6	3.7	3.1	3.7	6.1	8.6	2.5	4.3	4.3	0.6	3.1
QFT	0.0	5.4	0.0	0.0	0.0	1.8	1.8	12.5	6.2	7.1	6.2	8.9	0.9	1.8	1.8	0.0
Random circuit	0.0	0.0	0.1	0.0	0.1	0.0	0.2	0.1	0.1	0.0	0.2	0.2	0.1	0.1	0.0	0.0

Table D.3: Per core, % of active layers overloaded by own endpoint demand, capacity 2, hop counting (mean of three mapping seeds). Workloads with no overload are omitted.

Workload	C0	C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15
VQE real amplitudes	0.0	6.1	7.6	0.0	0.0	12.1	12.1	1.5	3.0	15.2	16.7	3.0	0.0	3.0	1.5	0.0
CDKM ripple-carry adder	0.0	0.2	0.4	0.0	0.6	0.8	0.8	0.2	0.4	0.6	0.6	0.0	0.0	0.2	0.2	0.0
Graph state	0.0	11.1	33.3	11.1	33.3	33.3	55.6	16.7	5.6	33.3	55.6	0.0	0.0	16.7	11.1	0.0
Draper QFT adder	0.5	11.6	15.0	6.3	1.0	25.4	13.5	5.8	4.3	39.4	34.1	17.4	0.0	8.5	14.5	8.2
QAOA	3.7	31.1	37.8	12.9	32.7	51.3	54.0	27.8	22.9	59.7	62.0	23.9	0.0	15.5	19.6	2.2
QFT	5.4	41.1	46.7	6.8	41.7	67.0	59.5	18.5	33.0	56.2	61.0	21.4	0.0	20.5	8.3	0.0
Random circuit	0.5	4.1	6.0	1.0	5.5	11.4	12.9	3.3	3.8	14.5	14.5	0.8	0.0	1.1	0.8	0.0

Table D.4: Per core, % of active layers overloaded by relay traffic only, capacity 2, hop counting (mean of three mapping seeds). Workloads with no overload are omitted.

Appendix E

Repository map

Repository: github.com/sanjeevkrishnaa/Compiler-Driven-ACE, branch codex/ace-scheduler-correctness. Every link below points to that branch; the generator checks that each file or folder exists. Each experiment folder under `results/` contains the raw per-run data, the figures, `run_parameters.json` (every parameter, trace hashes, code commit, machine) and, where timed, `timings.csv`.

Reports and plans

docs/reports/ace-correctness-audit.md	what was wrong in the legacy simulator (F1F10)
docs/reports/ace-scheduler-verification.md	verification of the corrected scheduler; wall-clock times
docs/reports/ace-physical-parameters.md	every physical parameter, its source, the open decision and the question for the guide
docs/reports/ace-budget-rerun.md	the 378-run budget study rerun (Gate 6)
docs/reports/experiment1-ten-benchmarks.md	Experiment 1 report (generated from the data)
docs/reports/experiment2-own-vs-relay.md	Experiment 2 report
docs/reports/memory-cutoff-study.md	memory cut-off study
docs/reports/offline-routing-research.md	can offline routing reduce congestion?
docs/reports/run-times.md	run times of every experiment
docs/reports/dynamic-vs-odg-diagnosis.md	why dynamic is slower than on-demand: code reading, measurements, ablations
docs/reports/four-policy-comparison.md	ODG, dynamic, CGP and ACGP on nine benchmarks, mesh and torus
docs/plans/ace-correctness-and-congestion-program.md	the day plan and gates
docs/plans/ace-request-scheduler-design.md	scheduler design and reasoning
docs/plans/handoff-2026-10-24.md	state, open decisions, pitfalls

ACE source changed or added

request_scheduler.py	the per-qubit request manager with event-driven admission
reservation.py	request identity in reservations; release observer; event hooks
parallel_core.py	scheduler selection (legacy or per-qubit)

execution_events.py	typed execution events and stable reservation serials
invariants.py	the invariant checker (window-aware)
latency_metrics.py	the common latency definition
compiler_trace.py	topology-aware trace validation, torus guard
run_trace_comparison.py	the runner: --scheduler, --topology, --autonomous-cache-follows-compiler-memories, --stop-after-workload

Tools

tools/ace_correctness	baseline, audit, harness and audit matrix
tools/experiment1	Experiment 1 driver, analysis, report, four-policy comparison and result assembler
tools/diagnostics	occupancy and admission diagnostics, parallel diagnostic batch, summariser
tools/experiment2	endpoint-versus-relay split
tools/heatmap	heatmap regeneration from raw traces
tools/ace_budget_rerun	parameterised budget sweep driver
tools/routing_research	offline re-routing: optimiser, study, simulation
tools/torus	torus config generator and runner
tools/cutoff_study	cut-off mechanism study
tools/timing	run-times report
tools/latex	generators for this report
tools/congestion_study/run_study.py	mapping study script (--topology torus, --mapping-only)

Results and data

results/ace_correctness_baseline_2026-10-24	the 164-row legacy baseline
results/ace_scheduler_verification_2026-10-24	verification matrices and wall times
results/ace_budget_rerun_2026-10-24	budget study rerun, both schedulers
results/heatmap_regenerated_2026-10-24	regenerated heatmap, its README and CSV
results/experiment2_own_vs_relay_2026-10-24	Experiment 2 data and figures, capacities 14
results/experiment1_ten_benchmarks_2026-10-24	Experiment 1 (mesh): results.csv, controls, figures, parameters, timings
results/experiment1_sensitivity_acgp_table1_2026-10-24	sensitivity arm
results/experiment1_timing_serial_2026-10-24	quiet serial timing pass
results/experiment1_torus_2026-10-24	Experiment 1 on the torus
results/experiment1_cgp_acgp_mesh_2026-10-24	CGP and ACGP on the Experiment 1 grid (mesh): per-invocation runs and results.csv
results/experiment1_cgp_acgp_torus_2026-10-24	CGP and ACGP on the torus
results/experiment1_four_policies_mesh_2026-10-24	ODG, dynamic, CGP, ACGP on the mesh: cell means, figures, who wins
results/experiment1_four_policies_torus_2026-10-24	the same on the torus
results/diagnostics_dynamic_vs_odg_2026-10-24	70 diagnostic runs and diagnostics.csv
results/torus_traces_2026-10-24	mapped torus traces
results/mesh_vs_torus_2026-10-24	mesh-versus-torus table

results/offline_routing_2026-10-24	offline routing data and re-routed traces
results/cutoff_study_2026-10-24	cut-off study data
results/congestion/mqt_ten_workload_congestion_results.zip	the archived mapped traces (ten workloads, seeds 4244)
mapper	the vendored HQA mapper with provenance

This report

docs/latex/ace_report	LaTeX source of this report
docs/latex/ace_report/ace_report.pdf	the compiled report

Appendix F

Commit timeline

The order in which the work was committed, grouped by the heading each commit carries. The last entry is the commit before the one that contains this version of the report.

Table F.1: Every commit of the branch since the starting point (`14cfdd2`), in order. Each hash links to the commit on GitHub.

Commit	Area	What
23a1cff	baseline	Add bit-for-bit legacy baseline tool for ACE (Gate 0)
f70fe50	docs	Record the working plan: ACE correctness first, then the congestion study
f4b7a09	audit	Add execution event log and invariant checker with tests (Gate 1)
6ab1dff	baseline	Record the legacy ACE baseline: 164 rows, reproduced bit for bit (Gate 0)
691644b	audit	Emit execution events from ACE, with no change in behaviour (Gate 1)
e14a176	audit	Add real-simulator harness, microcases and a trace audit tool (Gate 1)
4a2f49e	docs	Record the Gate 1 audit of legacy ACE: what it does, what it hides
3927bc0	reservation	Make application reservations distinct bookings: request identity in equality (Gate 2)
9e1391e	docs	Add the request scheduler design: per-qubit order, per-request retry (Gate 3)
630fcc7	scheduler	Add the per-qubit request manager behind scheduler="per-qubit" (Gate 3a)
ba014c8	audit	Audit the per-qubit scheduler on GHZ and record finding F9 (Gate 3a/4)
242d7a8	reservation	Notify an optional release observer when a booking is released
5984654	scheduler	Add event-driven admission, fixing a polling livelock (Gate 3b)
64cbee7	docs	Record event admission in the design and finding F10 in the audit
e89b4cc	audit	Add a parallel audit matrix over workloads, strategies, memories and seeds (Gate 4)
05b9a43	audit	Record the Gate 4 verification of the per-qubit scheduler: 120-cell matrix clean
5dde36e	audit	Add a bare-simulation timing mode to the audit tools
f2ae05a	docs	Compare ACE's physical parameters with the ACGP paper's Table I (Gate 5)
cdb502d	audit	Record wall-clock time of every benchmark under both schedulers
062d155	metrics	Add a latency definition that means the same under every scheduler
5d1270d	runner	Add --scheduler/--admission to the trace runner and eligible-latency columns
fac0b9a	audit	Let the audit matrix cover the archive's three mapping seeds
1d30f23	audit	Record mapping seeds 43/44 (120 cells clean) and the CGP/ACGP and latency findings
9bbc4cd	study	Add a parameterized rerun of the congestion budget study with a scheduler option (Gate 6)
0cc4d0e	study	Rerun the 378-run budget study under the corrected scheduler: the budget now binds (Gate 6)
4c6f29a	heatmap	Regenerate the per-core congestion heatmap from raw traces; all 160 cells match the project figure
0d368db	audit	Make the invariant checker window-aware and label reservations with stable serials
8d32809	heatmap	Document the regenerated per-core congestion heatmap: definition, parameters, worked example
db87af8	docs	Trace ACE's physical parameters to their sources and frame the open decision (Gate 5)
6116603	experiment1	Add the Experiment 1 driver (ten benchmarks x memory budgets) and admission-wait columns
0a48ed4	experiment2	Split per-core congestion into own endpoint demand and relay demand
55ffc56	experiment1	Add resume/config options, the analysis script, the unattended finisher and handoff notes
e510235	experiment1	Refine the controls and the definition of "waited" after the first full run
5f529a5	experiment1	Add the report generator; correct the parameter doc: coherence decides pre-generation and fidelity
993d98c	experiment1	Record each invocation's wall-clock time in the sweep driver

Commit	Area	What
7c53796	experiment1	Record every parameter, each invocation's time and the total with each experiment; add a serial timing pass
1284a41	routing	Add exact offline re-routing with proven lower bounds; make the trace reader topology-aware
6c8d046	experiment1	Results of the ten-benchmark memory-budget experiment: 1,368 runs, all five controls pass
7fdf5d2	routing	Add the offline re-routing study driver (all benchmarks, capacities, variants, detour allowances)
dea7468	report	Start the LaTeX report: scope, background, audit findings, corrections and verification
8562c0b	experiment1	Sensitivity arm: ACGP Table I memory parameters (coherence 1 ms, efficiency 0.85); controls pass
79f39fb	cutoff	Add the cut-off mechanism script (which timer discards a pair, and what ACE does next)
6d91eb2	torus	Add the torus config generator and topology/mapping-only options for the mapping study
f5e046b	experiment1	Quiet serial timing pass: every benchmark at budgets 1,2,4,8,32, one invocation at a time
392c57b	torus	Run ACE on the torus: topology-aware validation and guard, torus config, mapped torus traces, torus-capable tools
c4d7ed8	report	Report chapters for heatmap, Experiment 1 and appendices; table generator reads the committed results
8b6a565	routing	Add the simulation of re-routed traces (original routes vs optimal re-routing, same mapping and seeds)
8e32530	torus	Results on the 4x4 torus: heatmap, own-vs-relay split and Experiment 1 (1,368 runs, all five controls pass)
3e9290f	torus	Mesh-versus-torus comparison table (hops, structural overload, latency)
1e739c6	routing	Offline re-routing results on the mesh and torus: structural study and simulation of re-routed mesh traces
0ef04f7	timing	Run-times report: every experiment's wall clock, per-benchmark times (parallel and serial), scheduler cost
f51f0da	report	Routing, torus and run-times chapters; offline-routing report generator; cut-off mechanism data
b9abefb	cutoff	Study the memory cut-off: ACE already has it (SeQUeNCe cutoff_ratio), unused by default; measured what a discard does
9d38d30	report	Compiled LaTeX report (32 pages), the Experiment 1 report from the final data, routing/torus/run-time reports and cut-off tests
d3c2b76	docs	Update the handoff notes to the final state of the session
3bee99c	report	Comprehensive report (53 pages): executive summary, how and why with corrections log, Experiments 1 and 2 in full, repository map with links, timeline, glossary
9e03ced	report	Larger figures and three review rounds of the PDF (71 pages)
f3256cb	report	Landscape overview pages per view, full-read corrections, rebuilt PDF (62 pages)
0e48edd	diagnostics	Why dynamic is slower than on-demand: admission-blocking, hold-time and ablation experiments
7156800	diagnostics	Diagnosis chapter: why dynamic is slower than on-demand, with code reading and 73 diagnostic runs

Appendix G

Glossary and questions a reader may have

G.1 Glossary

ACE Adaptive Continuous Entanglement simulator, built on SeQUeNCe v0.8.1.

BSM Bell-state measurement station placed on a link between two cores; it heralds the generation of an EPR pair.

Budget The number of communication memories per core. 1–4 are modelled; above four is counterfactual (*).

Common latency Time from when a request could first be asked for until it completes, minus the 5.3 ms lead (Chapter 5).

Compiler cap The most memories per core that compiler pre-generation may hold at once (`budget - 1`). The memories are one shared pool: a request can use any memory that is free, including one the compiler could have held.

CGP, ACGP Continuous and adaptive continuous generation: autonomous protocols that keep generating pairs for a neighbour drawn at random (CGP: uniformly; ACGP: with probabilities raised for neighbours seen in recently used paths), whether or not a request wants them (Section 12.2).

ODG On-demand generation: a pair is generated only when a request asks for it.

Congestion Requests waiting because a core has no free communication memory.

Counterfactual A what-if capacity beyond the modelled hardware.

Cut-off Time after which a stored pair is discarded (Chapter 8).

Dynamic Compiler pre-generation: pairs are prepared ahead of the layer that needs them.

Endpoint demand D_{end} Hops touching a core that start or end a route there.

Excess Demand above the capacity, summed over cores and layers.

HQA The qubit-mapping algorithm (Hungarian-assignment based) that places logical qubits on cores layer by layer.

Hop One request for an EPR pair between two adjacent cores.

Layer One step of the mapped circuit; its hops are the moves needed to reach the next placement.

On-demand A pair is generated only when a request asks for it.

Relay A core strictly between a route's source and destination.

Route A qubit's consecutive hops within one layer.

Serialization The legacy per-core batching that stopped the budget from binding.

Torus A mesh whose opposite edges are joined by extra links.

G.2 Questions a reader may have

Why is the latency floor 1.1–1.2 ms? That is the generation time of one pair once nothing waits; it is the same for every workload and does not depend on the budget.

Why does dynamic start slower than on-demand? Its prepared pairs may occupy up to `budget - 1` memories, and a request needs a free memory of its own even when its pair is ready, so with two memories a prepared pair and the request that uses it already occupy both (Chapter 12).

Why do GHZ, Bernstein–Vazirani and BMW change under dynamic between two and three memories if they have no congestion? The structural overload is zero, so it is not congestion; the earlier budget study attributed it to planner coverage (not re-tested here).

Are these numbers physical? They come from a physical simulator with ACE's parameters, but those parameters are undecided; the congestion results depend on them little, the pre-generation and fidelity results entirely (Appendix A).

Can the results be reproduced? Yes: Appendix B lists the commands, and every result folder holds the parameters, trace hashes and code commit it was produced with. The two full Experiment 1 runs (first pass and rerun) are numerically identical apart from the one column that was redefined.

What was not done? Experiment 1 for fixed pre-generation and the autonomous caches; routing combined with pre-generation; joint mapping and routing; a cut-off sweep against the budget (Chapter 15).