

Unit 3

Asymmetric Ciphers

(8 Hours)

3.4. Number Theory: Prime Numbers, Fermat's Theorem, Euler's Theorem, Primality Testing, Miller-Rabin Algorithm, Extended Euclidean Theorem, Discrete Logarithms

3.5. Public Key Cryptosystems, Applications of Public Key Cryptosystems

3.6. Distribution of public key, Distribution of secret key by using public key cryptography, Diffie-Helman Key Exchange, Man-in-the-Middle Attack

3.7. RSA Algorithm


3.8. Elgamal Cryptographic System

Sanjeev Thapa, Er. DevOps, SRE, CKA, RHCSA, RHCE, RHCSA-Openstack, MTCNA, MTCTCE, UBSRS, HEv6, Research Evangelist

Public Key Cryptosystems

A **Public Key Cryptosystem** (also called **Asymmetric Cryptosystem**) is a cryptographic system that uses **two mathematically related keys**:

- **Public Key** → used for encryption (shared openly)
- **Private Key** → used for decryption (kept secret)



Working Principle

- Data encrypted with the **public key** can only be decrypted using the corresponding **private key**.
- Data signed with the **private key** can be verified using the **public key**.

Key Features	Examples of Public Key Cryptosystems
<ul style="list-style-type: none"> • Eliminates the problem of secure key distribution • Based on complex mathematical problems • Provides confidentiality, authentication, and non-repudiation 	<ul style="list-style-type: none"> • RSA • Diffie–Hellman • ElGamal • ECC (Elliptic Curve Cryptography)

Applications of Public Key Cryptosystems

1. Secure Data Communication

Public key cryptography ensures **confidential communication** over insecure networks like the Internet.

📌 Example: Secure web browsing using HTTPS.

2. Key Distribution

Public key cryptography is widely used to **securely exchange secret keys** used in symmetric encryption.

📌 Example: SSL/TLS uses public key encryption to exchange session keys.

3. Digital Signatures

Public key cryptosystems are used to **sign digital documents**, ensuring:

- Authentication
- Integrity
- Non-repudiation

📌 Example: Software updates, legal documents.

4. Authentication

Used to verify the identity of users or systems.

📌 Example: Login systems using public key certificates.


5. Secure Email

Public key cryptography secures email content and verifies sender identity.

📌 Example: PGP (Pretty Good Privacy).


Used to secure online transactions such as:

- Credit card payments
- Online banking

 Example: Secure payment gateways.

7. Digital Certificates

Public key cryptography supports **certificate authorities (CA)** to verify and bind identities to public keys.

 Example: SSL certificates issued by trusted CAs.



8. Software Distribution

Ensures that software is genuine and not altered.

 Example: Code signing in operating systems.

Advantages of Public Key Cryptosystems	Limitations
<ul style="list-style-type: none">• Secure key exchange• Supports digital signatures• High security• Suitable for open networks	<ul style="list-style-type: none">• Slower than symmetric cryptography• Requires more computation power

A **Man-in-the-Middle attack** occurs when an attacker secretly intercepts and possibly alters communication between two parties.



MITM in Diffie-Hellman

- Attacker intercepts key exchange messages.
- Establishes separate keys with both users.
- Users believe they are communicating securely, but attacker reads/modifies data.

Effects

- Loss of confidentiality
 - Data manipulation
 - Identity impersonation
-

Prevention of MITM Attack

- Digital signatures
- Authentication using certificates
- Secure protocols (TLS, HTTPS)
- Public key authentication

<p>Number</p> <p>A number is a mathematical value used to count, measure, or label objects.</p> <p>Examples: 1, 2, 3, -5, $\frac{1}{2}$, $\sqrt{2}$</p>	<p>Integer</p> <p>An integer is a whole number with no fractional part. It includes positive numbers, negative numbers, and zero.</p> <p>Set: $\{\dots, -3, -2, -1, 0, 1, 2, 3, \dots\}$</p> <p>Example: -4, 0, 7</p>
<p>Rational Number</p> <p>A rational number is any number that can be written in the form $\frac{p}{q}$, $q \neq 0$</p> <p>Examples: $\frac{1}{2}$, $-\frac{3}{4}$, 5, 0.25 (All integers are rational numbers.)</p>	<p>Odd Number</p> <p>An odd number is an integer that is not divisible by 2.</p> <p>Form: $2n + 1$</p> <p>Examples: 1, 3, 5, 7, 9</p>
<p>Even Number</p> <p>An even number is an integer that is divisible by 2.</p> <p>Form: $2n$</p> <p>Examples: 2, 4, 6, 8, 10</p>	
<p>Prime Number</p> <p>A prime number is a natural number greater than 1 that has exactly two factors: 1 and itself.</p> <p>Examples: 2, 3, 5, 7, 11 (Note: 2 is the only even prime number.)</p>	<p>Co-Prime Numbers</p> <p>Two numbers are co-prime (relatively prime) if their GCD = 1.</p> <p>Examples:</p> <ul style="list-style-type: none"> 8 and 15 \rightarrow co-prime 14 and 21 \rightarrow not co-prime (GCD = 7)

🔒 Connection of Basic Number Concepts with Number Theory in Cryptography

Cryptography relies heavily on **number theory**, especially properties of integers and prime numbers, to ensure secure communication.

1. Numbers & Integers in Cryptography

Cryptographic algorithms work entirely with **integers**, not real or rational numbers.

📌 Examples:

- Modular arithmetic uses integers only.
- Encryption and decryption operations are performed on integer values.

👉 **Integers form the foundation of cryptographic computations.**

2. Rational Numbers

Rational numbers are **not directly used** in cryptography because encryption algorithms require **exact, discrete values**.

📌 Cryptography avoids fractions to prevent precision errors and ensure deterministic results.

👉 **Only integer arithmetic is used in cryptographic systems.**

3. Odd and Even Numbers

- Most cryptographic primes are **odd numbers**.
- Even numbers (except 2) are avoided because they are easily factorable.

📌 Example:

- RSA selects two **large odd primes**.
- Even numbers reduce security.

👉 **Odd numbers help maintain complexity and security.**

4. Prime Numbers

Prime numbers are the **backbone of modern cryptography**.

📌 Uses:

- RSA uses large primes to generate keys.
- Diffie–Hellman and ElGamal rely on prime modulus.
- Prime factorization is computationally hard.

👉 **Security depends on the difficulty of breaking prime-based problems.**

5. Co-Prime Numbers

Two numbers are co-prime if their **GCD = 1**.

📌 Uses:

6. Modular Arithmetic & Integers

Most cryptographic operations use:

$a \bmod n$

- In RSA, public key e must be co-prime with $\phi(n)$.
- Modular inverse exists only when numbers are co-prime.

👉 **Co-primality ensures successful key generation and decryption.**

📌 Example:

- Encryption: $C = M^e \bmod n$
- Key exchange: $g^x \bmod p$

👉 **Modular arithmetic over integers enables secure encryption.**

📌 First 80 Prime Numbers

2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31, 37, 41, 43, 47, 53, 59, 61, 67, 71, 73, 79, 83, 89, 97, 101, 103, 107, 109, 113, 127, 131, 137, 139, 149, 151, 157, 163, 167, 173, 179, 181, 191, 193, 197, 199, 211, 223, 227, 229, 233, 239, 241, 251, 257, 263, 269, 271, 277, 281, 283, 293, 307, 311, 313, 317, 331, 337, 347, 349, 353, 359, 367, 373, 379, 383

GCD (Greatest Common Divisor)

The **GCD** of two integers **a** and **b** is the largest positive integer that divides both without remainder.

Euclidean Algorithm

$$\gcd(a, b) = \gcd(b, a \bmod b)$$

Key Properties

- $\gcd(a, b) = \gcd(b, a)$
- If $\gcd(a, b) = 1$, then **a and b are co-prime**
- GCD helps determine the **existence of modular inverse**

Cryptography Use

- In RSA, choose e such that $\gcd(e, \phi(n)) = 1$
- Extended Euclidean Algorithm uses GCD to find modular inverse

Euler's Totient Function $\phi(n)$

$\phi(n)$ is the number of **positive** integers less than **n** that are **co-prime with n**.

Formulas

- If $n = p$ (prime): $\phi(p) = p - 1$
- If $n = p^k$: $\phi(p^k) = p^k - p^{k-1}$
- If $n = pq$ (distinct primes):

$$\phi(n) = (p - 1)(q - 1)$$

- General form:

$$\phi(n) = n \prod_{p|n} \left(1 - \frac{1}{p}\right)$$

Examples	Cryptography Use Page 10 of 25
<p>Example 1</p> <p>Find gcd(24, 36)</p> <p>36 mod 24 = 12 24 mod 12 = 0</p> <p>✅ GCD = 12</p>	<ul style="list-style-type: none"> • RSA uses $\phi(n)$ to compute private key d • Determines key relationships in modular arithmetic
<p>Example 2</p> <p>Find gcd(48, 18)</p> <p>48 mod 18 = 12 18 mod 12 = 6 12 mod 6 = 0</p> <p>✅ GCD = 6</p>	<p>Examples</p> <p>Example 1</p> <p>Find $\phi(11)$</p> <p>11 is prime</p> $\phi(11) = 11 - 1 = 10$
<p>Example 3</p> <p>Find gcd(35, 64)</p> <p>64 mod 35 = 29 35 mod 29 = 6 29 mod 6 = 5 6 mod 5 = 1 5 mod 1 = 0</p> <p>✅ GCD = 1 (Co-prime)</p>	<p>Example 2</p> <p>Find $\phi(15)$</p> <p>15 = 3 × 5</p> $\phi(15) = 15 \left(1 - \frac{1}{3}\right) \left(1 - \frac{1}{5}\right)$ $= 15 \times \frac{2}{3} \times \frac{4}{5} = 8$
<p>Example 4</p> <p>Find gcd(81, 57)</p> <p>81 mod 57 = 24 57 mod 24 = 9 24 mod 9 = 6 9 mod 6 = 3 6 mod 3 = 0</p> <p>✅ GCD = 3</p>	<p>Example 3</p> <p>Find $\phi(16)$</p> <p>16 = 2⁴</p> $\phi(16) = 16 \left(1 - \frac{1}{2}\right) = 8$
	<p>Example 4</p> <p>Find $\phi(21)$</p> <p>21 = 3 × 7</p>

$$= 21 \times \frac{2}{3} \times \frac{6}{7} = 12$$

n	$\phi(n)$	Numbers co-prime to n (< n)
1	1	{1}
2	1	{1}
3	2	{1, 2}
4	2	{1, 3}
5	4	{1, 2, 3, 4}
6	2	{1, 5}
7	6	{1, 2, 3, 4, 5, 6}
8	4	{1, 3, 5, 7}
9	6	{1, 2, 4, 5, 7, 8}
10	4	{1, 3, 7, 9}

Euler's Theorem/ Fermat Euler's Theorem/ Euler's Totient Theorem

Statement

If $\gcd(a, n) = 1$, then: Coprime (GCD=1)

$$a^{\phi(n)} \equiv 1 \pmod{n}$$

Special Case (Fermat's Theorem)

If $n = p$ is prime:

$$a^{p-1} \equiv 1 \pmod{p}$$

Cryptography Use

- Basis of **RSA correctness**
- Ensures encrypted message decrypts to original message

Fermat's Little Theorem

◆ Statement

If **p** is a **prime number** and **a** is any integer such that

$$\gcd(a, p) = 1, \text{ then } a^{p-1} \equiv 1 \pmod{p}$$

Equivalently, $a^p \equiv a \pmod{p}$

◆ Why it matters in Cryptography

- Used in **primality testing**
- Foundation for **RSA, Diffie–Hellman, ElGamal**
- Helps simplify **large modular exponentiation**

Numerical Examples

Example 1

Let $p = 7, a = 3$

$$3^6 = 729 \equiv 1 \pmod{7}$$

Examples**Example 1**

Verify Euler's theorem for $a = 3, n = 10$

$$\phi(10) = 5 \times 2 = (5-1) \times (2-1) = 4$$

$$3^4 = 81 \equiv 1 \pmod{10}$$

✓ Verified

✓ Fermat's theorem verified

✓ Example 2

Let $p = 11, a = 2$

$$2^{10} = 1024 \equiv 1 \pmod{11}$$

Example 2

Verify for $a = 7, n = 15$

$$\phi(15) = 5 \times 3 = 4 \times 2 = 8$$

$$7^8 \equiv 1 \pmod{15}$$

✓ Verified

✓ Example 3

Let $p = 13, a = 5$

$$5^{12} \equiv 1 \pmod{13}$$

✗ Example 4 (Composite number)

Let $n = 15, a = 2$

$$2^{14} \not\equiv 1 \pmod{15}$$

⊘ Fermat's theorem **fails** for non-prime numbers

Example 3

Verify for $a = 2, n = 9$

$$\phi(9) = 9 - 3 = 6$$

$$2^6 = 64 \equiv 1 \pmod{9}$$

✓ Verified

🔒 Cryptography Insight

- If $a^{p-1} \not\equiv 1 \pmod{p}$, then **p is NOT prime**
- Used in **Fermat Primality Test**

Example 4

Verify for $a = 5, n = 14$

$$\phi(14) = 7 \times 2 = (7-1) \times (2-1) = 6$$

$$5^6 = 15625 \equiv 1 \pmod{14}$$

✓ Verified

Example 5

$$p = 5, a = 2$$

$$2^{5-1} = 2^4 = 16 \equiv 1 \pmod{5}$$

Example 6

$$p = 17, a = 3$$

$$3^{16} = 43046721 \equiv 1 \pmod{17}$$

Example 7

$$p = 19, a = 4$$

$$4^{18} \equiv 1(\text{mod}19)$$

Example 8

$$p = 23, a = 5$$

$$5^{22} \equiv 1(\text{mod}23)$$

✗ Composite Number Examples (Fermat Fails)**Example 9**

$$n = 9, a = 2$$

$$2^8 = 256 \equiv 4 \not\equiv 1(\text{mod}9)$$

Example 10

$$n = 12, a = 5$$

$$5^{11} \equiv 1 \not\equiv 1(\text{mod}12) (\text{actually } 5^{11} \equiv 5(\text{mod}12))$$

Example 11

$$n = 18, a = 7$$

$$7^{17} \equiv 7 \not\equiv 1(\text{mod}18)$$

Example 12

$$n = 20, a = 3$$

$$3^{19} \equiv 3 \not\equiv 1(\text{mod}20)$$

◆ Primality Testing**Definition:**

Primality testing is the process of determining whether a given number n is **prime** (only divisible by 1 and itself) or **composite** (has divisors other than 1 and itself).

1 Trial Division (Basic Method)**Euclidean Algorithm****Purpose:**

Find the **Greatest Common Divisor (GCD)** of two integers a and b .

Principle: $\text{gcd}(a, b) = \text{gcd}(b, a \bmod b)$

Repeat until remainder = 0. The last non-zero remainder is the GCD.

- Check divisibility of n by all integers from 2 to \sqrt{n} .
- Example:**

$$n = 29$$
 Check divisibility by 2, 3, 5 (since $\sqrt{29} \approx 5.39$)
 \rightarrow not divisible \rightarrow **prime**

Pros: Simple, accurate

Cons: Slow for large numbers

Examples Prime:

2,3,5,7,11,13,17,19,23,29,31,37,41,43,47

Step-by-Step Example

Find GCD of 252 and 105

- $252 \div 105 = 2$ remainder 42 $\rightarrow 252 = 105 \cdot 2 + 42$
- $105 \div 42 = 2$ remainder 21 $\rightarrow 105 = 42 \cdot 2 + 21$
- $42 \div 21 = 2$ remainder 0 \rightarrow Stop

 **GCD = 21**

Composite Numbers

Definition:

A **composite number** is a natural number greater than 1 that has **more than two positive divisors** (i.e., it has at least one divisor other than 1 and itself).

Properties:

- Divisible by numbers other than 1 and itself
- Can be expressed as a product of primes

Examples:

4,6,8,9,10,12,14,15,16,18,20,21,22,24,25

Feature	Prime Number	Composite Number
Divisors	2 (1 and itself)	More than 2
Examples	2, 3, 5, 7, 11	4, 6, 8, 9, 12
Factorization	Only itself $\times 1$	Product of primes
Even Numbers	Only 2	Rest of even numbers

Algorithm (Steps)

- Divide a by b , get remainder r
- Replace a by b , b by r
- Repeat until $r = 0$
- GCD = last non-zero remainder

Extended Euclidean Algorithm

Purpose:

Find integers x and y such that:

$$ax + by = \gcd(a, b)$$

- Very useful in **modular inverse calculation** for cryptography (RSA, ECC).

Step-by-Step Example

Find integers x and y such that:

$$252x + 105y = \gcd(252, 105)$$

Step 1: Apply Euclidean Algorithm



$$252 = 105 \cdot 2 + 42$$

$$105 = 42 \cdot 2 + 21$$

$$42 = 21 \cdot 2 + 0$$

Fermat Primality Test

- Uses **Fermat's Little Theorem**:
If n is prime, $a^{n-1} \equiv 1 \pmod{n}$ for any a with $\gcd(a, n) = 1$
- Steps:**

<ol style="list-style-type: none"> 1. Pick a random $a < n$ 2. Compute $a^{n-1} \bmod n$ 3. If $\not\equiv 1$, n is composite 4. If $\equiv 1$, n is probably prime <p>Example:</p> $n = 17, a = 3$ $3^{16} \equiv 1 \pmod{17} \Rightarrow 17 \text{ is probably prime}$ <p>Note: Some composite numbers (Carmichael numbers) can pass this test \rightarrow not fully reliable</p>	<div>  GCD = 21 </div> <div> Page 15 of 25 </div> <p>Step 2: Back-substitute to find x and y</p> <ol style="list-style-type: none"> 1. $21 = 105 - 42 \cdot 2$ 2. Replace $42 = 252 - 105 \cdot 2 \rightarrow$ $21 = 105 - (252 - 105 \cdot 2) \cdot 2$ $21 = 105 - (252 \cdot 2 - 105 \cdot 4)$ $21 = 105 - 252 \cdot 2 + 105 \cdot 4$ $21 = -252 \cdot 2 + 105 \cdot 5$ <div>  Solution: $x = -2, y = 5$ </div>
<p>3 Miller-Rabin Primality Test (Probabilistic)</p> <ul style="list-style-type: none"> • Advanced version of Fermat test, more reliable • Checks if n passes multiple modular exponentiation conditions • If n fails any, it is composite • If n passes all, it is probably prime <p>Use: Common in cryptography for generating large primes (RSA keys)</p>	$252(-2) + 105(5) = 21$
<p>4 AKS Primality Test (Deterministic)</p> <ul style="list-style-type: none"> • Always gives correct answer • Polynomial-time deterministic test • Less commonly used due to slower practical performance 	
<p>5 Applications in Cryptography</p> <ul style="list-style-type: none"> • RSA, Diffie-Hellman, ElGamal all require large prime numbers • Efficient primality tests help generate secure keys quickly 	

RSA Algorithm

- RSA is a public key cryptographic algorithm used for **secure data transmission** and **digital signatures**.
- It uses **two large prime numbers** to generate a public and private key pair.
- The public key encrypts data, while the private key decrypts it. RSA's security relies on the difficulty of **factoring large composite numbers**.
- The RSA (**Rivest–Shamir–Adleman**) cryptosystem is a family of public-key cryptosystems, one of the oldest widely used for secure data transmission.
- The initialism "RSA" comes from the surnames of **Ron Rivest**, **Adi Shamir** and **Leonard Adleman**, who publicly described the algorithm in 1977.
- An equivalent system was developed secretly in 1973 at Government Communications Headquarters (GCHQ), the British signals intelligence agency, by the English mathematician Clifford Cocks. That system was declassified in 1997.



Case Scenario RSA

Ram wants to send a secure message to Shyam. Shyam chooses prime numbers $p = 7$ and $q = 11$, giving $n = 77$ and $\phi(n) = 60$. He selects $e = 7$ and computes $d = 43$. Ram encrypts message $M = 9$ as $C = 9^7 \bmod 77 = 37$ using the public key. Shyam decrypts it using $M = 37^{43} \bmod 77 = 9$, recovering the original message.

Algorithm of RSA

Key Generation

Step 1: Choose two prime numbers p and q .

Step 2: Compute $n = p \times q$

Step 3: Compute Euler's Totient $\phi(n) = (p - 1)(q - 1)$

Step 4: Choose public key e such that $1 < e < \phi(n)$, $\gcd(e, \phi(n)) = 1$

Encryption $C = M^e \text{mod } n$

Decryption $M = C^d \text{mod } n$

Resulting Keys:

- Public Key: (e, n)
- Private Key: (d, n)

RSA Numerical Example


Ram wants to send a secure message to Shyam. Shyam chooses prime numbers $p = 7$ and $q = 11$, giving $n = 77$ and $\phi(n) = 60$.

He selects $e = 7$ and computes $d = 43$. Ram encrypts message $M = 9$ as $C = 9^7 \text{mod } 77 = 37$ using the public key. Shyam decrypts it using $M = 37^{43} \text{mod } 77 = 9$, recovering the original message.

Given:

$p = 7, q = 11$

Message $M = 9$

 **Original message recovered = 9**

Step	Operation	Calculation	Result
1	Compute n	7×11	77
2	Compute $\phi(n)$	$(7 - 1) \times (11 - 1)$	60
3	Choose e	$\text{gcd}(e, 60) = 1$ (Let $e = 7$)	$e = 7$
4	Compute d	$7d \equiv 1 \pmod{60}$	$d = 43$
5	Encryption	$C = 9^7 \pmod{77}$	$C = 37$
6	Decryption	$M = 37^{43} \pmod{77}$	$M = 9$

Diffie-Hellman Key Exchange

Diffie–Hellman is a key exchange technique that allows two users to **generate a shared secret key over an insecure channel**. It uses a public prime number and a generator. Each user selects a private key and exchanges computed public values. The shared secret key is never transmitted, making the method secure. Its security depends on the **discrete logarithm problem**.

Case Scenario: Diffie–Hellman

Two users, **Asha** and **Bikram**, want to share a secret key securely. They agree on public values $p = 23$ and $g = 5$. Asha chooses private key $a = 6$ and sends $5^6 \bmod 23 = 8$. Bikram chooses $b = 15$ and sends $5^{15} \bmod 23 = 19$. Asha computes $19^6 \bmod 23 = 2$, and Bikram computes $8^{15} \bmod 23 = 2$. Both obtain the same secret key **2**.

Algorithm of Diffie–Hellman Key Exchange

Step 1: Select a large prime number p and a primitive root g (public).

Step 2: Sender selects private key a .

Step 3: Receiver selects private key b .

Step 4: Sender computes public value $A = g^a \bmod p$

Step 5: Receiver computes public value $B = g^b \bmod p$

Step 6: Exchange A and B .

Step 7: Sender computes shared key $K = B^a \bmod p$

Step 8: Receiver computes shared key $K = A^b \bmod p$

Diffie–Hellman Numerical Example

Two users, **Asha** and **Bikram**, want to share a secret key securely. They agree on public values $p = 23$ and $g = 5$. Asha chooses private key $a = 6$ and sends $5^6 \bmod 23 = 8$. Bikram chooses $b = 15$ and sends $5^{15} \bmod 23 = 19$. Asha computes $19^6 \bmod 23 = 2$, and Bikram computes $8^{15} \bmod 23 = 2$. Both obtain the same secret key **2**.

Given: $p = 23, g = 5$ Private keys: $a = 6, b = 15$

Step	Operation	Calculation	Result
1	Public value A	$5^6 \bmod 23$	8
2	Public value B	$5^{15} \bmod 23$	19
3	Shared key (Sender)	$19^6 \bmod 23$	2
4	Shared key (Receiver)	$8^{15} \bmod 23$	2

 **Shared Secret Key = 2**

```

controlplane:~$ ssh-keygen -t rsa
Generating public/private rsa key pair.
Enter file in which to save the key (/root/.ssh/id_rsa):
/root/.ssh/id_rsa already exists.
Overwrite (y/n)? y
Enter passphrase (empty for no passphrase):
Enter same passphrase again:
Your identification has been saved in /root/.ssh/id_rsa
Your public key has been saved in /root/.ssh/id_rsa.pub
The key fingerprint is:
SHA256:tI6NdC0CNakrh878WcoHcEPuoMkCuFPTxuLLR4dMNEY root@controlplane
The key's randomart image is:
+---[RSA 3072]-----+
|o  +oOEo          |
|o.+oBo*..         |
|.++B.o ..         |
|o.o =... o        |
|. + +o S .        |
| o +. B .         |
| + o .+ o         |
|+.+.              |
|..                |
+----[SHA256]-----+
controlplane:~$

```

```

controlplane:~$
controlplane:~$ cat /root/.ssh/id_rsa
-----BEGIN OPENSSH PRIVATE KEY-----
b3B1bnNzaC1rZXktZjEAAAAABG5vbmUAAAAAEbm9uZQAAAAAAAAABAAABlwAAAAAdzc2gtcn
NhAAAAAwEAAQAAAYEAXbN+pd+41mRpgKwHRD29EEp1sVGu5JFEL9LWg5g9LuTTcu3EK210
VhgYvsJ4hx3nEyaNg1Q/nBkF1qK/xbycTE/c/O+6nWuwEFxtz4/NMjCqnDtRC2X5afCiZ8
KK/JHQEVVp06fngFD/NB1Yw0I/i4dXjdc/CJzo+F9Zx9SEQA7VmH/yIJ5+HT5DP4wcjU2
jtp3KMNpP0FDQJCVRnByyuznbqFFInwRQnE8p5kXXIGBkvDn2P7kxQDVJUUPP141V9cHca
sLULELHNW24bhNmm9//ZRQuGyWjTbtfgMdu3ast+Df2W0QvfdQWolwxHpTVkTcSxXmk3WsO
DS9XQGH0j4NHb4KGLNaNYAskN9RvXFTRYixdvJ7kFwS3CmsuTqaid2Km82jmh0cb8nrBW
IPsq/mECPlw5j+pJd1t4WRu4imIzk9sJXb2rMedaw5dx6vnqsZoEpjtzAQdSNmYmf00P
Hbb7KPIYjNwTwIzpvLDZ7DV9/sZVhybZZsd9JyGIAAAFICBevndgXr5wAAAAAB3NzaC1yc2
EAAAGBAMwzfQxvunZkayC1oUQ9vRBKZbFRuSRRC/S1oOYPS7k03LtxCttTlYYGL7CeIcd
5x4mjYJUP5wZBdaiv8W8nExP3Pzvup1rsBH17c+PzTIwqpw7UQtL+WnwomfCivry08BFVad
OnzYBQ/zd9WfTCp4uMS143XPwic6PhfwcFuHEA01Zh/8iCefh0+Qz+MHI1No7adyjVj6dB
Q0FyVawZ2Hrs526hRSJ8EUJxPkeZF1yBgZLw59jyZMTg1SVFDz5eWfX83GrC1JRCxzVtu
G4TZpvr/2UULOGMI027X4DHbt2rLfg391tEL3w0FqFsR6U1ZE3EsV5pN1rDg0vV0Bhzo+D
R24eChizwJjWALJDFub1xU0WIsXbye5BcEtwpRLk6mondipvNo5h9HG/J6wViD7Kv5hAqVu
Y/jyXZbeF1UbuIpmYvbiI29qzHnW5OXcer56rGaBKY7cwEHUjTWj3b9Djx22+yjyGIzc
E8C46by2Qw+1ff76Vym2wbHfSchpQAAAAABAAEAAAGALz5WfHL665ix4YHjCLisLnFo3b
fEUHB6v+dNRch4ik8sw0F0LLmBF8fIwghNE4dz+dDAZTtStIrNEFudrZmhM/Vt0Vqk+8hFi
0NfxDVgy2LSQ4Ka4fj43HN7ZIGx35CVAEHRVxrNpw0kXw/3bGGu7XbCX7hrSyJm/AqGG4x
az+MYSZ/Eh05WawY4ooXbd8gj4/HGI0aZ6nJnPNC52z5V2D1fJ1I8IIIEFaPlU4UDYT19Ump
YKDa9pfuBrInnTfKLCXu56LFERYlvKpP77Ntayy3BfWT6JCUCdXkevRxYF2ekK0903Nto6
VBetbsLWTXoVUMw2X9P4wfgU4r1RIm2kVgw3IMQHa2RXHy8DeIi3jeS2Qz2nGRw5/89u2
8cKnzOXmIYXpC7AjVkaia4ubCeufZ7yNExvhjLP8RC90LQABZkSb152aGmYyQ93N7IMwK
icq2s/jAxKosvtfkfcjcb+ziDQ5Hdck8qglxNr6H+pV1K3qXI0VY98PFFXgaZ5op4/LhAAAA
wGAfS0dEd7SwjsJS0i5WY0859EW2VZrnFor7vHY2JBwMUroS+2eIP11Hk4dW9eBfahQBK
nJq8QRqmt4wXKIjHM8KEFBCh9xC56CJBav13wo3XTpvB2byjDVoYmGwAxPEq6fMnHBdD
ns5YTKunCg+hi13rGggfsz29CmsQP3MdUfeYd7Va93tYHqhYxGsgRIUc0EMMLtAhrJDthJ
1I89XmgipB0+fkCqQgW/bIzptNLXmbavA5fnKEuIFKRAlRgAAAEAA8v4plwB/psaPFH6t8
juk7d8hSL38BnFYR8YUUm+UoiLXu1GwDiN7SEqKM1gG/gDF9qnt1/mGGzNtzGERDY+p4d
0g0sbK9IRa0msL001V2jRJZ/VQ8aYgBNzNDTkep9PDaLH55s0HzAiqS18HK/sIqXaWtX2d

```

```

controlplane:~$ cat /root/.ssh/id_rsa.pub

```

```


ssh-rsa AAAAB3NzaC1yc2EAAAADAQABAAQGDfS36137jWZGmApaFEPb0QSmWxUa7kkUQv0taDmD0u5NNy7cQrb
U5WGBi+wniHHeCTJo2CVD+cGQXWor/FvJxMT9z877qda7AR9e3Pj80yMKqc01ELZflp8KJnwor8kdARWlnTp82AUP
83FvhbQj+LjEteN1z8In0j4X1nH1IRADthWyF/Ignn4dPKM/jByNTa02nco1Y+nQUNBclWsgdjk70duoUUIfBFCCty
nmRdcgYGS80fY8mTE4NUIRQ8+XjVX1wdxqwtSUQsc1bbhuE2ab3/91FC6BjCNNU1+Ax27dqy34N/ZbRC98NBahEe
lNWRNXLFeaTdaw4NL1dAYc6Pg0duHgoYs1o1gCyQ31G9cVNF1LF28nuQXBLcKay50pqJ3Yqbza0YfRxyvesFYg+yr
+YQK1bpmP4812W3hZVG7iKYjMr2yNdvax51rD13Hq+eqxmgSm03MBB1I01iZ92/Q48dtvso8hiM3BPAj0m8tkPsNX
3+xlWHJt1mx30nIaU= root@controlplane
controlplane:~$

```

Public key distribution is the process of **making a user's public key available** to others in a secure and trustworthy way.

Methods of Public Key Distribution

a) Public Announcement

- User publishes public key openly (website, email).
-  Not secure (can be replaced by attacker).

b) Publicly Available Directory

- A trusted directory stores user identities with public keys.
- Users can retrieve keys when needed.

c) Public Key Authority


- Central trusted authority provides public keys on request.
- Ensures authenticity and freshness.

d) Certificates (Most Common)

- Public keys are distributed using **digital certificates** issued by a **Certificate Authority (CA)**.
- Certificate contains user identity and public key, signed by CA.

 **Most secure and widely used method**

Distribution of secret key by using public key cryptography

<p>Public key cryptography can be used to securely exchange a symmetric (secret) key.</p> <p>Steps</p> <ol style="list-style-type: none">1. Sender generates a random secret key.2. Encrypts the secret key using receiver's public key.3. Encrypted key is sent over the network.	<p>Purpose</p> <ul style="list-style-type: none">• Combines speed of symmetric encryption with security of asymmetric encryption.• Used in hybrid cryptosystems. <p> Example: SSL/TLS</p>
---	--

4. Receiver decrypts it using **private key**.
5. Both parties now share the same secret key.

ElGamal Cryptographic System

The ElGamal Cryptographic System is an **asymmetric (public key) encryption scheme** based on the **Discrete Logarithm Problem**. It provides confidentiality and is commonly used in secure communications. Unlike RSA, ElGamal produces **two ciphertext values**, which increases security.

ElGamal Algorithm

Key Generation

1. Choose a large prime number **p**.
1. Choose a generator **g** of the multiplicative group modulo **p**.
2. Choose a private key **x**, where **1 < x < p - 1**.
3. Compute public key **y = g^x mod p**

Public Key: (p, g, y)

Private Key: x

Encryption

To encrypt message **M**:

1. Choose a random number **k**, where **1 < k < p - 1**.
 2. Compute **C₁ = g^k mod p**
 3. Compute **C₂ = M × y^k mod p**
- Ciphertext:** (C₁, C₂)

Decryption

To decrypt ciphertext (C₁, C₂):

1. Compute

2. Compute modular inverse S^{-1} .
3. Recover message

$$M = C_2 \times S^{-1} \bmod p$$

Numerical Example (Step-wise Table)

Given:

$p = 23$, $g = 5$

Private key $x = 6$

Message $M = 10$

Random number $k = 7$

Key Generation

Step	Calculation	Result
$y = g^x \bmod p$	$5^6 \bmod 23$	8

Public Key: (23, 5, 8)

Private Key: 6

Encryption

Step	Formula	Calculation	Result
C_1	$g^k \bmod p$	$5^7 \bmod 23$	17
C_2	$M \times y^k \bmod p$	$10 \times 8^7 \bmod 23$	21

Ciphertext = (17, 21)

Decryption

Step	Formula	Calculation	Result
S	$C_1^x \bmod p$	$17^6 \bmod 23$	12
S^{-1}	Modular inverse of 12 mod 23	2	
M	$C_2 \times S^{-1} \bmod p$	$21 \times 2 \bmod 23$	10

 Original message recovered = 10

Key Features

- Based on **Discrete Logarithm Problem**
- Produces **two-part ciphertext**
- More secure but larger ciphertext than RSA

Sdsds

Sdsds

