

Rajalakshmi Engineering College

Name: Sanjay Kumar K

Email: 241801244@rajalakshmi.edu.in

Roll no: 241801244

Phone: 9710199820

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 4

Attempt : 1

Total Mark : 10

Marks Obtained : 10

Section 1 : Coding

1. Problem Statement

Ravi is developing a student registration system for a college. To efficiently store and manage the student IDs, he decides to implement a doubly linked list where each node represents a student's ID.

In this system, each student's ID is stored sequentially, and the system needs to display all registered student IDs in the order they were entered.

Implement a program that creates a doubly linked list, inserts student IDs, and displays them in the same order.

Input Format

The first line contains an integer N the number of student IDs.

The second line contains N space-separated integers representing the student IDs.

Output Format

The output should display the single line containing N space-separated integers representing the student IDs stored in the doubly linked list.

Refer to the sample output for formatting specifications.

Sample Test Case

Input: 5

10 20 30 40 50

Output: 10 20 30 40 50

Answer

// You are using GCC

#include <stdio.h>

#include <stdlib.h>

```
struct Node {  
    int data;  
    struct Node* next;  
    struct Node* prev;  
};
```

```
struct Node* createNode(int data) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    if (newNode == NULL) {  
        fprintf(stderr, "Memory allocation failed\n");  
        exit(EXIT_FAILURE);  
    }  
    newNode->data = data;  
    newNode->next = NULL;  
    newNode->prev = NULL;  
    return newNode;  
}
```

```
void insertAtEnd(struct Node** head, struct Node** tail, int data) {  
    struct Node* newNode = createNode(data);
```

```

    if (*head == NULL) {
        *head = newNode;
        *tail = newNode;
    } else {
        newNode->prev = *tail;
        (*tail)->next = newNode;
        *tail = newNode;
    }
}

```

```

void displayList(struct Node* head) {
    struct Node* current = head;
    while (current != NULL) {
        printf("%d", current->data);
        current = current->next;
        if (current != NULL) {
            printf(" ");
        }
    }
    printf("\n");
}

```

```

void freeList(struct Node* head) {
    struct Node* current = head;
    struct Node* nextNode;
    while (current != NULL) {
        nextNode = current->next;
        free(current);
        current = nextNode;
    }
}

```

```

int main() {
    int n, studentID;
    struct Node* head = NULL;
    struct Node* tail = NULL;

    if (scanf("%d", &n) != 1) {
        fprintf(stderr, "Error reading the number of student IDs\n");
        return 1;
    }
}

```

```
for (int i = 0; i < n; i++) {  
    if (scanf("%d", &studentID) != 1) {  
        fprintf(stderr, "Error reading student ID\n");  
        freeList(head);  
        return 1;  
    }  
    insertAtEnd(&head, &tail, studentID);  
}  
  
displayList(head);  
  
freeList(head);  
return 0;  
}
```

Status : Correct

Marks : 10/10