

# Rajalakshmi Engineering College

Name: Sanjay Kumar K

Email: 241801244@rajalakshmi.edu.in

Roll no: 241801244

Phone: 9710199820

Branch: REC

Department: I AI & DS FD

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 2

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

Mike is learning about Binary Search Trees (BSTs) and wants to implement various operations on them. He wants to write a basic program for creating a BST, inserting nodes, and printing the tree in the pre-order traversal.

Write a program to help him solve this program.

#### ***Input Format***

The first line of input consists of an integer N, representing the number of values to insert into the BST.

The second line consists of N space-separated integers, representing the values to insert into the BST.

#### ***Output Format***

The output prints the space-separated values of the BST in the pre-order traversal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

3 1 5 2 4

Output: 3 1 2 5 4

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct Node {
    int data;
    struct Node* left;
    struct Node* right;
};
```

```
struct Node* createNode(int value) {
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));
    newNode->data = value;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

// You are using GCC

```
struct Node* insert(struct Node* root, int value) {
    if (root == NULL) {
        return createNode(value);
    }
    if (value < root->data) {
        root->left = insert(root->left, value);
    } else {
        root->right = insert(root->right, value);
    }
    return root;
}
```

```
void printPreorder(struct Node* node) {
    if (node == NULL) {
        return;
    }
    printf("%d ", node->data);
    printPreorder(node->left);
    printPreorder(node->right);
}

int main() {
    struct Node* root = NULL;

    int n;
    scanf("%d", &n);

    for (int i = 0; i < n; i++) {
        int value;
        scanf("%d", &value);
        root = insert(root, value);
    }

    printPreorder(root);
    return 0;
}
```

**Status :** Correct

**Marks : 10/10**