Learning a Decoder-Free Depth Encoder for Fixed-Focus 3D Fluorescence Microscopy

Supplementary Material

This supplement gives the details of the optical study (Secs. S1 to S4), the learned plate and the four decoders (Secs. S5 to S13), the measurement-only analysis on the reduced field (Secs. S14 to S21), a preliminary single-stack study (Sec. S22) and implementation details (Sec. S23). Section, figure and table numbers of the main paper are written without the prefix S. Every experiment whose outcome could change a claim had its pass criterion fixed before it was run; failed criteria are reported as such.

S1. Optical encoders and photon model

Encoders. All four encoders share the NA-0.8 objective pupil, the vectorial Richards–Wolf excitation relay, the $0.32\,\mu\mathrm{m}$ analysis binning, the NA-0.1 emission PSF, the 12×12 camera, 256 frames and the voxel-integrated assembly; only the field reaching the relay object plane differs. *Phase plate*: tilted plane wave times a fixed random phase plate ($0.32\,\mu\mathrm{m}$ features, phases uniform on $[0, 2\pi)$) propagated over $D = 6.6\,\mu\mathrm{m}$. *No plate*: the same angle scan and propagation without the plate. *In-focus DMD*: 256 random binary amplitude patterns ($0.32\,\mu\mathrm{m}$ pixels, 50% on) imaged in focus. *Amplitude mask*: the angle scan through a fixed random binary amplitude mask ($0.32\,\mu\mathrm{m}$, 50% open) at the plate's position.

Illuminated aperture. If the simulated illuminated aperture equals the $30.7\,\mu\mathrm{m}$ field, its hard edge, $6.6\,\mu\mathrm{m}$ before the image plane, is itself a defocused amplitude encoder: tilted-beam edges sweep laterally by $z \tan\theta$ and their diffraction ripples reach the field centre, so even the no-plate control acquires depth structure. The comparison of the main paper therefore simulates every encoder on an optical grid twice the field width ($61.4\,\mu\mathrm{m}$ aperture) and crops the excitation to the field, as in a microscope whose illuminated area exceeds its field of view. This geometry was adopted after a first comparison with the field-sized aperture revealed the effect; that comparison is reported in Sec. S3. Twice the field is not yet enough for the no-plate control: per-pixel excitation sequences in the central third of the field still vary by $5.6\,\%$ between directions after removing each frame's mean brightness ($37\,\%$ at the field border), against $70\,\%$ for the plate. At four times the field ($123\,\mu\mathrm{m}$ aperture) this falls to $1.0\,\%$ ($1.2\,\%$ at the border) and the no-plate PnP depth error rises from 0.38, 0.50, 0.52 μm to 0.75, 1.04, 1.10 μm at $C = 1, 4, 8$ (PSNR 30.9, 30.4, 30.2 dB; TV: 0.30, 0.30, 0.34 μm to 0.48, 0.71, 0.74 μm), while the plate changes by at most 0.07 dB and 0.02 μm (parameters re-tuned on the extended grid; no edge selections). The main table therefore reports the no-plate row at four times the field; the remaining $1\,\%$ modulation, decodable only with many frames, is why its depth error stays below the depth-blind oracle at $C = 1$.

encoder	full field	reduced field	build (s)	incident power
phase plate	6.2e-07	1.4e-07	327	–
no plate	6.1e-07	1.3e-07	43	–
in-focus DMD	6.0e-07	1.3e-07	42	–
amplitude mask	6.3e-07	1.3e-07	36	–

encoder	full field	reduced field	build (s)	incident power
phase plate	8.0e-07	1.4e-07	111	0.277
no plate	1.4e-06	1.3e-07	186	0.570
in-focus DMD	6.3e-07	1.3e-07	104	0.378
amplitude mask	9.6e-07	1.4e-07	111	0.211

Table S1. Full-size operators ($36{,}864^2$) for the overfilled (top) and the field-sized aperture (bottom): largest relative ℓ_2 difference from the live forward model on three random volumes (full and reduced field; tolerance 10^{-5}), assembly time on one GPU, and the fraction of incident power that passes the pupil.

Photon model. Each encoder's excitation is normalised to the same mean over all frames and the analysis volume (equal deposited excitation dose). Counts are $\mathrm{Poisson}(\kappa_{\mathrm{frame}} y_i)$ with $\kappa_{\mathrm{frame}} = \kappa_0\, 256/k$. The exposure κ_0 of each specimen brings the plate to 1000 photons per pixel per frame at the mean signal at $k = 256$ (15 dB); it is computed from the forward model alone. At equal dose the mean detected signal of every encoder is within 4% of the plate's on every test crop with the overfilled aperture (within 17% with the field-sized aperture). Incident power through the pupil (Tab. S1) sets the laser power required, not the specimen dose: with the field-sized aperture the plate passes 28% and the amplitude mask 21% of the incident light.

PnP settings. Both PnP decoders run a fixed budget of 20 ADMM iterations, each with at most 20 conjugate-gradient iterations (relative tolerance 10^{-5}) for Eq. 5 of the main paper, start from the normalised back-projection and clip the result to $[0, 1]$. The base penalties are $\rho = 5$ for the denoising branches and 10 for the sparsity branch, both multiplied by one selected scale s; each denoising branch has weight 0.2 and the sparsity branch $0.2\,l$. The scales are selected per encoder and compression by mean validation PSNR on $s \in \{\frac{1}{16}, \frac{1}{8}, \ldots, 4\}$ and $l \in \{0, \frac{1}{16}\}$; a selection on an edge extends the grid (s halved or doubled, l multiplied by four),

		multi-slice PnP			box-constrained TV			beads (PnP)	
C	encoder	PSNR	FG-SSIM	depth	PSNR	FG-SSIM	depth	depth	ghost
1	phase plate	35.73	0.814	0.357	38.15	0.881	0.187	0.00	0.033
	amp. mask	35.24	0.788	0.347	37.59	0.857	0.191	0.00	0.030
	no plate‡	30.87	0.538	0.753	32.78	0.617	0.477	0.32	0.363
	in-focus DMD	28.96	0.501	2.168	28.48	0.435	2.285	3.84	1.007
4	phase plate†	35.40	0.801	0.389	37.34	0.852	0.223	0.01	0.013
	amp. mask†	34.88	0.778	0.382	36.79	0.823	0.239	0.01	0.017
	no plate‡	30.41	0.513	1.036	32.09	0.580	0.706	0.34	0.452
	in-focus DMD	28.91	0.493	2.168	28.49	0.465	2.326	2.94	1.013
8	phase plate†	34.86	0.784	0.430	37.00	0.847	0.243	0.01	0.039
	amp. mask†	34.14	0.744	0.446	36.74	0.827	0.237	0.08	0.048
	no plate‡	30.18	0.494	1.102	31.81	0.579	0.737	0.49	0.335
	in-focus DMD	28.83	0.482	2.169	28.53	0.473	2.311	2.60	1.013

Table S2. Encoder comparison behind main-paper Fig. 3 (mean over 12 test crops; depth errors in μm; beads: depth error of detected beads and mirror-ghost energy ratio). †PnP: mean over three plate or mask realisations; TV and all other rows: realisation 0. ‡Simulated aperture four times the field (two times for all other rows; the plate changes by ≤ 0.07 dB). Equal deposited excitation dose. Depth-blind oracle 1.32 μm, flat estimate 2.15 μm.

encoder	prior	$C = 1$	$C = 4$	$C = 8$
phase plate	DnCNN	2/0	0.5/0	0.25/0
	sparsity	1/4	0.5/4	0.25/4
no plate	DnCNN	0.5/0	0.125/0	0.125/0
	sparsity	0.5/4	0.25/4	0.25/4
in-focus DMD	DnCNN	1/0.0625	0.25/0	0.125/0
	sparsity	1/4	0.25/4	0.5/4
amplitude mask	DnCNN	2/0	0.5/0	0.5/0
	sparsity	1/4	0.5/4	0.5/4

Table S3. Selected PnP parameters (ρ scale / L1 scale) on the initial grid, overfilled aperture. Selections at $C = 4, 8$ on the expanded grid are in Tab. S12.

at most twice, and no reported selection remains on an edge. The pretrained denoiser is SCICO's 17-layer DnCNN [1] at its fixed training noise level; the neuron-trained denoisers are blind, trained over $\sigma \in [0, 0.25]$, and receive no noise level. The branch penalty therefore sets the effective denoising strength.

Specimens and tuning. Test: two crops from each of six cells of three animals (DEEP^2, public under the MIT licence [6]), selected from the reference volumes alone and frozen before any reconstruction. Validation: two crops of a separate vascular volume (DnCNN prior, TV) and a held-out bead layout (sparsity prior). The penalty scale ρ and the L1 scale are selected per encoder and compression by mean validation PSNR (Tab. S3); Sec. S4 repeats the selection with an expanded grid.

S2. Mechanism and point-emitter diagnostics

Depth structure of the excitation. Table S4 summarises, in the central half-field, how the per-pixel temporal excitation signature (its 256 values) decorrelates with depth. Without the plate every depth receives essentially the same sequence. The in-focus DMD decorrelates with depth as fast as the plate but is identical at mirror depths. The plate decorrelates within about 1 μm and its mirror depths are uncorrelated.




Figure S1. (a) Lateral shift of the plate's excitation between scan pattern 0 and patterns 1–3 (same azimuth) versus depth; lines: thin-screen prediction pivoting at the plate's conjugate plane. (b) Peak normalised correlation between scan patterns 0 and 1 per depth.

Shear with input tilt. Figure S1 measures the lateral translation of the plate's excitation between scan angles at every depth. The shift is linear in depth, with slopes 0.74–0.94 of the thin-screen prediction $\Delta s/\sqrt{1-s^2}$ and a pivot 6.2–7.0 µm from focus, against the plate's conjugate plane at $D = 6.6\,\mu$m. Patterns also partly decorrelate between angles because the pupil passes a different part of the tilted angular spectrum. The amplitude mask's patterns decorrelate between angles like the plate's, whereas the no-plate excitation barely changes.

Point-emitter diagnostics. Table S5 uses operator columns for 25 interior lateral positions and 16 depths, with a Gaussian approximation of shot noise at the plate's 15 dB exposure and unknown brightness. These quantities describe the information in the measurements, not optical resolution.

encoder	contrast (focus)	signature corr. at Δz (µm) 0.32	0.64	1.28	2.56	mirror corr.	border contrast
phase plate	0.71	0.86	0.53	0.09	0.05	0.05	0.71
no plate	0.18	1.00	1.00	1.00	1.00	1.00	0.25
in-focus DMD	0.82	0.96	0.56	0.13	0.02	1.00	0.82
defocused amplitude mask	0.54	0.92	0.72	0.44	0.43	0.44	0.55

encoder	contrast (focus)	signature corr. at Δz (µm) 0.32	0.64	1.28	2.56	mirror corr.	border contrast
phase plate	0.72	0.86	0.54	0.10	0.05	0.05	0.83
no plate	0.38	1.00	1.00	0.98	0.94	0.96	0.81
in-focus DMD	0.82	0.96	0.56	0.12	0.02	1.00	0.82
defocused amplitude mask	0.54	0.92	0.73	0.44	0.41	0.43	0.79

Table S4. Excitation statistics in the central half-field for the overfilled (left) and the field-sized aperture (right): lateral contrast at focus, median correlation of per-pixel temporal signatures Δz apart and at mirror depths about focus, and the lateral contrast at the field border.

encoder	k	cos(adjacent)	cos(mirror)	axial CRB (µm)	mirror d'	wrong depth (%)	mirror (%)
phase plate	256	0.940	0.823	0.134	10.2	1.0	0.01
	32	0.943	0.828	0.137	10.2	1.6	0.04
no plate	256	1.000	0.999	3.373	0.8	88.2	4.10
	32	1.000	0.999	3.376	0.7	88.7	4.25
in-focus DMD	256	0.967	0.990	0.183	2.4	24.6	13.23
	32	0.970	0.991	0.185	2.4	25.1	13.21
defocused amplitude mask	256	0.966	0.904	0.171	8.0	3.1	0.06
	32	0.969	0.908	0.180	7.7	4.5	0.09

encoder	k	cos(adjacent)	cos(mirror)	axial CRB (µm)	mirror d'	wrong depth (%)	mirror (%)
phase plate	256	0.941	0.807	0.113	12.4	0.9	0.01
	32	0.944	0.810	0.116	12.3	1.2	0.02
no plate	256	0.995	0.925	0.327	9.2	34.8	0.36
	32	0.996	0.915	0.361	9.1	36.8	0.37
in-focus DMD	256	0.968	0.991	0.180	2.4	24.0	12.97
	32	0.970	0.991	0.183	2.4	24.5	12.91
defocused amplitude mask	256	0.965	0.861	0.131	11.4	1.4	0.00
	32	0.968	0.860	0.137	11.4	2.2	0.02

Table S5. Point-emitter diagnostics, overfilled (top) and field-sized aperture (bottom): median cosine between operator columns of depth-adjacent ($0.64\,\mu$m) and mirror voxels, axial Cramér–Rao bound, mirror separation d', and Monte Carlo maximum-likelihood depth errors (any wrong depth / the mirror depth).

S3. Comparison with a field-sized aperture

With the field-sized aperture (Tab. S6 and Fig. S2) the aperture edge gives the no-plate scan and the amplitude mask depth structure: they match or exceed the plate in depth error, while the in-focus DMD result is unchanged. Equalising detected photons instead of deposited dose (Tab. S7) changes the plate and no-plate results by at most 0.1 dB.

C	encoder	PSNR	FG-SSIM	depth (μm)	bead (μm)	ghost
1	phase plate	34.25	0.778	0.329	0.00	0.035
	no plate	34.22 (4/12)	0.763 (7/12)	0.254 (1/12)	0.00	0.024
	in-focus DMD	28.76 (12/12)	0.485 (12/12)	2.169 (12/12)	2.99	1.007
	amp. mask	34.92 (2/12)	0.805 (1/12)	0.230 (0/12)	0.00	0.026
4	phase plate	33.23	0.712	0.424	0.00	0.042
	no plate	33.81 (2/12)	0.744 (3/12)	0.279 (0/12)	0.02	0.015
	in-focus DMD	28.70 (11/12)	0.476 (11/12)	2.170 (12/12)	3.29	1.010
	amp. mask	34.39 (0/12)	0.785 (0/12)	0.263 (0/12)	0.00	0.038
8	phase plate	32.87	0.698	0.466	0.00	0.062
	no plate	33.03 (4/12)	0.703 (6/12)	0.323 (1/12)	0.04	0.019
	in-focus DMD	28.65 (11/12)	0.468 (11/12)	2.170 (12/12)	3.14	1.015
	amp. mask	33.40 (0/12)	0.728 (0/12)	0.317 (0/12)	0.04	0.039

Table S6. Encoder comparison with the field-sized aperture (PnP, initial grid). In parentheses: crops on which the plate is better.

C	encoder	PSNR	FG-SSIM	depth (μm)	bead (μm)	ghost
1	phase plate	34.18	0.776	0.327	0.00	0.035
	no plate	34.22 (2/12)	0.762 (7/12)	0.253 (1/12)	0.00	0.023
	in-focus DMD	28.87 (5/5)	0.493 (5/5)	2.097 (5/5)	–	–
8	phase plate	32.90	0.698	0.467	0.00	0.063
	no plate	33.02 (4/12)	0.702 (6/12)	0.322 (1/12)	0.06	0.020

Table S7. Equal detected photons instead of equal dose (field-sized aperture, parameters of Tab. S6). The DMD was evaluated on 5 of 12 crops at $C = 1$ and the amplitude mask was not evaluated in this setting.




Figure S2. Main-paper Fig. 3 for the field-sized aperture (one realisation, PnP): (a) excitation xz sections, (b) shear with tilt, (c) point emitters assigned a wrong depth at $k = 32$, (d, e) depth error and foreground SSIM versus compression (mean $\pm$ s.e.m. over 12 crops).

S4. Robustness of the encoder comparison

Protocol. Before any result of this study was seen we fixed: three realisations of the phase plate and of the amplitude mask (seeds 0, 101, 202; realisation r draws the central encoder with seed r and the surround of the overfilled aperture with seed $r + 1$, so $r = 0$ is the encoder of the main comparison); a defocus sweep $D \in \{3.3, 6.6, 13.2\}$ μm for plate realisation 0; compressions $C = 8$ and 4; and an expanded tuning grid for every encoder (DnCNN prior: ρ scale $\in \{2^{-4}, \ldots, 4\} \times$ L1 scale $\in \{0, 0.0625\}$; sparsity prior: ρ scale $\in \{0.125, \ldots, 2\} \times$ L1 scale $\in \{1, 4, 16\}$), extended automatically by halving or doubling ρ (or multiplying the L1 scale by 4) whenever the optimum lay on an edge, at most twice. Every new operator was checked against the live forward model (relative error $\leq 6.3 \times 10^{-7}$). Relay, detector, dose, photon model, noise seeds, direction subsets, objects and metrics are those of the main comparison. Paired differences are computed per crop (mean over five direction subsets), with cell-level bootstrap intervals (6 cells, 10^4 resamples); realisations are summarised separately and never

pooled as specimens.

Defocus. Halving D degrades every metric at $C = 8$ (PSNR worse on 12 of 12 crops) and less at $C = 4$; doubling it leaves PSNR unchanged within the interval and lowers depth error slightly (0.016–$0.018\,\mu$m, 9 of 12 crops; Tab. S11). Single-pattern statistics barely change with D (lateral contrast 0.71, depth correlation 0.53 at $0.64\,\mu$m, mirror correlation 0.05), whereas sequence-level quantities do: the median cosine between the $k = 32$ sequences of adjacent depths falls from 0.948 to 0.943, and between mirror depths from 0.854 to 0.823, as D grows, and the shear pivot follows D. At $D = 13.2\,\mu$m only the smallest scan step gives a reliable fit; for larger steps the pattern decorrelates within the correlation window.

Tuning. No final selection lies on an edge of the extended grid (Tab. S12). For neurons only the no-plate scan at $C = 8$ changed: its test PSNR rose by 0.43 dB and its depth error fell by $0.085\,\mu$m. The sparsity prior for beads moved from L1 scale 4 to 16 for most encoders, which changes bead depth errors by at most $0.02\,\mu$m for the defocused encoders and $0.17\,\mu$m for the DMD (whose beads lie at mirror depths in both cases).

Total-variation baseline. We solve $\arg\min_{0\le\mathbf{x}\le1} \frac{1}{2}\|\mathbf{A}\mathbf{x} - \mathbf{y}\|_2^2 + \lambda\,\mathrm{TV}(\mathbf{x})$, isotropic 3D TV of forward differences, by ADMM [2] (penalties 1, conjugate-gradient x-update with at most 20 iterations at tolerance 10^{-5}, 300 iterations) on the same operators and noisy measurements. $\lambda \in \{0.01, 0.03, 0.1, 0.3, 1, 3\}$ is tuned per encoder and compression on the vascular validation crops with the same edge-extension rule. The relative change of $\mathbf{x}$ over the last 10 iterations has medians of 1.3×10^{-3}–1.9×10^{-2} per encoder and compression (largest at $C = 1$), so most solves do not meet a 10^{-3} criterion and we do not claim exact minimisers. Re-solving 12 prespecified test problems at $C = 8$ with 1000 iterations changed PSNR by -0.03 dB on average (at most 0.18 dB), foreground SSIM by at most 0.002 and depth error by at most $0.001\,\mu$m; four problems at $C = 1$ changed by at most 0.03 dB and $0.006\,\mu$m.

Qualitative comparison. Figures S5 and S6 show the median test crop and the bead layout at $C = 8$ for all encoders. Without the plate, depth is largely lost; the DMD places structure at mirror depths.

C	encoder	seed	PSNR	FG-SSIM	depth (μm)	bead (μm)	ghost
8	phase plate	0	34.81	0.784	0.431	0.00	0.051
8	phase plate	101	34.93	0.787	0.422	0.02	0.037
8	phase plate	202	34.85	0.782	0.438	0.02	0.029
8	amp. mask	0	33.70	0.703	0.523	0.06	0.044
8	amp. mask	101	34.37	0.766	0.419	0.17	0.067
8	amp. mask	202	34.36	0.763	0.396	0.00	0.035
4	phase plate	0	35.36	0.801	0.384	0.02	0.014
4	phase plate	101	35.38	0.801	0.391	0.00	0.015
4	phase plate	202	35.45	0.800	0.392	0.00	0.012
4	amp. mask	0	34.83	0.773	0.392	0.00	0.020
4	amp. mask	101	34.95	0.782	0.382	0.02	0.019
4	amp. mask	202	34.87	0.779	0.370	0.00	0.014

Table S8. Per-realisation results (multi-slice PnP, 12 test crops; beads: depth error of detected beads and mirror-ghost ratio).

C	seed	ΔPSNR (dB)	ΔFG-SSIM	Δdepth (μm)	cells (PSNR)
8	0	+1.10 [+0.71, +1.53] (12/12)	+0.081 [+0.062, +0.108] (12/12)	+0.091 [+0.067, +0.122] (11/12)	6/6
8	101	+0.56 [+0.28, +0.99] (11/12)	+0.021 [+0.009, +0.038] (12/12)	-0.003 [-0.062, +0.063] (4/12)	6/6
8	202	+0.48 [+0.23, +0.78] (10/12)	+0.019 [+0.008, +0.030] (11/12)	-0.042 [-0.096, +0.017] (4/12)	5/6
4	0	+0.53 [+0.25, +0.81] (11/12)	+0.028 [+0.019, +0.040] (12/12)	+0.008 [-0.018, +0.034] (7/12)	6/6
4	101	+0.43 [+0.19, +0.73] (12/12)	+0.018 [+0.011, +0.031] (12/12)	-0.009 [-0.051, +0.033] (5/12)	6/6
4	202	+0.58 [+0.30, +0.91] (12/12)	+0.021 [+0.014, +0.031] (12/12)	-0.022 [-0.059, +0.019] (4/12)	6/6

Table S9. Phase plate minus amplitude mask for matched realisations (positive: plate better; depth: reduction of depth error). Brackets: cell-bootstrap 95% interval; parentheses: crops favouring the plate; last column: cells favouring the plate in PSNR. Over all nine plate/mask pairings, including mismatched seeds, the plate is better in PSNR by 0.44–1.23 dB at $C = 8$ and 0.40–0.62 dB at $C = 4$ and in foreground SSIM by 0.016–0.084, while the depth-error difference ranges from -0.042 to $+0.101$ μm.

C	seed	SOM004 c1	SOM004 c2	SOM005 c1	SOM006 c1	SOM006 c2	SOM006 c3
8	0	+0.67	+1.96	+0.52	+0.81	+1.57	+1.09
8	101	+0.42	+0.39	+0.18	+0.23	+1.57	+0.59
8	202	+0.38	+0.45	+0.36	-0.02	+1.12	+0.61
4	0	+0.30	+1.07	+0.04	+0.43	+0.92	+0.41
4	101	+0.07	+0.54	+0.16	+0.31	+1.13	+0.35
4	202	+0.21	+0.79	+0.31	+0.15	+1.23	+0.79

Table S10. Phase plate minus amplitude mask PSNR (dB) per cell (mean over its two crops). 35 of 36 entries are positive. By animal, the plate's PnP PSNR at $C = 8$ spans 34.2–35.9 dB over realisations, with the same encoder ranking in every animal.




Figure S3. (a, b) PSNR and depth error of the three plate (P) and three amplitude-mask (M) realisations (markers; bar: mean) and of the no-plate scan (N). (c) Plate depth error versus defocus D.

C	D (μm)	PSNR	FG-SSIM	depth	bead	ΔPSNR vs. 6.6	wrong depth (%)	adj. cos.	mirror cos.	pivot (μm) / slope
8	3.3	33.80	0.709	0.579	0.06	-1.01 [-1.40, -0.62]	2.0	0.948	0.854	3.2 / 0.78
8	6.6	34.81	0.784	0.431	0.00	–	1.6	0.943	0.827	6.5 / 0.81
8	13.2	34.69	0.783	0.415	0.09	-0.11 [-0.30, +0.08]	1.5	0.943	0.823	15.3 / 0.66
4	3.3	34.97	0.785	0.421	0.02	-0.39 [-0.73, -0.09]	2.0	0.948	0.854	3.2 / 0.78
4	6.6	35.36	0.801	0.384	0.02	–	1.6	0.943	0.827	6.5 / 0.81
4	13.2	35.26	0.802	0.367	0.00	-0.09 [-0.23, +0.06]	1.5	0.943	0.823	15.3 / 0.66

Table S11. Plate defocus sweep (realisation 0, PnP). ΔPSNR: paired against $D = 6.6\,\mu$m with cell-bootstrap interval. Wrong depth, adjacent and mirror cosine: point-emitter diagnostics at $k = 32$. Pivot / slope ratio: shear fit between scan patterns 0 and 1 (thin-screen prediction: pivot D, ratio 1).

		neurons (DnCNN)		beads (L1)		neuron test	
encoder	C	original	expanded (ext.)	original	expanded (ext.)	PSNR	depth (μm)
phase plate	8	0.25/0	0.25/0 (0)	0.25/4	0.5/16 (1)	34.81 → 34.81	0.431 → 0.431
phase plate	4	0.5/0	0.5/0 (0)	0.5/4	1/16 (1)	35.36 → 35.36	0.384 → 0.384
no plate	8	0.125/0	0.0625/0 (1)	0.25/4	0.25/4 (0)	31.99 → 32.42	0.606 → 0.521
no plate	4	0.125/0	0.125/0 (0)	0.25/4	0.125/4 (1)	32.49 → 32.49	0.500 → 0.501
in-focus DMD	8	0.125/0	0.125/0 (0)	0.5/4	0.5/4 (0)	28.83 → 28.83	2.169 → 2.169
in-focus DMD	4	0.25/0	0.25/0 (0)	0.25/4	1/16 (1)	28.91 → 28.91	2.168 → 2.168
amp. mask	8	0.5/0	0.5/0 (0)	0.5/4	0.5/16 (1)	33.70 → 33.70	0.523 → 0.523
amp. mask	4	0.5/0	0.5/0 (0)	0.5/4	1/16 (1)	34.83 → 34.83	0.393 → 0.392

Table S12. Initial versus expanded tuning (ρ scale / L1 scale; in parentheses the number of automatic grid extensions) and the resulting neuron test means (initial → expanded).

C	encoder	λ	PSNR	FG-SSIM	depth (μm)	plate adv. PSNR	s	Δx
8	phase plate	0.1	37.00	0.847	0.243	–	9.5	1.3e-03
8	amp. mask	0.1	36.74	0.827	0.237	+0.26 [-0.04, +0.55] (9/12)	11.1	1.7e-03
8	no plate	0.03	34.34	0.676	0.342	+2.66 [+1.54, +3.78] (12/12)	9.9	2.6e-03
8	in-focus DMD	0.1	28.53	0.473	2.311	+8.47 [+6.74, +9.89] (12/12)	12.5	2.5e-03
4	phase plate	0.3	37.34	0.852	0.223	–	20.6	2.8e-03
4	amp. mask	0.3	36.79	0.823	0.239	+0.55 [+0.29, +0.82] (11/12)	18.9	3.8e-03
4	no plate	0.03	34.74	0.703	0.302	+2.60 [+1.22, +4.01] (12/12)	11.3	5.0e-03
4	in-focus DMD	0.3	28.49	0.465	2.326	+8.85 [+6.93, +10.42] (12/12)	17.5	6.4e-03
1	phase plate	1	38.15	0.881	0.187	–	55.3	9.1e-03
1	amp. mask	1	37.59	0.857	0.191	+0.56 [+0.22, +0.88] (10/12)	59.9	7.8e-03
1	no plate	0.3	34.39	0.682	0.295	+3.76 [+2.45, +5.21] (12/12)	55.3	1.8e-02
1	in-focus DMD	3	28.48	0.435	2.285	+9.67 [+7.82, +11.34] (12/12)	86.2	1.9e-02

Table S13. TV baseline (realisation 0; 12 test crops, five direction subsets for $C > 1$). Plate adv.: plate minus encoder PSNR with cell-bootstrap interval and crops favouring the plate; s: median solve time on one GPU; Δx: median relative change over the last 10 iterations.




Figure S4. **Full-size recovery with the phase plate** on the prespecified display crop (largest reference depth spread), one direction subset. Top: lateral maximum-intensity projection, colour coding the depth of the brightest voxel; bottom: xz projection. Identical display scale for all panels; below: PSNR and local depth error of this crop. Bar: $5\,\mu$m.




Figure S5. All encoders at $C = 8$ (PnP, one direction subset) on the crop of Fig. S4: depth-coded lateral projection and xz projection, identical display scale; below: PSNR and depth error of this crop.




Figure S6. Bead layout at $C = 8$ (PnP, one direction subset) for all encoders, as in Fig. S5.

S5. Learned plate

Training. Mirror pairs in the loss are planes $(z, 14 - z)$ of the 16-plane grid, the pairing about the detection focus used throughout; on the four-plane reduced field no pair qualifies and all weights are one. The plate loss (Eq. 4 of the main paper) is evaluated through the same simulation as the operator: angular-spectrum propagation over D, NA-0.8 vectorial relay, emission PSF at NA 0.1 and 8×8 pixel pooling, on the overfilled geometry (centre: the random plate of realisation 0, trained; surround: an independent draw, frozen, so the beam edges stay outside the field). Each Adam step (learning rate 0.05, 1000 steps) samples 24 lateral positions and 4 of the 256 directions (8 on the reduced field); the two seeds differ only in this sampling. Training changes the centre phase by 1.7–1.8 rad RMS and lowers the mean $|\rho|$ between depth columns of a training batch from 0.89 to 0.64 / 0.68 (full field, seeds 0 / 1) and from 0.88 to 0.78 / 0.82 (reduced field). It uses no specimen.

Measurement-only bounds and fabrication. Table S14 pairs every certification query (Sec. S14) of the learned plates with the same query of the random plate. Gains appear at both noise levels and no query is lost. The exact mean depth correlation of the reduced operator, $\langle|\rho|\rangle$ over all depth pairs and lateral positions, predicts the measured narrowing of the per-voxel bounds through the two-column rule of Sec. 4 (predicted 0.80, measured 0.79 at 15 dB). Across encoders the same rule orders the measured widths correctly but overstates the differences where $\rho \to 1$: predicted / measured width relative to the random plate is 1.29 / 1.14 for the mask ($\langle|\rho|\rangle = 0.922$), 2.52 / 1.26 for the DMD (0.967) and 11.5 / 2.47 without the plate (0.999). Rounding the trained phase to 8 or 4 levels and adding uniform phase error to the 8-level plate raise the correlation slightly and keep 32–33 certificates.

Full size. Table S15 and Fig. S7 list the full-field results behind the main paper. At equal total dose the learned plate with $k = 32$ matches the random plate with all $k = 256$ frames: learned PnP 0.164 against 0.161 μm (cell-bootstrap difference $-2\,\%$ [-17, $+15$]), TV 0.153 against 0.187 μm, pretrained PnP $-35\,\%$ [-42, -28] (12 of 12 crops). All encoders use the extended tuning grid of Sec. S4; the random plates select interior parameters at every C. Paired over crops, each learned plate has the lower depth error than each random plate on 12 of 12 crops at every C, and the higher PSNR on 12 of 12 at $C = 1$ and on 9–12 of 12 at $C = 4$ and 8. With TV (the λ grid and edge rule of Tab. S13; every selection interior) both learned plates beat the random plate on 10–12 of 12 crops in PSNR and 11–12 of 12 in depth at every C. The learned plates' TV results are not monotone in C: at $C = 4$ validation selects $\lambda = 1$, which ties $\lambda = 0.3$ within 0.01 dB on the vascular validation crops but over-smooths the neurons.

	15 dB			25 dB			
plate	cert.	+ / −	width	cert.	+ / −	width	$\langle\|\rho\|\rangle$
random plate	24	–	1.00	60	–	1.00	0.868
trained, seed 0	33	9 / 0	0.79	63	3 / 0	0.92	0.761
trained, seed 1	29	5 / 0	0.79	63	3 / 0	0.92	0.759
seed 0, 8 phase levels	32	8 / 0	0.80	63	3 / 0	0.92	0.767
seed 0, 4 phase levels	32	8 / 0	0.82	63	3 / 0	0.93	0.781
8 levels + 0.2 rad error	33	9 / 0	0.80	63	3 / 0	0.92	0.771
8 levels + 0.5 rad error	33	9 / 0	0.82	63	3 / 0	0.93	0.789

Table S14. Learned plate on the reduced field (72 queries per noise level). cert.: certified queries; + / −: queries certified only with this plate / only with the random plate; width: mean per-voxel bound width relative to the random plate; $\langle|\rho|\rangle$: exact mean depth correlation of the operator columns. No certificate contradicts the truth.




Figure S7. **Optics and prior gains add, where the optics record depth** (full-size field, 12 test crops, equal deposited dose). PSNR (a) and local depth error (b) against compression C; colour: encoder, line: decoder. Dashed lines in (b): the depth-blind oracle and the flat estimate. No decoder moves the DMD off the flat estimate.

		$C = 1$		$C = 4$		$C = 8$	
prior	encoder	PSNR	depth	PSNR	depth	PSNR	depth
pretrained PnP	random plate, realisation 0	35.73	0.357	35.35	0.384	34.81	0.431
	random plate, realisation 1	35.76	0.371	35.38	0.391	34.93	0.422
	random plate, realisation 2	35.80	0.369	35.45	0.392	34.85	0.438
	trained plate, seed 0	37.03	0.184	36.47	0.212	36.15	0.230
	trained plate, seed 1	37.12	0.173	36.49	0.206	36.21	0.234
TV	random plate, realisation 0	38.15	0.187	37.34	0.223	37.00	0.243
	trained plate, seed 0	39.29	0.135	38.18	0.166	38.61	0.153
	trained plate, seed 1	39.52	0.124	38.30	0.158	38.63	0.152
learned	random plate, realisation 0	39.18	0.161	38.29	0.184	37.11	0.221
	trained plate, seed 0	40.82	0.109	39.89	0.130	38.83	0.164

Table S15. Random and learned plates at full size with three priors (mean over 12 test crops; $C > 1$: five direction subsets per crop). Depth: local depth error in μm.

S6. Extended test set

The 12 prespecified test crops were chosen by a structure score (projected foreground area times depth spread). To check that the decoder comparison does not depend on this choice, we fixed the following before any run: per test cell, all crops eligible under the same occupancy rule except the two already used (34–60 per cell) were sorted by position, and eight were drawn uniformly at random with a fixed seed. These 48 crops were simulated exactly like the others and reconstructed with the weights already selected on the validation crops for each encoder and decoder; no weight was re-selected. Two gates were also fixed in advance and passed: the new code reproduced the stored clean measurements exactly and the recorded test reconstruction of one prespecified crop for every encoder and decoder to within 0.006 dB and $0.003\,\mu$m. The pass criterion was an interval excluding zero on the 48 new crops for each decoder; it holds for all three (Tab. S16). The new crops are less structured than the prespecified ones (depth-blind oracle 1.42 against $1.32\,\mu$m, flat estimate 1.93 against $2.15\,\mu$m); there the in-focus DMD with learned PnP scores $1.81\,\mu$m. Unless stated otherwise, "test crops" in this supplement are the 12 prespecified ones.

		12 prespecified		48 random		all 60	
decoder	seed	depth [95 % CI]	crops	depth [95 % CI]	crops	depth [95 % CI]	crops
TV	s0	−37 % [−41, −34]	12/12	−43 % [−49, −38]	48/48	−42 % [−46, −38]	60/60
	s1	−38 % [−40, −36]	12/12	−44 % [−49, −38]	48/48	−42 % [−46, −38]	60/60
pretrained PnP	s0	−47 % [−53, −41]	12/12	−56 % [−59, −52]	48/48	−54 % [−57, −51]	60/60
	s1	−46 % [−52, −40]	12/12	−57 % [−60, −52]	48/48	−55 % [−58, −51]	60/60
learned PnP	s0	−26 % [−35, −18]	11/12	−31 % [−34, −28]	48/48	−30 % [−32, −27]	59/60
	s1	−29 % [−35, −24]	12/12	−31 % [−34, −29]	48/48	−31 % [−33, −29]	60/60

Table S16. Depth change of the learned plate against the random plate ($C = 8$, 5 draws per crop, cell-bootstrap interval) on the prespecified crops, the randomly drawn crops and both together; crops: crops with a lower depth error.

S7. Background, read noise and low dose

The main paper models shot noise only. On the 12 prespecified crops we fixed two harder conditions before running them. *Background*: a uniform background equal to the random plate's mean signal per pixel and frame, the same for every encoder and specimen, plus Gaussian read noise of 2 electrons; the known mean background is subtracted before decoding. *Low dose*: one tenth of the photons, shot noise only. Noise draws use the main paper's seeds. Weights were selected again for every condition, encoder and decoder on the validation crops with the main paper's grids and edge rule (no selection at a grid edge). The pass criterion, an interval excluding zero for every condition and decoder, holds in all six cases (Tab. S17); every crop improves, and PSNR rises by 0.8–1.9 dB. With background the gain under TV shrinks from 37 to 28 %; at one tenth of the dose both plates lose depth accuracy, and the relative gain is similar or larger (36, 52 and 31 %).

condition	decoder	random	learned	depth [95 % CI]	crops
shot noise (main paper)	TV	0.243	0.153	−37 % [−41, −34]	12/12
	pretrained PnP	0.431	0.230	−47 % [−53, −41]	12/12
	learned PnP	0.221	0.164	−26 % [−35, −18]	11/12
background + read noise	TV	0.249	0.180	−28 % [−36, −20]	12/12
	pretrained PnP	0.548	0.247	−55 % [−60, −50]	12/12
	learned PnP	0.227	0.166	−27 % [−36, −18]	12/12
one tenth of the dose	TV	0.365	0.236	−36 % [−44, −28]	12/12
	pretrained PnP	0.733	0.352	−52 % [−59, −45]	12/12
	learned PnP	0.269	0.186	−31 % [−38, −24]	12/12

Table S17. Learned against random plate under harder noise ($C = 8$, 12 prespecified crops $\times$ 5 draws; mean local depth error in μm, depth change with cell-bootstrap interval; crops: crops with a lower depth error). Weights re-selected per condition on validation crops.

S8. Learned prior and hybrid

Configuration. Every result labelled learned PnP uses one configuration: the neuron-trained 2D network replaces the pretrained DnCNN in the three slice branches (same branch weights), and a fourth branch applies the neuron-trained 3D network (branch weight 1, same penalty ρ). The 3D network does not replace the slice branches; we did not evaluate the two networks separately.

Data and training. Training volumes come from SOM009 (cell 1, stacks 8 and 9), an animal that contributes no test cell; stack 10 is held out to monitor denoising. Planes whose mean intensity drops below half the median of their neighbours, or repeat the previous plane, are excluded. 459 training crops are cut on the $16 \times 48 \times 48$ reconstruction grid with the preprocessing of the test volumes. The 2D DnCNN (17 layers, 64 channels) is trained on random xy, xz and yz slices for 30k steps (batch 64), the 3D DnCNN (12 layers, 48 channels) on whole volumes for 15k steps (batch 8), both with Adam (10^{-3}), $\sigma \sim \mathcal{U}(0, 0.25)$, flips, lateral transposes and intensity scaling in $[0.3, 1]$; on held-out crops they gain 16.6 and 16.8 dB at $\sigma = 0.1$.

Hybrid. The hybrid adds to the learned prior an isotropic TV branch with weight λ_{TV} scaled from the standalone TV solver's selection (scales 0.3, 1, 3) and a box constraint, tuned with the extended grid. An earlier protocol fixed, before any test result, that the reported solver per encoder and compression would be the one with the best validation PSNR among TV, learned and hybrid; validation selects the hybrid for the plate and TV for the DMD at every C (bold in Tab. S18). The main paper instead reports each decoder separately, and does not use the hybrid. On the neuron test crops the hybrid matches the learned prior (higher PSNR on 4–7 of 12 crops) and beats TV on 8–11 of 12; the vascular validation crops favour the TV term more than the neurons do.

C	encoder	PSNR (dB) PnP	TV	learned	hybrid	depth error (μm) PnP	TV	learned	hybrid
1	phase plate	35.73	38.15	39.18	**38.77**	0.357	0.187	0.161	**0.175**
	amp. mask	35.24	37.60	38.44	–	0.347	0.191	0.159	–
	no plate (4×)	30.87	32.78	31.33	–	0.753	0.477	0.632	–
	in-focus DMD	28.96	**28.48**	29.02	28.97	2.168	**2.281**	2.246	2.233
4	phase plate	35.35	37.34	38.29	**37.99**	0.384	0.223	0.184	**0.202**
	amp. mask	34.83	36.79	37.58	–	0.393	0.239	0.198	–
	no plate (4×)	30.40	32.09	30.71	–	1.036	0.706	0.914	–
	in-focus DMD	28.91	**28.49**	28.95	28.99	2.168	**2.327**	2.248	2.240
8	phase plate	34.81	37.00	37.11	**37.22**	0.431	0.243	0.221	**0.226**
	amp. mask	33.70	36.74	36.69	–	0.523	0.237	0.237	–
	no plate (4×)	30.18	31.81	30.58	–	1.102	0.737	0.922	–
	in-focus DMD	28.83	**28.53**	28.82	28.88	2.169	**2.311**	2.249	2.234

Table S18. Every encoder with every solver (mean over 12 test crops, realisation 0, equal dose). Bold: solver selected on validation among TV, learned and hybrid (hybrid run for plate and DMD only). No plate: four-times aperture (Sec. S1).

		$C=1$		$C=4$		$C=8$	
solver	patterns	PSNR	depth	PSNR	depth	PSNR	depth
pretrained PnP	set 0	28.96	2.168	28.91	2.168	28.83	2.169
	set 1	28.95	2.167	28.90	2.168	28.81	2.169
TV	set 0	28.48	2.281	28.49	2.327	28.53	2.311
	set 1	28.48	2.289	28.52	2.314	28.47	2.249
learned	set 0	29.02	2.246	28.95	2.248	28.82	2.249
	set 1	29.05	2.238	28.95	2.245	28.81	2.243

Table S19. In-focus DMD with the original pattern set (set 0) and an independent one (set 1); mean over 12 test crops, depth error in μm. Flat estimate: 2.148 μm.

A second DMD pattern set. To check that the DMD's failure is not one unlucky draw, we built the DMD operator again with independent binary patterns (centre seed 101, surround 102; everything else unchanged) and reran pretrained PnP, TV and the learned prior with fresh tuning. Every solver reproduces the original pattern set to within 0.06 dB and 0.07 μm and stays at the depth error of a flat estimate (Tab. S19).

Where the prior's gain goes. For each lateral column of a crop we split the reconstruction error into its mean over depth (a wrong total intensity) and the zero-mean remainder (intensity in the wrong depth); the two squared parts add to the total. Table S20 gives the depth part's share and the learned / pretrained ratio of each part. With the plate and the mask the learned prior removes lateral and depth error, the latter on every crop; with the DMD it removes lateral error only.

		depth part of error		learned / pretrained		depth lower
encoder	C	pretrained	learned	lateral	depth	(crops)
phase plate	1	94 %	96 %	0.32	0.58	12 / 12
	8	93 %	95 %	0.48	0.71	12 / 12
amp. mask	1	93 %	96 %	0.32	0.61	12 / 12
	8	91 %	95 %	0.37	0.55	12 / 12
in-focus DMD	1	99 %	99 %	0.74	1.03	6 / 12
	8	99 %	99 %	0.77	1.04	4 / 12

Table S20. Lateral and depth parts of the squared reconstruction error (12 test crops; $C = 8$: draw 0). Ratios: median over crops.

S9. Diffusion decoder

Model. A 3D U-Net (14.0 M parameters; residual blocks at $16 \times 48 \times 48$, $8 \times 24 \times 24$ and $4 \times 12 \times 12$, self-attention at the coarsest level) is trained as an EDM denoiser [4] for 60k iterations on the training volumes of the learned PnP denoisers (SOM009), split by animal from the test set. On held-out SOM009 volumes it reaches 42.9, 40.7, 39.3, 37.5 and 34.4 dB at $\sigma = 0.02$, 0.05, 0.1, 0.2 and 0.5. Unconditional samples are not copies of training volumes: their median nearest-training distance over 16 flip and transpose symmetries is 0.567, against 0.560 for held-out volumes.

Sampling. DiffPIR [9] with 100 steps of the EDM schedule ($\rho = 7$, σ from 1 to 0.002). At each step the denoised estimate $\hat{\mathbf{x}}_0$ is replaced by $\arg\min_{\mathbf{x}} \frac{1}{2}\|\mathbf{A}\mathbf{x}-\mathbf{y}\|^2_{\mathbf{W}} + \frac{\lambda}{2\sigma_t^2}\|\mathbf{x}-\hat{\mathbf{x}}_0\|^2$, solved by conjugate gradients (at most 100 iterations, relative residual 10^{-6}), with $\mathbf{W}$ the inverse Poisson variance; ζ sets the fresh noise. λ and ζ are selected per encoder on the validation crops with the edge-extension rule of the other decoders (all encoders: $\lambda = 0.01$, $\zeta = 0.3$, interior). Eight samples per measurement; the reconstruction is their mean. The first tuning run used 20 conjugate-gradient iterations,

	sample mean		learned PnP		confident wrong
encoder	PSNR	depth	PSNR	depth	calls (of 240)
random plate	34.34	0.455	37.11	0.221	117
learned, seed 0	38.74	0.168	38.83	0.164	120
learned, seed 1	38.84	0.164	38.89	0.157	118
in-focus DMD	27.98	2.368	28.82	2.249	–

Table S21. Diffusion decoder at $C = 8$ (12 test crops $\times$ 5 draws; depth in μm) next to learned PnP on the same measurements, and confident wrong connectivity calls.

which left the data step unconverged; the change to 100 iterations was recorded before any test reconstruction.

Prespecified criteria and outcome. Before training we fixed four criteria (Tab. S21). (i) Competitive prior: the random-plate sample mean within 10 % of learned PnP's depth error and 0.5 dB of its PSNR. This *fails* (0.455 against 0.221 μm), so by our protocol the remaining comparisons are descriptive. (ii) Gain of the learned plate of at least 15 % with an interval excluding zero: -63 % [-70, -54] (seed 1: -64 %), 12 of 12 crops. (iii) Fewer confident wrong connectivity calls (at least 7 of 8 samples agreeing on the wrong answer) on 48 neuron queries $\times$ 5 draws: *fails* (117, 120 and 118 of 240; sign test $p = 0.25$ and 1.0). (iv) The DMD stays depth-blind: holds (2.37 μm). The samples are over-confident: the per-voxel error lies within two sample standard deviations for 71 % (random) and 75 % (learned) of voxels, although the per-crop spread tracks the error (Spearman 0.61–0.65).

S10. Plate objectives

All plates start from random realisation 0 and use the same sampling, 1000 Adam steps and seeds; only the loss changes. *Worst-case coherence*: a smooth maximum of $|\rho|$ over depth pairs, as in Miniscope3D [7]. *Depth Fisher information*: the Poisson Fisher information of a voxel's depth with its brightness marginalised, entered as $-$mean log of the Schur complement, a Cramér–Rao-type objective [5]. *Uncentred*: our loss without centring the columns. The mirror weight is undefined on the four-plane reduced field, so its ablation was dropped. On the reduced field (Tab. S23) every objective gains certificates against the random plate, loses none and issues no wrong certificate; paired against ours over query instances, both seeds pooled, Fisher is $+8/-2$, uncentred $+5/-0$ and coherence $+2/-5$; none is significant even before accounting for repeated noise draws. At full size (Tab. 3) ours and its uncentred variant are best and equal; Fisher information, nominally first on the reduced field, keeps 54–63 % of our depth gain. The reduced-field ranking therefore does not carry over to full-size reconstruction.

Second seed and other decoders. Fixed before the runs: coherence and Fisher plates were retrained with seed 1 (same start, sampling and 1000 steps), each plate was tuned on the validation crops for each decoder (no selection at a grid edge), and the criterion was an interval excluding zero for our plate against both objectives for both seeds under learned PnP at $C = 8$. It holds, and it holds under TV and pretrained PnP as well (Tab. S22). Gaps are larger under the two decoders with weaker priors.

ours vs	seed	TV	pretrained PnP	learned PnP
worst-case coherence	0	-18 % [-21, -15], 12/12	-22 % [-28, -17], 12/12	-12 % [-16, -9], 11/12
	1	-16 % [-19, -13], 12/12	-18 % [-25, -12], 11/12	-12 % [-16, -10], 12/12
depth Fisher information	0	-15 % [-17, -11], 12/12	-20 % [-25, -17], 12/12	-14 % [-19, -10], 10/12
	1	-15 % [-16, -13], 12/12	-16 % [-23, -11], 12/12	-17 % [-19, -15], 12/12

Table S22. Depth change of our plate against the coherence and Fisher plates of the same seed ($C = 8$, 12 prespecified crops $\times$ 5 draws, cell-bootstrap interval; crops with a lower depth error).

	certified at 15 dB		at 25 dB		bound width
objective	seed 0	seed 1	seeds 0 / 1	$\langle\lvert\rho\rvert\rangle$	vs random
none (random)	24		60	0.868	1
ours	33	29	63 / 63	0.761	0.79
ours, uncentred	33	34	63 / 62	0.751	0.76
worst-case coherence	30	29	63 / 63	0.816	0.90
depth Fisher information	36	32	63 / 63	0.767	0.73

Table S23. Plate objectives on the reduced field (72 queries per noise level; bound width at 15 dB, seed 0).

S11. Conformal depth intervals

Protocol. Fixed before any calibration reconstruction: $\alpha = 0.1$, $k = 32$, learned PnP with each plate's validation-selected weights. Calibration volumes are crops of a held-out stack of the training animal of the priors, simulated and reconstructed exactly like the test crops (the live forward model reproduces the stored test measurements exactly). The primary set holds the 35 non-overlapping crops; all 240 crops form a sensitivity set. Columns and weights are those of the local depth error; λ runs over a grid of 0.01 planes. The test reconstructions (12 crops $\times$ 5 draws) reproduce the paper's learned-PnP rows (largest difference 0.16 dB, $0.009\,\mu$m, from GPU nondeterminism). The 240-crop set overlaps and is not an independent check. The theorem's guarantee needs the calibration volumes and a new volume to be exchangeable; calibration and test come from different animals, so the test miscoverage is empirical evidence for that assumption, not a consequence of the theorem. Criteria: test miscoverage within $\alpha \pm 0.05$ for every plate, and $\hat{\lambda}$ of the learned plate at least 25 % below the random plate's with a calibration-bootstrap interval excluding zero.

Outcome. Table S24: validity holds for every plate on both calibration sets. Seed 0 passes the tightening criterion on both sets; seed 1 passes on all 240 crops and misses it by 0.2 points on the primary set (-24.8 %, interval excluding zero).

Connectivity calls. The same protocol was prespecified for error-controlled connectivity calls on 48 neuron queries, thresholding the widest-path bottleneck between two endpoints. It *fails*: false-disconnected rates are 0.23–0.48 against the 0.15 limit, and no test query is called connected. The bottleneck does not separate truly connected from disconnected queries even on the calibration crops (medians 0.35 against 0.39 for the random plate), and it shifts between the calibration animal and the test animals. We therefore make no connectivity claim.

	35 non-overlapping crops		all 240 crops	
plate	$\hat{\lambda}$ (μm)	test miscov.	$\hat{\lambda}$ (μm)	test miscov.
random	0.646	0.060	0.570	0.085
learned, seed 0	0.474	0.075	0.422	0.091
learned, seed 1	0.486	0.060	0.422	0.081

Table S24. Conformal depth intervals ($\alpha = 0.1$, $C = 8$): half-width and signal-weighted test miscoverage for both calibration sets.

S12. Calibration and tolerance

Misaligned systems are simulated and reconstructed with learned PnP ($k = 32$, five draws), paired with the nominal measurements. *Calibrated*: the operator is rebuilt from the fabricated or displaced plate and the weights are re-selected on validation (all interior). *Uncalibrated*: the nominal operator is used. Criteria fixed before any learned-plate row was read: calibrated variants keep an interval excluding zero and at least 75 % of the nominal reduction; uncalibrated, the learned plate beats the random plate under every error. The calibrated criteria pass; the uncalibrated one fails for plate distance and lateral shift (Tab. S25). A diagnostic shows why: a distance error of $\pm 0.5\,\mu$m shifts the excitation code axially by about $0.5\,\mu$m (correlation with the nominal code after the shift: 0.97 random, 0.99 learned), and a one-feature lateral plate shift moves it by one $0.32\,\mu$m pixel (correlation 1.00). These errors are unknown reference offsets, removed by registering one axial and one lateral constant, *e.g.* with a bead; the learned plate's measurements change more under them (7.6 against 1.5 % for the distance error) because its code has more depth structure.

	error	learned	random	change [95 % CI]
	none (design)	0.164	0.221	−25.9 % [−35, −18]
calibrated	4 phase levels	–	0.221	−25.5 % [−34, −18]
	8 levels, 0.5 rad RMS	–	0.221	−25.2 % [−33, −18]
	$D = 6.1\,\mu$m	0.162	0.225	−27.8 % [−37, −20]
	$D = 7.1\,\mu$m	0.167	0.227	−26.4 % [−35, −19]
uncalibrated	scan tilt 0.005	0.196	0.253	−22 % [−29, −15]
	scan tilt 0.01	0.251	0.307	−18 % [−22, −15]
	$D = 6.1\,\mu$m	0.571	0.528	+8 % [+3, +14]
	$D = 7.1\,\mu$m	0.438	0.383	+14 % [+12, +17]
	lateral shift 1 feature	0.400	0.372	+7 % [0, +19]

Table S25. Depth error (μm, $C = 8$, learned PnP) under fabrication and alignment errors, learned against random plate under the same error (cell-bootstrap 95 % interval). Fabrication rows are calibrated variants of the learned plate against the nominal random plate.

S13. Detection: what can replace scan frames?

The main experiments detect at NA 0.1 on 12×12 pixels of $2.56\,\mu$m, so nearly all information comes from the 256 directions. We ask whether better detection can replace directions. Excitation is unchanged (random plate, realisation 0, overfilled aperture); only the emission NA (0.1 or 0.3) and the camera pooling (12×12, 24×24 or 48×48 pixels) change, and configurations are compared at a fixed number of measurements $M = k\times$pixels. Every configuration detects the same total number of photons per specimen as the reference, so the larger collection of NA 0.3 is not credited. Operators hold only the rows of the selected frames (three direction subsets for $k < 256$) and match the live forward model to $< 10^{-6}$; the learned prior is tuned per configuration on the validation crops with the extended grid (all picks interior).

Table S26 gives three results. At NA 0.1 finer pixels cannot replace directions: 16 frames on 48×48 pixels lose 1.5 dB and raise the depth error from 0.15 to $0.23\,\mu$m on every crop, because the NA-0.1 emission spot (Airy radius $3.2\,\mu$m) is wider than the pixels, which resample the same blur. At NA 0.3 (radius $1.1\,\mu$m) the trade works: 16 frames on 48×48 pixels or 64 on 24×24 reconstruct as well as all 256 frames at NA 0.3 and better than the NA-0.1 reference on 12 of 12 crops in PSNR and 8 or 11 of 12 in depth, a 4- to 16-fold shorter scan. With 8 times fewer measurements depth needs directions: two frames on 48×48 pixels give $0.49\,\mu$m against 0.22–0.23 μm with 8 or 32 frames. Detection is thus part of the optics that decide what the measurements allow; the camera can carry lateral detail, but depth still comes from the angle scan through the plate.

M	NA	pixels	pitch	frames	PSNR	FG-SSIM	depth	crops > ref.
36,864	0.1	12×12	2.56	256	39.17	0.914	0.154	–
	0.3	12×12	2.56	256	41.33	0.949	0.123	12 / 8
	0.1	48×48	0.64	16	37.69	0.888	0.230	0 / 0
	0.3	48×48	0.64	16	41.72	0.956	0.134	12 / 8
	0.3	24×24	1.28	64	41.82	0.954	0.115	12 / 11
4,608	0.1	12×12	2.56	32	37.02	0.872	0.227	0 / 0
	0.3	24×24	1.28	8	38.53	0.906	0.215	5 / 0
	0.3	48×48	0.64	2	35.64	0.839	0.494	0 / 0

Table S26. Detection NA and camera pooling against scan frames at fixed measurement count M and equal detected photons (random plate, learned prior; mean over 12 test crops, three direction subsets for fewer than 256 frames). Pitch in μm; depth: local depth error in μm; crops > ref.: crops with higher PSNR / lower depth error than the reference (first row). The reference is an independent run (noise draw and tuning) of the plate entry of Tab. S18.

S14. Bounds and certificates without the learned prior

This part asks what the measurements determine without a reconstruction prior, using only the data, the intensity box $[0, 1]$ and the noise model, on a reduced field where exact optimisation is feasible. Given measurements $\mathbf{y}$ and per-row intervals $[\ell_i, h_i]$ that contain the noise-free measurement with stated probability, the consistency set is $\mathcal{C}(\mathbf{y}) = \{\mathbf{x} \in [0,1]^N : \ell_i \le (\mathbf{A}\mathbf{x})_i \le h_i\}$. For calibrated Gaussian noise we use the Bonferroni box $y_i \pm z\sigma$ with $z = \Phi^{-1}(1 - \alpha/2M)$, $\alpha = 0.05$, so the truth lies in $\mathcal{C}(\mathbf{y})$ with probability at least 0.95. A connectivity query asks whether two endpoints p, q in a query region are joined by a path of voxels with $x_v \ge \tau$ (6-adjacency), *i.e.* whether the bottleneck $b(\mathbf{x}) = \max_{P:p\to q} \min_{v\in P} x_v \ge \tau$. It is *certified connected* if $\min_{\mathcal{C}} b \ge \tau$, *certified disconnected* if $\max_{\mathcal{C}} b < \tau$, and *ambiguous* otherwise; ambiguity is proven by two validated volumes in $\mathcal{C}(\mathbf{y})$ with opposite connectivity. Per-voxel bounds decide many queries directly; the rest use the exact programs of Sec. S16. The queries use the central $4 \times 4 \times 4$ region, $\tau = 0.4$ and prespecified endpoints on 24 synthetic phantoms (Sec. S17) with three noise seeds, plus 48 windows cut from the test neurons.

Outcomes. At 15 dB the random plate certifies 24 of 72 synthetic queries and the learned plate 33 (seed 1: 29), gaining 9 query instances and losing none (seed 1: $+5/-0$). The three noise draws of a phantom are not independent: the gains come from four phantoms (P01, P03 and P17 in all three draws, P10 in one) and none is lost, an exact sign test over phantoms gives $p = 0.125$, so the count gain is consistent but not significant at the phantom level; the bound narrowing below is the more robust measure. All gains are connected queries (3 to 12 of 48); disconnected queries are saturated at 21 of 24 for every plate. Over 12.5–25 dB in 2.5 dB steps the gain is 0, +9, +9, +9, 0 and +3; at 17.5 dB

the learned plate loses one disconnected phantom in two of three draws, so "none lost" holds at 15 dB only. Per-voxel bounds narrow by the equivalent of 1.9 dB of SNR throughout (about 2.4 times the photons). A χ^2 ellipsoid in place of the Bonferroni box narrows the bounds by 33–39 % and lifts the random plate from 8 to 16 decided of 24 (seed 0), more than the plate does; the learned plate still leads (18 of 24). Choosing directions adaptively from the bounds did not meet its prespecified criterion. *On the 48 neuron windows, no query is decided by any plate at 15, 25, 35 or 45 dB*, and every bound spans $[0, 1]$; twelve of these windows remain undetermined at 15 dB even with 128 or 256 directions, where the operator has full rank, so noise amplification takes over from the null space. Dense neuronal tissue is therefore not determined by the measurements alone at these settings, which is why the main paper's depth intervals go through a calibrated prior.

S15. Reduced-field structural outcomes per encoder

Table S27 runs the certification pipeline of Sec. S14 on each encoder's reduced operator ($k = 32$, equal dose). With the overfilled aperture (top; 24 phantoms × 3 noise seeds) the no-plate control certifies 3 and 18 of 72 queries against 24 and 60 for the random plate, the in-focus DMD 19 and 36, and the learned plates 33 / 29 and 63. With a field-sized aperture (bottom; seed 0 only) the edge covers most of the 7.68 μm reduced field and gives the no-plate control depth structure.

	15 dB		25 dB	
encoder	cert. / ambig.	uncertain voxels	cert. / ambig.	uncertain voxels
random phase plate	24 / 48	7	60 / 12	0
trained plate, seed 0	33 / 39	4	63 / 9	0
trained plate, seed 1	29 / 43	4.5	63 / 9	0
defocused amplitude mask	24 / 48	10	59 / 13	0
no plate	3 / 69	54	18 / 54	15.5
in-focus DMD	19 / 53	17	36 / 36	4

	15 dB		25 dB	
encoder	cert. / ambig.	uncertain voxels	cert. / ambig.	uncertain voxels
phase plate	8 / 16	9.5	20 / 4	0
no plate	7 / 17	19	18 / 6	0
in-focus DMD	6 / 18	19	12 / 12	4
defocused amplitude mask	8 / 16	14	20 / 4	0

Table S27. Certified / ambiguous queries and median uncertain query voxels (of 64) per encoder on the reduced field. Top: overfilled aperture, 72 queries (24 phantoms × 3 seeds); . Bottom: field-sized aperture, 24 queries (seed 0).

S16. Formulation details

Variables and set. The reduced field has $N = 576$ voxels; the query region Q is the central $4 \times 4 \times 4$ block (64 voxels, 6-adjacency, 144 edges) and the remaining 512 voxels are free nuisance variables in $[0, 1]$. Each measurement row is rescaled by its largest coefficient before optimisation; all reported residuals are recomputed in unscaled units. For certificates the set is enlarged outward, $\mathcal{C}_\delta = \{\mathbf{x} : \ell_i - \delta\|a_i\|_1 \le a_i^\top \mathbf{x} \le h_i + \delta\|a_i\|_1\}$ with $\delta = 10^{-7}$, so that a certificate on $\mathcal{C}_\delta$ is robust to the solver's feasibility tolerance; witnesses must lie in the unenlarged $\mathcal{C}$ with residual at most 10^{-8} (scaled) and 10^{-6} (unscaled).

Minimum bottleneck (separator form). $b_{\min} = \min_{\mathbf{x}\in\mathcal{C}} \max_P \min_{v\in P} x_v$ is computed through vertex-separator duality. Binary s_v marks the side of v ($s_p = 1$, $s_q = 0$), binary z_v marks membership in the separator, and

$$\begin{aligned} \min\ t \ \text{ s.t. } & |s_u - s_v| \le z_u + z_v \quad \forall (u,v) \in E_Q, \\ & x_v \le t + (1 - t_{\text{lo}})(1 - z_v) \quad \forall v \in Q, \qquad \mathbf{x} \in \mathcal{C}. \end{aligned} \tag{S1}$$

Any feasible (s, z) defines a vertex set $S = \{v : z_v = 1\}$ that separates p from q, and $t \ge \max_{v\in S} x_v \ge b(\mathbf{x})$; conversely every separator is representable. The query is certified connected when the solver's dual bound on $\mathcal{C}_\delta$ exceeds $\tau + \eta$, $\eta = 10^{-6}$.

Maximum bottleneck (flow form). Binary w_v selects a path; a unit flow from p to q is supported on selected vertices ($0 \le f_{uv} \le w_u$, $f_{uv} \le w_v$, flow conservation), and $x_v \ge t - t_{\text{hi}}(1 - w_v)$; maximising t gives $b_{\max}$. The query is certified disconnected when the dual bound is below $\tau - \eta$.

Decision versions and witnesses. Fixing $t = \tau \pm \mu$ turns each program into a feasibility problem whose solution, if

any, is a candidate witness $\mathbf{x}_C$ ($b \geq \tau+\mu$) or $\mathbf{x}_D$ ($b \leq \tau-\mu$). Every candidate is re-checked independently: residual in unscaled units, active set at τ, connectivity by breadth-first search and by union–find, and threshold margin $\geq \eta$. Only re-checked pairs count as proven ambiguity.

Route order and guards. (i) Per-voxel envelope: 2×64 LPs on $\mathcal{C}_\delta$, warm-started, with failed solves retried cold and a feasible-point check; (ii) witness-first decision MIPs; (iii) LP path/separator enumeration when at most 16 voxels are uncertain and at most 200 induced paths exist; (iv) the joint MIP verifier. A certificate that contradicts a validated witness or a verified feasible point is reported as numerically undecided, and timeouts are never counted as ambiguity. All programs are solved with HiGHS [3] (single thread, tolerances 10^{-9}, zero relative MIP gap).

S17. Reduced operator and phantoms

The reduced operator uses the optics of the full system (532 nm, NA 0.8/0.1, one random plate with $0.32\,\mu$m features at $D = 6.6\,\mu$m, 256 directions, $2 \times 2 \times 2$ patch integration, equal dose) on a smaller field: optical grid 96×96 at $0.08\,\mu$m, analysis grid $8 \times 24 \times 24$ at $0.32\,\mu$m, reconstruction grid $4 \times 12 \times 12$ at $0.64\,\mu$m, and 3×3 camera pixels of $2.56\,\mu$m per pattern. It agrees with the live simulator to $\leq 3.1 \times 10^{-7}$ relative ℓ_2 error on 10 volumes, 3 geometries and all 576 re-simulated columns, and $\mathsf{A} = \mathsf{BU}$ holds to 1.3×10^{-7}; negative controls (column order, axis swap, depth flip) give 8.4%, 7.4% and 3.5% error. All entries are positive; singular values range from 125.3 to 0.058 at $k = 256$ (condition number 2.2×10^3), and the nested direction subsets have condition numbers 2.0×10^2, 5.6×10^2, 8.9×10^5 and 2.9×10^3 at $k = 16, 32, 64, 128$. The cosine between operator columns of depth-adjacent voxels is 0.958, 0.869 and 0.802 at separations of 1, 2 and 3 planes. Table S28 lists the 24 phantoms.

id	family	structure (query region, $4 \times 4 \times 4$)	p	q
P01	connected	straight filament through all depths	(0,5,5)	(3,5,5)
P02	connected	3D staircase filament, U(0.5,1)	(0,4,4)	(3,7,7)
P03	connected	lateral staircase filament in one plane	(1,4,4)	(1,7,7)
P04	disconnected	two separated filaments (z=0 and z=3)	(0,4,4)	(3,7,7)
P05	disconnected	filament with one missing voxel	(0,5,4)	(3,6,7)
P06	disconnected	filament with one weak (0.3) bridge voxel	(0,6,4)	(3,5,7)
P07	connected	two alternative-depth routes (z=0 and via z=3), both bright	(0,4,5)	(0,7,5)
P08	connected	alternative-depth routes, shallow route dim (0.15-0.25)	(0,4,5)	(0,7,5)
P09	disconnected	laterally crossing filaments at different depths	(0,4,5)	(3,6,7)
P10	connected	crossing filaments joined by a vertical connector	(0,4,5)	(3,6,7)
P11	disconnected	four isolated beads (endpoints on beads)	(0,4,4)	(3,7,7)
P12	connected	bead chain (adjacent beads of varying brightness)	(0,7,4)	(3,7,7)
P13	connected	three alternative routes, intensities 0.5-0.8	(0,4,4)	(1,4,7)
P14	connected	P01 filament + U(0,0.15) background over the field	(0,5,5)	(3,5,5)
P15	disconnected	P04 + bright distractor blobs outside the ROI	(0,4,4)	(3,7,7)
P16	connected	graded filament $1.0 \rightarrow 0.45$	(0,7,4)	(3,4,7)
P17	connected	thick (2-voxel) vertical filament	(0,5,5)	(3,6,5)
P18	connected	in-plane filament at z=0 (mirror-depth control: mirror plane empty)	(0,4,6)	(0,7,6)
P19	connected	ring in plane z=1, endpoints opposite	(1,4,4)	(1,7,7)
P20	connected	dim filament (0.42-0.48), just above tau = 0.4	(0,4,4)	(3,7,7)
P21	connected	random lattice walk (9 voxels)	(0,4,4)	(1,6,5)
P22	unknown	two random walks (connectivity decided by truth BFS)	(0,7,7)	(3,4,4)
P23	unknown	sparse random volume (15% of ROI voxels U(0.3,1)); fixed corners	(0,4,4)	(3,7,7)
P24	unknown	dense random volume U(0,1) over the whole field	(0,4,4)	(3,7,7)

Table S28. The 24 phantoms. Coordinates are global (z, a, b); the query region is $z \in [0, 3]$, $a, b \in [4, 7]$. For the "unknown" families, connectivity is decided by the truth.

S18. Reconstruction versus ambiguity: all cases

All 26 reconstructions (two estimators, 13 cases) lie inside $\mathcal{C}(\mathbf{y})$ (Tab. S29 and Fig. S8). In the dense phantom P24 the reconstruction fits the data more closely than the truth (largest normalised residual 0.24 vs. 0.83 at 15 dB, 0.001 vs. 0.83 at 25 dB) while reporting the wrong topology. The total variation of the opposite-topology witnesses is close to that of the truth for the filament phantoms (P01: truth 11.6, witnesses 13.2 and 12.6; P20: 17.5, 17.7 and 20.4; P06: 23.4, 24.3 and 23.0), so these volumes are not rough artefacts. The TV weight of the reconstruction baseline was selected on ten calibration phantoms: $\lambda = 3 \times 10^{-4}$ at 15 dB (mean calibration PSNR 46.9 dB vs. 46.2 dB without TV) and $\lambda = 0$ at 25 dB.



Figure S8. All 13 reduced-field cases (15 dB, $k = 32$): ground truth, box-constrained least squares + TV reconstruction, and the validated connected and disconnected volumes in $\mathcal{C}(\mathbf{y})$ where they exist. Certified cases show no opposite-topology volume because none exists in $\mathcal{C}(\mathbf{y})$.

case	dB	truth	recon. TV	PSNR	recon. LS	consistent C	consistent D	data decide
P01	15	C 0.60 / 0.61	C 0.64 / 0.62	51.5	C 0.62 / 0.62	C 0.49 / 1.00	D 0.40 / 1.00	ambiguous
P06	15	D 0.30 / 0.72	D 0.30 / 0.68	46.4	D 0.30 / 0.69	C 0.40 / 1.00	D 0.40 / 1.00	ambiguous
P07	15	C 0.72 / 0.83	C 0.59 / 0.83	41.5	C 0.55 / 0.83	C 0.41 / 1.00	D 0.40 / 1.00	ambiguous
P13	15	C 0.54 / 0.79	C 0.45 / 0.74	31.2	C 0.42 / 0.74	C 0.40 / 1.00	D 0.20 / 1.00	ambiguous
P20	15	C 0.42 / 0.54	C 0.42 / 0.55	48.1	C 0.41 / 0.56	C 0.45 / 1.00	D 0.10 / 1.00	ambiguous
P24	15	C 0.43 / 0.83	D 0.00 / 0.23	7.8	D 0.00 / 0.24	C 0.40 / 1.00	D 0.00 / 1.00	ambiguous
P13	25	C 0.54 / 0.79	C 0.53 / 0.74	50.3	C 0.53 / 0.74	C 0.56 / 1.00	D 0.40 / 1.00	ambiguous
P20	25	C 0.42 / 0.54	C 0.42 / 0.56	68.2	C 0.42 / 0.56	C 0.41 / 1.00	D 0.40 / 1.00	ambiguous
P24	25	C 0.43 / 0.83	D 0.20 / 0.00	13.6	D 0.20 / 0.00	C 0.40 / 1.00	D 0.40 / 1.00	ambiguous
P09	15	D 0.00 / 0.61	D 0.01 / 0.64	50.5	D 0.00 / 0.64	–	–	cert. D
P18	15	C 0.77 / 0.80	C 0.75 / 0.72	58.2	C 0.76 / 0.70	–	–	cert. C
P06	25	D 0.30 / 0.72	D 0.30 / 0.69	65.3	D 0.30 / 0.69	–	–	cert. D
P07	25	C 0.72 / 0.83	C 0.70 / 0.83	59.1	C 0.70 / 0.83	–	–	cert. C

Table S29. All 13 reduced-field cases. Each entry: topology at $\tau = 0.4$ (C/D), bottleneck b, and the largest normalised residual $\max_i |(\mathbf{A}\mathbf{x} - \mathbf{y})_i|/z\sigma$ (inside $\mathcal{C}$ iff ≤ 1). Reconstruction PSNR is against the coarse truth.

S19. Ambiguity versus directions and photon budget

Figure S9 and Tab. S30 report, for the queries that are proven ambiguous with $k = 32$ directions, how many become certified with k directions (row confidence set, $\tau = 0.4$, three seeds pooled, after the 600 s rerun). The decision rule (primary metric: certified fraction at $k = 256$ with fixed total photons; outcomes A ≥ 0.30, B 0.10–0.30, C < 0.10) was fixed before any aggregate was computed; the outcome is C.

Numerical validation. 1776 problems were solved with no errors and no wrong certificates. The 110 problems that hit the 60 s limit were rerun at 600 s with nothing else changed: 59 became proven ambiguities, 5 became certificates and 1 numerical boundary case remained. The 1325 stored witness volumes were re-validated on independently rebuilt problems (maximum unscaled residual 9.6×10^{-10}), and all 18 certificates not issued by the envelope were re-derived by the other exact route. Total compute: 696 CPU-hours.




Figure S9. (a) Fraction of the queries proven ambiguous at $k = 32$ that become certified with k directions, with fixed total photons or fixed per-frame exposure ($8\times$ photons at $k = 256$). (b) Median uncertain query voxels over all 72 queries. Three seeds; no query remained undecided.

k	16	32	64	128	256
total dose / baseline	1×	1×	1×	1×	1×
certified	0	0	0	0	0
proven ambiguous	48	48	48	48	48
undecided	0	0	0	0	0
median uncertain voxels	11.5	10	8	9	10
mean bound width	0.338	0.306	0.291	0.301	0.320

(a) 15 dB, fixed total photons ($n = 48$)

k	16	32	64	128	256
total dose / baseline	1×	1×	1×	1×	1×
certified	0	0	0	0	0
proven ambiguous	12	12	12	12	12
undecided	0	0	0	0	0
median uncertain voxels	0	0	0	0	0
mean bound width	0.132	0.114	0.099	0.095	0.096

(b) 25 dB, fixed total photons ($n = 12$)

k	16	32	64	128	256
total dose / baseline	0.5×	1×	2×	4×	8×
certified	0	0	0	2	6
proven ambiguous	48	48	48	46	42
undecided	0	0	0	0	0
median uncertain voxels	19	10	6	4	3.5
mean bound width	0.392	0.306	0.245	0.211	0.184

(c) 15 dB, fixed per-frame exposure ($n = 48$)

k	16	32	64	128	256
total dose / baseline	0.5×	1×	2×	4×	8×
certified	0	0	3	3	3
proven ambiguous	12	12	9	9	9
undecided	0	0	0	0	0
median uncertain voxels	0	0	0	0	0
mean bound width	0.149	0.114	0.087	0.073	0.065

(d) 25 dB, fixed per-frame exposure ($n = 12$)

Table S30. Outcomes per number of directions k. "Median uncertain voxels" and "mean bound width" describe the per-voxel envelope over all 72 queries.

set	dB	photons	ambig. k=32	certified k=256	ambiguous	undecided	truth $\notin \mathcal{C}$
row+SVD	15	8×	16	4	11	1	3
row+SVD	15	fixed	16	0	15	1	3
row+SVD	25	8×	4	1	3	0	3
row+SVD	25	fixed	4	0	4	0	3
Poisson (Garwood)	15	8×	17	2	15	0	1
Poisson (Garwood)	15	fixed	17	0	17	0	1
Poisson (Garwood)	25	8×	5	2	3	0	0
Poisson (Garwood)	25	fixed	5	0	5	0	0

Table S31. Secondary confidence sets (seed 0, $k \in \{32, 256\}$). Row+SVD adds 576 calibrated projections of the 2304 rows; Poisson uses Garwood intervals at the same family level.

S20. Total-variation prior

$\mathcal{C}_R(\mathbf{y}) = \{\mathbf{x} \in \mathcal{C}(\mathbf{y}) : \sum_{(u,v)\in E} |x_u - x_v| \le R\}$ over the 1488 6-neighbour edges of the reduced field is encoded exactly with one auxiliary variable $e_{uv} \ge |x_u - x_v|$ per edge and $\sum e_{uv} \le R$. $R_{\mathrm{cal}} = 31.9$ is the largest TV among ten calibration phantoms and was fixed before any test case. The certification pipeline (600 s per solve) was run on the nine ambiguous cases of Sec. S18 at R_{cal}, $2R_{\mathrm{cal}}$ and $4R_{\mathrm{cal}}$ (Tab. S32). In all 18 runs whose budget the truth satisfies, two validated opposite-topology witnesses exist inside $\mathcal{C}_R$, and they are as regular as the truth (P20 at 25 dB: TV 17.3 and 17.5 vs. 17.5; P01 at 15 dB: 12.2 and 12.9 vs. 11.6). No run produced a certificate. Only TV was tested; a neurite-specific learned prior was not.

case	dB	TV(truth)	R_{cal}	$2R_{\mathrm{cal}}$	$4R_{\mathrm{cal}}$
P01	15	11.6	ambiguous	ambiguous	ambiguous
P06	15	23.4	ambiguous	ambiguous	ambiguous
P07	15	33.9	ambiguous†	ambiguous	ambiguous
P13	15	44.3	empty set†	ambiguous	ambiguous
P20	15	17.5	ambiguous	ambiguous	ambiguous
P24	15	454.0	ambiguous†	ambiguous†	ambiguous†
P13	25	44.3	empty set†	ambiguous	ambiguous
P20	25	17.5	ambiguous	ambiguous	ambiguous
P24	25	454.0	empty set†	empty set†	empty set†

Table S32. Outcomes under a TV budget. †: the true object violates the budget. "Empty set": no volume satisfies both the data and the prior.

S21. Fine-grid model mismatch

Fine objects live on the $8 \times 24 \times 24$ analysis grid: *sub-voxel occupancy* (each voxel's value carried by 4 of its 8 sub-voxels at twice the value, so $\mathsf{R}\mathbf{x}_f$ equals the coarse truth)

fine structure	dB	noise only	+ mismatch (max)	+ mismatch (99.9%)
sub-voxel	15	0/24	21/24	21/24
sub-voxel	25	0/24	21/24	21/24
multiplicative	15	1/24	22/24	22/24
multiplicative	25	0/24	22/24	20/24

Table S33. Held-out coverage of the coarse truth (8 phantoms $\times$ 3 seeds). All failures with the allowance come from phantom P18 (a filament confined to the outermost depth plane), whose residual reaches 25%, outside the calibration range.

and a *multiplicative* model $\mathbf{x}_f = \mathrm{clip}(\mathsf{U}\mathbf{x} \cdot U(0,2), 0, 1)$. Measurements are $\mathsf{B}\mathbf{x}_f$ from the fine-grid simulator plus the Gaussian noise of the main study. The allowance $\epsilon_i = c(|y_i| + z\sigma)$ uses c calibrated on ten calibration phantoms $\times$ three seeds: $c = 0.78$ / 0.58 (sub-voxel; maximum / 99.9% row quantile) and 0.37 / 0.25 (multiplicative). Calibration residuals $\|\mathsf{B}\mathbf{x}_f - \mathsf{A}\mathsf{R}\mathbf{x}_f\|/\|\mathsf{B}\mathbf{x}_f\|$ were 5.8–13.0% and 2.3–7.1%.

fine structure	dB	model	n	truth $\in \mathcal{C}$	empty	certified	ambiguous	undecided	contradicts truth
multiplicative	15	noise	8	0	7	0	1	0	0
multiplicative	15	noise + allowance (max)	8	8	0	0	8	0	0
multiplicative	15	noise + allowance (99.9%)	8	8	0	0	8	0	0
multiplicative	25	noise	8	0	7	0	1	0	0
multiplicative	25	noise + allowance (max)	8	8	0	0	8	0	0
multiplicative	25	noise + allowance (99.9%)	8	7	0	0	8	0	0
multiplicative	exact	exact	8	0	7	0	1	0	0
sub-voxel	15	noise	8	0	7	0	1	0	0
sub-voxel	15	noise + allowance (max)	8	7	0	0	8	0	0
sub-voxel	15	noise + allowance (99.9%)	8	7	0	0	8	0	0
sub-voxel	25	noise	8	0	7	0	1	0	0
sub-voxel	25	noise + allowance (max)	8	7	0	0	8	0	0
sub-voxel	25	noise + allowance (99.9%)	8	7	0	1	7	0	1
sub-voxel	exact	exact	8	0	8	0	0	0	0

Table S34. Query outcomes under model mismatch (seed 0). "Contradicts truth" counts certificates opposite to the true connectivity regardless of coverage; the single case (P18, sub-voxel, 25 dB, 99.9% rule) occurred when the allowance did not cover the truth.

S22. Preliminary single-stack study

Before the encoder comparison, the phase-plate system was evaluated on eight prespecified crops of *one* neuron stack with a Gaussian relative-noise model at 15 dB and the field-sized aperture (Tab. S35); the main paper uses an independent crop set from six cells. On a held-out crop of that study, voxel integration lowers the reconstruction error throughout the iterations relative to a coarse-grid simulation (Fig. S10), and foreground SSIM is 0.913, 0.832 and 0.761 at $C = 1$, 16 and 32 (depth errors 0.177, 0.354 and $0.443\ \mu$m); the higher compressions are exploratory and not part of the test-set evaluation.

C	depth err. (μm)	FG-SSIM	Δdepth (μm)	ΔPSNR (dB)
1	0.497 ± 0.183	0.679 ± 0.238	–	–
4	0.550 ± 0.170	0.652 ± 0.252	$+0.053 \pm 0.016$	-0.45 ± 0.35
8	0.626 ± 0.207	0.588 ± 0.273	$+0.129 \pm 0.032$	-0.91 ± 0.45

Table S35. Preliminary study: eight crops of one stack, phase plate, mean $\pm$ s.d. over crops of five-subset averages; Δ: paired change against each crop's own $C = 1$ result.




Figure S10. Relative reconstruction error over ADMM iterations with the voxel-integrated and the coarse-simulation operator, on (a) a neuron crop and (b) a bead phantom of the preliminary study (mean of three noise realisations).

S23. Implementation details

Optical simulation, operator assembly and reconstruction run in PyTorch and JAX on NVIDIA RTX 6000 Ada and RTX 4500 Ada GPUs; PnP and TV reconstruction use SCICO [1] with a pretrained 17-layer DnCNN [8]. A full-size operator is assembled in 0.6–7 minutes; a PnP reconstruction takes 2–9 s and a TV reconstruction 9–150 s on one GPU. Certification uses HiGHS [3] on CPUs with BLAS threads fixed to one. All tuned quantities of the structural study (TV weight, TV budget, mismatch allowance) were selected on

ten calibration phantoms (P02, P03, P04, P05, P08, P10, P12, P16, P17, P21) and fixed before any test case was run.

References

[1] Thilo Balke, Fernando Davis, Cristina Garcia-Cardona, Soumendu Majee, Michael McCann, Luke Pfister, and Brendt Wohlberg. Scientific computational imaging code (SCICO). *Journal of Open Source Software*, 7(78):4722, 2022. 2, 22

[2] Stephen Boyd, Neal Parikh, Eric Chu, Borja Peleato, and Jonathan Eckstein. Distributed optimization and statistical learning via the alternating direction method of multipliers. *Foundations and Trends in Machine Learning*, 3(1):1–122, 2011. 5

[3] Q. Huangfu and J. A. J. Hall. Parallelizing the dual revised simplex method. *Mathematical Programming Computation*, 10(1):119–142, 2018. 16, 22

[4] Tero Karras, Miika Aittala, Timo Aila, and Samuli Laine. Elucidating the design space of diffusion-based generative models. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022. 11

[5] Yoav Shechtman, Steffen J. Sahl, Adam S. Backer, and W. E. Moerner. Optimal point spread function design for 3D imaging. *Physical Review Letters*, 113(13):133902, 2014. 12

[6] Navodini Wijethilake, Mithunjha Anandakumar, Cheng Zheng, Peter T. C. So, Murat Yildirim, and Dushan N. Wadduwage. DEEP-squared: deep learning powered De-scattering with Excitation Patterning. *Light: Science & Applications*, 12:228, 2023. 2

[7] Kyrollos Yanny, Nick Antipa, William Liberti, Sam Dehaeck, Kristina Monakhova, Fanglin Linda Liu, Konlin Shen, Ren Ng, and Laura Waller. Miniscope3D: optimized single-shot miniature 3D fluorescence microscopy. *Light: Science & Applications*, 9:171, 2020. 12

[8] Kai Zhang, Wangmeng Zuo, Yunjin Chen, Deyu Meng, and Lei Zhang. Beyond a Gaussian denoiser: Residual learning of deep CNN for image denoising. *IEEE Transactions on Image Processing*, 26(7):3142–3155, 2017. 22

[9] Yuanzhi Zhu, Kai Zhang, Jingyun Liang, Jiezhang Cao, Bihan Wen, Radu Timofte, and Luc Van Gool. Denoising diffusion models for plug-and-play image restoration. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition Workshops (CVPRW)*, pages 1219–1229, 2023. 11