



School: ..... Campus: .....

Academic Year: ..... Subject Name: ..... Subject Code: .....

Semester: ..... Program: ..... Branch: ..... Specialization: .....

Date: .....

## Applied and Action Learning

(Learning by Doing and Discovery)

**Name of the Experiment :** Read the Chain – Web3.js Basics

### Objective/Aim:

To read blockchain data using **Web3.js** by connecting to an Ethereum blockchain node and fetching details like the latest block, block number, and account balances.

### Apparatus/Software Used:

- Node.js
- Web3.js library
- Ethereum test network (e.g., Ganache / Sepolia / Goerli)
- MetaMask (optional, for account management)
- VS Code or any code editor

### Theory/Concept:

Web3.js is a JavaScript library that allows interaction with Ethereum blockchain nodes using RPC (Remote Procedure Calls).

- **Blockchain** is a decentralized ledger consisting of blocks.
- Each block has a block number, timestamp, transactions, and hash.
- Using **Web3.js**, developers can:
  - Connect to an Ethereum node (via HTTP or WebSocket).
  - Read chain data such as current block number, gas price, or balances.
  - Interact with smart contracts.

In this experiment, we focus on **reading the chain**, i.e., fetching basic blockchain information.

## Procedure:

Step 1: Write Token Contract (in Remix IDE)

Step 2: Open Remix IDE → Select compiler **0.8.x** → Compile MyToken.sol.

Step 3: **Deploy Token**

- In Remix → “Deploy & Run Transactions” tab.
- Select **Injected Web3** (MetaMask connected to local testnet).

Step 4: **Verify on Aave.net**

- Copy deployed contract address.
- Go to **Aave.net** → Add Token → Paste contract address.
- Token appears in the dashboard.

Step 5: **Interact with Token**


- Check total supply.
- Transfer tokens between MetaMask accounts.
- Use Aave.net to approve and transfer tokens on behalf of another account.

```


1  // SPDX-License-Identifier: MIT
2  pragma solidity ^0.8.27;
3
4  import {ERC20} from "@openzeppelin/contracts/token/ERC20/ERC20.sol";
5  import {ERC20Permit} from "@openzeppelin/contracts/token/ERC20/extensions/ERC20Permit.sol";
6
7  contract MyToken is ERC20, ERC20Permit {
8      constructor(string memory name, string memory symbol) infinite gas 1399400 gas
9          ERC20(name, symbol)
10         ERC20Permit(name) // ✓ Required for EIP-2612 (Permit)
11     {
12         _mint(msg.sender, 1000000 * 10 ** decimals());
13     }
14 }
15


```

contract



Token





## Observation

- Token contract deployed successfully.
- Contract address was visible and verified through Aave.net.
- Initial supply was credited to the deployer's wallet (MetaMask).
- Able to transfer tokens and check balances on Aave.net interface.

## ASSESSMENT

Rubrics	Full Mark	Marks Obtained	Remarks
Concept	10		
Planning and Execution/ Practical Simulation/ Programming	10		
Result and Interpretation	10		
Record of Applied and Action Learning	10		
Viva	10		
<b>Total</b>	<b>50</b>		

**Signature of the Student:**

**Name :**

**Signature of the Faculty:**

**Regn. No. :**