

Package ‘queueing’

November 9, 2015

Version 0.2.6

Date 2015-11-08

Title Analysis of Queueing Networks and Models

Author Pedro Canadilla

Maintainer Pedro Canadilla <pedro.canadilla@gmail.com>

Depends R (>= 2.11.1)

Suggests

Description

It provides versatile tools for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It imple-

ments M/M/1, M/M/c, M/M/Infinite, M/M/1/K, M/M/c/K, M/M/c/c, M/M/1/K/K, M/M/c/K/K, M/M/c/K/m, M/M/Infinite/K

Multiple Channel Open Jackson Networks, Multiple Channel Closed Jackson Networks,

Single Channel Multiple Class Open Networks, Single Channel Multiple Class Closed Networks

and Single Channel Multiple Class Mixed Networks.

Also it provides a B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

License GPL-2

Copyright Pedro Canadilla

URL <http://www.r-project.org>

NeedsCompilation no

Repository CRAN

Date/Publication 2015-11-09 15:01:31

R topics documented:

queueing-package	8
B_erlang	9
CheckInput	10
CheckInput.i_CJN	11
CheckInput.i_MCCN	12

CheckInput.i_MCMN	13
CheckInput.i_MCON	14
CheckInput.i_MM1	15
CheckInput.i_MM1K	16
CheckInput.i_MM1KK	17
CheckInput.i_MMC	18
CheckInput.i_MMCC	19
CheckInput.i_MMCK	20
CheckInput.i_MMCKK	21
CheckInput.i_MMCKM	22
CheckInput.i_MMInf	23
CheckInput.i_MMInfKK	24
CheckInput.i_OJN	25
CompareQueueingModels	26
C_erlang	27
Engset	28
Inputs	28
Inputs.o_CJN	29
Inputs.o_MCCN	31
Inputs.o_MCMN	32
Inputs.o_MCON	33
Inputs.o_MM1	34
Inputs.o_MM1K	35
Inputs.o_MM1KK	36
Inputs.o_MMC	37
Inputs.o_MMCC	38
Inputs.o_MMCK	39
Inputs.o_MMCKK	40
Inputs.o_MMCKM	41
Inputs.o_MMInf	42
Inputs.o_MMInfKK	43
Inputs.o_OJN	44
L	45
L.o_CJN	46
L.o_MCCN	47
L.o_MCMN	48
L.o_MCON	50
L.o_MM1	51
L.o_MM1K	52
L.o_MM1KK	53
L.o_MMC	54
L.o_MMCC	55
L.o_MMCK	56
L.o_MMCKK	57
L.o_MMCKM	58
L.o_MMInf	59
L.o_MMInfKK	60
L.o_OJN	61

Lc	62
Lc.o_MCCN	63
Lc.o_MCMN	64
Lc.o_MCON	65
Lck	66
Lck.o_MCCN	68
Lck.o_MCMN	69
Lck.o_MCON	70
Lk	71
Lk.o_CJN	72
Lk.o_MCCN	74
Lk.o_MCMN	75
Lk.o_MCON	76
Lk.o_OJN	77
Lq	78
Lq.o_MM1	79
Lq.o_MM1K	80
Lq.o_MM1KK	81
Lq.o_MMC	82
Lq.o_MMCC	83
Lq.o_MMCK	84
Lq.o_MMCKK	85
Lq.o_MMCKM	86
Lq.o_MMInf	87
Lq.o_MMInfKK	88
Lqq	89
Lqq.o_MM1	90
Lqq.o_MM1K	91
Lqq.o_MM1KK	92
Lqq.o_MMC	93
Lqq.o_MMCC	94
Lqq.o_MMCK	95
Lqq.o_MMCKK	96
Lqq.o_MMCKM	97
Lqq.o_MMInf	98
Lqq.o_MMInfKK	99
NewInput.CJN	100
NewInput.MCCN	102
NewInput.MCMN	103
NewInput.MCON	105
NewInput.MM1	106
NewInput.MM1K	107
NewInput.MM1KK	108
NewInput.MMC	109
NewInput.MMCC	110
NewInput.MMCK	111
NewInput.MMCKK	112
NewInput.MMCKM	113

NewInput.MMInf	114
NewInput.MMInfKK	115
NewInput.OJN	116
Pn	118
Pn.o_MM1	119
Pn.o_MM1K	120
Pn.o_MM1KK	121
Pn.o_MMC	122
Pn.o_MMCC	123
Pn.o_MMCK	124
Pn.o_MMCKK	125
Pn.o_MMCKM	126
Pn.o_MMInf	127
Pn.o_MMInfKK	128
Pn.o_OJN	129
QueueingModel	130
QueueingModel.i_CJN	131
QueueingModel.i_MCCN	132
QueueingModel.i_MCMN	134
QueueingModel.i_MCON	135
QueueingModel.i_MM1	136
QueueingModel.i_MM1K	137
QueueingModel.i_MM1KK	138
QueueingModel.i_MMC	139
QueueingModel.i_MMCC	140
QueueingModel.i_MMCK	141
QueueingModel.i_MMCKK	142
QueueingModel.i_MMCKM	143
QueueingModel.i_MMInf	144
QueueingModel.i_MMInfKK	145
QueueingModel.i_OJN	146
RO	147
RO.o_MM1	148
RO.o_MM1K	149
RO.o_MM1KK	150
RO.o_MMC	151
RO.o_MMCC	152
RO.o_MMCK	153
RO.o_MMCKK	154
RO.o_MMCKM	155
RO.o_MMInf	156
RO.o_MMInfKK	157
ROck	158
ROck.o_MCCN	159
ROck.o_MCMN	160
ROck.o_MCON	161
ROk	162
ROk.o_CJN	164

ROk.o_MCCN	165
ROk.o_MCMN	166
ROk.o_MCON	167
ROk.o_OJN	168
SP	169
SP.o_MM1KK	170
summary.o_CJN	171
summary.o_MCCN	172
summary.o_MCMN	174
summary.o_MCON	175
summary.o_MM1	176
summary.o_MM1K	177
summary.o_MM1KK	178
summary.o_MMC	179
summary.o_MMCC	180
summary.o_MMCK	181
summary.o_MMCKK	182
summary.o_MMCKM	183
summary.o_MMInf	184
summary.o_MMInfKK	185
summary.o_OJN	186
Throughput	187
Throughput.o_CJN	188
Throughput.o_MCCN	189
Throughput.o_MCMN	190
Throughput.o_MCON	191
Throughput.o_MM1	192
Throughput.o_MM1K	193
Throughput.o_MM1KK	194
Throughput.o_MMC	195
Throughput.o_MMCC	196
Throughput.o_MMCK	197
Throughput.o_MMCKK	198
Throughput.o_MMCKM	199
Throughput.o_MMInf	200
Throughput.o_MMInfKK	201
Throughput.o_OJN	202
Throughputc	203
Throughputc.o_MCCN	204
Throughputc.o_MCMN	205
Throughputc.o_MCON	207
Throughputck	208
Throughputck.o_MCCN	209
Throughputck.o_MCMN	210
Throughputck.o_MCON	211
Throughputcn	213
Throughputcn.o_MCCN	214
Throughputk	215

Throughputk.o_CJN	216
Throughputk.o_MCCN	217
Throughputk.o_MCMN	219
Throughputk.o_MCON	220
Throughputk.o_OJN	221
Throughputn	222
Throughputn.o_CJN	223
VN	225
VN.o_MM1	226
VN.o_MM1K	227
VN.o_MM1KK	228
VN.o_MMC	229
VN.o_MMCC	230
VN.o_MMCK	231
VN.o_MMCKK	232
VN.o_MMCKM	233
VN.o_MMInf	234
VN.o_MMInfKK	235
VNq	236
VNq.o_MM1	237
VNq.o_MM1K	238
VNq.o_MM1KK	239
VNq.o_MMC	240
VNq.o_MMCC	241
VNq.o_MMCK	242
VNq.o_MMCKK	243
VNq.o_MMCKM	244
VNq.o_MMInf	245
VNq.o_MMInfKK	246
VT	247
VT.o_MM1	248
VT.o_MM1K	249
VT.o_MM1KK	250
VT.o_MMC	251
VT.o_MMCC	252
VT.o_MMInf	253
VT.o_MMInfKK	254
VTq	255
VTq.o_MM1	256
VTq.o_MM1K	257
VTq.o_MM1KK	258
VTq.o_MMC	259
VTq.o_MMCC	260
VTq.o_MMCK	261
VTq.o_MMCKK	262
VTq.o_MMInf	263
VTq.o_MMInfKK	264
W	265

W.o_CJN	266
W.o_MCCN	267
W.o_MCMN	268
W.o_MCON	269
W.o_MM1	270
W.o_MM1K	271
W.o_MM1KK	272
W.o_MMC	273
W.o_MMCC	274
W.o_MMCK	275
W.o_MMCKK	276
W.o_MMCKM	277
W.o_MMInf	278
W.o_MMInfKK	279
W.o_OJN	280
Wc	281
Wc.o_MCCN	282
Wc.o_MCMN	283
Wc.o_MCON	284
Wck	286
Wck.o_MCCN	287
Wck.o_MCMN	288
Wck.o_MCON	289
Wk	290
Wk.o_CJN	291
Wk.o_MCCN	293
Wk.o_MCMN	294
Wk.o_MCON	295
Wk.o_OJN	296
Wq	297
Wq.o_MM1	298
Wq.o_MM1K	299
Wq.o_MM1KK	300
Wq.o_MMC	301
Wq.o_MMCC	302
Wq.o_MMCK	303
Wq.o_MMCKK	304
Wq.o_MMCKM	305
Wq.o_MMInf	306
Wq.o_MMInfKK	307
Wqq	308
Wqq.o_MM1	309
Wqq.o_MM1K	310
Wqq.o_MM1KK	311
Wqq.o_MMC	312
Wqq.o_MMCC	313
Wqq.o_MMCK	314
Wqq.o_MMCKK	315

Wqq.o_MMCKM 316

Wqq.o_MMInf 317

Wqq.o_MMInfKK 318

WWs 319

WWs.o_MM1KK 320

Index 322

queueing-package	<i>Analysis of Queueing Networks and Models.</i>
------------------	--

Description

It provides a versatile tool for analysis of birth and death based Markovian Queueing Models and Single and Multiclass Product-Form Queueing Networks.

It implements the following basic markovian models:

M/M/1,	M/M/c,	M/M/Infinite,
M/M/1/K,	M/M/c/K,	M/M/c/c,
M/M/1/K/K,	M/M/c/K/K,	M/M/c/K/m, M/M/Infinite/K/K

It also solves the following types of networks:

- Multiple Channel Open Jackson Networks.
- Multiple Channel Closed Jackson Networks.
- Single Channel Multiple Class Open Networks.
- Single Channel Multiple Class Closed Networks
- Single Channel Multiple Class Mixed Networks

Also it provides B-Erlang, C-Erlang and Engset calculators.

This work is dedicated to the memory of D. Sixto Rios Insua.

Details

All models are used in the same way:

1. Create inputs calling the appropriate *NewInput.model*. For example, `x <- NewInput.MM1(lambda=0.25, mu=1, n=10)` for a M/M/1 model. To know the exact acronymn model to use for *NewInput* function, you can search the html help or write `help.search("NewInput")` at the command line.

2. Optionally, as a help for creating the inputs, the CheckInput(x) function can be called
3. Solve the model calling `y <- QueueingModel(x)`. In this step, the CheckInput(x) will be called. That is the reason that the previous step is optional
4. Finally, you can get a performance value as $W(y)$, $Wq(y)$ or a report of the principals performance values calling `summary(y)`

See the examples for more detailed information of the use.

Author(s)

Author, Maintainer and Copyright: Pedro Canadilla <pedro.canadilla@gmail.com>

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

Examples

```
## M/M/1 model
summary(QueueingModel(NewInput.MM1(lambda=1/4, mu=1/3, n=0)))

## M/M/1/K model
summary(QueueingModel(NewInput.MM1K(lambda=1/4, mu=1/3, k=3)))
```

B_erlang

Returns the probability that all servers are busy

Description

Returns the probability that all servers are busy

Usage

```
B_erlang(c=1, u=0)
```

Arguments

c	numbers of servers
u	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability that all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[C_erlang](#)

Examples

```
## two servers
B_erlang(2, 0.5/0.7)
```

CheckInput	<i>Generic S3 method to check the params of a queueing model (or network)</i>
------------	---

Description

Generic S3 method to check the params of a queueing model (or network)

Usage

```
CheckInput(x, ...)
```

Arguments

- x a object of class i_MM1, i_MMC, i_MM1K, i_MMCK, i_MM1KK, i_MMCKK, i_MMCC, i_MMCKM, i_MMInfKK, i_MMInf, i_OJN
- ... additional arguments

Details

Generic S3 method to check the params of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MM1](#)
[CheckInput.i_MMC](#)
[CheckInput.i_MM1K](#)
[CheckInput.i_MMCK](#)
[CheckInput.i_MM1KK](#)
[CheckInput.i_MMCKK](#)
[CheckInput.i_MMCC](#)
[CheckInput.i_MMCKM](#)
[CheckInput.i_MMInfKK](#)
[CheckInput.i_MMInf](#)
[CheckInput.i_OJN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Check the inputs
CheckInput(i_mm1)
```

CheckInput.i_CJN	<i>Check the input params of a Closed Jackson Network</i>
------------------	---

Description

Check the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_CJN
...	additional arguments

Details

Check the input params of a Closed Jackson Network. The inputs params are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

CheckInput(cjn1)
```

CheckInput.i_MCCN

Check the input params of a MultiClass Closed Network

Description

Check the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCCN
...	additional arguments

Details

Check the input params of a MultiClass Closed Network. The inputs params are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_MCCN1)
```

CheckInput.i_MCMN

Check the input params of a MultiClass Mixed Network

Description

Check the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCMN
...	additional arguments

Details

Check the input params of a MultiClass Mixed Network. The inputs params are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

CheckInput(i_mcmn1)
```

CheckInput.i_MCON

Check the input params of a MultiClass Open Network

Description

Check the input params of a MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MCON
...	additional arguments

Details

Check the input params of a MultiClass Open Network. The inputs params are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

CheckInput(i_mcon1)
```

CheckInput.i_MM1	<i>Checks the input params of a M/M/1 queueing model</i>
------------------	--

Description

Checks the input params of a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1
...	additional arguments

Details

Checks the input params of a M/M/1 queueing model. The inputs params are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Check the inputs
CheckInput(i_mm1)
```

CheckInput.i_MM1K	<i>Checks the input params of a M/M/1/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1K
...	aditional arguments

Details

Checks the input params of a M/M/1/K queueing model. The inputs params are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## check the parameters
CheckInput(i_mm1k)
```

CheckInput.i_MM1KK	<i>Checks the input params of a M/M/1/K/K queueing model</i>
--------------------	--

Description

Checks the input params of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MM1KK
...	additional arguments

Details

Checks the input params of a M/M/1/K/K queueing model. The inputs params are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## check the parameters
CheckInput(i_mm1kk)
```

CheckInput.i_MMC	<i>Checks the input params of a M/M/c queueing model</i>
------------------	--

Description

Checks the input params of a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMC
...	additional arguments

Details

Checks the input params of a M/M/c queueing model. The inputs params are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC.](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## check the parameters
CheckInput(i_mmc)
```

CheckInput.i_MMCC	<i>Checks the input params of a M/M/c/c queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCC
...	additional arguments

Details

Checks the input params of a M/M/c/c queueing model. The inputs params are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## check the parameters
CheckInput(i_mmcc)
```

CheckInput.i_MMCK	<i>Checks the input params of a M/M/c/K queueing model</i>
-------------------	--

Description

Checks the input params of a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCK
...	additional arguments

Details

Checks the input params of a M/M/c/K queueing model. The inputs params are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Check the inputs
CheckInput(i_mmck)
```

CheckInput.i_MMCKK	<i>Checks the input params of a M/M/c/K/K queueing model</i>
--------------------	--

Description

Checks the input params of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCKK
...	additional arguments

Details

Checks the input params of a M/M/c/K/K queueing model. The inputs params are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## check the parameters
CheckInput(i_mmckk)
```

CheckInput.i_MMCKM	<i>Checks the input params of a M/M/c/K/m queueing model</i>
--------------------	--

Description

Checks the input params of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Checks the input params of a M/M/c/K/m queueing model. The inputs params are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## check the parameters  
CheckInput(i_mmckm)
```

CheckInput.i_MMInf	<i>Checks the input params of a M/M/Infinite queueing model</i>
--------------------	---

Description

Checks the input params of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'i_MMInf'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Checks the input params of a M/M/Infinite queueing model. The inputs params are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Check the parameters  
CheckInput(i_mminf)
```

CheckInput.i_MMInfKK *Checks the input params of a M/M/Infinite/K/K queueing model*

Description

Checks the input params of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'  
CheckInput(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	additional arguments

Details

Checks the input params of a M/M/Infinite/K/K queueing model. The inputs params are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## check the parameters  
CheckInput(i_MMInfKK)
```

CheckInput.i_OJN

Check the input params of an Open Jackson Network

Description

Check the input params of an Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'
CheckInput(x, ...)
```

Arguments

x	a object of class i_OJN
...	additional arguments

Details

Check the input params of an Open Jackson Network. The inputs params are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

CheckInput(ojn1)
```

CompareQueueingModels *Compare several queueing models in a tabulated format*

Description

Compare several queueing models in a tabulated format

Usage

```
CompareQueueingModels(model, ...)
CompareQueueingModels2(models)
```

Arguments

model	A Queueing Model obtained calling QueueingModel from classes described in the details section
...	a separated by comma list of queueing models obtained calling QueueingModel from classes described in the details section
models	A list of queueing models obtained calling QueueingModel from classes described in the details section

Details

Compare several queueing models in a tabulated format. By now, only o_MM1, o_MMC, o_MMInf, o_MM1K, o_MMCK, o_MMCC, o_MM1KK, o_MMCKK, o_MMCKM, o_MMInfKK classes can be compared

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel](#)

Examples

```
q1 <- QueueingModel(NewInput.MM1(lambda=5, mu=7))
q2 <- QueueingModel(NewInput.MMC(lambda=5, mu=3, c=4))
q3 <- QueueingModel(NewInput.MMInf(lambda=3, mu=4))
q4 <- QueueingModel(NewInput.MMCC(lambda=5, mu=3, c=4))

CompareQueueingModels(q1, q2, q3)
CompareQueueingModels2(list(q1, q2, q3, q4))
```

C_erlang	Returns the probability to wait in queue because all servers are busy
----------	---

Description

Returns the probability to wait in queue because all servers are busy

Usage

```
C_erlang(c=1, r=0)
```

Arguments

c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability to wait in queue because all servers are busy

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[B_erlang](#)

Examples

```
## two servers  
C_erlang(2, 0.5/0.7)
```

Engset	<i>Returns the probability that all servers are busy</i>
--------	--

Description

Returns the probability that all servers are busy

Usage

```
Engset(k=1, c=0, r=0)
```

Arguments

k	numbers of users
c	numbers of servers
r	lambda/mu, that is, ratio of rate of arrivals and rate of service

Details

Returns the probability of blocking in a finite source model

See Also

[B_erlang](#)

Examples

```
## three users, two servers
Engset(3, 2, 0.5/0.7)
```

Inputs	<i>Returns the input parameters of a queueing model (or network)</i>
--------	--

Description

Returns the inputs parameters of a already built queueing model (or network)

Usage

```
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the input parameters of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Inputs.o_MM1](#)
[Inputs.o_MMC](#)
[Inputs.o_MM1K](#)
[Inputs.o_MMCK](#)
[Inputs.o_MM1KK](#)
[Inputs.o_MMCKK](#)
[Inputs.o_MMCC](#)
[Inputs.o_MMCKM](#)
[Inputs.o_MMInfKK](#)
[Inputs.o_MMInf](#)
[Inputs.o_OJN](#)
[Inputs.o_CJN](#)
[Inputs.o_MCON](#)
[Inputs.o_MCCN](#)
[Inputs.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Inputs
Inputs(o_mm1)
```

Inputs.o_CJN

Returns the input params of a Closed Jackson Network

Description

Returns the input params of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Inputs(x, ...)
```

Arguments

```
x                a object of class o_CJN
...              additional arguments
```

Details

Returns the input params of a Closed Jackson Network. The inputs parameters are created calling previously the [NewInput.CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos determinísticos y estocásticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Inputs(m_cjn1)
```

Inputs.o_MCCN	<i>Returns the input params of a MultiClass Closed Network</i>
---------------	--

Description

Returns the input params of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the input params of a MultiClass Closed Network. The inputs parameters are created calling previously the [NewInput.MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)
```

```
Inputs(o_MCMN1)
```

Inputs.o_MCMN	<i>Returns the input params of a MultiClass Mixed Network</i>
---------------	---

Description

Returns the input params of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Inputs(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the input params of a MultiClass Mixed Network. The inputs parameters are created calling previously the [NewInput.MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```



```

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Inputs(o_mcmn1)

```

Inputs.o_MCON	<i>Returns the input params of a MultiClass Open Network</i>
---------------	--

Description

Returns the input params of a MultiClass Open Network

Usage

```

## S3 method for class 'o_MCON'
Inputs(x, ...)

```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns the input params of a MultiClass Open Network. The inputs parameters are created calling previously the [NewInput.MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Inputs(o_mcon1)
```

Inputs.o_MM1

Returns the input parameters of a M/M/1 queueing model

Description

Returns the inputs parameters of a already built M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the input parameters of a M/M/1 queueing model. The inputs parameters are created calling previously the [NewInput.MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Inputs
Inputs(o_mm1)
```

Inputs.o_MM1K	<i>Returns the input parameters of a M/M/1/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the input parameters of a M/M/1/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Inputs
Inputs(o_mm1k)
```

Inputs.o_MM1KK	<i>Returns the input parameters of a M/M/1/K/K queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the input parameters of a M/M/1/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Inputs
Inputs(o_mm1kk)
```

Inputs.o_MMC	<i>Returns the input parameters of a M/M/c queueing model</i>
--------------	---

Description

Returns the inputs parameters of a already built M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the input parameters of a M/M/c queueing model. The inputs parameters are created calling previously the [NewInput.MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC.](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Inputs
Inputs(o_mmc)
```

Inputs.o_MMCC	<i>Returns the input parameters of a M/M/c/c queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the input parameters of a M/M/c/c queueing model. The inputs parameters are created calling previously the [NewInput.MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Inputs
Inputs(o_mmcc)
```

Inputs.o_MMCK	<i>Returns the input parameters of a M/M/c/K queueing model</i>
---------------	---

Description

Returns the inputs parameters of a already built M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the input parameters of a M/M/c/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Inputs
Inputs(o_mmck)
```

Inputs.o_MMCKK	<i>Returns the input parameters of a M/M/c/K/K queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the input parameters of a M/M/c/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Inputs
Inputs(o_mmckk)
```

Inputs.o_MMCKM	<i>Returns the input parameters of a M/M/c/K/m queueing model</i>
----------------	---

Description

Returns the inputs parameters of a already built M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the input parameters of a M/M/c/K/m queueing model. The inputs parameters are created calling previously the [NewInput.MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Inputs
Inputs(o_mmckm)
```

Inputs.o_MMInf	<i>Returns the input parameters of a M/M/Infinite queueing model</i>
----------------	--

Description

Returns the inputs parameters of a already built M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the input parameters of a M/M/Infinite queueing model. The inputs parameters are created calling previously the [NewInput.MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Inputs
Inputs(o_mminf)
```

Inputs.o_MMInfKK	<i>Returns the input parameters of a M/M/Infinite/K/K queueing model</i>
------------------	--

Description

Returns the inputs parameters of a already built M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Inputs(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the input parameters of a M/M/Infinite/K/K queueing model. The inputs parameters are created calling previously the [NewInput.MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[NewInput.MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Inputs
Inputs(o_MMInfKK)
```

Inputs.o_OJN	<i>Returns the input params of an Open Jackson Network</i>
--------------	--

Description

Returns the input params of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Inputs(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Returns the input params of an Open Jackson Network. The inputs parameters are created calling previously the [NewInput.OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn1 <- QueueingModel(i_ojn1)

Inputs(o_ojn1)
```

L	<i>Returns the mean number of customers in a queueing model (or network)</i>
---	--

Description

Returns the mean number of customers in a queueing model (or network)

Usage

`L(x, ...)`

Arguments

x	a object of class <code>o_MM1</code> , <code>o_MMC</code> , <code>o_MM1K</code> , <code>o_MMCK</code> , <code>o_MM1KK</code> , <code>o_MMCKK</code> , <code>o_MMCC</code> , <code>o_MMCKM</code> , <code>o_MMInfKK</code> , <code>o_MMInf</code> , <code>o_OJN</code> , <code>o_MCON</code> , <code>o_MCCN</code> , <code>o_MCMN</code>
...	additional arguments

Details

Returns the mean number of customers in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[L.o_MM1](#)
[L.o_MMC](#)
[L.o_MM1K](#)
[L.o_MMCK](#)
[L.o_MM1KK](#)
[L.o_MMCKK](#)
[L.o_MMCC](#)
[L.o_MMCKM](#)
[L.o_MMInfKK](#)
[L.o_MMInf](#)
[L.o_OJN](#)
[L.o_CJN](#)
[L.o_MCON](#)
[L.o_MCCN](#)
[L.o_MCMN](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the L
L(o_mm1)

```

L.o_CJN

Returns the mean number of customers of a Closed Jackson Network

Description

Returns the mean number of customers of a Closed Jackson Network

Usage

```

## S3 method for class 'o_CJN'
L(x, ...)

```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Returns the mean number of customers of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

L(m_cjn1)
```

L.o_MCCN

Returns the mean number of customers of a MultiClass Closed Network

Description

Returns the mean number of customers of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
L(x, ...)
```

Arguments

x a object of class o_MCCN
 ... additional arguments

Details

Returns the mean number of customers of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

L(o_MCCN1)
```

L.o_MCMN

Returns the mean number of customers of a MultiClass Mixed Network

Description

Returns the mean number of customers of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'  
L(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the mean number of customers of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.  
  
classes <- 4  
vLambda <- c(1, 1/2)  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=1, nrow=4, ncol=2)  
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)  
  
i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcmn1 <- QueueingModel(i_mcmn1)  
  
L(o_mcmn1)
```

L.o_MCON

Returns the mean number of customers of a MultiClass Open Network

Description

Returns the mean number of customers of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
L(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns the mean number of customers of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

L(o_mcon1)
```

L.o_MM1	Returns the mean number of customers in the M/M/1 queueing model
---------	--

Description

Returns the mean number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'  
L(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the mean number of customers in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)  
  
## Build the model  
o_mm1 <- QueueingModel(i_mm1)  
  
## Returns the L  
L(o_mm1)
```

L.o_MM1K	<i>Returns the mean number of customers in the M/M/1/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
L(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the mean number of customers in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the L
L(o_mm1k)
```

L.o_MM1KK	<i>Returns the mean number of customers in the M/M/1/K/K queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
L(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean number of customers in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the L
L(o_mm1kk)
```

L.o_MMC

Returns the mean number of customers in the M/M/c queueing model

Description

Returns the mean number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
L(x, ...)
```

Arguments

```
x          a object of class o_MMC
...        additional arguments
```

Details

Returns the mean number of customers in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the L
L(o_mmc)
```

L.o_MMCC	<i>Returns the mean number of customers in the M/M/c/c queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
L(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the L
L(o_mmcc)
```

L.o_MMCK	<i>Returns the mean number of customers in the M/M/c/K queueing model</i>
----------	---

Description

Returns the mean number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
L(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the L
L(o_mmck)
```

L.o_MMCKK	Returns the mean number of customers in the M/M/c/K/K queueing model
-----------	--

Description

Returns the mean number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the L  
L(o_mmckk)
```

L.o_MMCKM	<i>Returns the mean number of customers in the M/M/c/K/m queueing model</i>
-----------	---

Description

Returns the mean number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
L(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the L  
L(o_mmckm)
```

L.o_MMInf	Returns the mean number of customers in the M/M/Infinite queueing model
-----------	---

Description

Returns the mean number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
L(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the L  
L(o_mminf)
```

L.o_MMInfKK	<i>Returns the mean number of customers in the M/M/Infinite/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
L(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the L  
L(o_MMInfKK)
```

L.o_OJN	Returns the mean number of customers of an Open Jackson Network
---------	---

Description

Returns the mean number of customers of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
L(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Returns the mean number of customers of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)
```

L(o_ojn)

Lc	Returns the vector with the mean number of customers of each class in a multiclass queueing network
----	---

Description

Returns the vector with the mean number of customers of each class in a multiclass queueing network

Usage

Lc(x, ...)

Arguments

- x a object of class o_MCON, o_MCCN, o_MCMN
- ... additional arguments

Details

Returns the vector with the mean number of customers of each class in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

- [Lc.o_MCON](#)
- [Lc.o_MCCN](#)
- [Lc.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lc.o_MCCN

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lc(o_MCCN1)
```

Lc.o_MCMN

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Description

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lc(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lc(o_mcmn1)
```

Lc.o_MCON

*Returns the vector with the mean number of customers of each class
in a MultiClass Open Network*

Description

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lc(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns the vector with the mean number of customers of each class in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lc(o_mcon1)
```

Lck	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network</i>
-----	--

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

Usage

```
Lck(x, ...)
```

Arguments

x a object of class o_MCON, o_MCCN, o_MCMN
... additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Lck.o_MCON](#)
[Lck.o_MCCN](#)
[Lck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Lck(o_mcon1)
```

Lck.o_MCCN

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lck(x, ...)
```

Arguments

x a object of class o_MCCN
 \dots additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lck(o_MCCN1)
```

Lck.o_MCMN	<i>Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network</i>
------------	--

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lck(o_mcmn1)
```

Lck.o_MCON

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Description

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lck(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MCON</code>
<code>...</code>	additional arguments

Details

Reports a matrix with the mean number of customers of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lck(o_mcon1)
```

Lk	<i>Returns the vector with the mean number of customers in each node (server) of a queueing network</i>
----	---

Description

Returns the vector with the mean number of customers in each node (server) of a queueing network

Usage

```
Lk(x, ...)
```

Arguments

x	a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

- [Lk.o_OJN](#)
- [Lk.o_CJN](#)
- [Lk.o_MCON](#)
- [Lk.o_MCCN](#)
- [Lk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_CJN	Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network
----------	--

Description

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Lk(x, ...)
```

Arguments

```
x          a object of class o_CJN
...        additional arguments
```

Details

Returns the vector with the mean number of customers in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Lk(m_cjn1)
```

Lk.o_MCCN	<i>Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network</i>
-----------	--

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Lk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Lk(o_MCCN1)
```

Lk.o_MCMN	<i>Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network</i>
-----------	---

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Lk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Lk(o_mcmn1)
```

Lk.o_MCON

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

Description

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Lk(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns a vector with the mean number of customers in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Lk(o_mcon1)
```

Lk.o_OJN

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Lk(x, ...)
```

Arguments

x a object of class o_OJN
... additional arguments

Details

Returns the vector with the mean number of customers in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the model
o_ojn <- QueueingModel(i_ojn)

Lk(o_ojn)
```

Lq	Returns the mean number of customers in the queue in a queueing model
----	---

Description

Returns the mean number of customers in the queue in a queueing model

Usage

```
Lq(x, ...)
```

Arguments

- x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
- ... additional arguments

Details

Returns the mean number of customers in the queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

- Lq.o_MM1
- Lq.o_MMC
- Lq.o_MM1K
- Lq.o_MMCK
- Lq.o_MM1KK
- Lq.o_MMCKK
- Lq.o_MMCC
- Lq.o_MMCKM
- Lq.o_MMInfKK
- Lq.o_MMInf

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1	Returns the mean number of customers in the queue in the M/M/1 queueing model
----------	---

Description

Returns the mean number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lq(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lq
Lq(o_mm1)
```

Lq.o_MM1K

Returns the mean number of customers in the queue in the M/M/1/K queueing model

Description

Returns the mean number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lq(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lq(o_mm1k)
```

Lq.o_MM1KK	<i>Returns the mean number of customers in the queue in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lq
Lq(o_mm1kk)
```

Lq.o_MMC	<i>Returns the mean number of customers in the queue in the M/M/c queueing model</i>
----------	--

Description

Returns the mean number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lq
Lq(o_mmc)
```

Lq.o_MMCC	<i>Returns the mean number of customers in the queue in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lq
Lq(o_mmcc)
```

Lq.o_MMCK	<i>Returns the mean number of customers in the queue in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the mean number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lq(x, ...)
```

Arguments

- x a object of class o_MMCK
- ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lq
Lq(o_mmck)
```

Lq.o_MMCKK	Returns the mean number of customers in the queue in the M/M/c/K/K queueing model
------------	---

Description

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lq(x, ...)
```

Arguments

- x a object of class o_MMCKK
- ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lq
Lq(o_mmckk)
```

Lq.o_MMCKM	Returns the mean number of customers in the queue in the M/M/c/K/m queueing model
------------	---

Description

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lq(x, ...)
```

Arguments

- x a object of class o_MMCKM
- ... additional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM.](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lq
Lq(o_mmckm)
```

Lq.o_MMInf	<i>Returns the mean number of customers in the queue in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lq
Lq(o_mminf)
```

Lq.o_MMInfKK	<i>Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK.](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lq
Lq(o_MMInfKK)
```

Lqq	<i>Returns the mean number of customers in queue when there is queue in a queueing model</i>
-----	--

Description

Returns the mean number of customers in queue when there is queue in a queueing model

Usage

```
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Lqq.o_MM1](#)
[Lqq.o_MMC](#)
[Lqq.o_MM1K](#)
[Lqq.o_MMCK](#)
[Lqq.o_MM1KK](#)
[Lqq.o_MMCKK](#)
[Lqq.o_MMCC](#)

```
Lqq.o_MMCKM
Lqq.o_MMInfKK
Lqq.o_MMInf
```

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1	<i>Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Lqq
Lqq(o_mm1)
```

Lqq.o_MM1K	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Lq
Lqq(o_mm1k)
```

Lqq.o_MM1KK	<i>Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Lqq
Lqq(o_mm1kk)
```

Lqq.o_MMC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Lqq
Lqq(o_mmc)
```

Lqq.o_MMCC	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Lqq
Lqq(o_mmcc)
```

Lqq.o_MMCK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Lqq
Lqq(o_mmck)
```

Lqq.o_MMCKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Lqq
Lqq(o_mmckk)
```

Lqq.o_MMCKM	<i>Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	--

Description

Returns the mean number of customers in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	aditional arguments

Details

Returns the mean number of customers in the queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Lqq
Lqq(o_mmckm)
```

Lqq.o_MMInf	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Lqq
Lqq(o_mminf)
```

Lqq.o_MMInfKK	<i>Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Lqq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean number of customers in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Lqq
Lqq(o_MMInfKK)
```

NewInput.CJN

Define the inputs of a Closed Jackson Network

Description

Define the inputs of a Closed Jackson Network

Usage

```
NewInput.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, ...)
NewInput2.CJN(prob=NULL, n=0, z=0, operational=FALSE, method=0, tol=0.001, nodes)
NewInput3.CJN(n, z, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio (a probability, that is, a value between 0 and 1) to node i. Also, the visit ratio can express the number of times that a client visits the queueing center, in a more operational point of view. See the parameter operational
n	number of customers in the Network
z	think time of the client
operational	If prob is a vector with the visit ratios, operational equal to FALSE gives to the visit ratio a probability meaning, that is, as the stationary values of the imbedded markov chain. If operational is equal to TRUE, the operational point of view is used: it is the number of visits that the same client makes to a node.
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used.
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm.
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
numNodes	The number of nodes of the network
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios. It represent visit counts to a center as if the parameter operational were TRUE

vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of a Closed Jackson Network. For a operational use, NewInput3.CJN is recommended. For a more academic use, NewInput.CJN or NewInput2.CJN is recommended. Please, note that the different ways to create the inputs for a Closed Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

## think time = 0
z <- 0

## operational value
operational <- FALSE

## definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

## Not run:
cjn1 <- NewInput2.CJN(prob, n, z, operational, 0, 0.001, list(n1, n2))

## End(Not run)
```

```

## using visit ratios and service demands. See [Lazowska84] pag 117.
## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(mu=1/0.005)

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(mu=1/0.027)

## The visit ratios.
vVisit <- c(121, 70, 50)

operational <- TRUE

net <- NewInput.CJN(prob=vVisit, n=3, z=15, operational, 0, 0.001, cpu, disk1, disk2)

## Using the operational creation function
n <- 3
think <- 15
numNodes <- 3
vType <- c("Q", "Q", "Q")
vService <- c(0.005, 0.030, 0.027)
vChannel <- c(1, 1, 1)

net2 <- NewInput3.CJN(n, think, numNodes, vType, vVisit, vService, vChannel, method=0, tol=0.001)

```

NewInput.MCCN

Define the inputs of a MultiClass Closed Network

Description

Define the inputs of a MultiClass Closed Network

Usage

```

NewInput.MCCN(
  classes, vNumber, vThink, nodes, vType, vVisit, vService, method=1, tol=0.01
)

```

Arguments

classes	The number of classes
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network

vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service time for each class i in each node j
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

NewInput.MCMN

Define the inputs of a MultiClass Mixed Network

Description

Define the inputs of a MultiClass Mixed Network

Usage

```
NewInput.MCMN(
  classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService, method=0, tol=0.01
)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
vNumber	A vector with the number of customers of each class
vThink	A vector with the think time of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j. Take caution about the orden: open classes are defined first and closed clases are defined second
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j. Take caution about the orden: open classes are defined first and closed clases are defined second.
method	If method is 0, the exact MVA algorithm is used. If method is 1, the Bard-Schweitzer approximation algorithm is used
tol	If the parameter method is 1, this is the tolerance parameter of the algorithm

Details

Define the inputs of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4 # A and B are open classes and C and D are closed classes.
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
```



```

vType <- c("Q", "Q")

# When the visit ratios and vService are set,
#   be sure that the open classes are in the first positions
#   and the closed classes after the open classes.
vVisit <- matrix(data=1, nrow=4, ncol=2)

# A and B are open classes:
#   with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
# C and D are open classes:
#   with demand service of 1/4 and 1/2 at the node 1 and 1/2 and 1 at the node 2
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

```

NewInput.MCON

Define the inputs of a MultiClass Open Network

Description

Define the inputs of a MultiClass Open Network

Usage

```
NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

Arguments

classes	The number of classes
vLambda	It is a vector with the rate of arrivals of each class
nodes	The number of nodes in the network
vType	A vector with the type of node: "Q" for queueing nodes or "D" for delay nodes
vVisit	A matrix[i, j]. The rows represents the different visit count for each class i to each node j
vService	A matrix[i, j]. The rows represents the different service times for each class i in each node j

Details

Define the inputs of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

NewInput.MM1	<i>Define the inputs of a new M/M/1 queueing model</i>
--------------	--

Description

Define the inputs of a new M/M/1 queueing model

Usage

```
NewInput.MM1(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system. Put n=0 for a idle probability. With n=-1, no probabilities are computed

Details

Define the inputs of a new M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also[CheckInput.i_MM1](#)**Examples**

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)
```

NewInput.MM1K	<i>Define the inputs of a new M/M/1/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/1/K queueing model

Usage

```
NewInput.MM1K(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also[CheckInput.i_MM1K](#)**Examples**

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)
```

NewInput.MM1KK	Define the inputs of a new M/M/1/K/K queueing model
----------------	---

Description

Define the inputs of a new M/M/1/K/K queueing model

Usage

NewInput.MM1KK(lambda=0, mu=0, k=1, method=3)

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, aproximate results are calculated using Stirling aproximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used. With method=3, the result that K-n customers up has a truncated poisson distribution is used [Kobayashi2012] pag. 709

Details

Define the inputs of a new M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).
A course on Queueing Models.
Chapman-Hall.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).
Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)
```

NewInput.MMC	<i>Define the inputs of a new M/M/c queueing model</i>
--------------	--

Description

Define the inputs of a new M/M/c queueing model

Usage

```
NewInput.MMC(lambda=0, mu=0, c=1, n=0, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
n	number of customers in the system. Put n=0 for a idle probability. With n=-1, no probabilities are computed
method	method of computation of the probabilities of n number of customers in the system. With method=0, the exact results are calculated using the formal definition. With method=1, aproximate results are calculated using Stirling aproximation of factorials and logaritms.

Details

Define the inputs of a new M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)
```

NewInput.MMCC	<i>Define the inputs of a new M/M/c/c queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/c/c queueing model

Usage

```
NewInput.MMCC(lambda=0, mu=0, c=1, method=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
method	with method = 0, the state probabilities are calculated using the formal definition (with overflow problems with factorials; with method = 1 (default), the truncated poisson distribution is used (recommended for professional use)

Details

Define the inputs of a new M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Kobayashi2012] Hisashi Kobayashi, Brian L. Mark, William Turin (2012).
Probability, Random Processes, and Statistical Analysis: Applications to Communications, Signal Processing, Queueing Theory and Mathematical Finance.
Cambridge University Press.

See Also

[CheckInput.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)
```

NewInput.MMCK	<i>Define the inputs of a new M/M/c/K queueing model</i>
---------------	--

Description

Define the inputs of a new M/M/c/K queueing model

Usage

```
NewInput.MMCK(lambda=0, mu=0, c=1, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity

Details

Define the inputs of a new M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)
```

NewInput.MMCKK

Define the inputs of a new M/M/c/K/K queueing model

Description

Define the inputs of a new M/M/c/K/K queueing model

Usage

```
NewInput.MMCKK(lambda=0, mu=0, c=1, k=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, approximate results are calculated using Stirling approximation of factorials and logarithms. With method=2, Jain's Method [Jain2007], pag. 26 is used

Details

Define the inputs of a new M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Jain2007] Joti Lal Jain, Sri Gopal Mohanty, Walter Bohm (2007).
A course on Queueing Models.
 Chapman-Hall.

See Also

[CheckInput.i_MMCKK](#)

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)
```

NewInput.MMCKM	<i>Define the inputs of a new M/M/c/K/m queueing model</i>
----------------	--

Description

Define the inputs of a new M/M/c/K/m queueing model

Usage

```
NewInput.MMCKM(lambda=0, mu=0, c=1, k=1, m=1, method=0)
```

Arguments

lambda	arrival rate
mu	server service rate
c	number of servers
k	system capacity
m	poblation size. Please, observe that should be $m \geq k$
method	method of computation of the probabilities of k (system capacity) customers down. With method=0, the exact results are calculated using the formal definition. With method=1, aproximate results are calculated using Stirling aproximation of factorials and logaritms.

Details

Define the inputs of a new M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)
```

NewInput.MMInf	<i>Define the inputs of a new M/M/Infinite queueing model</i>
----------------	---

Description

Define the inputs of a new M/M/Infinite queueing model

Usage

```
NewInput.MMInf(lambda=0, mu=0, n=0)
```

Arguments

lambda	arrival rate
mu	server service rate
n	number of customers in the system. Put n=0 for a standard model

Details

Define the inputs of a new M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)
```

NewInput.MMInfKK	<i>Define the inputs of a new M/M/Infinite/K/K queueing model</i>
------------------	---

Description

Define the inputs of a new M/M/Infinite/K/K queueing model

Usage

```
NewInput.MMInfKK(lambda=0, mu=0, k=1)
```

Arguments

lambda	arrival rate
mu	server service rate
k	system capacity

Details

Define the inputs of a new M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)
```

NewInput.OJN

*Define the inputs of an Open Jackson Network***Description**

Define the inputs of an Open Jackson Network

Usage

```
NewInput.OJN(prob=NULL, ...)
NewInput2.OJN(prob=NULL, nodes)
NewInput3.OJN(vLambda, numNodes, vType, vVisit, vService, vChannel)
```

Arguments

prob	It is probability transition matrix or visit ratio vector. That is, the prob[i, j] is the transition probability of node i to node j, or prob[i] is the visit ratio to node i (the visit ratio values doesn't need to be probabilities, that is, a value greater than 1 can be used here. See the examples)
...	a separated by comma list of nodes of i_MM1, i_MMC or i_MMInf class
nodes	A list of nodes of i_MM1, i_MMC or i_MMInf class
vLambda	Vector with the arrivals rates to each node
numNodes	Number of nodes
vType	A vector with the type of server: "Q" for a queueing node, "D" for a delay node
vVisit	A vector with the visit ratios
vService	A vector with the services time of each node
vChannel	A vector with the number of channels of the node. The type of the server has to be "Q" to be inspected

Details

Define the inputs of an Open Jackson Network. For a operational use, NewInput3.OJN is recommended. For a more academic use, NewInput.OJN or NewInput2.OJN is recommended. Please, note that the different ways to create the inputs for a Open Jackson Network are equivalent to each other, and no validation is done at this stage. The validation is done calling CheckInput function.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

## Using function NewInput2
## Not run:
  ojn1 <- NewInput2.OJN(prob, list(n1, n2, n3, n4))

## End(Not run)

## Using visit ratios. Values taken from [Lazowska84], pag. 113.

## E[S] cpu = 0.005, Visit cpu = 121, D cpu = E[S] cpu * Visit cpu = 0.605
cpu <- NewInput.MM1(lambda=0.2, mu=1/0.005)

## E[S] disk1 = 0.030, Visit disk1 = 70, D disk1 = E[S] disk1 * Visit disk1 = 2.1
disk1 <- NewInput.MM1(lambda=0.2, mu=1/0.030)

## E[S] disk2 = 0.027, Visit disk2 = 50, D disk2 = E[S] disk2 * Visit disk2 = 1.35
disk2 <- NewInput.MM1(lambda=0.2, mu=1/0.027)

## In this example, to have the throughput per node, the visit ratios has to be given in this form.
## Please, don't use in the closed Jackson Network
visit <- c(121, 70, 50)
net <- NewInput.OJN(visit, cpu, disk1, disk2)

## Using NewInput3
vLambda <- c(0.2, 0.2, 0.2)
vService <- c(0.005, 0.030, 0.027)
numNodes <- 3
vType <- c("Q", "Q", "Q")
vChannel <- c(1, 1, 1)
net2 <- NewInput3.OJN(vLambda, numNodes, vType, visit, vService, vChannel)
```

Pn	Returns the probabilities of a queueing model (or network)
----	--

Description

Pn returns the probabilities that a queueing model (or network) has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers in it

Usage

Pn(x, ...)
Qn(x, ...)

Arguments

x	For Pn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN. For Qn, an object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	aditional arguments

Details

Pn returns the system probabilities of a queueing model (or network). Qn returns the probability that an effective arrival see n customers in the system

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

- Pn.o_MM1
- Qn.o_MM1
- Pn.o_MMC
- Qn.o_MMC
- Pn.o_MM1K
- Qn.o_MM1K
- Pn.o_MMCK
- Qn.o_MMCK
- Pn.o_MM1KK
- Qn.o_MM1KK
- Pn.o_MMCKK
- Qn.o_MMCKK

```

Pn.o_MMCC
Qn.o_MMCC
Pn.o_MMCKM
Qn.o_MMCKM
Pn.o_MMInfKK
Qn.o_MMInfKK
Pn.o_MMInf
Qn.o_MMInf
Pn.o_OJN

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the probabilities
Pn(o_mm1)

```

Pn.o_MM1

Returns the probabilities of a M/M/1 queueing model

Description

Pn returns the probabilities that a M/M/1 queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```

## S3 method for class 'o_MM1'
Pn(x, ...)
## S3 method for class 'o_MM1'
Qn(x, ...)

```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the probabilities
Pn(o_mm1)
Qn(o_mm1)
```

Pn.o_MM1K

Returns the probabilities of a M/M/1/K queueing model

Description

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1K'
Pn(x, ...)
## S3 method for class 'o_MM1K'
Qn(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Pn returns the probabilities that a M/M/1/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the probabilities
Pn(o_mm1k)
Qn(o_mm1k)
```

Pn.o_MM1KK

Returns the probabilities of a M/M/1/K/K queueing model

Description

Pn returns the probabilities of a M/M/1/K/K queueing model Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MM1KK'
Pn(x, ...)
## S3 method for class 'o_MM1KK'
Qn(x, ...)
```

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/1/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the probabilities
Pn(o_mm1kk)
Qn(o_mm1kk)
```

Pn.o_MMC

Returns the probabilities of a M/M/c queueing model

Description

Pn returns the probabilities that a M/M/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMC'
Pn(x, ...)
## S3 method for class 'o_MMC'
Qn(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Pn returns the probabilities that a M/M/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC.](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the probabilities
Pn(o_mmc)
Qn(o_mmc)
```

Pn.o_MMCC

Returns the probabilities of a M/M/c/c queueing model

Description

Pn returns the probabilities that a M/M/c/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCC'
Pn(x, ...)
## S3 method for class 'o_MMCC'
Qn(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Pn returns the probabilities that a M/M/c/c queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the probabilities
Pn(o_mmcc)
Qn(o_mmcc)
```

Pn.o_MMCK

Returns the probabilities of a M/M/c/K queueing model

Description

Pn returns the probabilities that a M/M/c/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCK'
Pn(x, ...)
## S3 method for class 'o_MMCK'
Qn(x, ...)
```

Arguments

x a object of class o_MMCK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/c/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the probabilities
Pn(o_mmck)
Qn(o_mmck)
```

Pn.o_MMCKK

Returns the probabilities of a M/M/c/K/K queueing model

Description

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKK'
Pn(x, ...)
## S3 method for class 'o_MMCKK'
Qn(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Pn returns the probabilities that a M/M/c/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the parameters
Pn(o_mmckk)
Qn(o_mmckk)
```

Pn.o_MMCKM	<i>Returns the probabilities of a M/M/c/K/m queueing model</i>
------------	--

Description

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMCKM'
Pn(x, ...)
## S3 method for class 'o_MMCKM'
Qn(x, ...)
```

Arguments

x a object of class o_MMCKM
... additional arguments

Details

Pn returns the probabilities that a M/M/c/K/m queueing model has n customers.
Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the probabilities
Pn(o_mmckm)
Qn(o_mmckm)
```

Pn.o_MMInf

Returns the probabilities of a M/M/Infinite queueing model

Description

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInf'
Pn(x, ...)
## S3 method for class 'o_MMInf'
Qn(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Pn returns the probabilities that a M/M/Infinite queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers. By the PASTA property, both probabilities has to be the same.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the probabilities
Pn(o_mminf)
Qn(o_mminf)
```

Pn.o_MMInfKK

Returns the probabilities of a M/M/Infinite/K/K queueing model

Description

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers in it.

Usage

```
## S3 method for class 'o_MMInfKK'
Pn(x, ...)
## S3 method for class 'o_MMInfKK'
Qn(x, ...)
```

Arguments

x a object of class o_MMInfKK
 ... additional arguments

Details

Pn returns the probabilities that a M/M/Infinite/K/K queueing model has n customers.
 Qn returns the probabilities that an arrival that enter the system see n customers.

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the probabilities
Pn(o_MMInfKK)
Qn(o_MMInfKK)
```

Pn.o_OJN	<i>Returns vector of the probabilities of each node (server) of an Open Jackson Network</i>
----------	---

Description

Returns vector of the probabilities of each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Pn(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Returns vector of the probabilities of each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Pn(o_ojn)
```

QueueingModel

Generic S3 method to build a queueing model (or network)

Description

Generic S3 method to build a queueing model (or network)

Usage

```
QueueingModel(x, ...)
```

Arguments

x	a object of class <code>i_MM1</code> , <code>i_MMC</code> , <code>i_MM1K</code> , <code>i_MMCK</code> , <code>i_MM1KK</code> , <code>i_MMCKK</code> , <code>i_MMCC</code> , <code>i_MMCKM</code> , <code>i_MMInfKK</code> , <code>i_MMInf</code> , <code>o_OJN</code> , <code>o_MCON</code>
...	additional arguments

Details

Generic S3 method to build a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#)
[QueueingModel.i_MMC](#)
[QueueingModel.i_MM1K](#)
[QueueingModel.i_MMCK](#)
[QueueingModel.i_MM1KK](#)
[QueueingModel.i_MMCKK](#)
[QueueingModel.i_MMCC](#)
[QueueingModel.i_MMCKM](#)
[QueueingModel.i_MMInfKK](#)
[QueueingModel.i_MMInf](#)
[QueueingModel.i_OJN](#)
[QueueingModel.i_MCON](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
QueueingModel(i_mm1)
```

QueueingModel.i_CJN *Builds one Closed Jackson Network*

Description

Builds one Closed Jackson Network

Usage

```
## S3 method for class 'i_CJN'
QueueingModel(x, ...)
```

Arguments

x a object of class i_CJN
 ... additional arguments

Details

Build one Closed Jackson Network. It also checks the input params calling the [CheckInput.i_CJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

m_cjn1
```

QueueingModel.i_MCCN *Builds one MultiClass Closed Network*

Description

Builds one MultiClass Closed Network

Usage

```
## S3 method for class 'i_MCCN'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCCN
...	additional arguments

Details

Build one MultiClass Closed Network. It also checks the input params calling the [CheckInput.i_MCCN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)  
  
o_MCCN1
```

QueueingModel.i_MCMN *Builds one MultiClass Mixed Network*

Description

Builds one MultiClass Mixed Network

Usage

```
## S3 method for class 'i_MCMN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MCMN
...	additional arguments

Details

Build one MultiClass Mixed Network. It also checks the input params calling the [CheckInput.i_MCMN](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)
```

```
o_mcmn1
```

```
QueueingModel.i_MCON  Builds one MultiClass Open Network
```

Description

Builds one MultiClass Open Network

Usage

```
## S3 method for class 'i_MCON'
QueueingModel(x, ...)
```

Arguments

```
x          a object of class i_MCON
...        additional arguments
```

Details

Build one MultiClass Open Network. It also checks the input params calling the [CheckInput.i_MCON](#)

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[CheckInput.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

```
# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

o_mcon1
```

QueueingModel.i_MM1	<i>Builds a M/M/1 queueing model</i>
---------------------	--------------------------------------

Description

Builds a M/M/1 queueing model

Usage

```
## S3 method for class 'i_MM1'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1
...	aditional arguments

Details

Build a M/M/1 queueing model. It also checks the input params calling the [CheckInput.i_MM1](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
QueueingModel(i_mm1)
```

QueueingModel.i_MM1K *Builds a M/M/1/K queueing model*

Description

Builds a M/M/1/K queueing model

Usage

```
## S3 method for class 'i_MM1K'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1K
...	aditional arguments

Details

Build a M/M/1/K queueing model. It also checks the input params calling the [CheckInput.i_MM1K](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
QueueingModel(i_mm1k)
```

QueueingModel.i_MM1KK *Builds a M/M/1/K/K queueing model*

Description

Builds a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'i_MM1KK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MM1KK
...	aditional arguments

Details

Build a M/M/1/K/K queueing model. It also checks the input params calling the [CheckInput.i_MM1KK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
QueueingModel(i_mm1kk)
```

QueueingModel.i_MMC *Builds a M/M/c queueing model*

Description

Builds a M/M/c queueing model

Usage

```
## S3 method for class 'i_MMC'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMC
...	aditional arguments

Details

Build a M/M/c/ queueing model. It also checks the input params calling the [CheckInput.i_MMC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
QueueingModel(i_mmc)
```

QueueingModel.i_MMCC *Builds a M/M/c/c queueing model*

Description

Builds a M/M/c/c queueing model

Usage

```
## S3 method for class 'i_MMCC'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCC
...	aditional arguments

Details

Build a M/M/c/c queueing model. It also checks the input params calling the [CheckInput.i_MMCC](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
QueueingModel(i_mmcc)
```

QueueingModel.i_MMCK *Builds a M/M/c/K queueing model*

Description

Builds a M/M/c/K queueing model

Usage

```
## S3 method for class 'i_MMCK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCK
...	aditional arguments

Details

Build a M/M/c/K queueing model. It also checks the input params calling the [CheckInput.i_MMCK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
QueueingModel(i_mmck)
```

QueueingModel.i_MMCKK *Builds a M/M/c/K/K queueing model*

Description

Builds a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'i_MMCKK'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKK
...	additional arguments

Details

Build a M/M/c/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMCKK](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
QueueingModel(i_mmckk)
```

QueueingModel.i_MMCKM *Builds a M/M/c/K/m queueing model*

Description

Builds a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'i_MMCKM'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMCKM
...	additional arguments

Details

Build a M/M/c/K/m queueing model. It also checks the input params calling the [CheckInput.i_MMCKM](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMCKM](#)

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
QueueingModel(i_mmckm)
```

QueueingModel.i_MMInf *Builds a M/M/Infinite queue model*

Description

Builds a M/M/Infinite queue model

Usage

```
## S3 method for class 'i_MMInf'  
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInf
...	additional arguments

Details

Build a M/M/Infinite model. It also checks the input params calling the [CheckInput.i_MMInf](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_MMInf](#)

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
QueueingModel(i_mminf)
```

`QueueingModel.i_MMInfKK`*Builds a M/M/Infinite/K/K queueing model*

Description

Builds a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'i_MMInfKK'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_MMInfKK
...	aditional arguments

Details

Build a M/M/Infinite/K/K queueing model. It also checks the input params calling the [CheckInput.i_MMInfKK](#)

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[CheckInput.i_MMInfKK](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
QueueingModel(i_MMInfKK)
```

QueueingModel.i_OJN *Builds one Open Jackson Network*

Description

Builds one Open Jackson Network

Usage

```
## S3 method for class 'i_OJN'
QueueingModel(x, ...)
```

Arguments

x	a object of class i_OJN
...	additional arguments

Details

Build one Open Jackson Network. It also checks the input params calling the [CheckInput.i_OJN](#)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[CheckInput.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

m_ojn1 <- QueueingModel(ojn1)
```

m_ojn1

RO	<i>Reports the server use of a queueing model</i>
----	---

Description

Reports the server use of a queueing model)

Usage

RO(x, ...)

Arguments

- | | |
|-----|---|
| x | a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf |
| ... | aditional arguments |

Details

Reports the server use of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

- [RO.o_MM1](#)
- [RO.o_MMC](#)
- [RO.o_MM1K](#)
- [RO.o_MMCK](#)
- [RO.o_MM1KK](#)
- [RO.o_MMCKK](#)
- [RO.o_MMCC](#)
- [RO.o_MMCKM](#)
- [RO.o_MMInfKK](#)
- [RO.o_MMInf](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)
```

RO.o_MM1

Reports the server use of a M/M/1 queueing model

Description

Reports the server use of a M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
RO(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Reports the server use of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the use of the server
RO(o_mm1)
```

RO.o_MM1K

*Reports the server use of a M/M/1/K queueing model***Description**

Reports the server use of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
RO(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Reports the server use of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Report the use of the server
RO(o_mm1k)
```

RO.o_MM1KK

Reports the server use of a M/M/1/K/K queueing model

Description

Reports the server use of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
RO(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Reports the server use of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the use of the server
RO(o_mm1kk)
```

RO.o_MMC

*Reports the server use of a M/M/c queueing model***Description**

Reports the server use of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
RO(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Reports the server use of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Report the use of the server
RO(o_mmc)
```

RO.o_MMCC

Reports the server use of a M/M/c/c queueing model

Description

Reports the server use of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
RO(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Reports the server use of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the use of the server
RO(o_mmcc)
```

RO.o_MMCK

*Reports the server use of a M/M/c/K queueing model***Description**

Reports the server use of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Reports the server use of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Report the use of the server
RO(o_mmck)
```

RO.o_MMCKK

Reports the server use of a M/M/c/K/K queueing model

Description

Reports the server use of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
RO(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Reports the server use of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the use of the server
RO(o_mmckk)
```

RO.o_MMCKM

Reports the server use of a M/M/c/K/m queueing model

Description

Reports the server use of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
RO(x, ...)
```

Arguments

x a object of class o_MMCKM
 ... additional arguments

Details

Reports the server use of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Report the use of the server
RO(o_mmckm)
```

RO.o_MMInf	<i>Reports the server use of a M/M/Infinite queueing model</i>
------------	--

Description

Reports the server use of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
RO(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Reports the server use of a M/M/Infinite queueing model. It should be noted that in this model, the RO parameter has a different meaning, its the traffic intensity and it coincides exactly with the average number of customers in the system (L)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#)
[L.o_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the use of the server
RO(o_mminf)
```

RO.o_MMInfKK

Reports the server use of a M/M/Infinite/K/K queueing model

Description

Reports the server use of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
RO(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Reports the server use of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the use of the server
RO(o_MMInfKK)
```

ROck	<i>Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network</i>
------	--

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
ROck(x, ...)
```

Arguments

- x a object of class o_MCON, o_MCCN, o_MCMN
- ... additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROck.o_MCON](#)
[ROck.o_MCCN](#)
[ROck.o_MCMN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)
```

ROck.o_MCCN

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
ROck(x, ...)
```

Arguments

x a object of class o_MCCN
 \dots additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROck(o_MCCN1)
```

ROck.o_MCMN

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the use of class i in each node (server) j in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROck(o_mcmn1)
```

ROck.o_MCON

*Reports a matrix with the use of class i in each node (server) j in a
 MultiClass Open Network*

Description

Reports a matrix with the use of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROck(x, ...)
```

Arguments

`x` a object of class `o_MCON`
`...` additional arguments

Details

Reports a matrix with the use of class `i` in each node (server) `j` in a

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

ROck(o_mcon1)
```

 ROk

Reports a vector with each node (server) use of a queueing network

Description

Reports a vector with each node (server) use of a queueing network

Usage

```
ROk(x, ...)
```

Arguments

`x` a object of class `o_OJN`, `o_CJN`, `o_MCON`, `o_MCCN`, `o_MCMN`
`...` additional arguments

Details

Reports a vector with each node (server) use of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos CaballeROk, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial CentROk de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[ROk.o_OJN](#)
[ROk.o_CJN](#)
[ROk.o_MCON](#)
[ROk.o_MCCN](#)
[ROk.o_MCMN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_CJN	<i>Reports a vector with each node (server) use of a Closed Jackson Network</i>
-----------	---

Description

Reports a vector with each node (server) use of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
ROk(x, ...)
```

Arguments

x	a object of class o_CJN
...	aditional arguments

Details

Reports a vector with each node (server) use of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)
```

```
# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

ROk(m_cjn1)
```

ROk.o_MCCN	<i>Reports a vector with each node (server) use of a MultiClass Closed Network</i>
------------	--

Description

Reports a vector with each node (server) use of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
ROk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

ROk(o_MCCN1)
```

ROk.o_MCMN

Reports a vector with each node (server) use of a MultiClass Mixed Network

Description

Reports a vector with each node (server) use of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
ROk(x, ...)
```

Arguments

x a object of class o_MCMN
... additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

ROk(o_mcmn1)
```

ROk.o_MCON	<i>Reports a vector with each node (server) use of a MultiClass Open Network</i>
------------	--

Description

Reports a vector with each node (server) use of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
ROk(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each node (server) use of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

R0k(o_mcon1)
```

R0k.o_OJN	<i>Reports a vector with each node (server) use of an Open Jackson Network</i>
-----------	--

Description

Reports a vector with each node (server) use of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
R0k(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Reports a vector with each node (server) use of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Deinition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

R0k(o_ojn)
```

 SP

Returns the saturation point of a queueing model

Description

Returns the saturation point of a queueing model

Usage

SP(x, ...)

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

Returns the saturation point of a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[SP.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

SP.o_MM1KK

Returns the saturation point of a M/M/1/K/K queueing model

Description

Returns the saturation point, or the maximum number of customers that the M/M/1/K/K queueing model can support with no interference or synchronization between themselves

Usage

```
## S3 method for class 'o_MM1KK'
SP(x, ...)
```

Arguments

x a object of class o_MM1KK
 ... additional arguments

Details

The value returned is the optimal number of customers of a M/M/1/K/K queueing model. It coincides with the inverse of the serialization parameter of Amdahl's Law. That is, the value which converges the speedup $\text{func}(k) = k/(1 + \text{ser} * (k-1))$. It makes sense, because the saturation point is the maximum value in which no synchronization happens.

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=4, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the saturation point
SP(o_mm1kk)
```

summary.o_CJN

Reports the results of a Closed Jackson Network

Description

Reports the results of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
summary(object, ...)
```

Arguments

object	a object of class o_CJN
...	additional arguments

Details

generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN](#).

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

summary(m_cjn1)
```

summary.o_MCCN

Reports the results of a MultiClass Closed Network

Description

Reports the results of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
summary(object, ...)
```

Arguments

object	a object of class o_MCCN
...	additional arguments

Details

generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.  
  
classes <- 2  
vNumber <- c(1, 1)  
vThink <- c(0, 0)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)  
  
# Build the model  
o_MCCN1 <- QueueingModel(i_MCCN1)  
  
summary(o_MCCN1)
```

summary.o_MCMN

*Reports the results of a MultiClass Mixed Network***Description**

Reports the results of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
summary(object, ...)
```

Arguments

object	a object of class o_MCMN
...	additional arguments

Details

generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)
```

```
summary(o_mcmn1)
```

summary.o_MCON	<i>Reports the results of a MultiClass Open Network</i>
----------------	---

Description

Reports the results of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
summary(object, ...)
```

Arguments

object	a object of class o_MCON
...	additional arguments

Details

generates a report of the queueing network received as parameter

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)
```

```
# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

summary(o_mcon1)
```

summary.o_MM1

Reports the results of a M/M/1 queueing model

Description

Reports the results of a M/M/1 queueing model.

Usage

```
## S3 method for class 'o_MM1'
summary(object, ...)
```

Arguments

object	a object of class o_MM1
...	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Report the results
summary(o_mm1)
```

summary.o_MM1K*Reports the results of a M/M/1/K queueing model*

Description

Reports the results of a M/M/1/K queueing model.

Usage

```
## S3 method for class 'o_MM1K'  
summary(object, ...)
```

Arguments

object	a object of class o_MM1K
...	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Report the results  
summary(o_mm1k)
```

`summary.o_MM1KK`*Reports the results of a M/M/1/K/K queueing model*

Description

Reports the results of a M/M/1/K/K queueing model.

Usage

```
## S3 method for class 'o_MM1KK'
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MM1KK</code>
<code>...</code>	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Report the results
summary(o_mm1kk)
```

summary.o_MMC*Reports the results of a M/M/c queueing model*

Description

Reports the results of a M/M/c queueing model.

Usage

```
## S3 method for class 'o_MMC'  
summary(object, ...)
```

Arguments

object	a object of class o_MMC
...	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Report the results  
summary(o_mmc)
```

`summary.o_MMCC`*Reports the results of a M/M/c/c queueing model*

Description

Reports the results of a M/M/c/c queueing model.

Usage

```
## S3 method for class 'o_MMCC'
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCC</code>
<code>...</code>	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Report the results
summary(o_mmcc)
```

summary.o_MMCK*Reports the results of a M/M/c/K queueing model*

Description

Reports the results of a M/M/c/K queueing model.

Usage

```
## S3 method for class 'o_MMCK'  
summary(object, ...)
```

Arguments

object	a object of class o_MMCK
...	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.  
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Report the results  
summary(o_mmck)
```

`summary.o_MMCKK`*Reports the results of a M/M/c/K/K queueing model*

Description

Reports the results of a M/M/c/K/K queueing model.

Usage

```
## S3 method for class 'o_MMCKK'
summary(object, ...)
```

Arguments

<code>object</code>	a object of class <code>o_MMCKK</code>
<code>...</code>	additional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Report the results
summary(o_mmckk)
```

summary.o_MMCKM	<i>Reports the results of a M/M/c/K/m queueing model</i>
-----------------	--

Description

Reports the results of a M/M/c/K/m queueing model.

Usage

```
## S3 method for class 'o_MMCKM'  
summary(object, ...)
```

Arguments

object	a object of class o_MMCKM
...	additional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Report the results  
summary(o_mmckm)
```

summary.o_MMInf	<i>Reports the results of a M/M/Infinite queueing model</i>
-----------------	---

Description

Reports the results of a M/M/Infinite queueing model.

Usage

```
## S3 method for class 'o_MMInf'
summary(object, ...)
```

Arguments

object	a object of class o_MMInf
...	additional arguments

Details

generates a report of the queueing model received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Report the results
summary(o_mminf)
```

summary.o_MMInfKK	<i>Reports the results of a M/M/Infinite/K/K queueing model</i>
-------------------	---

Description

Reports the results of a M/M/Infinite/K/K queueing model.

Usage

```
## S3 method for class 'o_MMInfKK'
summary(object, ...)
```

Arguments

object	a object of class o_MMInfKK
...	aditional arguments

Details

generates a report of the queueing model received as parameter

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Report the results
summary(o_MMInfKK)
```

summary.o_OJN

*Reports the results of an Open Jackson Network***Description**

Reports the results of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
summary(object, ...)
```

Arguments

object	a object of class o_OJN
...	additional arguments

Details

generates a report of the queueing network received as parameter

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

o_ojn <- QueueingModel(i_ojn)
```

summary(o_ojn)

Throughput	<i>Throughput of a queueing model (or network)</i>
------------	--

Description

Returns the throughput of a queueing model (or network)

Usage

Throughput(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf, o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the throughput of a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

- [Throughput.o_MM1](#)
- [Throughput.o_MMC](#)
- [Throughput.o_MM1K](#)
- [Throughput.o_MMCK](#)
- [Throughput.o_MM1KK](#)
- [Throughput.o_MMCKK](#)
- [Throughput.o_MMCC](#)
- [Throughput.o_MMCKM](#)
- [Throughput.o_MMInfKK](#)

```
Throughput.o_MMInf
Throughput.o_OJN
Throughput.o_CJN
Throughput.o_MCON
Throughput.o_MCCN
Throughput.o_MCMN
```

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)
```

Throughput.o_CJN	<i>Reports the network throughput of a Closed Jackson Network</i>
------------------	---

Description

Reports the network throughput of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughput(x, ...)
```

Arguments

x	a object of class o_CJN
...	additional arguments

Details

Reports the network throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughput(m_cjn1)
```

Throughput.o_MCCN	<i>Reports the throughput of a MultiClass Closed Network</i>
-------------------	--

Description

Reports the throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughput(x, ...)
```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Reports the throughput of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughput(o_MCCN1)
```

Throughput.o_MCMN

Reports the throughput of a MultiClass Mixed Network

Description

Reports the throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughput(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports the throughput of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughput(o_mcmn1)
```

Throughput.o_MCON	<i>Reports the throughput of a MultiClass Open Network</i>
-------------------	--

Description

Reports the throughput of a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughput(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Reports the throughput of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughput(o_mcon1)
```

Throughput.o_MM1

Throughput of a M/M/1 queueing model

Description

Returns the throughput of a M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
Throughput(x, ...)
```


Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the throughput of a M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1](#), [CheckInput.i_MM1](#), [QueueingModel.i_MM1](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Throughput
Throughput(o_mm1)
```

Throughput.o_MM1K	<i>Throughput of a M/M/1/K queueing model</i>
-------------------	---

Description

Returns the throughput of a M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Throughput(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the throughput of a M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1K](#), [CheckInput.i_MM1K](#), [QueueingModel.i_MM1K](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mmck <- QueueingModel(i_mm1k)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MM1KK	<i>Throughput of a M/M/1/K/K queueing model</i>
--------------------	---

Description

Returns the throughput of a M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the throughput of a M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MM1KK](#), [CheckInput.i_MM1KK](#), [QueueingModel.i_MM1KK](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_MM1KKk <- QueueingModel(i_mm1kk)

## Throughput
Throughput(o_MM1KKk)
```

Throughput.o_MMC

Throughput of a M/M/c queueing model

Description

Returns the throughput of a M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the throughput of a M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos determinísticos y estocásticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMC](#), [CheckInput.i_MMC](#), [QueueingModel.i_MMC](#)

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Throughput
Throughput(o_mmc)
```

Throughput.o_MMCC

Throughput of a M/M/c/c queueing model

Description

Returns the throughput of a M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the throughput of a M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCC](#), [CheckInput.i_MMCC](#), [QueueingModel.i_MMCC](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Throughput
Throughput(o_mmcc)
```

Throughput.o_MMCK

Throughput of a M/M/c/K queueing model

Description

Returns the throughput of a M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the throughput of a M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCK](#), [CheckInput.i_MMCK](#), [QueueingModel.i_MMCK](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Throughput
Throughput(o_mmck)
```

Throughput.o_MMCKK	<i>Throughput of a M/M/c/K/K queueing model</i>
--------------------	---

Description

Returns the throughput of a M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the throughput of a M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKK](#), [CheckInput.i_MMCKK](#), [QueueingModel.i_MMCKK](#)

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## build the model
o_mmckk <- QueueingModel(i_mmckk)

## Throughput
Throughput(o_mmckk)
```

Throughput.o_MMCKM	<i>Throughput of a M/M/c/K/m queueing model</i>
--------------------	---

Description

Returns the throughput of a M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the throughput of a M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMCKM](#), [CheckInput.i_MMCKM](#), [QueueingModel.i_MMCKM](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Throughput
Throughput(o_mmckm)
```

Throughput.o_MMInf	<i>Throughput of a M/M/Infinite queueing model</i>
--------------------	--

Description

Returns the throughput of a M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMInf
...	aditional arguments

Details

Returns the throughput of a M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.MMInf](#), [CheckInput.i_MMInf](#), [QueueingModel.i_MMInf](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Throughput
Throughput(o_mminf)
```

Throughput.o_MMInfKK	<i>Throughput of a M/M/Infinite/K/K queueing model</i>
----------------------	--

Description

Returns the throughput of a M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Throughput(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the throughput of a M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[NewInput.MMInfKK](#), [CheckInput.i_MMInfKK](#), [QueueingModel.i_MMInfKK](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Throughput
Throughput(o_MMInfKK)
```

Throughput.o_OJN

Reports the throughput of an Open Jackson Network

Description

Reports the throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughput(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Reports the throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughput(o_ojn)
```

Throughputc	<i>Reports a vector with each class throughput in a multiclass queueing network</i>
-------------	---

Description

Reports a vector with each class throughput in a multiclass queueing network

Usage

```
Throughputc(x, ...)
```

Arguments

- x a object of class o_MCON, o_MCCN, o_MCMN
- ... additional arguments

Details

Reports a vector with each class throughput in a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputc.o_MCON](#)

[Throughputc.o_MCCN](#)

[Throughputc.o_MCCN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputc(o_mcon1)
```

Throughputc.o_MCCN	<i>Reports a vector with each class throughput in a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputc(o_MCCN1)
```

Throughputc.o_MCMN	<i>Reports a vector with each class throughput in a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each class throughput in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputc(x, ...)
```

Arguments

```
x          a object of class o_MCMN
...        additional arguments
```

Details

Reports a vector with each class throughput in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputc(o_mcmn1)
```

Throughputc.o_MCON	<i>Reports a vector with each class throughput in a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each class throughput in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughputc(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each class throughput in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)
```

```
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputck	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network</i>
--------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

Usage

```
Throughputck(x, ...)
```

Arguments

- x a object of class o_MCON, o_MCCN
- ... additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

- [Throughputck.o_MCON](#)
- [Throughputck.o_MCCN](#)
- [Throughputck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputck.o_MCCN	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network</i>
---------------------	---

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputck(o_MCCN1)
```

Throughputck.o_MCMN	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network</i>
---------------------	--

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputck(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.

Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.

Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputck(o_mcmn1)
```

Throughputck.o_MCON	<i>Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network</i>
---------------------	---

Description

Reports a matrix with the throughput of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Throughputck(x, ...)
```

Arguments

```
x                a object of class o_MCON
...              additional arguments
```

Details

Reports a matrix with the throughput of class *i* in each node (server) *j* in a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputck(o_mcon1)
```

Throughputcn	<i>Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network</i>
--------------	--

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
Throughputcn(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputcn.o_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)
```

```
# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputcn.o_MCCN	<i>Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network</i>
---------------------	--

Description

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputcn(x, ...)
```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Returns a matrix with the Throughput from each class and every population of a Multi Class Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputcn(o_MCCN1)
```

Throughputk	<i>Reports a vector with each node (server) throughput of a queueing network</i>
-------------	--

Description

Reports a vector with each node (server) throughput of a queueing network

Usage

```
Throughputk(x, ...)
```

Arguments

- x a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
- ... additional arguments

Details

Reports a vector with each node (server) throughput of a queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik

(1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Throughputk.o_OJN](#)
[Throughputk.o_CJN](#)
[Throughputk.o_MCON](#)
[Throughputk.o_MCCN](#)
[Throughputk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_CJN	<i>Reports a vector with each node (server) throughput of a Closed Jackson Network</i>
-------------------	--

Description

Reports a vector with each node (server) throughput of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputk(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Reports a vector with each node (server) throughput of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputk(m_cjn1)
```

Throughputk.o_MCCN	<i>Reports a vector with each node (server) throughput of a MultiClass Closed Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Throughputk(x, ...)
```

Arguments

```
x                a object of class o_MCCN
...              additional arguments
```

Details

Reports a vector with each node (server) throughput of a MultiClass Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCCN](#), [CheckInput.i_MCCN](#), [QueueingModel.i_MCCN](#)

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Throughputk(o_MCCN1)
```

Throughputk.o_MCMN	<i>Reports a vector with each node (server) throughput of a MultiClass Mixed Network</i>
--------------------	--

Description

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Mixed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCMN](#), [CheckInput.i_MCMN](#), [QueueingModel.i_MCMN](#)

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.
```

```
classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
```

```

vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Throughputk(o_mcmn1)

```

Throughputk.o_MCON	<i>Reports a vector with each node (server) throughput of a MultiClass Open Network</i>
--------------------	---

Description

Reports a vector with each node (server) throughput of a MultiClass Open Network

Usage

```

## S3 method for class 'o_MCON'
Throughputk(x, ...)

```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Reports a vector with each node (server) throughput of a MultiClass Open Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).

Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).

Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[NewInput.MCON](#), [CheckInput.i_MCON](#), [QueueingModel.i_MCON](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Throughputk(o_mcon1)
```

Throughputk.o_OJN	<i>Reports a vector with each node (server) throughput of an Open Jackson Network</i>
-------------------	---

Description

Reports a vector with each node (server) throughput of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Throughputk(x, ...)
```

Arguments

x	a object of class o_OJN
...	additional arguments

Details

Reports a vector with each node (server) throughput of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.OJN](#), [CheckInput.i_OJN](#), [QueueingModel.i_OJN](#)

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

Throughputk(o_ojn)
```

Throughputn	Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network
-------------	--

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

Usage

```
Throughputn(x, ...)
```

Arguments

- x a object of class o_CJN
- ... additional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Throughputn.o_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

Throughputn.o_CJN	<i>Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network</i>
-------------------	---

Description

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Throughputn(x, ...)
```

Arguments

x a object of class o_CJN
 ... additional arguments

Details

Returns a vector with the each Throughput from 1 to the parameter n (population passed as input) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos determinísticos y estocásticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[NewInput.CJN](#), [CheckInput.i_CJN](#), [QueueingModel.i_CJN](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

Throughputn(m_cjn1)
```

VN	<i>Returns the variance of the number of customers in a queueing model (or network)</i>
----	---

Description

Returns the variance of the number of customers in a queueing model (or network)

Usage

```
VN(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[VN.o_MM1](#)
[VN.o_MMC](#)
[VN.o_MMCC](#)
[VN.o_MMInf](#)
[VN.o_MMInfKK](#)
[VN.o_MM1K](#)
[VN.o_MMCK](#)
[VN.o_MM1KK](#)
[VN.o_MMCKK](#)
[VN.o_MMCKM](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance
VN(o_mm1)
```

VN.o_MM1	<i>Returns the variance of the number of customers in the M/M/1 queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VN(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance
VN(o_mm1)
```

VN.o_MM1K	<i>Returns the variance of the number of customers in the M/M/1/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VN(o_mm1k)
```

VN.o_MM1KK	<i>Returns the variance of the number of customers in the M/M/1/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VN(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VN(o_mm1kk)
```

VN.o_MMC	<i>Returns the variance of the number of customers in the M/M/c queueing model</i>
----------	--

Description

Returns the variance of the number of customers in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VN(o_mmc)
```

VN.o_MMCC	<i>Returns the variance of the number of customers in the M/M/c/c queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VN(o_mmcc)
```

VN.o_MMCK	<i>Returns the variance of the number of customers in the M/M/c/K queueing model</i>
-----------	--

Description

Returns the variance of the number of customers in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VN(o_mmck)
```

VN.o_MMCKK	<i>Returns the variance of the number of customers in the M/M/c/K/K queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VN(o_mmckk)
```

VN.o_MMCKM	<i>Returns the variance of the number of customers in the M/M/c/K/m queueing model</i>
------------	--

Description

Returns the variance of the number of customers in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'  
VN(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters  
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)  
  
## Build the model  
o_mmckm <- QueueingModel(i_mmckm)  
  
## Returns the variance  
VN(o_mmckm)
```

VN.o_MMInf	<i>Returns the variance of the number of customers in the M/M/Infinite queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VN(o_mminf)
```

VN.o_MMInfKK	<i>Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model</i>
--------------	---

Description

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'  
VN(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the number of customers in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters  
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)  
  
## Build the model  
o_MMInfKK <- QueueingModel(i_MMInfKK)  
  
## Returns the variance  
VN(o_MMInfKK)
```

VNq	<i>Returns the variance of the number of customers in the queue in a queueing model</i>
-----	---

Description

Returns the variance of the number of customers in the queue in a queueing model

Usage

VNq(x, ...)

Arguments

x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
... additional arguments

Details

Returns the variance of the number of customers in the queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[VNq.o_MM1](#)
[VNq.o_MM1](#)
[VNq.o_MMCC](#)
[VNq.o_MMInf](#)
[VNq.o_MMInfKK](#)
[VNq.o_MM1K](#)
[VNq.o_MMCK](#)
[VNq.o_MM1KK](#)
[VNq.o_MMCKK](#)
[VNq.o_MMCKM](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)
```

```
## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1	<i>Returns the variance of the number of customers in the queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VNq(x, ...)
```

Arguments

x	a object of class o_MM1
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance
VNq(o_mm1)
```

VNq.o_MM1K	<i>Returns the variance of the number of customers in the queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VNq(o_mm1k)
```

VNq.o_MM1KK	<i>Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VNq(o_mm1kk)
```

VNq.o_MMC	<i>Returns the variance of the number of customers in the queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance  
VNq(o_mmc)
```

VNq.o_MMCC	<i>Returns the variance of the number of customers in the queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VNq(o_mmcc)
```

VNq.o_MMCK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VNq(o_mmck)
```

VNq.o_MMCKK	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters  
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)  
  
## Build the model  
o_mmckk <- QueueingModel(i_mmckk)  
  
## Returns the variance  
VNq(o_mmckk)
```

VNq.o_MMCKM	<i>Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
VNq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/c/K/m queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the variance
VNq(o_mmckm)
```

VNq.o_MMInf	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model</i>
-------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VNq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VNq(o_mminf)
```

VNq.o_MMInfKK	<i>Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model</i>
---------------	--

Description

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
VNq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the variance of the number of customers in the queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the VNq
VNq(o_MMInfKK)
```

VT	<i>Returns the variance of the time spend in a queueing model (or network)</i>
----	--

Description

Returns the variance of the time spend in a queueing model (or network)

Usage

```
VT(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the time spend in a queueing model (or network)

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[VT.o_MM1](#)
[VT.o_MMC](#)
[VT.o_MMCC](#)
[VT.o_MMInf](#)
[VT.o_MMInfKK](#)
[VT.o_MM1K](#)
[VT.o_MM1KK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in the system
VT(o_mm1)
```

`VT.o_MM1`*Returns the variance of the time spend in the M/M/1 queueing model*

Description

Returns the variance of the time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VT(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MM1</code>
<code>...</code>	additional arguments

Details

Returns the variance of the time spend in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in the system
VT(o_mm1)
```

VT.o_MM1K	<i>Returns the variance of the time spend in the M/M/1/K queueing model</i>
-----------	---

Description

Returns the variance of the time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VT(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the variance of the time spend in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VT(o_mm1k)
```

VT.o_MM1KK	<i>Returns the variance of the time spend in the M/M/1/K/K queueing model</i>
------------	---

Description

Returns the variance of the time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VT(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the variance  
VT(o_mm1kk)
```

VT.o_MMC*Returns the variance of the time spend in the M/M/c queueing model*

Description

Returns the variance of the time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VT(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the variance of the time spend in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in the system  
VT(o_mmc)
```

`VT.o_MMCC`*Returns the variance of the time spend in the M/M/c/c queueing model*

Description

Returns the variance of the time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VT(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MMCC</code>
<code>...</code>	additional arguments

Details

Returns the variance of the time spend in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VT(o_mmcc)
```

VT.o_MMInf	<i>Returns the variance of the time spend in the M/M/Infinite queueing model</i>
------------	--

Description

Returns the variance of the time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VT(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the the variance of the time spend in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VT(o_mminf)
```

VT.o_MMInfKK	<i>Returns the variance of the time spend in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
VT(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the time spend in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the variance
VT(o_MMInfKK)
```

VTq	<i>Returns the variance of the time spend in queue in a queueing model</i>
-----	--

Description

Returns the variance of the time spend in queue in a queueing model

Usage

```
VTq(x, ...)
```

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	additional arguments

Details

Returns the variance of the time spend in queue in a queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[VTq.o_MM1](#)
[VTq.o_MMC](#)
[VTq.o_MMCC](#)
[VTq.o_MMInf](#)
[VTq.o_MMInfKK](#)
[VTq.o_MM1K](#)
[VTq.o_MMCK](#)
[VTq.o_MM1KK](#)
[VTq.o_MMCKK](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in queue
VTq(o_mm1)
```

VTq.o_MM1	<i>Returns the variance of the time spend in queue in the M/M/1 queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
VTq(x, ...)
```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1 queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the variance of the time spend in queue
VTq(o_mm1)
```

VTq.o_MM1K	<i>Returns the variance of the time spend in queue in the M/M/1/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## create input parameters  
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)  
  
## Build the model  
o_mm1k <- QueueingModel(i_mm1k)  
  
## Returns the variance  
VTq(o_mm1k)
```

VTq.o_MM1KK	<i>Returns the variance of the time spend in queue in the M/M/1/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/1/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the VTq  
VTq(o_mm1kk)
```

VTq.o_MMC	<i>Returns the variance of the time spend in queue in the M/M/c queueing model</i>
-----------	--

Description

Returns the variance of the time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## create input parameters  
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)  
  
## Build the model  
o_mmc <- QueueingModel(i_mmc)  
  
## Returns the variance of the time spend in queue  
VTq(o_mmc)
```

VTq.o_MMCC	<i>Returns the variance of the time spend in queue in the M/M/c/c queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/c queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## create input parameters  
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)  
  
## Build the model  
o_mmcc <- QueueingModel(i_mmcc)  
  
## Returns the variance  
VTq(o_mmcc)
```

VTq.o_MMCK	<i>Returns the variance of the time spend in queue in the M/M/c/K queueing model</i>
------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCK](#).

Examples

```
## create input parameters  
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)  
  
## Build the model  
o_mmck <- QueueingModel(i_mmck)  
  
## Returns the variance  
VTq(o_mmck)
```

VTq.o_MMCKK	<i>Returns the variance of the time spend in queue in the M/M/c/K/K queueing model</i>
-------------	--

Description

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
VTq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the variance of the time spend in queue in the M/M/c/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
 University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the variance
VTq(o_mmckk)
```

VTq.o_MMInf	<i>Returns the variance of the time spend in queue in the M/M/Infinite queueing model</i>
-------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'  
VTq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters  
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)  
  
## Build the model  
o_mminf <- QueueingModel(i_mminf)  
  
## Returns the variance  
VTq(o_mminf)
```

VTq.o_MMInfKK	<i>Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model</i>
---------------	---

Description

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
VTq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the variance of the time spend in queue in the M/M/Infinite/K/K queueing model

References

[Sztrik2012] Dr. Janos Sztrik (2012).
Basic Queueing Theory.
University of Debrecen, Faculty of Informatics.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the variance
VTq(o_MMInfKK)
```

W	<i>Returns the mean time spend in a queueing model (or network)</i>
---	---

Description

Returns the mean time spend in a queueing model (or network)

Usage

`W(x, ...)`

Arguments

x	a object of class <code>o_MM1</code> , <code>o_MMC</code> , <code>o_MM1K</code> , <code>o_MMCK</code> , <code>o_MM1KK</code> , <code>o_MMCKK</code> , <code>o_MMCC</code> , <code>o_MMCKM</code> , <code>o_MMInfKK</code> , <code>o_MMInf</code> , <code>o_OJN</code> , <code>o_MCON</code> , <code>o_MCCN</code> , <code>o_MCMN</code>
...	additional arguments

Details

Returns the mean time spend in a queueing model (or network)

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[W.o_MM1](#)
[W.o_MMC](#)
[W.o_MM1K](#)
[W.o_MMCK](#)
[W.o_MM1KK](#)
[W.o_MMCKK](#)
[W.o_MMCC](#)
[W.o_MMCKM](#)
[W.o_MMInfKK](#)
[W.o_MMInf](#)
[W.o_OJN](#)
[W.o_MCON](#)
[W.o_MCCN](#)
[W.o_MCMN](#)

Examples

```
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_CJN

Returns the mean time spend in a Closed Jackson Network

Description

Returns the mean time spend in a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
W(x, ...)
```

Arguments

x a object of class o_CJN
 ... additional arguments

Details

Returns the mean time spend in a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.
## create the nodes
n <- 2
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)

# think time = 0
z <- 0

# operational value
operational <- FALSE

# definition of the transition probabilities
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)

# Define a new input
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)

# Check the inputs and build the model
m_cjn1 <- QueueingModel(cjn1)

W(m_cjn1)
```

W.o_MCCN

Returns the mean time spend in a MultiClass Closed Network

Description

Returns the mean time spend in a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
W(x, ...)
```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Returns the mean time spend in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

W(o_MCCN1)
```

W.o_MCMN

Returns the mean time spend in a MultiClass Mixed Network

Description

Returns the mean time spend in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
W(x, ...)
```

Arguments

x	a object of class o_MCMN
...	additional arguments

Details

Returns the mean time spend in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

W(o_mcmn1)
```

W.o_MCON

Returns the mean time spend in a MultiClass Open Network

Description

Returns the mean time spend in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
W(x, ...)
```

Arguments

x a object of class o_MCON
 ... additional arguments

Details

Returns the mean time spend in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

W(o_mcon1)
```

W.o_MM1

Returns the mean time spend in the M/M/1 queueing model

Description

Returns the mean time spend in the M/M/1 queueing model

Usage

```
## S3 method for class 'o_MM1'
W(x, ...)
```

Arguments

x a object of class o_MM1
 ... additional arguments

Details

Returns the mean time spend in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1](#).

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the W
W(o_mm1)
```

W.o_MM1K

Returns the mean time spend in the M/M/1/K queueing model

Description

Returns the mean time spend in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
W(x, ...)
```

Arguments

x a object of class o_MM1K
 ... additional arguments

Details

Returns the mean time spend in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K](#).

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the W
W(o_mm1k)
```

W.o_MM1KK

Returns the mean time spend in the M/M/1/K/K queueing model

Description

Returns the mean time spend in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
W(x, ...)
```

Arguments

```
x          a object of class o_MM1KK
...        additional arguments
```

Details

Returns the mean time spend in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the W
W(o_mm1kk)
```

W.o_MMC

Returns the mean time spend in the M/M/c queueing model

Description

Returns the mean time spend in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
W(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the mean time spend in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the W
W(o_mmc)
```

W.o_MMCC

Returns the mean time spend in the M/M/c/c queueing model

Description

Returns the mean time spend in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
W(x, ...)
```

Arguments

x a object of class o_MMCC
... additional arguments

Details

Returns the mean time spend in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the W
W(o_mmcc)
```

W.o_MMCK

Returns the mean time spend in the M/M/c/K queueing model

Description

Returns the mean time spend in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
W(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean time spend in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the W
W(o_mmck)
```

W.o_MMCKK

Returns the mean time spend in the M/M/c/K/K queueing model

Description

Returns the mean time spend in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
W(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	additional arguments

Details

Returns the mean time spend in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK.](#)

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the W
W(o_mmckk)
```

W.o_MMCKM

Returns the mean time spend in the M/M/c/K/m queueing model

Description

Returns the mean time spend in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
W(x, ...)
```

Arguments

x a object of class o_MMCKM
 ... additional arguments

Details

Returns the mean time spend in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM.](#)

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the W
W(o_mmckm)
```

W.o_MMInf

Returns the time spend in the M/M/Infinite queueing model

Description

Returns the mean time spend in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
W(x, ...)
```

Arguments

x a object of class o_MMInf
 ... additional arguments

Details

Returns the mean time spend in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the W
W(o_mminf)
```

W.o_MMInfKK	<i>Returns the mean time spend in the M/M/Infinite/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
W(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	aditional arguments

Details

Returns the mean time spend in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK.](#)

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the W
W(o_MMInfKK)
```

W.o_OJN	Returns the mean time spend in an Open Jackson Network
---------	--

Description

Returns the mean time spend in an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
W(x, ...)
```

Arguments

- x a object of class o_OJN
- ... additional arguments

Details

Returns the mean time spend in an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

# Definition of the new input
i_ojn <- NewInput.OJN(prob, n1, n2, n3, n4)

# Build the models
o_ojn <- QueueingModel(i_ojn)

W(o_ojn)
```

Wc	<i>Returns the vector with each class mean time spend on a multiclass queueing network</i>
----	--

Description

Returns the vector with each class mean time spend on a multiclass queueing network

Usage

```
Wc(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Returns the vector with each class mean time spend on a multiclass queueing network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

Wc.o_MCON
Wc.o_MCCN
Wc.o_MCMN

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Wc(o_mcon1)
```

Wc.o_MCCN	Returns the vector with each class mean time spend on a MultiClass Closed Network
-----------	---

Description

Returns the vector with each class mean time spend on a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'  
Wc(x, ...)
```

Arguments

x a object of class o_MCCN
... additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wc(o_MCCN1)
```

Wc.o_MCMN

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Description

Returns the vector with each class mean time spend on a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wc(x, ...)
```

Arguments

x a object of class o_MCMN
 ... additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wc(o_mcmn1)
```

Wc.o_MCON

*Returns the vector with each class mean time spend on a MultiClass
 Open Network*

Description

Returns the vector with each class mean time spend on a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'  
Wc(x, ...)
```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns the vector with each class mean time spend on a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.  
  
classes <- 2  
vLambda <- c(3/19, 2/19)  
nodes <- 2  
vType <- c("Q", "Q")  
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)  
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)  
  
i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)  
  
# Build the model  
o_mcon1 <- QueueingModel(i_mcon1)  
  
Wc(o_mcon1)
```

Wck	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network</i>
-----	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

Usage

```
Wck(x, ...)
```

Arguments

x	a object of class o_MCON, o_MCCN, o_MCMN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Queueing Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.
 [Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wck.o_MCON](#)
[Wck.o_MCCN](#)
[Wck.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
```

```

vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)

```

Wck.o_MCCN	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network</i>
------------	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

Usage

```

## S3 method for class 'o_MCCN'
Wck(x, ...)

```

Arguments

x	a object of class o_MCCN
...	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)

Wck(o_MCCN1)
```

Wck.o_MCMN

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wck(x, ...)
```

Arguments

<code>x</code>	a object of class <code>o_MCMN</code>
<code>...</code>	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wck(o_mcmn1)
```

Wck.o_MCON	<i>Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network</i>
------------	--

Description

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

Usage

```
## S3 method for class 'o_MCON'
Wck(x, ...)
```

Arguments

x	a object of class o_MCON
\dots	additional arguments

Details

Reports a matrix with the mean time of class i in each node (server) j in a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wck(o_mcon1)
```

Wk	<i>Generic S3 method to return the mean time spend in each node (or server) of a network</i>
----	--

Description

Generic S3 method to return the mean time spend in each node (or server) of a network

Usage

```
Wk(x, ...)
```

Arguments

- x a object of class o_OJN, o_CJN, o_MCON, o_MCCN, o_MCMN
- ... additional arguments

Details

Generic S3 method to return the mean time spend in each node (or server) of a network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.
 [Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[Wk.o_OJN](#)
[Wk.o_CJN](#)
[Wk.o_MCON](#)
[Wk.o_MCCN](#)
[Wk.o_MCMN](#)

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_CJN

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

Description

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

Usage

```
## S3 method for class 'o_CJN'
Wk(x, ...)
```

Arguments

x a object of class o_CJN
... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of a Closed Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_CJN.](#)

Examples

```
## See example 11.13 in reference [Sixto2004] for more details.  
## create the nodes  
n <- 2  
n1 <- NewInput.MM1(lambda=0, mu=1/0.2, n=0)  
n2 <- NewInput.MM1(lambda=0, mu=1/0.4, n=0)  
  
# think time = 0  
z <- 0  
  
# operational value  
operational <- FALSE  
  
# definition of the transition probabilities  
prob <- matrix(data=c(0.5, 0.5, 0.5, 0.5), nrow=2, ncol=2, byrow=TRUE)  
  
# Define a new input  
cjn1 <- NewInput.CJN(prob, n, z, operational, 0, 0.001, n1, n2)  
  
# Check the inputs and build the model  
m_cjn1 <- QueueingModel(cjn1)  
  
Wk(m_cjn1)
```

Wk.o_MCCN	<i>Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network</i>
-----------	---

Description

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

Usage

```
## S3 method for class 'o_MCCN'
Wk(x, ...)
```

Arguments

x	a object of class o_MCCN
...	aditional arguments

Details

Returns a vector with the mean time spend in each node (server) of a MultiClass Closed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCCN](#).

Examples

```
## See example in pag 142 in reference [Lazowska84] for more details.

classes <- 2
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_MCCN1 <- NewInput.MCCN(classes, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_MCCN1 <- QueueingModel(i_MCCN1)
```

Wk(o_MCCN1)

Wk.o_MCMN	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network</i>
-----------	--

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

Usage

```
## S3 method for class 'o_MCMN'
Wk(x, ...)
```

Arguments

x	a object of class o_MCMN
...	aditional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Mixed Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984).
Quantitative System Performance: Computer System Analysis Using Queueing Network Models.
 Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCMN](#).

Examples

```
## See example in pag 147 in reference [Lazowska84] for more details.

classes <- 4
vLambda <- c(1, 1/2)
vNumber <- c(1, 1)
vThink <- c(0, 0)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=1, nrow=4, ncol=2)
vService <- matrix(data=c(1/4, 1/2, 1/2, 1, 1/6, 1, 1, 4/3), nrow=4, ncol=2)
```

```

i_mcmn1 <- NewInput.MCMN(classes, vLambda, vNumber, vThink, nodes, vType, vVisit, vService)

# Build the model
o_mcmn1 <- QueueingModel(i_mcmn1)

Wk(o_mcmn1)

```

Wk.o_MCON	<i>Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network</i>
-----------	---

Description

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

Usage

```

## S3 method for class 'o_MCON'
Wk(x, ...)

```

Arguments

x	a object of class o_MCON
...	additional arguments

Details

Returns a matrix with the mean time spend in each node (server) of a MultiClass Open Network

References

[Lazowska84] Edward D. Lazowska, John Zahorjan, G. Scott Graham, and Kenneth C. Sevcik (1984). *Quantitative System Performance: Computer System Analysis Using Queueing Network Models*. Prentice-Hall, Inc., Englewood Cliffs, New Jersey

See Also

[QueueingModel.i_MCON](#).

Examples

```
## See example in pag 138 in reference [Lazowska84] for more details.

classes <- 2
vLambda <- c(3/19, 2/19)
nodes <- 2
vType <- c("Q", "Q")
vVisit <- matrix(data=c(10, 9, 5, 4), nrow=2, ncol=2, byrow=TRUE)
vService <- matrix(data=c(1/10, 1/3, 2/5, 1), nrow=2, ncol=2, byrow=TRUE)

i_mcon1 <- NewInput.MCON(classes, vLambda, nodes, vType, vVisit, vService)

# Build the model
o_mcon1 <- QueueingModel(i_mcon1)

Wk(o_mcon1)
```

Wk.o_OJN

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Description

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

Usage

```
## S3 method for class 'o_OJN'
Wk(x, ...)
```

Arguments

x a object of class o_OJN
 ... additional arguments

Details

Returns the vector with the mean time spend in each node (server) of an Open Jackson Network

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_OJN](#).

Examples

```
## See example 11.11 in reference [Sixto2004] for more details.
## create the nodes
n1 <- NewInput.MM1(lambda=8, mu=14, n=0)
n2 <- NewInput.MM1(lambda=0, mu=9, n=0)
n3 <- NewInput.MM1(lambda=6, mu=17, n=0)
n4 <- NewInput.MM1(lambda=0, mu=7, n=0)
m <- c(0, 0.2, 0.56, 0.24, 1, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0, 0)

# definition of the transition probabilities
prob <- matrix(data=m, nrow=4, ncol=4, byrow=TRUE)

ojn1 <- NewInput.OJN(prob, n1, n2, n3, n4)

m_ojn1 <- QueueingModel(ojn1)

Wk(m_ojn1)
```

Wq

Returns the mean time spend in queue in a queueing model

Description

Returns the mean time spend in queue in a queueing model

Usage

Wq(x, ...)

Arguments

x	a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
...	aditional arguments

Details

Returns the mean time spend in queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[Wq.o_MM1](#)
[Wq.o_MMC](#)
[Wq.o_MM1K](#)
[Wq.o_MMCK](#)
[Wq.o_MM1KK](#)
[Wq.o_MMCKK](#)
[Wq.o_MMCC](#)
[Wq.o_MMCKM](#)
[Wq.o_MMInfKK](#)
[Wq.o_MMInf](#)

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)

```

Wq.o_MM1

Returns the mean time spend in queue in the M/M/1 queueing model

Description

Returns the mean time spend in queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wq(x, ...)

```

Arguments

x a object of class o_MM1
... additional arguments

Details

Returns the mean time spend in queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wq
Wq(o_mm1)
```

Wq.o_MM1K

Returns the mean time spend in queue in the M/M/1/K queueing model

Description

Returns the mean time spend in queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wq
Wq(o_mm1k)
```

Wq.o_MM1KK	Returns the mean time spend in queue in the M/M/1/K/K queueing model
------------	--

Description

Returns the mean time spend in queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wq(x, ...)
```

Arguments

- x a object of class o_MM1KK
- ... additional arguments

Details

Returns the mean time spend in queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wq
Wq(o_mm1kk)
```

Wq.o_MMC

Returns the mean time spend in queue in the M/M/c queueing model

Description

Returns the mean time spend in queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wq(x, ...)
```

Arguments

x	a object of class o_MMC
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wq
Wq(o_mmc)
```

Wq.o_MMCC	<i>Returns the mean time spend in queue in the M/M/c/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC](#).

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wq
Wq(o_mmcc)
```

Wq.o_MMCK	<i>Returns the mean time spend in queue in the M/M/c/K queueing model</i>
-----------	---

Description

Returns the mean time spend in queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wq
Wq(o_mmck)
```

Wq.o_MMCKK	<i>Returns the mean time spend in queue in the M/M/c/K/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wq
Wq(o_mmckk)
```

Wq.o_MMCKM	<i>Returns the mean time spend in queue in the M/M/c/K/m queueing model</i>
------------	---

Description

Returns the mean time spend in queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wq(x, ...)
```

Arguments

x	a object of class o_MMCKM
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wq
Wq(o_mmckm)
```

Wq.o_MMInf	Returns the mean time spend in queue in the M/M/Infinite queueing model
------------	---

Description

Returns the mean time spend in queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wq(x, ...)
```

Arguments

- x a object of class o_MMInf
- ... additional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf](#).

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wq
Wq(o_mminf)
```

Wq.o_MMInfKK	<i>Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model</i>
--------------	--

Description

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wq(x, ...)
```

Arguments

x	a object of class o_MMInfKK
...	additional arguments

Details

Returns the mean time spend in queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
 John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wq
Wq(o_MMInfKK)
```

Wqq	Returns the mean time spend in queue when there is queue in a queueing model
-----	--

Description

Returns the mean time spend in queue when there is queue in a queueing model

Usage

```
Wqq(x, ...)
```

Arguments

- x a object of class o_MM1, o_MMC, o_MM1K, o_MMCK, o_MM1KK, o_MMCKK, o_MMCC, o_MMCKM, o_MMInfKK, o_MMInf
- ... additional arguments

Details

Returns the mean time spend in queue when there is queue in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

- [Wqq.o_MM1](#)
- [Wqq.o_MMC](#)
- [Wqq.o_MM1K](#)
- [Wqq.o_MMCK](#)
- [Wqq.o_MM1KK](#)
- [Wqq.o_MMCKK](#)
- [Wqq.o_MMCC](#)

```

Wqo.o_MMCKM
Wqo.o_MMInfKK
Wqo.o_MMInf

```

Examples

```

## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqo
Wqo(o_mm1)

```

Wqo.o_MM1	<i>Returns the mean time spend in queue when there is queue in the M/M/1 queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

Usage

```

## S3 method for class 'o_MM1'
Wqo(x, ...)

```

Arguments

x	a object of class o_MM1
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1 queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1.](#)

Examples

```
## See example 10.3 in reference [Sixto2004] for more details.
## create input parameters
i_mm1 <- NewInput.MM1(lambda=1/4, mu=1/3, n=0)

## Build the model
o_mm1 <- QueueingModel(i_mm1)

## Returns the Wqq
Wqq(o_mm1)
```

Wqq.o_MM1K	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

Usage

```
## S3 method for class 'o_MM1K'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1K
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1K.](#)

Examples

```
## See example 10.7 in reference [Sixto2004] for more details.
## create input parameters
i_mm1k <- NewInput.MM1K(lambda=5, mu=5.714, k=15)

## Build the model
o_mm1k <- QueueingModel(i_mm1k)

## Returns the Wqq
Wqq(o_mm1k)
```

Wqq.o_MM1KK	<i>Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK.](#)

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wqq
Wqq(o_mm1kk)
```

Wqq.o_MMC	<i>Returns the mean time spend in queue when there is queue in the M/M/c queueing model</i>
-----------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

Usage

```
## S3 method for class 'o_MMC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMC
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMC](#).

Examples

```
## See example 10.9 in reference [Sixto2004] for more details.
## create input parameters
i_mmc <- NewInput.MMC(lambda=5, mu=10, c=2, n=0, method=0)

## Build the model
o_mmc <- QueueingModel(i_mmc)

## Returns the Wqq
Wqq(o_mmc)
```

Wqq.o_MMCC	<i>Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

Usage

```
## S3 method for class 'o_MMCC'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCC
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/c queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCC.](#)

Examples

```
## See example 10.12 in reference [Sixto2004] for more details.
## create input parameters
i_mmcc <- NewInput.MMCC(lambda=3, mu=0.25, c=15)

## Build the model
o_mmcc <- QueueingModel(i_mmcc)

## Returns the Wqq
Wqq(o_mmcc)
```

Wqq.o_MMCK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model</i>
------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

Usage

```
## S3 method for class 'o_MMCK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCK.](#)

Examples

```
## See example 10.11 in reference [Sixto2004] for more details.
## create input parameters
i_mmck <- NewInput.MMCK(lambda=8, mu=4, c=5, k=12)

## Build the model
o_mmck <- QueueingModel(i_mmck)

## Returns the Wqq
Wqq(o_mmck)
```

Wqq.o_MMCKK	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

Usage

```
## S3 method for class 'o_MMCKK'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMCKK
...	aditional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKK](#).

Examples

```
## create input parameters
i_mmckk <- NewInput.MMCKK(lambda=8, mu=2, c=5, k=12, method=0)

## Build the model
o_mmckk <- QueueingModel(i_mmckk)

## Returns the Wqq
Wqq(o_mmckk)
```

Wqq.o_MMCKM	<i>Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model</i>
-------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

Usage

```
## S3 method for class 'o_MMCKM'
Wqq(x, ...)
```

Arguments

- x a object of class o_MMCKM
- ... additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/c/K/m queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMCKM](#).

Examples

```
## create input parameters
i_mmckm <- NewInput.MMCKM(lambda=0.25, mu=4, c=2, k=4, m=8, method=0)

## Build the model
o_mmckm <- QueueingModel(i_mmckm)

## Returns the Wqq
Wqq(o_mmckm)
```

Wqq.o_MMInf	<i>Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model</i>
-------------	--

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

Usage

```
## S3 method for class 'o_MMInf'
Wqq(x, ...)
```

Arguments

x	a object of class o_MMInf
...	additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MMInf.](#)

Examples

```
## create input parameters
i_mminf <- NewInput.MMInf(lambda=0.25, mu=4, n=0)

## Build the model
o_mminf <- QueueingModel(i_mminf)

## Returns the Wqq
Wqq(o_mminf)
```

Wqq.o_MMInfKK	Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model
---------------	---

Description

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

Usage

```
## S3 method for class 'o_MMInfKK'
Wqq(x, ...)
```

Arguments

- x a object of class o_MMInfKK
- ... additional arguments

Details

Returns the mean time spend in queue when there is queue in the M/M/Infinite/K/K queueing model

References

[Kleinrock1975] Leonard Kleinrock (1975).
Queueing Systems Vol 1: Theory.
John Wiley & Sons.

See Also

[QueueingModel.i_MMInfKK](#).

Examples

```
## create input parameters
i_MMInfKK <- NewInput.MMInfKK(lambda=0.25, mu=4, k=4)

## Build the model
o_MMInfKK <- QueueingModel(i_MMInfKK)

## Returns the Wqq
Wqq(o_MMInfKK)
```

WWs

Returns the normalized mean response time in a queueing model

Description

Returns the normalized mean response time in a queueing model

Usage

```
WWs(x, ...)
```

Arguments

x	a object of class o_MM1KK
...	additional arguments

Details

Returns the normalized mean response time in a queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004).
Investigacion Operativa. Modelos deterministicos y estocasticos.
 Editorial Centro de Estudios Ramon Areces.

See Also

[WWs.o_MM1KK.](#)

Examples

```
## create input parameters
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)

## Build the model
o_mm1kk <- QueueingModel(i_mm1kk)

## Returns the Wws
Wws(o_mm1kk)
```

Wws.o_MM1KK	Returns the normalized mean response time in the M/M/1/K/K queueing model
-------------	---

Description

Returns the normalized mean response time in the M/M/1/K/K queueing model

Usage

```
## S3 method for class 'o_MM1KK'
Wws(x, ...)
```

Arguments

- x a object of class o_MM1KK
- ... additional arguments

Details

Returns the normalized mean response time in the M/M/1/K/K queueing model

References

[Sixto2004] Sixto Rios Insua, Alfonso Mateos Caballero, M Concepcion Bielza Lozoya, Antonio Jimenez Martin (2004). *Investigacion Operativa. Modelos deterministicos y estocasticos*. Editorial Centro de Estudios Ramon Areces.

See Also

[QueueingModel.i_MM1KK](#).

Examples

```
## See example 10.13 in reference [Sixto2004] for more details.  
## create input parameters  
i_mm1kk <- NewInput.MM1KK(lambda=0.25, mu=4, k=2, method=3)  
  
## Build the model  
o_mm1kk <- QueueingModel(i_mm1kk)  
  
## Returns the WVs  
WVs(o_mm1kk)
```

Index

- *Topic **B_erlang**
 - B_erlang, [9](#)
- *Topic **C_erlang**
 - C_erlang, [27](#)
- *Topic **Closed Jackson Network**
 - CheckInput.i_CJN, [11](#)
 - Inputs.o_CJN, [29](#)
 - L.o_CJN, [46](#)
 - Lk.o_CJN, [72](#)
 - NewInput.CJN, [100](#)
 - QueueingModel.i_CJN, [131](#)
 - ROk.o_CJN, [164](#)
 - summary.o_CJN, [171](#)
 - Throughput.o_CJN, [188](#)
 - Throughputk.o_CJN, [216](#)
 - Throughputn.o_CJN, [223](#)
 - W.o_CJN, [266](#)
 - Wk.o_CJN, [291](#)
- *Topic **CompareQueueingModels**
 - CompareQueueingModels, [26](#)
- *Topic **Engset**
 - Engset, [28](#)
- *Topic **M/M/1/K/K**
 - CheckInput.i_MM1KK, [17](#)
 - Inputs.o_MM1KK, [36](#)
 - L.o_MM1KK, [53](#)
 - Lq.o_MM1KK, [81](#)
 - Lqq.o_MM1KK, [92](#)
 - NewInput.MM1KK, [108](#)
 - Pn.o_MM1KK, [121](#)
 - QueueingModel.i_MM1KK, [138](#)
 - RO.o_MM1KK, [150](#)
 - SP, [169](#)
 - SP.o_MM1KK, [170](#)
 - summary.o_MM1KK, [178](#)
 - Throughput.o_MM1KK, [194](#)
 - VN.o_MM1KK, [228](#)
 - VNq.o_MM1KK, [239](#)
 - VT.o_MM1KK, [250](#)
 - VTq.o_MM1KK, [258](#)
 - W.o_MM1KK, [272](#)
 - Wq.o_MM1KK, [300](#)
 - Wqq.o_MM1KK, [311](#)
 - Wws, [319](#)
 - Wws.o_MM1KK, [320](#)
- *Topic **M/M/1/K**
 - CheckInput.i_MM1K, [16](#)
 - Inputs.o_MM1K, [35](#)
 - L.o_MM1K, [52](#)
 - Lq.o_MM1K, [80](#)
 - Lqq.o_MM1K, [91](#)
 - NewInput.MM1K, [107](#)
 - Pn.o_MM1K, [120](#)
 - QueueingModel.i_MM1K, [137](#)
 - RO.o_MM1K, [149](#)
 - summary.o_MM1K, [177](#)
 - Throughput.o_MM1K, [193](#)
 - VN.o_MM1K, [227](#)
 - VNq.o_MM1K, [238](#)
 - VT.o_MM1K, [249](#)
 - VTq.o_MM1K, [257](#)
 - W.o_MM1K, [271](#)
 - Wq.o_MM1K, [299](#)
 - Wqq.o_MM1K, [310](#)
- *Topic **M/M/1**
 - CheckInput.i_MM1, [15](#)
 - Inputs.o_MM1, [34](#)
 - L.o_MM1, [51](#)
 - Lq, [78](#)
 - Lq.o_MM1, [79](#)
 - Lqq, [89](#)
 - Lqq.o_MM1, [90](#)
 - NewInput.MM1, [106](#)
 - Pn.o_MM1, [119](#)
 - QueueingModel.i_MM1, [136](#)
 - RO.o_MM1, [148](#)
 - summary.o_MM1, [176](#)
 - Throughput.o_MM1, [192](#)

- VN.o_MM1, 226
- VNq, 236
- VNq.o_MM1, 237
- VT.o_MM1, 248
- VTq, 255
- VTq.o_MM1, 256
- W.o_MM1, 270
- Wq, 297
- Wq.o_MM1, 298
- Wqq, 308
- Wqq.o_MM1, 309
- *Topic M/M/Infinite/K/K**
 - CheckInput.i_MMInfKK, 24
 - Inputs.o_MMInfKK, 43
 - L.o_MMInfKK, 60
 - Lq.o_MMInfKK, 88
 - Lqq.o_MMInfKK, 99
 - NewInput.MMInfKK, 115
 - Pn.o_MMInfKK, 128
 - QueueingModel.i_MMInfKK, 145
 - RO.o_MMInfKK, 157
 - summary.o_MMInfKK, 185
 - Throughput.o_MMInfKK, 201
 - VN.o_MMInfKK, 235
 - VNq.o_MMInfKK, 246
 - VT.o_MMInfKK, 254
 - VTq.o_MMInfKK, 264
 - W.o_MMInfKK, 279
 - Wq.o_MMInfKK, 307
 - Wqq.o_MMInfKK, 318
- *Topic M/M/Infinite**
 - CheckInput.i_MMInf, 23
 - Inputs.o_MMInf, 42
 - L.o_MMInf, 59
 - Lq.o_MMInf, 87
 - Lqq.o_MMInf, 98
 - NewInput.MMInf, 114
 - Pn.o_MMInf, 127
 - QueueingModel.i_MMInf, 144
 - RO.o_MMInf, 156
 - summary.o_MMInf, 184
 - Throughput.o_MMInf, 200
 - VN.o_MMInf, 234
 - VNq.o_MMInf, 245
 - VT.o_MMInf, 253
 - VTq.o_MMInf, 263
 - W.o_MMInf, 278
 - Wq.o_MMInf, 306
 - Wqq.o_MMInf, 317
- *Topic M/M/c/K/K**
 - CheckInput.i_MMCKK, 21
 - Inputs.o_MMCKK, 40
 - L.o_MMCKK, 57
 - Lq.o_MMCKK, 85
 - Lqq.o_MMCKK, 96
 - NewInput.MMCKK, 112
 - Pn.o_MMCKK, 125
 - QueueingModel.i_MMCKK, 142
 - RO.o_MMCKK, 154
 - summary.o_MMCKK, 182
 - Throughput.o_MMCKK, 198
 - VN.o_MMCKK, 232
 - VNq.o_MMCKK, 243
 - VTq.o_MMCKK, 262
 - W.o_MMCKK, 276
 - Wq.o_MMCKK, 304
 - Wqq.o_MMCKK, 315
- *Topic M/M/c/K/m**
 - CheckInput.i_MMCKM, 22
 - Inputs.o_MMCKM, 41
 - L.o_MMCKM, 58
 - Lq.o_MMCKM, 86
 - Lqq.o_MMCKM, 97
 - NewInput.MMCKM, 113
 - Pn.o_MMCKM, 126
 - QueueingModel.i_MMCKM, 143
 - RO.o_MMCKM, 155
 - summary.o_MMCKM, 183
 - Throughput.o_MMCKM, 199
 - VN.o_MMCKM, 233
 - VNq.o_MMCKM, 244
 - W.o_MMCKM, 277
 - Wq.o_MMCKM, 305
 - Wqq.o_MMCKM, 316
- *Topic M/M/c/K**
 - CheckInput.i_MMCK, 20
 - Inputs.o_MMCK, 39
 - L.o_MMCK, 56
 - Lq.o_MMCK, 84
 - Lqq.o_MMCK, 95
 - NewInput.MMCK, 111
 - Pn.o_MMCK, 124
 - QueueingModel.i_MMCK, 141
 - RO.o_MMCK, 153
 - summary.o_MMCK, 181
 - Throughput.o_MMCK, 197

VN.o_MMCK, 231

VNq.o_MMCK, 242

VTq.o_MMCK, 261

W.o_MMCK, 275

Wq.o_MMCK, 303

Wqq.o_MMCK, 314

***Topic M/M/c/c**

CheckInput.i_MMCC, 19

Inputs.o_MMCC, 38

L.o_MMCC, 55

Lq.o_MMCC, 83

Lqq.o_MMCC, 94

NewInput.MMCC, 110

Pn.o_MMCC, 123

QueueingModel.i_MMCC, 140

RO.o_MMCC, 152

summary.o_MMCC, 180

Throughput.o_MMCC, 196

VN.o_MMCC, 230

VNq.o_MMCC, 241

VT.o_MMCC, 252

VTq.o_MMCC, 260

W.o_MMCC, 274

Wq.o_MMCC, 302

Wqq.o_MMCC, 313

***Topic M/M/c**

CheckInput.i_MMC, 18

Inputs.o_MMC, 37

L.o_MMC, 54

Lq.o_MMC, 82

Lqq.o_MMC, 93

NewInput.MMC, 109

Pn.o_MMC, 122

QueueingModel.i_MMC, 139

RO.o_MMC, 151

summary.o_MMC, 179

Throughput.o_MMC, 195

VN.o_MMC, 229

VNq.o_MMC, 240

VT.o_MMC, 251

VTq.o_MMC, 259

W.o_MMC, 273

Wq.o_MMC, 301

Wqq.o_MMC, 312

***Topic MultiClass Closed Network**

CheckInput.i_MCCN, 12

Inputs.o_MCCN, 31

L.o_MCCN, 47

Lc.o_MCCN, 63

Lck.o_MCCN, 68

Lk.o_MCCN, 74

NewInput.MCCN, 102

QueueingModel.i_MCCN, 132

ROck.o_MCCN, 159

ROk.o_MCCN, 165

summary.o_MCCN, 172

Throughput.o_MCCN, 189

Throughputc.o_MCCN, 204

Throughputck.o_MCCN, 209

Throughputcn, 213

Throughputcn.o_MCCN, 214

Throughputk.o_MCCN, 217

W.o_MCCN, 267

Wc.o_MCCN, 282

Wck.o_MCCN, 287

Wk.o_MCCN, 293

***Topic MultiClass Mixed Network**

CheckInput.i_MCMN, 13

Inputs.o_MCMN, 32

L.o_MCMN, 48

Lc.o_MCMN, 64

Lck.o_MCMN, 69

Lk.o_MCMN, 75

NewInput.MCMN, 103

QueueingModel.i_MCMN, 134

ROck.o_MCMN, 160

ROk.o_MCMN, 166

summary.o_MCMN, 174

Throughput.o_MCMN, 190

Throughputc.o_MCMN, 205

Throughputck.o_MCMN, 210

Throughputk.o_MCMN, 219

W.o_MCMN, 268

Wc.o_MCMN, 283

Wck.o_MCMN, 288

Wk.o_MCMN, 294

***Topic MultiClass Open Network**

CheckInput.i_MCON, 14

Inputs.o_MCON, 33

L.o_MCON, 50

Lc.o_MCON, 65

Lck.o_MCON, 70

Lk.o_MCON, 76

NewInput.MCON, 105

QueueingModel.i_MCON, 135

ROck.o_MCON, 161

- ROk.o_MCON, 167
- summary.o_MCON, 175
- Throughput.o_MCON, 191
- Throughputc.o_MCON, 207
- Throughputck.o_MCON, 211
- Throughputk.o_MCON, 220
- W.o_MCON, 269
- Wc.o_MCON, 284
- Wck.o_MCON, 289
- Wk.o_MCON, 295
- *Topic **MultiClass Queueing Models**
 - Lck, 66
- *Topic **MultiClass Queueing Networks**
 - ROck, 158
- *Topic **MultiClass Queueing Network**
 - Lc, 62
 - Throughputc, 203
 - Throughputck, 208
 - Wc, 281
 - Wck, 286
- *Topic **Open Jackson Network**
 - CheckInput.i_OJN, 25
 - Inputs.o_OJN, 44
 - L.o_OJN, 61
 - Lk.o_OJN, 77
 - NewInput.OJN, 116
 - Pn.o_OJN, 129
 - QueueingModel.i_OJN, 146
 - ROk.o_OJN, 168
 - summary.o_OJN, 186
 - Throughput.o_OJN, 202
 - Throughputk.o_OJN, 221
 - W.o_OJN, 280
 - Wk.o_OJN, 296
- *Topic **Queueing Models**
 - CheckInput, 10
 - Inputs, 28
 - L, 45
 - Lk, 71
 - Pn, 118
 - QueueingModel, 130
 - RO, 147
 - Throughput, 187
 - VN, 225
 - VT, 247
 - W, 265
- *Topic **Queueing Networks**
 - ROk, 162
- *Topic **Queueing Network**
 - Throughputk, 215
 - Throughputn, 222
 - Wk, 290
- *Topic **queueing**
 - queueing-package, 8
- B_erlang, 9, 27, 28
- C_erlang, 10, 27
- CheckInput, 10
- CheckInput.i_CJN, 11, 132, 189, 217, 224
- CheckInput.i_MCCN, 12, 133, 190, 205, 210, 214, 218
- CheckInput.i_MCMN, 13, 134, 191, 206, 211, 219
- CheckInput.i_MCON, 14, 135, 192, 207, 212, 220
- CheckInput.i_MM1, 11, 15, 107, 136, 193
- CheckInput.i_MM1K, 11, 16, 107, 137, 194
- CheckInput.i_MM1KK, 11, 17, 108, 138, 195
- CheckInput.i_MMC, 11, 18, 109, 139, 196
- CheckInput.i_MMCC, 11, 19, 110, 140, 197
- CheckInput.i_MMCK, 11, 20, 111, 141, 198
- CheckInput.i_MMCKK, 11, 21, 112, 142, 199
- CheckInput.i_MMCKM, 11, 22, 113, 143, 200
- CheckInput.i_MMInf, 11, 23, 114, 144, 200
- CheckInput.i_MMInfKK, 11, 24, 115, 145, 201
- CheckInput.i_OJN, 11, 25, 146, 202, 222
- CompareQueueingModels, 26
- CompareQueueingModels2 (CompareQueueingModels), 26
- Engset, 28
- Inputs, 28
- Inputs.o_CJN, 29, 29
- Inputs.o_MCCN, 29, 31
- Inputs.o_MCMN, 29, 32
- Inputs.o_MCON, 29, 33
- Inputs.o_MM1, 29, 34
- Inputs.o_MM1K, 29, 35
- Inputs.o_MM1KK, 29, 36
- Inputs.o_MMC, 29, 37
- Inputs.o_MMCC, 29, 38
- Inputs.o_MMCK, 29, 39
- Inputs.o_MMCKK, 29, 40
- Inputs.o_MMCKM, 29, 41

Inputs.o_MMInf, 29, 42
 Inputs.o_MMInfFKK, 29, 43
 Inputs.o_OJN, 29, 44

L, 45

L.o_CJN, 46, 46
 L.o_MCCN, 46, 47
 L.o_MCMN, 46, 48
 L.o_MCON, 46, 50
 L.o_MM1, 46, 51
 L.o_MM1K, 46, 52
 L.o_MM1KK, 46, 53
 L.o_MMC, 46, 54
 L.o_MMCC, 46, 55
 L.o_MMCK, 46, 56
 L.o_MMCKK, 46, 57
 L.o_MMCKM, 46, 58
 L.o_MMInf, 46, 59, 156
 L.o_MMInfFKK, 46, 60
 L.o_OJN, 46, 61
 Lc, 62
 Lc.o_MCCN, 62, 63
 Lc.o_MCMN, 62, 64
 Lc.o_MCON, 62, 65
 Lck, 66
 Lck.o_MCCN, 67, 68
 Lck.o_MCMN, 67, 69
 Lck.o_MCON, 67, 70
 Lk, 71
 Lk.o_CJN, 72, 72
 Lk.o_MCCN, 72, 74
 Lk.o_MCMN, 72, 75
 Lk.o_MCON, 72, 76
 Lk.o_OJN, 72, 77
 Lq, 78
 Lq.o_MM1, 79, 79
 Lq.o_MM1K, 79, 80
 Lq.o_MM1KK, 79, 81
 Lq.o_MMC, 79, 82
 Lq.o_MMCC, 79, 83
 Lq.o_MMCK, 79, 84
 Lq.o_MMCKK, 79, 85
 Lq.o_MMCKM, 79, 86
 Lq.o_MMInf, 79, 87
 Lq.o_MMInfFKK, 79, 88
 Lqq, 89
 Lqq.o_MM1, 89, 90
 Lqq.o_MM1K, 89, 91
 Lqq.o_MM1KK, 89, 92

Lqq.o_MMC, 89, 93
 Lqq.o_MMCC, 89, 94
 Lqq.o_MMCK, 89, 95
 Lqq.o_MMCKK, 89, 96
 Lqq.o_MMCKM, 90, 97
 Lqq.o_MMInf, 90, 98
 Lqq.o_MMInfFKK, 90, 99

NewInput.CJN, 11, 12, 30, 100, 217, 224
 NewInput.MCCN, 13, 31, 102, 190, 205, 210, 214, 218
 NewInput.MCMN, 14, 32, 103, 191, 206, 211, 219
 NewInput.MCON, 15, 33, 105, 192, 207, 212, 220
 NewInput.MM1, 16, 34, 35, 106, 193
 NewInput.MM1K, 16, 17, 35, 107, 194
 NewInput.MM1KK, 17, 18, 36, 108, 195
 NewInput.MMC, 18, 37, 109, 196
 NewInput.MMCC, 19, 38, 110, 197
 NewInput.MMCK, 20, 39, 111, 198
 NewInput.MMCKK, 21, 40, 112, 199
 NewInput.MMCKM, 22, 41, 113, 200
 NewInput.MMInf, 23, 42, 114, 200
 NewInput.MMInfFKK, 24, 43, 115, 201
 NewInput.OJN, 25, 44, 116, 189, 202, 222
 NewInput2.CJN (NewInput.CJN), 100
 NewInput2.OJN (NewInput.OJN), 116
 NewInput3.CJN (NewInput.CJN), 100
 NewInput3.OJN (NewInput.OJN), 116

Pn, 118

Pn.o_MM1, 118, 119
 Pn.o_MM1K, 118, 120
 Pn.o_MM1KK, 118, 121
 Pn.o_MMC, 118, 122
 Pn.o_MMCC, 119, 123
 Pn.o_MMCK, 118, 124
 Pn.o_MMCKK, 118, 125
 Pn.o_MMCKM, 119, 126
 Pn.o_MMInf, 119, 127
 Pn.o_MMInfFKK, 119, 128
 Pn.o_OJN, 119, 129

Qn (Pn), 118

Qn.o_MM1, 118
 Qn.o_MM1 (Pn.o_MM1), 119
 Qn.o_MM1K, 118
 Qn.o_MM1K (Pn.o_MM1K), 120

- Qn.o_MM1KK, [118](#)
- Qn.o_MM1KK (Pn.o_MM1KK), [121](#)
- Qn.o_MMC, [118](#)
- Qn.o_MMC (Pn.o_MMC), [122](#)
- Qn.o_MMCC, [119](#)
- Qn.o_MMCC (Pn.o_MMCC), [123](#)
- Qn.o_MMCK, [118](#)
- Qn.o_MMCK (Pn.o_MMCK), [124](#)
- Qn.o_MMCKK, [118](#)
- Qn.o_MMCKK (Pn.o_MMCKK), [125](#)
- Qn.o_MMCKM, [119](#)
- Qn.o_MMCKM (Pn.o_MMCKM), [126](#)
- Qn.o_MMInf, [119](#)
- Qn.o_MMInf (Pn.o_MMInf), [127](#)
- Qn.o_MMInfKK, [119](#)
- Qn.o_MMInfKK (Pn.o_MMInfKK), [128](#)
- queueing (queueing-package), [8](#)
- queueing-package, [8](#)
- QueueingModel, [26](#), [130](#)
- QueueingModel.i_CJN, [47](#), [73](#), [101](#), [131](#), [164](#), [172](#), [189](#), [217](#), [224](#), [266](#), [292](#)
- QueueingModel.i_MCCN, [48](#), [64](#), [68](#), [74](#), [103](#), [132](#), [160](#), [165](#), [173](#), [190](#), [205](#), [210](#), [214](#), [218](#), [268](#), [283](#), [287](#), [293](#)
- QueueingModel.i_MCMN, [49](#), [65](#), [69](#), [75](#), [104](#), [134](#), [161](#), [167](#), [174](#), [191](#), [206](#), [211](#), [219](#), [269](#), [284](#), [289](#), [294](#)
- QueueingModel.i_MCON, [50](#), [66](#), [71](#), [77](#), [106](#), [131](#), [135](#), [162](#), [168](#), [175](#), [192](#), [207](#), [212](#), [220](#), [270](#), [285](#), [290](#), [295](#)
- QueueingModel.i_MM1, [51](#), [80](#), [90](#), [120](#), [131](#), [136](#), [148](#), [176](#), [193](#), [226](#), [237](#), [248](#), [256](#), [271](#), [299](#), [309](#)
- QueueingModel.i_MM1K, [52](#), [53](#), [81](#), [91](#), [121](#), [131](#), [137](#), [149](#), [177](#), [194](#), [227](#), [228](#), [238](#), [249](#), [257](#), [272](#), [300](#), [310](#)
- QueueingModel.i_MM1KK, [82](#), [92](#), [122](#), [131](#), [138](#), [150](#), [171](#), [178](#), [195](#), [239](#), [250](#), [258](#), [273](#), [300](#), [311](#), [320](#)
- QueueingModel.i_MMC, [54](#), [83](#), [93](#), [123](#), [131](#), [139](#), [151](#), [179](#), [196](#), [229](#), [240](#), [251](#), [259](#), [274](#), [301](#), [312](#)
- QueueingModel.i_MMCC, [55](#), [84](#), [94](#), [124](#), [131](#), [140](#), [152](#), [180](#), [197](#), [230](#), [241](#), [252](#), [260](#), [274](#), [302](#), [313](#)
- QueueingModel.i_MMCK, [56](#), [85](#), [95](#), [125](#), [131](#), [141](#), [153](#), [181](#), [198](#), [231](#), [242](#), [261](#), [275](#), [303](#), [314](#)
- QueueingModel.i_MMCKK, [57](#), [86](#), [96](#), [126](#), [131](#), [142](#), [154](#), [182](#), [199](#), [232](#), [243](#), [262](#), [276](#), [304](#), [315](#)
- QueueingModel.i_MMCKM, [58](#), [87](#), [97](#), [127](#), [131](#), [143](#), [155](#), [183](#), [200](#), [233](#), [244](#), [277](#), [305](#), [316](#)
- QueueingModel.i_MMInf, [59](#), [87](#), [98](#), [128](#), [131](#), [144](#), [156](#), [184](#), [200](#), [234](#), [245](#), [253](#), [263](#), [278](#), [306](#), [317](#)
- QueueingModel.i_MMInfKK, [60](#), [88](#), [99](#), [129](#), [131](#), [145](#), [157](#), [185](#), [201](#), [235](#), [246](#), [254](#), [264](#), [279](#), [307](#), [318](#)
- QueueingModel.i_OJN, [61](#), [78](#), [117](#), [130](#), [131](#), [146](#), [169](#), [186](#), [202](#), [222](#), [280](#), [297](#)
- RO, [147](#)
- RO.o_MM1, [147](#), [148](#)
- RO.o_MM1K, [147](#), [149](#)
- RO.o_MM1KK, [147](#), [150](#)
- RO.o_MMC, [147](#), [151](#)
- RO.o_MMCC, [147](#), [152](#)
- RO.o_MMCK, [147](#), [153](#)
- RO.o_MMCKK, [147](#), [154](#)
- RO.o_MMCKM, [147](#), [155](#)
- RO.o_MMInf, [147](#), [156](#)
- RO.o_MMInfKK, [147](#), [157](#)
- ROck, [158](#)
- ROck.o_MCCN, [159](#), [159](#)
- ROck.o_MCMN, [159](#), [160](#)
- ROck.o_MCON, [159](#), [161](#)
- ROk, [162](#)
- ROk.o_CJN, [163](#), [164](#)
- ROk.o_MCCN, [163](#), [165](#)
- ROk.o_MCMN, [163](#), [166](#)
- ROk.o_MCON, [163](#), [167](#)
- ROk.o_OJN, [163](#), [168](#)
- SP, [169](#)
- SP.o_MM1KK, [170](#), [170](#)
- summary.o_CJN, [171](#)
- summary.o_MCCN, [172](#)
- summary.o_MCMN, [174](#)
- summary.o_MCON, [175](#)
- summary.o_MM1, [176](#)
- summary.o_MM1K, [177](#)
- summary.o_MM1KK, [178](#)
- summary.o_MMC, [179](#)
- summary.o_MMCC, [180](#)
- summary.o_MMCK, [181](#)

summary.o_MMCKK, 182
 summary.o_MMCKM, 183
 summary.o_MMInf, 184
 summary.o_MMInfKK, 185
 summary.o_OJN, 186

Throughput, 187
 Throughput.o_CJN, 188, 188
 Throughput.o_MCCN, 188, 189
 Throughput.o_MCMN, 188, 190
 Throughput.o_MCON, 188, 191
 Throughput.o_MM1, 187, 192
 Throughput.o_MM1K, 187, 193
 Throughput.o_MM1KK, 187, 194
 Throughput.o_MMC, 187, 195
 Throughput.o_MMCC, 187, 196
 Throughput.o_MMCK, 187, 197
 Throughput.o_MMCKK, 187, 198
 Throughput.o_MMCKM, 187, 199
 Throughput.o_MMInf, 188, 200
 Throughput.o_MMInfKK, 187, 201
 Throughput.o_OJN, 188, 202
 Throughputc, 203
 Throughputc.o_MCCN, 204, 204
 Throughputc.o_MCMN, 205
 Throughputc.o_MCON, 204, 207
 Throughputck, 208
 Throughputck.o_MCCN, 208, 209
 Throughputck.o_MCMN, 208, 210
 Throughputck.o_MCON, 208, 211
 Throughputcn, 213
 Throughputcn.o_MCCN, 213, 214
 Throughputk, 215
 Throughputk.o_CJN, 216, 216
 Throughputk.o_MCCN, 216, 217
 Throughputk.o_MCMN, 216, 219
 Throughputk.o_MCON, 216, 220
 Throughputk.o_OJN, 216, 221
 Throughputn, 222
 Throughputn.o_CJN, 223, 223

VN, 225
 VN.o_MM1, 225, 226
 VN.o_MM1K, 225, 227
 VN.o_MM1KK, 225, 228
 VN.o_MMC, 225, 229
 VN.o_MMCC, 225, 230
 VN.o_MMCK, 225, 231
 VN.o_MMCKK, 225, 232

VN.o_MMCKM, 225, 233
 VN.o_MMInf, 225, 234
 VN.o_MMInfKK, 225, 235
 VNq, 236
 VNq.o_MM1, 236, 237
 VNq.o_MM1K, 236, 238
 VNq.o_MM1KK, 236, 239
 VNq.o_MMC, 240
 VNq.o_MMCC, 236, 241
 VNq.o_MMCK, 236, 242
 VNq.o_MMCKK, 236, 243
 VNq.o_MMCKM, 236, 244
 VNq.o_MMInf, 236, 245
 VNq.o_MMInfKK, 236, 246
 VT, 247
 VT.o_MM1, 247, 248
 VT.o_MM1K, 247, 249
 VT.o_MM1KK, 247, 250
 VT.o_MMC, 247, 251
 VT.o_MMCC, 247, 252
 VT.o_MMInf, 247, 253
 VT.o_MMInfKK, 247, 254
 VTq, 255
 VTq.o_MM1, 255, 256
 VTq.o_MM1K, 255, 257
 VTq.o_MM1KK, 255, 258
 VTq.o_MMC, 255, 259
 VTq.o_MMCC, 255, 260
 VTq.o_MMCK, 255, 261
 VTq.o_MMCKK, 255, 262
 VTq.o_MMInf, 255, 263
 VTq.o_MMInfKK, 255, 264

W, 265
 W.o_CJN, 266
 W.o_MCCN, 265, 267
 W.o_MCMN, 265, 268
 W.o_MCON, 265, 269
 W.o_MM1, 265, 270
 W.o_MM1K, 265, 271
 W.o_MM1KK, 265, 272
 W.o_MMC, 265, 273
 W.o_MMCC, 265, 274
 W.o_MMCK, 265, 275
 W.o_MMCKK, 265, 276
 W.o_MMCKM, 265, 277
 W.o_MMInf, 265, 278
 W.o_MMInfKK, 265, 279
 W.o_OJN, 265, 280

Wc, [281](#)
Wc.o_MCCN, [282](#), [282](#)
Wc.o_MCMN, [282](#), [283](#)
Wc.o_MCON, [282](#), [284](#)
Wck, [286](#)
Wck.o_MCCN, [286](#), [287](#)
Wck.o_MCMN, [286](#), [288](#)
Wck.o_MCON, [286](#), [289](#)
Wk, [290](#)
Wk.o_CJN, [291](#), [291](#)
Wk.o_MCCN, [291](#), [293](#)
Wk.o_MCMN, [291](#), [294](#)
Wk.o_MCON, [291](#), [295](#)
Wk.o_OJN, [291](#), [296](#)
Wq, [297](#)
Wq.o_MM1, [298](#), [298](#)
Wq.o_MM1K, [298](#), [299](#)
Wq.o_MM1KK, [298](#), [300](#)
Wq.o_MMC, [298](#), [301](#)
Wq.o_MMCC, [298](#), [302](#)
Wq.o_MMCK, [298](#), [303](#)
Wq.o_MMCKK, [298](#), [304](#)
Wq.o_MMCKM, [298](#), [305](#)
Wq.o_MMInf, [298](#), [306](#)
Wq.o_MMInfKK, [298](#), [307](#)
Wqq, [308](#)
Wqq.o_MM1, [308](#), [309](#)
Wqq.o_MM1K, [308](#), [310](#)
Wqq.o_MM1KK, [308](#), [311](#)
Wqq.o_MMC, [308](#), [312](#)
Wqq.o_MMCC, [308](#), [313](#)
Wqq.o_MMCK, [308](#), [314](#)
Wqq.o_MMCKK, [308](#), [315](#)
Wqq.o_MMCKM, [309](#), [316](#)
Wqq.o_MMInf, [309](#), [317](#)
Wqq.o_MMInfKK, [309](#), [318](#)
Wws, [319](#)
Wws.o_MM1KK, [319](#), [320](#)