

Chapter 5: CPU Scheduling



Chapter 5: CPU Scheduling


- Basic Concepts
- Scheduling Criteria
- Scheduling Algorithms
- Thread Scheduling
- Multiple-Processor Scheduling
- Real-Time CPU Scheduling
- Operating Systems Examples
- Algorithm Evaluation

Objectives


- To introduce CPU scheduling, which is the basis for multiprogrammed operating systems
- To describe various CPU-scheduling algorithms
- To discuss evaluation criteria for selecting a CPU-scheduling algorithm for a particular system
- To examine the scheduling algorithms of several operating systems

Basic Concepts

- Maximum CPU utilization obtained with multiprogramming
- CPU–I/O Burst Cycle – Process execution consists of a **cycle** of CPU execution and I/O wait
- **CPU burst** followed by **I/O burst**
- CPU burst distribution is of main concern



Histogram of CPU-burst Times



CPU Scheduler

- **Short-term scheduler** selects from among the processes in ready queue, and allocates the CPU to one of them
 - Queue may be ordered in various ways
- CPU scheduling decisions may take place when a process:
 1. Switches from running to waiting state
 2. Switches from running to ready state
 3. Switches from waiting to ready
 4. Terminates
- Scheduling under 1 and 4 is **nonpreemptive**
- All other scheduling is **preemptive**
 - Consider access to shared data
 - Consider preemption while in kernel mode
 - Consider interrupts occurring during crucial OS activities

Dispatcher

- Dispatcher module gives control of the CPU to the process selected by the short-term scheduler; this involves:
 - switching context
 - switching to user mode
 - jumping to the proper location in the user program to restart that program
- **Dispatch latency** – time it takes for the dispatcher to stop one process and start another running

Scheduling Criteria

- **CPU utilization** – keep the CPU as busy as possible
- **Throughput** – # of processes that complete their execution per time unit
- **Turnaround time** – amount of time to execute a particular process
- **Waiting time** – amount of time a process has been waiting in the ready queue
- **Response time** – amount of time it takes from when a request was submitted until the first response is produced, not output (for time-sharing environment)

Scheduling Algorithm Optimization Criteria

- Max CPU utilization
- Max throughput
- Min turnaround time
- Min waiting time
- Min response time

First- Come, First-Served (FCFS) Scheduling


<u>Process</u>	<u>Burst Time</u>
----------------	-------------------

P_1	24
-------	----

P_2	3
-------	---

P_3	3
-------	---

- Suppose that the processes arrive in the order: P_1, P_2, P_3
The Gantt Chart for the schedule is:




- Waiting time for $P_1 = 0$; $P_2 = 24$; $P_3 = 27$
- Average waiting time: $(0 + 24 + 27)/3 = 17$

FCFS Scheduling (Cont.)

Suppose that the processes arrive in the order:

$$P_2, P_3, P_1$$

- The Gantt chart for the schedule is:



- Waiting time for $P_1 = 6$; $P_2 = 0$; $P_3 = 3$
- Average waiting time: $(6 + 0 + 3)/3 = 3$
- Much better than previous case
- **Convoy effect** - short process behind long process
 - Consider one CPU-bound and many I/O-bound processes


Shortest-Job-First (SJF) Scheduling

- Associate with each process the length of its next CPU burst
 - Use these lengths to schedule the process with the shortest time
- SJF is optimal – gives minimum average waiting time for a given set of processes
 - The difficulty is knowing the length of the next CPU request
 - Could ask the user

Example of SJF

	<u>Process</u>	<u>Burst Time</u>
P_1	6	
P_2	8	
P_3	7	
P_4	3	

- SJF scheduling chart




- Average waiting time = $(3 + 16 + 9 + 0) / 4 = 7$

Determining Length of Next CPU Burst

- Can only estimate the length – should be similar to the previous one
 - Then pick process with shortest predicted next CPU burst
- Can be done by using the length of previous CPU bursts, using exponential averaging
 1. t_n = actual length of n^{th} CPU burst
 2. τ_{n+1} = predicted value for the next CPU burst
 3. $\alpha, 0 \leq \alpha \leq 1$
 4. Define : $\tau_{n+1} = \alpha t_n + (1 - \alpha)\tau_n$.
- Commonly, α set to $\frac{1}{2}$
- Preemptive version called **shortest-remaining-time-first**

Prediction of the Length of the Next CPU Burst



CPU burst (t_i)	6	4	6	4	13	13	13	...	
"guess" (τ_i)	10	8	6	6	5	9	11	12	...

Examples of Exponential Averaging

- $\alpha = 0$
 - $\tau_{n+1} = \tau_n$
 - Recent history does not count
- $\alpha = 1$
 - $\tau_{n+1} = \alpha t_n$
 - Only the actual last CPU burst counts

- If we expand the formula, we get:

$$\begin{aligned}\tau_{n+1} = & \alpha t_n + (1 - \alpha)\alpha t_{n-1} + \dots \\ & + (1 - \alpha)^j \alpha t_{n-j} + \dots \\ & + (1 - \alpha)^{n+1} \tau_0\end{aligned}$$

- Since both α and $(1 - \alpha)$ are less than or equal to 1, each successive term has less weight than its predecessor

Example of Shortest-remaining-time-first

- Now we add the concepts of varying arrival times and preemption to the analysis

	<u>Process</u>	<u>Arrival Time</u>	<u>Burst Time</u>
P_1	0	8	
P_2	1	4	
P_3	2	9	
P_4	3	5	

- Preemptive* SJF Gantt Chart



- Average waiting time = $[(10-1)+(1-1)+(17-2)+(5-3)]/4 = 26/4 = 6.5 \text{ msec}$
- Average turnaround time = $[(17-0)+(5-1)+(26-2)+(10-3)]/4 = (17+4+24+7)/4 = 52/4 = 12.4 \text{ ms}$
- Alternative, Avg waiting time = $[(17-8)+(4-4)+(24-9)+(7-5)]/4 = (9+0+15+2)/4 = 26/4 = 6.5 \text{ ms}$


Priority Scheduling

- A priority number (integer) is associated with each process
- The CPU is allocated to the process with the highest priority (smallest integer \equiv highest priority)
 - Preemptive
 - Nonpreemptive
- SJF is priority scheduling where priority is the inverse of predicted next CPU burst time
- Problem \equiv **Starvation** – low priority processes may never execute
- Solution \equiv **Aging** – as time progresses increase the priority of the process

Example of Priority Scheduling

	<u>Process</u>	<u>Burst Time</u>	<u>Priority</u>
P_1	10	3	
P_2	1	1	
P_3	2	4	
P_4	1	5	
P_5	5	2	

- Priority scheduling Gantt Chart



- Average waiting time = $(6+0+16+18+1)/5=41/5=8.2$ ms
- Average turnaround time = $(16+1+18+19+6)/5=60/5=12$ ms

Round Robin (RR)

- Each process gets a small unit of CPU time (**time quantum q**), usually 10-100 milliseconds. After this time has elapsed, the process is preempted and added to the end of the ready queue.
- If there are n processes in the ready queue and the time quantum is q , then each process gets $1/n$ of the CPU time in chunks of at most q time units at once. No process waits more than $(n-1)q$ time units.
- Timer interrupts every quantum to schedule next process
- Performance
 - q large \Rightarrow FIFO
 - q small $\Rightarrow q$ must be large with respect to context switch, otherwise overhead is too high

Example of RR with Time Quantum = 4


Process Burst Time

P_1 24

P_2 3

P_3 3

- The Gantt chart is:



- Avg. waiting time is $17/3=5.66$ ms.
- Typically, higher average turnaround than SJF, but better *response*
- q should be large compared to context switch time
- q usually 10ms to 100ms, context switch < 10 usec


Round Robin (RR)

- **Completion Time:** Time at which process completes its execution.
- **Turn Around Time:** Time Difference between completion time and arrival time. **Turn Around Time = Completion Time – Arrival Time**
- **Waiting Time(W.T):** Time Difference between turn around time and burst time. **Waiting Time = Turn Around Time – Burst Time**

Example-1: Consider the following table of arrival time and burst time for four processes **P1, P2, P3, and P4** and given **Time Quantum = 2**

Process	Burst Time	Arrival Time
P1	5 ms	0 ms
P2	4 ms	1 ms
P3	2 ms	2 ms
P4	1 ms	4 ms


Round Robin (RR)




Processes	AT	BT	CT	TAT	WT
P1	0	5	12	$12 - 0 = 12$	$12 - 5 = 7$
P2	1	4	11	$11 - 1 = 10$	$10 - 4 = 6$
P3	2	2	6	$6 - 2 = 4$	$4 - 2 = 2$
P4	4	1	9	$9 - 4 = 5$	$5 - 1 = 4$

- *Average Turn around time* = $(12 + 10 + 4 + 5)/4 = 31/4 = 7.7$
- *Average waiting time* = $(7 + 6 + 2 + 4)/4 = 19/4 = 4.7$

Time Quantum and Context Switch Time



Turnaround Time Varies With The Time Quantum



process	time
P_1	6
P_2	3
P_3	1
P_4	7


80% of CPU bursts
should be shorter than q

Multilevel Queue

- Ready queue is partitioned into separate queues, eg:
 - **foreground** (interactive)
 - **background** (batch)
- Process permanently in a given queue
- Each queue has its own scheduling algorithm:
 - foreground – RR
 - background – FCFS
- Scheduling must be done between the queues:
 - Fixed priority scheduling; (i.e., serve all from foreground then from background). Possibility of starvation.
 - Time slice – each queue gets a certain amount of CPU time which it can schedule amongst its processes; i.e., 80% to foreground in RR
 - 20% to background in FCFS

Multilevel Queue Scheduling

highest priority



lowest priority

Multilevel Feedback Queue

- A process can move between the various queues; aging can be implemented this way
- Multilevel-feedback-queue scheduler defined by the following parameters:
 - number of queues
 - scheduling algorithms for each queue
 - method used to determine when to upgrade a process
 - method used to determine when to demote a process
 - method used to determine which queue a process will enter when that process needs service

Example of Multilevel Feedback Queue

- Three queues:
 - Q_0 – RR with time quantum 8 ms
 - Q_1 – RR time quantum 16 ms
 - Q_2 – FCFS
- Scheduling
 - A new job enters queue Q_0 which is served FCFS
 - 4 When it gains CPU, job receives 8 ms
 - 4 If it does not finish in 8 ms, job is moved to queue Q_1
 - At Q_1 job is again served FCFS and receives 16 additional milliseconds
 - 4 If it still does not complete, it is preempted and moved to queue Q_2

