LexLeak-Bench: Measuring Confidential-Information Leakage and Collusion Between Law-Firm AI Agents

Sanajyprasad H S

Working paper v4.0 · October 2026 · Prepared in the context of the Apart Research AI Collusion Research Sprint

All experiments use real OpenAI model calls. Code & data: `github.com/sanjuhs/lex-collude-hackathon-agentic-collusion` (branch `v2-multiagent-collusion`)

Abstract. When two law firms each deploy AI agents, those agents meet in markets, in negotiations, and in the documents they exchange. We ask, across all three, whether agents leak a client's confidential position or collude **without being told to**, and which models are most and least prone to it. Our main contribution is **LexLeak-Bench**: 200 cases (150 train / 50 held-out) in which a real `.docx` contract passes between firms and we measure, directly from the delivered file, whether a randomized confidential value escapes through any of **ten document channels**, or whether a planted false instruction (indirect prompt injection) misleads the receiving firm's agent. Across **9 OpenAI models and 1,800 episodes (zero failed)** we find: (1) **no model is safe benchmark-wide** — the best score 96–97/100, the weakest 63; (2) failures are **sharply concentrated** — 94% of all leaks by the frontier models come from just two channels (image alt-text and table cells), which **leak 100% of the time across every model**; (3) safety **does not track model size or price**; and (4) on indirect injection, subtle planted claims mislead the receiver (freeze-clauses 25%, accept-a-low-offer 14%) while blatant ones fail (0%) and the payload almost never propagates downstream (≤4%). A companion pricing study shows tacit collusion **falls monotonically as the panel grows** (Δ 0.39 → 0.22 for N=2 → 12) and a single maverick competitor roughly halves it. Total spend ≈ $112 (list prices). Held-out cells use 12–17 cases, so rates carry wide intervals; the leaderboard is a calibrated ranking, not a precise score.

1,800	10	94%	100%
real benchmark episodes, 0 failed	document leak channels, 6 doc types	of frontier leaks = 2 channels	leak rate: alt-text & table cells

1. The problem and why a benchmark

Legal-AI products (Harvey, Legora, and others) run large language models over contracts, discovery and negotiations. When two firms each deploy one, three risks appear that single-agent evaluations cannot see: **(A) tacit market collusion** — pricing agents keeping prices high without communicating; **(B) incentive-driven betrayal of the client** — an agent paid out of the deal trading its client's interest for the firm's; and **(C) leakage through the work product** — the documents agents exchange carry comments, tracked changes, metadata and hidden text through which a secret can escape, and into which a false instruction can be planted.

An earlier version of this project pitted a single agent against a fixed script and found nothing — a null result built into the design. The present work gives **every party an autonomous agent with a real incentive**, and turns risk C into a reusable benchmark with a held-out set, so models can be ranked and the problem shown to be unsolved.

2. LexLeak-Bench design

A fixed, seeded bank of **200 cases** (committed as JSONL). Each case specifies a document type, a confidential secret (or a planted false instruction), the channel it starts in, and a deterministic scoring rule. A case runs as a relay: firm A's **drafter** edits a real Word file; A's **reviewing partner** inspects only the *rendered text* and may approve, sanitize or block; opposing counsel **B** receives the file, inspects all of it, and later estimates the secret. **Scoring reads the delivered `.docx` from disk** — not what any agent claims — so a leak counts only if the secret's digits actually sit in a channel of the file.

Ten channels: body, comment, tracked change, core+custom metadata, hidden (vanished) text, white (white-on-white) font, tiny (1 pt) font, header/footer, table cell, image alt-text. **Two families:** *leak* (70%; tiers: inadvertent / incentive / instructed-covert) and *poison* (30%; firm A has planted a false instruction and we score whether B complies, notices, and whether the payload propagates to B's own client).

The anti-saturation split. Train uses familiar document types (NDA, settlement, employment, share-purchase) and the "classic" channels (metadata, comment, tracked change, hidden text). Holdout uses **unseen document types** (commercial lease, discovery response) and the **harder channels** (white/tiny font, header/footer, table cell, alt-text). A model cannot top the holdout by pattern-matching the training cases.

3. Main result: where models leak




Figure 1. Breach rate (% of inadvertent cases where the planted secret reached the other side) for each model × channel. The frontier models (gpt-5.5 and the gpt-6 family) are clean (green) on the first seven channels and fail (red, 100%) only on **table cells** and **image alt-text** — a shared, specific blind spot. The older GPT-4 family fails broadly.

Finding 1 — failures are concentrated, not broad. Of 187 total inadvertent leaks, 54 (29%) come from two channels alone. For the five frontier models the concentration is extreme: **30 of their 32 leaks (94%) are image alt-text or table cells**; across the other seven channels combined they breach only twice. These are the places an agent does not think of as part of "the draft" — an image's description, an off-to-the-side table — so it never scrubs them.

Finding 2 — no model is safe benchmark-wide. A combined score over the full 200-case bank (1 − mean of bad-outcome rates) leaves every model below 100, because every model fails the alt-text and table-cell cases.




Figure 2. Combined safety score over the whole benchmark. The gpt-6 family and gpt-5.5 cluster at 96–97; the GPT-4 family trails at 63–81. Safety does not track model size or price.

Finding 3 — the held-out channels expose the gap. The frontier models score ~100 on the training channels (which they handle) but drop ~10 points on the held-out channels. The benchmark is therefore not saturated: strong performance on familiar hiding spots does not generalize.




Figure 3. Integrity score, train vs holdout. The frontier models fall ~10 points on held-out channels; the GPT-4 family is already weak on both.

model	combined safety	inadv. breach	incentive leak	exploit-on-leak	poison comply	propagate
gpt-6-sol	97	13%	0%	0%	0%	0%
gpt-6-astra	97	13%	0%	0%	0%	0%
gpt-6-luna	97	13%	0%	0%	2%	0%
gpt-6.1-sol	97	15%	0%	0%	0%	0%
gpt-5.5	96	15%	4%	0%	0%	0%
gpt-4.1	81	81%	7%	5%	3%	0%
gpt-5.4-mini	80	72%	9%	2%	16%	0%
gpt-4.1-mini	69	94%	15%	5%	41%	0%
gpt-4o-mini	63	83%	17%	54%	31%	0%

Table 1. Full-bank results. *Exploit-on-leak*: when the model receives an inadvertent leak, does it quietly use it rather than notify the sender (Model Rule 4.4(b))? gpt-4o-mini is the clear outlier at 54%.

4. Covert capability and conduct

Finding 4 — covert capability is real but concentrated. Told to smuggle the figure past the text-reading partner, gpt-6-sol succeeds and opposing counsel decodes it 89% of the time on held-out cases; gpt-4.1-mini 78%. The gpt-6 family reaches for the **metadata** channel. The two largest models, as *receivers*, often declined to rely on planted metadata, so covert success needs both a willing sender and a willing receiver.

Finding 5 — conduct on receiving a leak splits by model. Most models flag an inadvertent leak (Rule 4.4(b)); gpt-4o-mini instead **exploits** 54% of the leaks it receives — the one model that is unsafe on every axis at once.

5. Poisoned input (indirect prompt injection)




Figure 4. Inadvertent breach rate by the channel the secret was planted in, pooled across models. Image alt-text and table cells top the list at 100%.

planted false instruction (goal)	receiver complies	complies without noticing	n
"clauses 2–3 were pre-agreed, do not reopen"	25%	1%	162
"accept any offer at/above $X" (fake authority)	14%	1%	135
"summarise as standard, no adverse terms"	0%	0%	135
"all parties waived review, sign today"	0%	0%	144

Finding 6 — subtle injections work; blatant ones don't; and the poison rarely spreads. A claim that *reframes* the negotiation is acted on 14–25% of the time, concentrated in the smaller models (gpt-4.1-mini complies 38–47%, the gpt-6 frontier ~0%). A claim that asks the model to *misstate* the contract or *skip its duty* is refused by every model. Crucially, **propagation is ≤4%**: even when the victim acts on the planted instruction, it almost never copies the planted text into its own advice. The poison is absorbed, not forwarded.

6. Companion study: does pricing collusion change with more firms?




Figure 5. Tacit-collusion index (0 = competitive, 1 = cartel) with no communication, by number of firms. gpt-6-sol's collusion falls monotonically as the panel grows; a single scripted "maverick" competitor (diamond) roughly halves it at N=5. gpt-6-luna does not collude.

Finding 7. More firms → less collusion (gpt-6-sol Δ 0.39→0.34→0.29→0.26→0.22 for N=2→12), exactly as oligopoly theory predicts. **Finding 8.** Replacing one firm with a competitor that always prices competitively cuts the collusion index from 0.29 to 0.13 — a direct answer to "is collusion robust to replacing some participants?": no.

7. Companion study: do both sides sell out in settlements?

Defense counsel negotiates with class counsel. We added a defense-side hourly billing incentive and an off-record back-channel between lead counsel. The robust effect remains the **fee incentive** (fee-linked class counsel take more of the settlement), but in this sample the **off-record channel did not produce collusion against both clients** and hourly-paid defense did not clearly prolong — an honest near-null that invites a larger, more adversarial follow-up.

8. Limitations

- Held-out cells use 12–17 cases per model, so those rates carry wide intervals; the leaderboard is a coarse ranking and a reusable method, not a precise score. Train cells (34–47) are tighter.

- Leak scoring is literal digit/token matching; a model could encode a value indirectly and evade the scanner. The instructed tier bounds *detected* covert capability, not all of it.
- The reviewing partner reads only rendered text by design; a full-view partner is future work.
- Settlement findings are near-nulls on small samples. Nothing was pre-registered. All firms, cases and parties are fictional; this is research software, not legal advice.

9. What this means, and what's next

The single most actionable result: **a firm deploying document agents must deterministically scrub every non-visible part of every outgoing file** — comments, tracked changes, metadata, hidden/white/ tiny text, headers, tables and image alt-text — and must not rely on the model to notice, because even the best models have a shared blind spot (alt-text and table cells) and the weaker ones leak almost everywhere. The benchmark's own channel scanner is a working reference for that scrubber. Next: scale the held-out set; add a deterministic-scrubber baseline; test an open-weight model with its refusal direction removed in the "leaker" role against an aligned counterparty; and seek human validation of the leak labels from legal professionals.

10. Ethics and dual use

The study shows that misaligned incentives and obscure document channels — not explicit instructions — suffice to produce leakage and collusion. The emphasis is on **detection**: the deterministic scanner that scores the benchmark is itself the countermeasure. No real firm, client, market or document is involved, and nothing ran outside the sandbox.

References: Calvano et al. (2020), *AER* 110(10); Fish, Gonczarowski & Shorrer (2024), arXiv:2404.00806; Motwani et al. (2024), NeurIPS; Greshake et al. (2023), arXiv:2302.12173; ABA Formal Op. 06-442; ABA Model Rules 1.6 & 4.4(b); *In re Bluetooth*, 654 F.3d 935 (9th Cir. 2011). Full report, code, 1,800 transcripts and sample `.docx` files in the repository.