

- I. One source code file can include more than one class.
- II. Package statement should come before class and import statements.
- III. One source code file can include more than one package.

Which is/are true based on the above scenario?

Select any one of given answer :

☐ Choice A	Only II.
☐ Choice B	Only III.
☐ Choice C	Only I and II.
☐ Choice D	Only I and III.
☐ Choice E	None.

The answer is: C

Consider following interface:

```
1. interface Movable{  
2. static int speed = 12;  
3. String s = "speed: ";  
4. }
```

Which of the following is a valid statement?

Select any one of given answer :

☐ Choice A	<code>new Movable().s;</code>
☐ Choice B	<code>Movable.speed = 10;</code>
☐ Choice C	<code>System.out.println(Movable.s);</code>
☐ Choice D	Given interface is invalid.

The answer is: C

You need to generate random numbers between 0 and 100. Which Java Class can achieve this goal?

Select any one of given answer :

☐ Choice A	<code>java.util.Math</code>
☐ Choice B	<code>java.lang.Object</code>
☐ Choice C	<code>java.lang.Integer</code>
☐ Choice D	<code>java.lang.Random</code>
☐ Choice E	<code>java.util.Random</code>

The answer is: E

Code:

```
1. public class MyExamCloud{
2. static int x = 16;
3. public static void main(String args[]){
4. MyExamCloud mec = new MyExamCloud ();
5. mec.x = 4;
6. int y = x/mec.x;
7. System.out.print("y = ");
8. System.out.print();
9. System.out.print(y);
10. }
11. }
```

What will be the result?

Select any one of given answer :

☐ Choice A	y = 1
☐ Choice B	y = 2
☐ Choice C	y = 4
☐ Choice D	An exception is thrown.
☐ Choice E	Compilation fails due to an error on line 8.

The answer is: E

Which of the following/followings is true about java?

Select any one of given answer :

☐ Choice A	Source code file can have only one public class.
☐ Choice B	Source code can contains only one class.
☐ Choice C	Source code may contain more than one package statement.
☐ Choice D	Source code name should have .class extention.
☐ Choice E	All of above.

The answer is: A

Code :

```
class Test {  
  
    public static void main(String args[]) {  
        int[] i = { 1, 2, 3, 4, 5 };  
        float[] j = new float[5];  
  
        for (int k = 0; k<j.length(); k++) {  
            i[k] = (char) j[k];  
            System.out.println(i[k]);  
        }  
    }  
}
```

What will be the result of an attempt to compile and run this program?

Select any one of given answer :

☐ Choice A	Compiler error - char cannot be assigned to int
☐ Choice B	Compiler error - Array j is not initialized
☐ Choice C	ArrayIndexOutOfBoundsException at runtime
☐ Choice D	Prints 0 five times
☐ Choice E	Prints 0.0 five times

The answer is: B

Code:

```
1. class MyExamCloud{
2.
3. public static void main(String[] args){
4. byte count = 0;
5. while (true) {
6. System.out.println( count++ + "");
7. }
8. }
9. }
```

Which is the output?

Select any one of given answer :

☐ Choice A	Prints 0 to 127
☐ Choice B	Infinite loop prints nothing
☐ Choice C	Prints 0 to 127 and -128 to 0 once
☐ Choice D	Infinite loop prints 0 to 127 and -128 to 0
☐ Choice E	Compilation fails.

The answer is: D

Code:

```
1. class MyExamCloud{
2. public static void main(String [] args){
3. int y=10;
4. int x = 10;
5. if(x!=10 && y++==1);
6. if(y==11 | ++x==11) y+=10;
7. System.out.print(y);
8. }
9. }
```

What is the result?

Select any one of given answer :

☐ Choice A	11
☐ Choice B	10
☐ Choice C	20
☐ Choice D	21
☐ Choice E	Compilation fails

The answer is: C

Code:

```
1. public class MyExamCloud{  
2. public static void main(String[] args){  
3.  
4. int[] numbers = {1,2,3,4,5};  
5. // insert here  
6. System.out.print(i);  
7. }  
8. }
```

Which insert at line 5, will provide following output?

12345

Select any one of given answer :

☐ Choice A	for(int i : numbers);
☐ Choice B	for(int i ; numbers)
☐ Choice C	for(i : numbers)
☐ Choice D	for(numbers : int i)
☐ Choice E	for(int i : numbers)

The answer is: E

```

1.  import java.util.Random;
2.  import java.lang.System;
3.  import java.util.*;
4.  import java.lang.*;
5.
6.  public class MyExamCloud {
7.
8.      public static void main(String[] args) {
9.          Random r = new Random();
10.         System.out.println(r.nextInt(10));
11.
12.     }
13.}

```

Which lines contains redundant imports that not necessary for this code to compile?

Select any one of given answer :

☐ Choice A	Online lines 1 and 2
☐ Choice B	Online lines 1,2 and 3
☐ Choice C	Online lines 2,3 and 4
☐ Choice D	Online lines 1,3 and 4
☐ Choice E	All

The answer is: C