

Given:

```
String test = "a";  
for (; test.compareTo ("aaa") == 0; test = test + "a")  
    System.out.print (test.length () + " ");  
System.out.print (test);
```

What is the output?

- ☐ A. Compilation fails
- ☐ B. 1 2 3 aaaa
- ☐ C. 1 2 aaa
- ☐ D. a

The answer is: D. a

Given the code fragment:

```
boolean checkOut = true;  
int days = 0;  
while (checkOut) {  
    days++;  
    if (days > 3) {  
        checkOut = false;  
    }  
}  
System.out.print (days);
```

What is the result?

- ☐ A. 3
- ☐ B. The program executes an infinite number of times.
- ☐ C. 2
- ☐ D. 4

The answer is: D.4

Given the code fragment:

```
Random r1 = new Random(10);  
Random r2 = new Random(10); // line n1  
  
if (r1.nextInt() == r2.nextInt()) {  
    System.out.println("Jack");  
} else {  
    System.out.println("Queen");  
}
```

What is the result?

- ☐ A. A compilation error occurs at line n1.
- ☐ B. The program prints either Jack or Queen.
- ☒ C. Jack
- ☐ D. Queen

~~The answer is: D. Queen~~

The ans is jack cause its int and == operator

Given the code fragment:

```
int[] arr = {1, 2, 3, 4, 5};
```

Which for loop statement can be used to print 135?

- ☐ A. for(int idx = 1; idx < arr.length; idx+=2) {
 System.out.print (arr[idx]);
}
- ☐ B. for(int idx = 0; idx < arr.length; idx+=2) {
 System.out.print (arr[idx]);
}
- ☐ C. for(int idx = 0; idx < arr.length; idx++) {
 System.out.print (arr[idx]);
}
- ☐ D. for(int idx = 1; idx < arr.length-1; idx++) {
 System.out.print (arr[idx++]);
}

The answer is: B

Which two components can class declarations include?

- ☐ A. A list of instance methods
 - ☐ B. The main method
 - ☐ C. The public modifier
 - ☐ D. Interfaces implemented by the class
-

The Answer is: C and D

Given the code fragment:

```
String[] codes = {"CA", "JP", "US", "CA", "UK"};
int count = 0;
for (String c : codes) {
    if (c.equals("CA")) {
        continue;
    } else {
        count++;
    }
}
System.out.println(count);
```

What is the result?

- ☐ A. 3
- ☐ B. A compilation error occurs.
- ☐ C. 2
- ☐ D. 0

The answer is: A

Given the code fragment:

```
// line n1
switch (var) {
    case "1":
        System.out.println ("one");
        break;
}
```

Which code fragment, when inserted at line n1, enables the code to print one?

- ☐ A. char var = '1';
- ☐ B. String var = 1;
- ☐ C. String var = "1";
- ☐ D. int var = 1;

The answer is: C

