


Test Execution Report — DemoQA + ReqRes Automation

- **Author:** Sanjushree Rajan
- **Date:** August 8, 2026
- **Tool:** Playwright (chromium)
- **Total tests:** 4
- **Result:** 4 passed, 0 failed

Screenshots



Scope

Two flows were automated per the assignment brief:

1. UI — DemoQA Book Store: manual user login, search, capture book details, logout.
2. API — reqres.in: create, fetch, and update a user via CRUD requests.

Results

#	Test	File	Status	Duration
1	create a user and validate status code + store userId	api-reqres.spec.js	Pass	1.0s
2	get the created user and validate the response	api-reqres.spec.js	Pass	387ms
3	update the user name and validate the response	api-reqres.spec.js	Pass	265ms
4	login, search book, capture details, logout	ui-bookstore.spec.js	Pass	11.8s

UI flow details

- Logged in with a manually created DemoQA account.
- Confirmed username and logout button rendered after login.
- Navigated to the Book Store, searched “Learning JavaScript Design Patterns”.
- Confirmed the result row appeared and contained the book.
- Captured Title, Author, and Publisher into `output/book-details.txt`.
- Logged out and confirmed redirect back to the login page.

Captured output:

Title: Learning JavaScript Design Patterns
Author: Addy Osmani
Publisher: O'Reilly Media




Figure 1: Login success




Figure 2: Book search result




Figure 3: Logout success

API flow details

- **Create:** POST /api/users → 201, response echoed the submitted name and job, id stored for later steps.
- **Get:** GET /api/users/{id} → 200. reqres.in's seed data only covers ids 1–12, so the test falls back to a known seed id when the created id falls outside that range — this is expected reqres.in behaviour, not a bug in the suite.
- **Update:** PUT /api/users/{id} → 200, response reflected the new name and an updated timestamp.

API tests passing

Figure 4: API tests passing

Issues found during development and how they were resolved

Issue	Cause	Fix
UI test failing on <code>toBeVisible()</code> for the book search row	DemoQA changed the book table from a div-based react-table (<code>.rt-tr-group</code>) to a semantic HTML <code><table></code>	Switched the locator to <code>page.getByRole('row', { name: ... })</code>
API tests returning 403	Hardcoded API key was a shared/public tutorial key, throttled due to overuse across many projects	Signed up for a personal reqres.in account and key, moved it to <code>.env</code>
API tests still returning 403 after key rotation	<code>.env</code> wasn't actually being loaded — <code>dotenv</code> wasn't wired into <code>playwright.config.js</code>	Added <code>require('dotenv').config()</code> as the first line of <code>playwright.config.js</code>
API key hardcoded in source	Original spec had a fallback key baked into the code	Removed the fallback, added a <code>beforeAll</code> check that fails fast with a clear message if <code>REQRES_API_KEY</code> isn't set

Notes

- `.env` and `config/credentials.js` are excluded from version control; `.env.example` documents the required variable.

- Full HTML report available via `npx playwright show-report` after any local run.