

LeetCode Solutions

Sankalp Sangle

Last updated on May 2, 2020

Contents

I	LeetCode Top Interview Questions	1
1	Easy	3
1.1	Arrays	3
1.1.1	26. Remove Duplicates from Sorted Array	3
1.1.2	122. Best Time to Buy and Sell Stock II	4
1.1.3	189. Rotate Array	4
1.1.4	217. Contains Duplicate	5
1.1.5	136. Single Number	5
1.1.6	350. Intersection of Two Arrays II	6
1.1.7	66. Plus One	6

Part I

LeetCode Top Interview Questions

Chapter 1

Easy

Link: [LeetCode Top Interview Questions: Easy section.](#)

1.1 Arrays

Link: [Arrays](#)

1.1.1 26. Remove Duplicates from Sorted Array

[Link to question](#), [Link to submission](#)

Concepts Two pointer

Algorithm description

- Maintain a read pointer and a write pointer, both starting from zero.
- Advance the write pointer until you see a new value or reach end of array.
- Write value at write location into read location.

- Return read.

1.1.2 122. Best Time to Buy and Sell Stock II

[Link to question](#), [Link to submission](#)

Concepts Greedy

Algorithm description

- Construct a consecutive elements difference array
- Return sum of all positive elements in difference array

1.1.3 189. Rotate Array

[Link to question](#), [Link to submission approach 1](#), [Link to submission approach 2](#)

Concepts Cyclic replacements, Implementation

Approach 1 description

- Maintain a visited array and a pointer initialized to 0
- while pointer + k is not visited, replace arr[pointer + k] with arr[pointer]. Update pointer to pointer + k. Set pointer + k to visited, increment a numberOfChanges variable.
- Increment pointer by 1
- Keep doing this while numberOfChanges less than size of array.

Approach 2 description

- Reverse the entire array
- Reverse from start to start + k
- Reverse from start + k to end

1.1.4 217. Contains Duplicate

[Link to question](#), [Link to submission](#)

Concepts Hash Table, Set

Algorithm description

- Initialize a Set
- For an element in array, if element in Set, return true
- else add element to Set
- If out of loop, return False

1.1.5 136. Single Number

[Link to question](#), [Link to submission](#)

Concepts Bit Manipulation, XOR

Algorithm description

- Initialize an answer variable to 0
- For every element, XOR it to answer. Elements appearing twice get XOR'd out to zero

- Return answer

1.1.6 350. Intersection of Two Arrays II

[Link to question](#), [Link to submission approach 1](#), [Link to submission approach 2](#)

Concepts Hash Table, Two Pointers

Approach 1 description

- Form an element:frequency mapping using map for smaller array (to save space)
- Traverse bigger array
- If frequency of element less than 0, add to answer. Decrement frequency

Approach 2 description

- If arrays are sorted, use two pointers p1 and p2
- If $\text{nums1}[p1] == \text{nums2}[p2]$, add to answer and increment both
- Else if $\text{nums1}[p1]$ is smaller, increment p1. Else increment p2
- Keep doing until reach end of either array

1.1.7 66. Plus One

[Link to question](#), [Link to submission](#)

Concepts Array

Algorithm description

- Initialize a carry variable to 1
- Traverse array from the end.
 $\text{digit}[i] = \text{carry} + \text{digit} \bmod 10$, $\text{carry} = \text{carry} + \text{digit} \text{ div } 10$
- Finally, if carry is not zero, insert carry at start of array