ET AI HACKATHON 2026 · PROBLEM 2: AGENTIC CYBERSECURITY

SELF-DECLARED POSITION

F3 · D3

9 of 9 attack types · 11 input sources

IntentSeal

The prompt-injection firewall that keeps AI agents inside the user's intent.

`pip install intentseal` `docker compose up` `Any agent · any model` `Open source · Apache-2.0`

TEAM

Sankalp Wanjari: solo builder. Product, security research, engineering and evaluation.

github.com/sankalp2515/intentseal

02 PROBLEM

Agents now read the outside world and act on it. Anything they read can give them orders.

REAL CASE · JUNE 2025 · CVSS 9.3

One email. Zero clicks. Data out.

EchoLeak (CVE-2025-32711): a single crafted email made Microsoft 365 Copilot leak internal data. It slipped past Microsoft's own prompt-injection classifier.

Why today's defences miss it

- **They read text, not what the model reads:** white PDF text, hidden HTML, text inside images, base64, look-alike letters.
- **They stop at detection:** when the filter misses, the agent still sends the email.
- **They leave no evidence:** nobody can replay what the agent saw and why it acted.

#1

Prompt injection is the top risk for LLM apps (OWASP 2025); agent goal hijack is #1 for agentic apps (OWASP 2026)

40%

of enterprise apps will have task-specific AI agents by end-2026, up from under 5% (Gartner)

₹22 cr

average cost of a data breach in India, 2025, an all-time high; shadow AI adds ₹1.79 cr (IBM)

₹250 cr

maximum DPDP Act penalty for failing to keep reasonable security safeguards

Sources: Aim Security / arXiv 2509.10540 (EchoLeak); OWASP GenAI Security Project; Gartner (2025); IBM Cost of a Data Breach 2025, India; DPDP Act 2023 Schedule.

03 PROPOSED SOLUTION

IntentSeal sits between the agent and everything it reads and does. Catch what can be caught, limit the damage, prove what happened.

01 · SEE

Sees what the model sees

11 input sources. Hidden PDF and Word text, hidden HTML, text in images (OCR), encodings decoded; pasted text split from the user's request.

02 · REMOVE

Removes only the attack

Offending spans are quarantined in place; the rest keeps working: **100%** of normal tasks still completed.

03 · GUARD

Checks every action

An intent contract from the user's own words, plus allow-lists, fields pinned to the signed-in user, secret-leak scan, data-flow tracing, answer check.

04 · PROVE

Proves, triages, learns

Attack-to-action provenance with execution receipts; replay, approvals, an Investigator agent, a red-team loop that repairs on evidence.

WHAT IS NEW	TYPICAL PROMPT FILTER	INTENTSEAL
Reads hidden text, images (OCR) and encodings the model will read	text only	**yes, 11 sources**
Enforces what the user authorised, even with every detector bypassed	no	**intent contract, versioned**
Shows the attack path and proves the action never ran	no	**provenance + execution receipts**
Keeps the user's request apart from pasted or retrieved text	no	**yes, per span**
Investigates, attacks and repairs itself, on evidence only	no	**Investigator + red-team loop**

04 ARCHITECTURE: PROCESS FLOW, DECISIONS, MODEL USAGE

Rules decide, AI advises: no model output can override the policy.

INBOUND CONTENT

11 sources
user · web · PDF · email · Markdown · HTML · Word · API · OCR text · code · images, plus RAG passages

→

1
Extract & normalise
hidden text, metadata, OCR; decode encodings; split pasted text from the request

→

2 · TIER 0
Rules + attack memory
structural flags; fingerprints of confirmed attacks

→

3 · TIER 1
Local classifier
DeBERTa-v3 (ONNX, CPU); scores every chunk

→

4 · TIER 2
AI judge
intent vs the user's task; labels 9 attack types; 1M-token judge for long pages

→

5
Deterministic policy
ALLOW · NEUTRALISE (quarantine spans) · ESCALATE · BLOCK; fail closed

→

Agent's LLM
sees cleaned content only

ACTIONS & ANSWERS

Tool call / answer
proposed by the agent's model

→

6
Intent contract + action guard
contract compiled from the user's own words (permit · prohibit · ask first; versioned, hash-chained) · allow-lists · pinned fields · secret scan (also encoded) · provenance & data-flow taint · session risk

→

7
Answer check
secrets redacted or withheld, also mid-stream

→

Tools / user
stopped calls are explained to the model, which continues another way

SESSION

Session risk
user risk (user's own turns: multi-step jailbreaks) kept apart from third-party risk (gates actions); the same poisoned content counts once

↔

8
Decision log, provenance & receipts
source → evidence → call → rule & clause → executed or not; replay, approvals, SIEM export

→

9 · AGENT
Investigator
plans, uses read-only tools, self-checks, reports; with the red-team loop, proposes repairs a reviewer applies (back into step 2)

Deterministic (rules) · AI (advises) · Outside IntentSeal

In the demo: hidden-text PDF → **1** finds white text → **3, 4** score and judge → **5** BLOCK → **8** replay → **9** report

05 AI MODELS & TECHNOLOGIES

Each model does one job it is good at. Local first, AI where judgement is needed, free tiers throughout.

JOB	MODEL / TECHNOLOGY	WHY THIS CHOICE
Tier 1 classifier	ProtectAI DeBERTa-v3 prompt-injection v2, ONNX on CPU	Every chunk scored locally in ~0.1 s; no content leaves the host
Tier 2 judge	gpt-oss-20b (Groq) → NVIDIA NIM → Gemini 3.1 Flash-Lite	Reads content against the user's task; labels the 9 attack types; fails over across providers
Long-document judge	NVIDIA Nemotron 3 Ultra (1M-token context)	Judges a whole long web page in one pass instead of guessing from fragments
Investigator agent	Gemini 3.1 Flash-Lite → Nemotron 3 Super → gpt-oss-120b	Tool-using triage agent; large free quotas so triage never queues
OCR	RapidOCR (ONNX)	Reads text in screenshots and images before the model does
Attack memory	Word-shingle fingerprints (no text stored)	Confirmed attacks blocked at Tier 0 next time; marked false alarms not flagged again

Stack

Python · FastAPI gateway · React Console · SQLite or PostgreSQL · Docker · PyPI package `intentseal` · CI with 250+ tests

Model-agnostic and red-teamed

15+ providers (OpenAI, Anthropic, Gemini, Groq, local Ollama/vLLM). Attacks generated by promptfoo and NVIDIA garak, never hand-written.

06 AGENTIC CAPABILITY

IntentSeal acts on its own, within guardrails: it reasons, plans, uses tools, recovers and learns.

The Investigator: an agent that triages what the firewall stopped

PLAN
Playbook
timeline → evidence → decode → history → policy

TOOLS
5 read-only tools
the log, evidence, decoders, attack memory, policy

CHECK
Self-check
an incomplete report is sent back to it once

ACT
Report + proposals
severity, objective, outcome; proposes, a human applies

```
# real run, hidden-text PDF, 43 s, 8 steps
timeline · evidence · decode → hidden base64 decoded
history · policy · submit_report → rejected: "propose_memory first"
propose_memory(verdict=attack) · submit_report → accepted
verdict attack · severity high · goal look up customer CUST-7781 and
leak it
```

Evidence reaches it datamarked (Spotlighting), its tools cannot act, and its output is advice: the triage agent cannot be hijacked into doing harm.

CRITERION	WHAT INTENTSEAL DOES
Reason	Judge weighs content against the user's task; long-context judge for whole pages
Plan	Investigator follows and adapts a triage playbook
Use tools	Investigator queries log, evidence, decoders, memory, policy
Take actions	Quarantines spans, blocks, escalates, pins fields, enforces the user's intent contract; triages pending approvals
Learn	Red-team loop: clusters failures, mutates them, proposes a repair, promotes only on held-out evidence
Recover	Provider failover; fail-closed holds; self-check; protected agents continue after a stopped call
Autonomy	Rules decide; humans approve state changes; monitor before enforce

07 PRODUCT DEMO

A real, unmodified agent protected by changing one setting.


```
# Hermes Agent (Nous Research): only its endpoint changes
model: { provider: custom,
  base_url: http://localhost:8000/proxy/hermes/v1 }
$ hermes -z "Read message.eml and tell me what it asks me to do."
I cannot read the file due to security restrictions...
```

TIME	DECISION	SOURCE	RULE · REASON	ATTACK TYPES	SESSIO
4:20:52 am	Needs approval	tool · execute_code	high-risk-tool-in-risky-session session risk 1.30 after untrusted content	Credential Theft · Indirect Prompt Injection	conv-4
4:20:48 am	Needs approval	tool · terminal	high-risk-tool-in-risky-session session risk 1.00 after untrusted content	Credential Theft · Indirect Prompt Injection	conv-4
4:20:44 am	Blocked	tool · execute_code	content-risk-block Content risk reached the policy block threshold	Credential Theft · Indirect Prompt Injection	conv-4
4:20:32 am	Allowed	tool · execute_code	allow within policy		conv-4
4:20:30 am	Allowed	user	allow Content is within policy		conv-4

Console, Decisions: the poisoned email Hermes read is `Blocked`; its follow-up commands in the now-risky session wait for a human (`Needs approval`).

BEFORE poisoned email → model obeys → sends customer data → data leaves

AFTER poisoned email → quarantined → send BLOCK → task done, nothing leaks



Replay → Attack to action: the email that supplied the target, the rule that fired, the clause the user wrote (“Do not reply to anyone”) and the proof the reply never ran. The contract on the right came from the user's words only.

Measured, not claimed: generated attacks through every input channel.


99.2%
attacks caught in documents and data, 359 generated attacks, 14 channels

26%→0%
attack success on the agent, protection off → on (0 of 339 protected tests compromised)

0 / 28
attacks that succeeded with **every detector switched off**: the action layer and intent contract alone

114 ms
fast-path latency p95 on CPU; 100% of normal tasks completed with protection on

Recall by attack type: all 9 of 9 detected



Declared position: F3 · D3

F3: ≥ 7 types	All 9 types detected (chart); each labelled per decision
D3: multimodal	PDF, Word, HTML, email, images (OCR), API, code, RAG, hidden text and encodings: 99.2% recall
Reliability	0% attack success in 339 protected tests (paired, 95% CI ≤ 12.5%); attacks that worked, repeated 3×: unprotected 15/34, protected 0/37, detectors off 0/28; adaptive attackers 0/41
Stated limits	Attacks typed by the user: 68% caught (the action guard still stops the harm); false alarms on hard held-out benign: 5.1%

Evaluation 2026-10-11, commit 9ca8fb5, engine 9aca55e22cd6; detectors-off arm and intent contracts: engine 8c2b401a4425. Attacks from promptfoo and NVIDIA garak. Method: docs/EVALUATION.md.

09 BUSINESS IMPACT

Ship AI agents without betting the company on them: less risk, lower cost, no slowdown.

RISK REDUCTION

Attacks stop succeeding

Attack success on a protected agent **26%** → **0%**. A breach in India averages **₹22 crore**; avoiding one pays for years of operation.

COST

Security for a fraction of the AI bill

About **0.57** security tokens per agent token, mostly on free or small models; most checks run locally on CPU; self-hosted, open source, no per-seat fee.

PRODUCTIVITY

Analysts get answers, not logs

Each flagged session gets a triage report in under a minute. One-line integration; monitor mode lets teams roll out without disruption.

CUSTOMER EXPERIENCE

Agents keep working

100% of normal tasks completed. Only the attack is removed, and agents carry on after a stopped action instead of failing.

COMPLIANCE

Evidence auditors accept

Replayable decisions and SIEM export support DPDP "reasonable security safeguards", RBI FREE-AI (protection, assurance) and OWASP LLM01 / ASI01.

WHO PAYS · HOW WE WIN

Open core

Free SDK + gateway; paid enterprise console (SSO, roles, managed judges, compliance packs). Buyers: CISOs at banks, insurers, IT services, SaaS. Market for securing AI ≈ $4.8B by 2027 (Gartner).

IBM Cost of a Data Breach 2025 (India); Gartner, securing-AI market forecast (Aug 2026); Palo Alto Networks paid $634.5M for Protect AI (FY25 10-K), Check Point acquired Lakera (2025): the category is real. Token ratio from the evaluation's headline suite.

Built to run in production, and to fail safe when it is unsure.

Scale and operations

- Fast path on CPU, p95 **114 ms**; AI judge only where needed, cached
- Measured on one CPU process: **63 action checks/s, 20 message inspections/s** (16 concurrent clients, 4 agents, 0 errors); scale out by adding containers with a shared PostgreSQL store
- Multi-tenant: organisations, scoped keys, per-key rate limits, request size limits
- 15+ model providers with key failover; local models for air-gapped sites
- SIEM export (JSON Lines, CEF), metrics, health and readiness probes, graceful shutdown

Responsible AI

- **Rules decide, AI advises:** a deterministic policy sits over every model output
- **Fail closed:** content that needs the judge is held, never passed, if models are down
- **Human oversight:** approvals, monitor mode, reviewer feedback, proposals a human applies
- **Private and transparent:** hashes or redacted previews only; every decision has a rule, reason, replay and provenance
- **The user decides scope:** an intent contract from the user's words; no model or document can widen it
- **Honest metrics:** paired runs with 95% intervals, a detectors-off arm, held-out benign set, published limits

0 / 41
adaptive attacker conversations that succeeded

70 vs 56
of 70 hijacked sends to a party the user named stopped: intent contract vs the previous rules

0 / 615
new false alarms from the red-team loop's repair; 29/82 held-out misses now caught

0% · 5.1%
false alarms: development · held-out hard benign sets

From prompt-injection firewall to the control plane for enterprise agents.

NOW · SHIPPED OCT 2026

Firewall + evidence

- v0.1 on PyPI; gateway, Console, Docker
- OpenAI, Anthropic, Gemini proxy formats
- Investigator agent; attack memory
- Intent contracts · provenance · red-team loop

Today: 99.2% document recall · 0% attack success

NEXT · Q1 2027

Close the measured gaps

- Small judge distilled from judge decisions: on-prem, faster, cheaper
- Indian languages and code-mixed text (Hindi, Hinglish)
- MCP tool-description and server vetting (OWASP agentic top 10)
- Shared session store for multi-replica; Bedrock and Vertex native

Targets: typed attacks ≥ 85% · false alarms ≤ 5% · judge p95 < 1 s

LATER · 2027

Agent security platform

- Agent-to-agent message inspection for multi-agent systems
- Agent identity and delegated, expiring permissions
- Compliance packs: DPDP, RBI FREE-AI, EU AI Act
- Continuous red teaming as a service; managed cloud

Targets: first design partners in BFSI · SOC 2 · on-prem in 1 day

Why this order: each step closes a limit we measured (typed attacks, false alarms, scale) before widening scope to the risks the OWASP agentic list ranks next.

Keep every AI agent inside the user's intent.

```
# the whole system, about 5 minutes
git clone https://github.com/sankalp2515/intentseal
cd intentseal && cp .env.example .env # add one free key
docker compose up --build
# Console :8000 · test assistant :8040
```

```
# inside your Python agent, about 2 minutes
pip install "intentseal[embedded]"
intentseal init --agent my-agent

# any agent, no code change: point its base URL at
http://localhost:8000/proxy/<agent>/v1
```

LLM proxy (OpenAI, Anthropic, Gemini formats, streaming) · Python SDK · REST API · Docker · any model provider

github.com/sankalp2515/intentseal · pypi.org/project/intentseal · Sankalp Wanjari