

Project Proposal: Deep Graph Neural Networks for Academic Paper Classification on the OGBN-Arxiv Benchmark

Formal Technical & Experimental Proposal

Course Module: CCS4354 Tensors & Graphs	Target Dataset: Open Graph Benchmark (ogbn-arxiv)	Evaluation Metric: Test Accuracy, Weighted F1
Proposed Models: GCN (256 hidden) vs. GAT (4-head)	Key Focus: Inductive Temporal Generalization	Status: Project Proposal Document

Proposal Summary: Automated classification of academic literature is a vital challenge in modern information retrieval. Unlike Euclidean text data, academic citation networks encode crucial relational homophily across non-Euclidean citation graphs. This project proposes an end-to-end investigation into Graph Representation Learning on the **OGBN-Arxiv** benchmark (169,343 papers, 2,315,598 citations, 40 categories). We propose to implement, train, tune, evaluate, and interpret two core GNN architectures: **Graph Convolutional Networks (GCN)** and **Graph Attention Networks (GAT)** under strict out-of-distribution **temporal splitting** (train ≤ 2017 , validation 2018, test 2019–2020), complemented by latent embedding explainability (PCA/t-SNE) and an interactive **Streamlit dashboard**.

1. Problem Statement & Research Motivation

Relational Dependencies in Scientific Literature: Standard text classification models treat documents as independent and identically distributed (i.i.d.), ignoring citation networks. A research paper's domain is strongly signaled by the papers it cites and the works that cite it. Graph Representation Learning leverages tensor-based message passing to propagate semantic context across multi-hop citation neighborhoods.

Inductive Temporal Distribution Drift: In real-world deployment, models trained on historical papers must predict future research categories. Standard random splitting creates severe temporal data leakage. We propose to strictly adopt OGB's chronological split: **Training** (≤ 2017 : 90,941 nodes, 53.7%), **Validation** (2018: 29,799 nodes, 17.6%), and **Test** (2019–2020: 48,603 nodes, 28.7%).

2. Project Objectives & Research Questions

- **Objective 1 (Data & Topology):** Ingest 169K nodes and 2.3M edges, compute degree distributions, density, and local subgraphs.
- **Objective 2 (GNN Modeling):** Implement 2-layer GCN (256 hidden) and 2-layer Multi-Head GAT (4 heads $\times$ 64 channels).
- **Objective 3 (Optimization):** Perform controlled hyperparameter grid searches across hidden dimensions, dropout, and learning rates.
- **Objective 4 (Benchmarking):** Evaluate Test Accuracy, Weighted Precision, Recall, F1-scores, and 40-class confusion matrices.
- **Objective 5 (Explainability):** Extract hidden embeddings and compute 2D linear PCA and non-linear t-SNE projections with neighborhood homophily agreement scoring.
- **Objective 6 (Interactive Deployment):** Engineer a 5-module Streamlit web dashboard for real-time model querying.

3. Technical Methodology & Proposed Architectures

3.1 Spectral Graph Convolutional Network (GCN)

The spectral graph convolution propagates messages via symmetric normalized adjacency:

$$H^{(l+1)} = \sigma(D^{-1/2} A D^{-1/2} H^{(l)} W^{(l)})$$

where $A_{ij} = A + I_N$, $D_{ii} = \sum_j A_{ij}$, and $W^{(l)}$ is the layer weight tensor. Layer 1 transforms 128-dim features to 256 hidden channels (ReLU, Dropout=0.5), and Layer 2 outputs 40 class logits.

3.2 Spatial Graph Attention Network (GAT)

The spatial attention network learns anisotropic edge importance weights:

$$\alpha_{ij} = \exp(\text{LeakyReLU}(a^T [W h_i || W h_j])) / \sum_{(k \in N_i)} \exp(\text{LeakyReLU}(a^T [W h_i || W h_k]))$$

Multi-head attention with $K = 4$ heads computes: $h_i^{(l+1)} = ||_{(k=1..K)} \text{ELU}(\sum_{(j \in N_i)} \alpha_{ij}^{(k)} W^{(k)} h_j^{(l)})$.

4. Benchmark Dataset Specifications (OGBN-Arxiv)

Feature / Attribute	Value / Dimension	Description & Analytical Role
Total Nodes (V)	169,343	Academic computer science papers in corpus
Total Edges (E)	2,315,598	Directed citation links between academic papers
Node Features	128-dim	Word2Vec skip-gram averaged title/abstract embeddings
Target Classes	40 Categories	Fine-grained arXiv CS primary categories (cs.CV, cs.LG, etc.)
Graph Density	1.615×10^{-4}	Sparse scale-free network suited for sparse tensor convolutions
Chronological Split	53.7% / 17.6% / 28.7%	Train (≤ 2017 : 90.9K), Valid (2018: 29.8K), Test (2019–20: 48.6K)

Table 1: Technical specifications of the target OGBN-Arxiv benchmark dataset.

5. Project Execution Work Plan & Milestones

Phase	Focus Area / Milestone	Key Output Deliverable
Phase 1	Tensor Algebra & GPU Acceleration	Notebook 01: Tensor operations, broadcasting, memory profile
Phase 2	Graph Topology & Temporal Splitting	Notebooks 02–03: Degree plots, density, processed data tensors
Phase 3	GNN Architecture Implementation	Notebooks 04–05: GCN/GAT checkpoints (models/*.pt) & loss history
Phase 4	Hyperparameter Optimization	Notebook 06: Grid search tuning table (results/training/)
Phase 5	Model Benchmarking & Evaluation	Notebook 07: Test accuracy/F1 table & 40-class confusion matrices
Phase 6	Explainability & Latent Projections	Notebook 08: 2D PCA & t-SNE embedding figures, homophily score
Phase 7	Interactive Dashboard Engineering	dashboard/app.py: Live Streamlit web application on port 8501
Phase 8	Reporting & GitHub Repository Setup	Technical Report PDF/MD, Proposal Document, GitHub README

Table 2: Proposed 8-phase execution roadmap and deliverables.

6. Risk Assessment & Key References

Identified Risks & Mitigations: (1) *Memory Bottlenecks*: Addressed by utilizing sparse COO edge representations (edge_index). (2) *Oversmoothing*: Mitigated by maintaining a 2-layer depth with 50% dropout regularization. (3) *Temporal Data Leakage*: Prevented by strictly honoring OGB chronological partitioning.

Key References: [1] Kipf & Welling, ICLR 2017. [2] Veličković et al., ICLR 2018. [3] Hu et al., NeurIPS 2020. [4] Hamilton et al., NeurIPS 2017.