

Electronic Component Solar Panels

Classic Application Series

The Classic Application Series offer a new opportunity to solve the old problem of limited power for wireless electronics designed for portable and remote applications. Classic Application panels are lightweight, paper thin, and durable.

Their ultra-thin profile enables them to be easily integrated into devices for solar recharging or for direct power. Panels have been specifically developed to recharge a variety of common battery sizes. These panels do not have a UV-stabilized surface, but are suitable for intermittent outdoor use.

Are you looking for a custom Electronic Component Solar Panel? We offer custom sizes, voltages, encapsulations and substrates.

Contact us at www.powerfilmsolar.com to learn more.

0.0035

0.0025

0.001

€ 0.003

ONP1.2-12x24

Electrical Specifications:

Full Sun

Power: 4mW

Operating Voltage: 1.2V Operating Current: 3.3mA

1/4 Sun

Power: 0.9mW

Operating Voltage: 1.2V Operating Current: 0.7mA

All Levels

Average Voc: 1.6V Maximum Voc: 1.9V

Isc: 4.3mA

Physical Specifications:

Dimensions: 24.0 x 12.0 (mm) 0.94 x 0.47 (in)

Weight: 0.003oz / 0.09g



IV Curve

Voltage (V)

ONP1.2-12x24

ONP1.2-37x54

Electrical Specifications:

Full Sun

Power: 70mW

Operating Voltage: 1.2V Operating Current: 50.8mA

1/4 Sun

Power: 13.7mW Operating Voltage: 1.2V

Operating Current: 11.4mA

All Levels

0.0035

0.003

0.0015

Average Voc: 1.6V Maximum Voc: 1.9V


Isc: 66mA

Physical Specifications:

Dimensions: 54.0 x 36.5 (mm) 2.13 x 1.44 (in)

Weight: 0.02oz / 0.58g





Poverfine SOLAR SOLAR

ONP2.4-15x94

Electrical Specifications:

Full Sun

Power: 45mW

Operating Voltage: 2.4V Operating Current: 18.6mA

1/4 Sun

Power: 10.1mW Operating Voltage: 2.4V Operating Current: 4.2mA

All Levels

Average Voc: 3.2V Maximum Voc: 3.7V Isc: 24.2mA

Physical Specifications:

Dimensions: 94.0 x 14.6 (mm) 3.70 x 0.57 (in) Weight: 0.01oz / 0.40g

SP3-37

Electrical Specifications:

Full Sun

Power: 66mW

Operating Voltage: 3.0V Operating Current: 22mA

1/4 Sun

Power: 15mW

Operating Voltage: 3.0V Operating Current: 5.0mA

All Levels


Average Voc: 4.1V Maximum Voc: 4.6V Isc: 28.0mA


Physical Specifications:

Dimensions: 64.0 x 36.5 (mm) 2.52 x 1.44 (in) Weight: 0.03oz / 0.85g




IV Curve





IV Curve



MPT2.4-21

Electrical Specifications:

Full Sun

Power: 34mW

Operating Voltage: 2.4V Operating Current: 14.2mA

1/4 Sun

Power: 7.7mW

Operating Voltage: 2.4V Operating Current: 3.2mA

All Levels

Average Voc: 3.2V Maximum Voc: 3.7V

Isc: 18.3mA

Physical Specifications:

Dimensions: 54.0 x 20.9 (mm) 2.13 x 0.82 (in) Weight: 0.02oz / 0.40g

MP3-25

Electrical Specifications:

Full Sun

Power: 93mW

Operating Voltage: 3.0V Operating Current: 31mA

1/4 Sun

Power: 21mW Operating Voltage: 3.0V

Operating Current: 7.0mA

All Levels


Average Voc: 4.1V Maximum Voc: 4.6V

Isc: 35mA


Physical Specifications:

Dimensions: 114.0 x 24.0 (mm) 4.49 x 0.94 (in) Weight: 0.03oz / 0.85g

IV Curve







Poverfine USA SOLAR ®

MP3-37

Electrical Specifications:

Full Sun

Power: 150mW Operating Voltage: 3.0V Operating Current: 50mA

1/4 Sun

Power: 34mW

Operating Voltage: 3.0V Operating Current: 11.3mA

All Levels

Average Voc: 4.1V Maximum Voc: 4.6V Isc: 63mA

Physical Specifications:

Dimensions: 114.0 x 36.5 (mm) 4.49 x 1.44 (in) Weight: 0.04oz / 1.13g

MPT3.6-150

Electrical Specifications:

Full Sun

Power: 360mW Operating Voltage: 3.6V Operating Current: 100mA

1/4 Sun

Power: 81mW

Operating Voltage: 3.6V Operating Current: 22.5mA

All Levels


Average Voc: 4.9V Maximum Voc: 5.5V Isc: 128mA

Physical Specifications:


Dimensions: 74.0 x 146.0 (mm) 2.91 x 5.75 (in) Weight: 0.10oz / 2.83g



IV Curve



IV Curve



MPT3.6-75

Electrical Specifications:

Full Sun

Power: 180mW Operating Voltage: 3.6V Operating Current: 50mA

1/4 Sun

Power: 41mW Operating Voltage: 3.6V Operating Current: 11.3mA

All Levels

Average Voc: 4.9V Maximum Voc: 5.5V Isc: 64mA

Physical Specifications:

Dimensions: 74.0 x 73.0 (mm) 2.91 x 2.87 (in) Weight: 0.06oz / 1.70g

SP4.2-37

Electrical Specifications:

Full Sun

Power: 92mW

Operating Voltage: 4.2V Operating Current: 22mA

1/4 Sun

Power: 21mW Operating Voltage: 4.2V Operating Current: 5.0mA

All Levels


Average Voc: 5.9V Maximum Voc: 6.5V Isc: 28mA

Physical Specifications:


Dimensions: 84.0 x 36.5 (mm) 3.31 x 1.44 (in) Weight: 0.03oz / 0.85g



IV Curve







Poverfine USA SOLAR ®

MPT4.8-75

Electrical Specifications:

Full Sun

Power: 240mW Operating Voltage: 4.8V Operating Current: 50mA

1/4 Sun

Power: 54mW Operating Voltage: 4.8V Operating Current: 11.3mA

All Levels

Average Voc: 6.4V Maximum Voc: 7.4V Isc: 64mA

Physical Specifications:

Dimensions: 94.0 x 73.0 (mm) 3.70 x 2.87 (in) Weight: 0.07oz / 1.98g

MPT6-75

Electrical Specifications:

Full Sun

Power: 300mW Operating Voltage: 6.0V Operating Current: 50mA

1/4 Sun

Power: 68mW Operating Voltage: 6.0V Operating Current: 11.3mA

All Levels


Average Voc: 8.0V Maximum Voc: 9.3V Isc: 64mA

Physical Specifications:


Dimensions: 114.0 x 73.0 (mm) 4.49 x 2.87 (in) Weight: 0.08oz / 2.30g



IV Curve



IV Curve



MPT4.8-150

Electrical Specifications:

Full Sun

Power: 480mW Operating Voltage: 4.8V Operating Current: 100mA

1/4 Sun

Power: 108mW Operating Voltage: 4.8V Operating Current: 22.5mA

All Levels

Average Voc: 6.4V Maximum Voc: 7.4V Isc: 128mA

Physical Specifications:

Dimensions: 94.0 x 146.0 (mm) 3.70 x 5.75 (in) Weight: 0.10oz / 2.83g

MPT6-150

Electrical Specifications:

Full Sun

Power: 600mW Operating Voltage: 6.0V Operating Current: 100mA

1/4 Sun

Power: 135mW Operating Voltage: 6.0V Operating Current: 22.5mA

All Levels


Average Voc: 8.0V Maximum Voc: 9.3V Isc: 128mA

Physical Specifications:


Dimensions: 114.0 x 146.0 (mm) 4.49 x 5.75 (in) Weight: 0.10oz / 2.83g



IV Curve







PowerFilm_® MADE IN THE USA

MP7.2-75F

Electrical Specifications:

Full Sun

Power: 864mW Operating Voltage: 7.2V Operating Current: 120mA

1/4 Sun

Power: 194mW Operating Voltage: 7.2V Operating Current: 27.0mA

All Levels

Average Voc: 10.5V Maximum Voc: 11.1V Isc: 154mA

Physical Specifications:

Dimensions: 253.0 x 73.0 (mm) 9.96 x 2.87 (in) Weight: 0.50oz / 14.17g

MPT15-75

Electrical Specifications:

Full Sun

Power: 770mW

Operating Voltage: 15.4V Operating Current: 50mA

1/4 Sun

Power: 173mW

Operating Voltage: 15.4V Operating Current: 11.3mA

All Levels


Average Voc: 19.0V Maximum Voc: 22.2V

Isc: 64mA

Physical Specifications:


Dimensions: 253.0 x 73.0 (mm) 9.96 x 2.87 (in) Weight: 0.50oz / 14.17g







IV Curve



MP7.2-150F

Electrical Specifications:

Full Sun

Power: 1.73W

Operating Voltage: 7.2V Operating Current: 240mA

1/4 Sun

Power: 389mW Operating Voltage: 7.2V Operating Current: 54.0mA

All Levels

Average Voc: 10.5V Maximum Voc: 11.1V Isc: 308mA

Physical Specifications:

Dimensions: 253.0 x 146.0 (mm) 9.96 x 5.75 (in) Weight: 0.90oz / 25.51g

MPT15-150

Electrical Specifications:

Full Sun

Power: 1.54W

Operating Voltage: 15.4V Operating Current: 100mA

1/4 Sun

Power: 347mW


Operating Voltage: 15.4V Operating Current: 22.5mA

All Levels


Average Voc: 19.0V Maximum Voc: 22.2V Isc: 128mA

Physical Specifications:


Dimensions: 253.0 x 146.0 (mm) 9.96 x 5.75 (in) Weight: 1.00oz / 28.35g



IV Curve







Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PowerFilm:

<u>MP7.2-75F</u> <u>MPT3.6-150</u> <u>MPT4.8-75</u> <u>SP4.2-37</u> <u>MPT3.6-75</u> <u>MPT15-150</u> <u>SP3-37</u> <u>MP7.2-150F</u> <u>MP3-37</u> <u>MP3-25</u> MPT15-75 MPT6-75 MPT4.8-150 MPT6-150 ONP1.2-12x24 ONP1.2-37x54 ONP2.4-15x94