

PRN : 202501120148
Name : Sanket Narayan Patil
Batch : D23

Practical No 4

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d69/667a7e...

CODETANTRA Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.1.1. Pandas - series creation and manipulation

Write a Python program that takes a list of numbers from the user, creates a Pandas series from it, and then calculates the mean of even and odd numbers separately using the `groupby` and `mean()` operations.

Hint: You can group the Series based on whether each number is even or odd.

Input Format:

- The user should enter a list of numbers separated by space when prompted.

Output Format:

- The program should display the mean of even and odd numbers separately.
- Each mean value should be displayed with a label indicating whether it corresponds to even or odd numbers.

Refer to the sample test cases for better understanding regarding input and output format.

Sample Test Cases

```
1 import pandas as pd
2
3 # Take inputs from the user to create a list of numbers
4 numbers = list(map(int, input().split()))
5
6 # Create a Pandas series from the list of numbers
7 series = pd.Series(numbers)
8 # Grouping by even and odd numbers and calculating the mean
9 grouped = series.groupby(series % 2 == 0).mean()
10
11 # Display the mean of even and odd numbers with labels
```

Average time: 0.008 s, 8.17 ms | Maximum time: 0.019 s, 19.00 ms

3 out of 3 shown test case(s) passed
3 out of 3 hidden test case(s) passed

Test case 1 10 ms Debug

Expected output	Actual output
1 2 3 4 5 6 7 8 9 10	1 2 3 4 5 6 7 8 9 10
Mean of even and odd numbers:	Mean of even and odd numbers:
Odd ---- 5.0	Odd ---- 5.0
Even ---- 6.0	Even ---- 6.0
dtype: float64	dtype: float64

Terminal Test cases

< Prev Reset Submit Next >

Course

mitaoe.codetantra.com/secure/course.jsp?euclid=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d69/667aa3...

CODETANTRA Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.1.2. Dictionary to dataframe

A dictionary of lists has been provided to you in the editor. Create a DataFrame from the dictionary of lists and perform the listed operations, then display the DataFrame before and after each manipulation.

Create the DataFrame:

- Convert the dictionary to a Pandas DataFrame.

Add a new row:

- Take inputs from the user for the new row data (name, age).
- Add the new row to the DataFrame.
- Display the DataFrame after adding the new row.

Modify a row:

- Modify a specific row by changing the age. Take the row index and new age value from the user.
- Display the DataFrame after modifying the row.

Delete a row:

- Take the row index to be deleted from the user.
- Remove the specified row.
- Display the DataFrame after deleting the row.

Add a new column:

- Add a column **Gender** with values taken from the user.
- Display the DataFrame after adding the new column.

Modify a column:

- Convert names to uppercase.

```
1 # import pandas as pd
2
3 ## Provided dictionary of lists
4 data = {
5     'Name': ['Alice', 'Bob', 'Charlie'],
6     'Age': [25, 30, 35],
7 }
8
9 ## Convert the dictionary to a DataFrame
10 df = pd.DataFrame(data)
11
```

Average time: 0.067 s, 66.50 ms | Maximum time: 0.077 s, 77.00 ms

1 out of 1 shown test case(s) passed
1 out of 1 hidden test case(s) passed

Test case 1 77 ms Debug

Expected output	Actual output
Original DataFrame:	Original DataFrame:
.....Name Age	Name Age
0 Alice 25	0 Alice 25
1 Bob 30	1 Bob 30
2 Charlie 35	2 Charlie 35
New name: Susan	New name: Susan

Terminal Test cases

< Prev Reset Submit Next >

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?euclid=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d69/667cf60...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.1.3. Student Information

69.53

Write a program to read a text file containing student information (name, age, and grade) using Pandas. Perform the following tasks:

• Display the first five rows of the data frame.

• Calculate the average age of the students (limit the average age up to 2 decimal places).

• Filter out the students who have a grade above a certain threshold (consider the threshold grade is 'B').

Note:
Refer to the displayed test cases for better understanding.

Sample Test Cases

studentin...

Submit

1 import pandas as pd

2

3 # Read the text file into a DataFrame

4 file = input()

5 data = pd.read_csv(file, sep="\s+", header=None, names=["Name", "Age", "Grade"])

6

7

8 # write your code here..

9 print("First five rows:")

10 print(data.head())

11

Average time 0.029 s 28.80 ms

Maximum time 0.040 s 40.00 ms

1 out of 1 shown test case(s) passed

1 out of 1 hidden test case(s) passed

Test case 1 40 ms Debug

Expected output studentdata.txt

Actual output studentdata.txt

First five rows:

0 John 25 A

1 Alin 22 B

2 Emma 24 A

Terminal Test cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?euclid=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/678609...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.1. Month with the Highest Total Sales

172.0

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

• The CSV file contains the columns: Date, Product, Quantity, Price, and City.

• Group the data by Month and calculate the total sales for each month.

• Find the month with the highest total sales and display it.

• Also, display the total sales for the best month.

Sample Data:

Date,Product,Quantity,Price,City
2025-01-01,Product A,5,20,New York
2025-01-01,Product B,3,15,Los Angeles
2025-01-02,Product A,7,20,New York
2025-01-02,Product C,4,30,Chicago
2025-01-03,Product B,2,15,Chicago
2025-01-03,Product A,8,20,Los Angeles
2025-01-04,Product C,6,30,New York
2025-01-04,Product B,5,15,Los Angeles
2025-01-05,Product A,3,20,Chicago
2025-01-05,Product C,10,30,Los Angeles

Note:
The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...

Submit

1 import pandas as pd

2

3 # Prompt the user for the file name

4 file_name = input()

5

6 # Load the data

7 df = pd.read_csv(file_name)

8 df['Date'] = pd.to_datetime(df['Date'])

9

10 df['Month'] = df['Date'].dt.to_period('M')

11

Average time 0.018 s 18.00 ms

Maximum time 0.036 s 36.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 1 36 ms Debug

Expected output sales_data.csv

Actual output sales_data.csv

Best month: 2025-01

Total sales: \$1210.00

Terminal Test cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/678613...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.2. Best Selling Product

0.025

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Find the product that sold the most in terms of quantity sold.
- Display the product that sold the most and the total quantity sold for that product.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...

Submit

1import pandas as pd

2

3# Prompt the user for the file name

4file_name = input()

5

6# Load the data

7df = pd.read_csv(file_name)

8

9

10# Find the product with the highest total quantity sold

11best_product = df.groupby('Product')['Quantity'].sum().idxmax()

Average time0.014 sMaximum time0.027 s

13.67 ms27.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 127 msDebug

Expected output

Actual output

sales_data.csvsales_data.csv

Best-selling product: Product ABest-selling product: Product A

Total quantity sold: 23Total quantity sold: 23

TerminalTest cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/678615...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.3. City that Sold the Most Products

0.030

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the columns: Date, Product, Quantity, Price, and City.
- Group the data by City and calculate the total quantity of products sold for each city.
- Find the city that sold the most products (based on the total quantity sold).

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Note:

The data cannot be displayed in the file. You can refer to the sample data provided for insights.

Sample Test Cases

monthFor...

Submit

1import pandas as pd

2

3# Prompt the user for the file name

4file_name = input()

5

6# Load the data

7df = pd.read_csv(file_name)

8

9city_sales = df.groupby('City')['Quantity'].sum()

10best_city = city_sales.idxmax()

11

Average time0.014 sMaximum time0.027 s

13.67 ms27.00 ms

1 out of 1 shown test case(s) passed

2 out of 2 hidden test case(s) passed

Test case 127 msDebug

Expected output

Actual output

sales_data.csvsales_data.csv

City sold the most products: Los AngelesCity sold the most products: Los Angeles

TerminalTest cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/6788ee...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.4. Most Frequently Sold Product Pairs

05:51

Write a Python program that takes the file name of a CSV file as input, reads the data, and performs the following operations:

- The CSV file contains the following columns: Date, Product, Quantity, Price, and City.
- For each date, find all pairs of products that were sold together (i.e., two products sold on the same date).
- Output the product pair/s that was sold most frequently.

Sample Data:

Date	Product	Quantity	Price	City
2025-01-01	Product A	5	20	New York
2025-01-01	Product B	3	15	Los Angeles
2025-01-02	Product A	7	20	New York
2025-01-02	Product C	4	30	Chicago
2025-01-03	Product B	2	15	Chicago
2025-01-03	Product A	8	20	Los Angeles
2025-01-04	Product C	6	30	New York
2025-01-04	Product B	5	15	Los Angeles
2025-01-05	Product A	3	20	Chicago
2025-01-05	Product C	10	30	Los Angeles

Explanation:
Transactions:

- 2025-01-01: Product A, Product B
- 2025-01-02: Product A, Product C
- 2025-01-03: Product B, Product A
- 2025-01-04: Product C, Product B
- 2025-01-05: Product A, Product C

frequent...

Submit

1import pandas as pd
2from itertools import combinations
3from collections import Counter
4
5# Prompt user to input the file name
6file_name = input()
7
8# Read data from the specified CSV file
9df = pd.read_csv(file_name)
10
11# write the code

Average time 0.016 s 15.87 ms Maximum time 0.030 s 30.00 ms
1 out of 1 shown test case(s) passed
2 out of 2 hidden test case(s) passed

Test case 1 30 ms Debug
Expected output sales_data.csv
Actual output sales_data.csv
Product A and Product B: 2 times
Product A and Product B: 2 times
Product A and Product C: 2 times
Product A and Product C: 2 times

Terminal Test cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/67e2b9...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.5. Titanic Dataset Analysis and Data Cleaning

02:37

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset. For each question, perform necessary data cleaning, transformations, and calculations as required.

- Display the first 5 rows of the dataset.
- Display the last 5 rows of the dataset.
- Get the shape of the dataset (number of rows and columns).
- Get a summary of the dataset (using .info()).
- Get basic statistics (mean, standard deviation, etc.) of the dataset using .describe().
- Check for missing values and display the count of missing values for each column.
- Fill missing values in the 'Age' column with the median age.
- Fill missing values in the 'Embarked' column with the most frequent value (mode()).
- Drop the 'Cabin' column due to many missing values.
- Create a new column, 'FamilySize' by adding the 'SibSp' and 'Parch' columns.

The Titanic dataset contains columns as shown below,

PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked

Sample Data:

titanicDat...

Submit

1import pandas as pd
2import numpy as np
3
4# Load the Titanic dataset
5data = pd.read_csv('Titanic-Dataset.csv')
6
7data = pd.read_csv('Titanic-Dataset.csv')
8print(data.head())
9print(data.tail())
10print(data.shape)
11print(data.info())

Average time 0.131 s 131.00 ms Maximum time 0.131 s 131.00 ms
1 out of 1 shown test case(s) passed

Test case 1 131 ms Debug
Expected output ... PassengerId Survived Pclass ... Fare Cabin Embarked
Actual output ... PassengerId Survived Pclass ... Fare Cabin Embarked
0 1 0 3 7.2500 0 1 3 7.2500
1 NaN 5
1 2 1 1 71.2833 1 2 1 71.2833
C85 C
2 3 1 3 7.9250 2 3 1 7.9250
NaN 5

Terminal Test cases

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/67e378...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.6. Titanic Dataset Analysis and Data Cleaning - 2

02:34

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

- Create a new column 'IsAlone' which is 1 if the passenger is alone (FamilySize = 0), otherwise 0.
- Convert the 'Sex' column to numeric values (male: 0, female: 1).
- One-hot encode the 'Embarked' column, dropping the first category.
- Get the mean age of passengers.
- Get the median fare of passengers.
- Get the number of passengers by class.
- Get the number of passengers by gender.
- Get the number of passengers by survival status.
- Calculate the survival rate of passengers.
- Calculate the survival rate by gender.

The Titanic dataset contains columns as shown below.

Pas sen ger id	Sur vive d	Pcla ss	Na me	Sex	Age	Sib Sp	Par ch	Tick et	Fare	Cab in	Em bark ed

Sample Data:

titanicDat...

Submit

Debugger

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data['FamilySize'] = data['SibSp'] + data['Parch']
7 # 1. Create a new column 'IsAlone' (1 if alone, 0 otherwise)
8 data['IsAlone'] = np.where(data['FamilySize'] == 0, 1, 0)
9
10 # 2. Convert 'Sex' to numeric (male: 0, female: 1)
11 data['Sex'] = data['Sex'].map({'male': 0, 'female': 1})
```

Average time0.055 s65.00 ms

Maximum time0.055 s65.00 ms

1 out of 1 shown test case(s) passed

Test case 155 ms

Debug

Expected output

Actual output

29.69911764705882

29.69911764705882

14.4542

14.4542

3...491

3...491

1...216

1...216

2...184

2...184

Name: PClass, dtype: int64

Name: PClass, dtype: int64

Terminal

Test cases

< Prev

Reset

Submit

Next >

Course

Google Chrome Web Browser

Ask Gemini

mitaoe.codetantra.com/secure/course.jsp?eucld=698c54860aba96214c8b7d5e#/contents/698c54860aba96214c8b7d6a/67e380...

Verify that it's you

CODETANTRA

Home Learn Anywhere

202501120148@mitaoe.ac.in Support Logout

4.2.7. Titanic Dataset Analysis and Data Cleaning - 3

02:35

You are provided with the Titanic dataset containing information about passengers on the Titanic. Your task is to write Python code to answer the following questions based on the dataset.

- Calculate the survival rate by class.
- Calculate the survival rate by embarkation location (Embarked_S).
- Calculate the survival rate by family size (FamilySize).
- Calculate the survival rate by being alone (IsAlone).
- Get the average fare by passenger class (Pclass).
- Get the average age by passenger class (Pclass).
- Get the average age by survival status (Survived).
- Get the average fare by survival status (Survived).
- Get the number of survivors by class (Pclass).
- Get the number of non-survivors by class (Pclass).

The Titanic dataset contains columns as shown below.

Pas sen ger id	Sur vive d	Pcla ss	Na me	Sex	Age	Sib Sp	Par ch	Tick et	Fare	Cab in	Em bark ed

Sample Data:

titanicDat...

Submit

Debugger

```
1 import pandas as pd
2 import numpy as np
3
4 # Load the Titanic dataset
5 data = pd.read_csv('Titanic-Dataset.csv')
6 data['FamilySize'] = data['SibSp'] + data['Parch']
7 data['IsAlone'] = np.where(data['FamilySize'] > 0, 0, 1)
8 data = pd.get_dummies(data, columns=['Embarked'], drop_first=True)
9
10 print(data.groupby('Pclass')['Survived'].mean())
11 print(data.groupby('Embarked_S')['Survived'].mean())
```

Average time0.064 s64.00 ms

Maximum time0.064 s64.00 ms

1 out of 1 shown test case(s) passed

Test case 164 ms

Debug

Expected output

Actual output

Pclass

Pclass

1...0.629630

1...0.629630

2...0.472826

2...0.472826

3...0.242363

3...0.242363

Name: Survived, dtype: float64

Name: Survived, dtype: float64

Embarked_S

Embarked_S

0.629630

0.629630

Terminal

Test cases

< Prev

Reset

Submit

Next >