

Assignment No - 9

DATE		
PAGE NO.		

Title :- Mongo DB queries :

Objective :- To acquire the skills to use a powerful flexible & scalable general purpose databases to handle Big data .

Outcome :- Implement No SQL queries using MongoDB

Software :- Mongoddb

Theory :-

The use command

use DATABASE_NAME

MongoDB use DATABASE_NAME is used to create database. The command will create a new database, if it doesn't exist otherwise it will return the exit existing database.

Syntax :-

eg:- If you want to create a database with name < mydb > then use DATABASE statement would be as follows :

> use mydb

To check you currently selected database use the command db

> db;

The drop data

Mongo DB : `db.drop database()` command is used to drop a existing database.

Syntax: Basic syntax of `drop database()` command is as follows:

`db.dropDatabase()`

This will delete the selected database. If you have not selected any database, then it will delete default 'test' database.

MongoDB create collection The `create collection()` method.

- MongoDB `db.create collection (name, options)` is used to create collection.

`db.create collection (name, options)`

Syntax :-

In the command, name is name of collection to be created. options is a document & used to specify configuration of Collection.

The drop () Method

MongoDB's `db.collection.drop()` is used to drop a collection from the database

`db.COLLECTION_NAME.drop()`

Syntax :-

MongoDB - Insert Document The insert () method.

To insert data into MongoDB collection, you need to use MongoDB's insert () or save () method.

Syntax :-

Basic syntax of insert () command is as follows.

```
> db.COLLECTION_NAME.insert (document)
```

eg :-

```
> db.Stud1.insert (name : 'abc', age : 20)
```

Query Documents (find)

In MongoDB, the db.collection find () method retrieves documents from a collection. The db.collection find () method returns a cursor to the retrieved document.

The db.collection find one () method also perform a read operation to return a single document.

Internally, the db.collection find one () method is the db.collection.find () method with limit of 1.

1) Select All Documents in a Collection

An empty query document ({} (selects all document in the collection

```
db.inventory.find ({}))
```

Not specifying a query document to the field() is equivalent to specifying an empty query document. There fore the following operation is equivalent to the previous operation db.inventory.find().

Specify Conditions Using Query Operators.

To specify equality condition, use the query document { <field> : <value> } to select all document that contain the <field> with the specified <value>.

Conclusion :

We have Implement CRUD operations using MongoDB.

