

# ProxyChains Cheat Sheet — Kali Linux

## Purpose

- Route network traffic through one or more proxies to hide your real IP.
  - Useful for Tor integration, chaining free/paid proxies, and preventing DNS leaks.
- 

## File location

```
/etc/proxychains.conf
```

## Open as root

```
su  
leafpad /etc/proxychains.conf
```

---

## Chain types (choose one)

- **strict\_chain** — Proxies used in fixed order; *all* must be online.
- **dynamic\_chain** — Skips dead proxies automatically. **Recommended.**
- **random\_chain** — Uses random proxies each request.

Enable **dynamic\_chain**: uncomment the `dynamic_chain` line and comment the other two.

---

## Protect against DNS leaks

Uncomment this line in the config to prevent DNS leakage:

```
proxy_dns
```

This forces DNS resolution through the proxy chain (no accidental leak of your real IP).

---

## ProxyList format (at bottom of file)

Under the `[ProxyList]` header, each line must follow this format:

```
[type] [host] [port] [user] [pass]
```

- `type`: `socks4`, `socks5`, or `http`
- `host`: proxy IP or hostname
- `port`: numeric port
- `user pass`: optional credentials for paid proxies

#### Example entries:

```
socks5 127.0.0.1 9050
socks4 192.168.1.49 1080
http 203.0.113.5 8080 paiduser secret
```

## Tor defaults — add socks5 entry

ProxyChains often ships with `socks4 127.0.0.1 9050`. Add a socks5 line for modern compatibility:

```
socks5 127.0.0.1 9050
```

## Commands — check/start Tor

```
service tor status
service tor start # start Tor if not running
```

## Run a browser (through ProxyChains)

```
proxychains firefox www.duckduckgo.com
# or for the Tor Browser you usually use the tor-browser launcher directly
```

## Test for leaks

- Visit a DNS leak test site (e.g., `dnsleaktest.com`) while using `proxychains` and compare with your normal browser.
- Expected: the test shows a proxy/foreign IP, not your real local IP.

## Quick checklist (before testing)

-

---

## Common troubleshooting

- **No connection / fails:** If `strict_chain` is enabled, ensure all listed proxies are alive or switch to `dynamic_chain`.
  - **DNS leak showing real IP:** Confirm `proxy_dns` is uncommented and retest.
  - **Tor not starting:** Check logs ( `journalctl -u tor` or `/var/log/tor/` ) and ensure port `9050` is open locally.
  - **Slow browsing:** Chained proxies add latency. Test removing slower proxies.
- 

## Tips & Notes

- Use `dynamic_chain` for resilience — it automatically skips dead proxies.
  - Keep paid-proxy credentials off public or shared systems.
  - Test with a privacy-focused search engine (duckduckgo) and DNS leak tests while connected.
  - Chaining many proxies increases fingerprinting risk and latency — prefer Tor + single proxy when appropriate.
-