```
Microsoft Windows [Version 10.0.18362.1139]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\Users\HP>cd ../..

C:\>cd xampp

C:\xampp>cd mysql

C:\xampp\mysql>cd bin

C:\xampp\mysql\bin>mysql -u root -p -h localhost
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 11
Server version: 10.4.18-MariaDB mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]>
```

```
Microsoft Windows [Version 10.0.18362.1139]
(c) 2019 Microsoft Corporation. All rights reserved.

C:\Users\HP>cd ../..

C:\>cd xampp

C:\xampp>cd mysql

C:\xampp\mysql>cd bin

C:\xampp\mysql\bin>mysql -u root -p -h localhost
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 11
Server version: 10.4.18-MariaDB mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.
```

How to show/check **Databases**
Using CMD and PhpMyAdmin.

```
show databases;
```

```
MariaDB [(none)]> show databases;
+--------------------+
| Database           |
+--------------------+
| fd                 |
| information_schema |
| mysql              |
| performance_schema |
| phpmyadmin         |
| test               |
+--------------------+
6 rows in set (0.001 sec)
```

How to create Database

Database Server

CREATE DATABASE <databasename>;

```
MariaDB [(none)]> create database student_data;
Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> create database teacher_data;
Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> show databases;
+--------------------+
| Database           |
+--------------------+
| fd                 |
| information_schema |
| mysql              |
| performance_schema |
| phpmyadmin         |
| student_data       |
| teacher_data       |
| test               |
+--------------------+
8 rows in set (0.001 sec)
```

How to delete **Databases**
Using CMD and PhpMyAdmin.

```
DROP database <databasename>;
```

```
MariaDB [(none)]> drop database teacher_data;
Query OK, 0 rows affected (0.002 sec)

MariaDB [(none)]> drop database student_data;
Query OK, 0 rows affected (0.001 sec)

MariaDB [(none)]> show databases;
+--------------------+
| Database           |
+--------------------+
| fd                 |
| information_schema |
| mysql              |
| performance_schema |
| phpmyadmin         |
| test               |
+--------------------+
6 rows in set (0.001 sec)
```

How to use **Databases**
Using CMD and PhpMyAdmin.

```
USE <databasename>;
```

```
MariaDB [student_data]> use teacher_data;
Database changed
MariaDB [teacher_data]> use student_data;
Database changed
MariaDB [student_data]> use teacher_data;
Database changed
MariaDB [teacher_data]>
```

How to check current **Database**
Using CMD and PhpMyAdmin.

```
SELECT DATABASE();
```

```
MariaDB [teacher_data]> use student_data;
Database changed
MariaDB [student_data]> select database();
+---------------+
| database()    |
+---------------+
| student_data |
+---------------+
1 row in set (0.000 sec)
```