		In	pι	ıt			E	хре	ecte	d	G	ot	
~	•	2					1	4			1	4	~
		4					1	2			1	2	
		5											
		1	4	5	3	2							
		4											
		4											
		2	2	4	3								

```
#include<stdio.h>
int main(){
    int n,m,c,c1=0,co;
    scanf("%d",&n);
    int arr[n];
    for(int a=0;a<n;a++){
        scanf("%d",&arr[a]);
    }
    scanf("%d",&m);
    int brr[m],ans[m];
    for(int b=0;b<m;b++){
        scanf("%d",&brr[b]);
    }
    for(int j=0;j<m;j++)
    {</pre>
```

```
16
              c=0;
              for(int i=0;i<n;i++){</pre>
17 ▼
18 •
                   if(arr[i]==brr[j]){
19
                       c=1;
                       arr[i]=-1;
20
21
                       break;
22
                   }
23
              if(c==0){
24 •
25
                  ans[c1]=brr[j];
26
                   c1++;
27
28
         for(int a=0;a<c1;a++){</pre>
29 🔻
30
              co=0;
```

```
for(int b=0;b<c1;b++){
    if(ans[b]<ans[a])
    co++;
}
int temp=ans[a];
ans[a]=ans[co];
ans[co]=temp;
}
for(int i=0;i<c1;i++)
printf("%d ",ans[i]);</pre>
```

Input	Expected	Got
10 203 204 205 206 207 208 203 204 205 206 13 203 204 204 205 206 207 205 208 203 206 205 206 204	204 205 206	204 205 206

Passed all tests! 🗸

```
1
    #include<stdio.h>
 2
    int main()
 3 ⋅
    {
        int t,n,Is,rs,m;
 4
 5
        scanf("%d",&t);
        for(int i=0;i<t;i++){
 6 ₹
 7
             Is=0;
 8
             rs=0;
             scanf("%d",&n);
 9
             int arr[n];
10
             for(int j=0;j<n;j++)</pre>
11
             scanf("%d",&arr[j]);
12
        m=n/2;
13
        if(arr[m]==0){
14 •
             for(m=0;arr[m]==0&&m<n;m++);
15
```

```
16
         for(int j=0;j<=m;j++)</pre>
17
18
         Is=Is+arr[j];
         for(int j=m;j<n;j++)</pre>
19
         rs=rs+arr[j];
20
         printf("%s\n",(Is==rs)?"YES":"NO");
21
22
         }
23
         return 0;
24
   }
```

	Input	Expected	Got	
•	3 5 1 1 4 1 1 4 2 0 0 0 4	YES YES YES	YES YES YES	
	0020			
~	2 3 1 2 3 4 1 2 3 3	NO YES	NO YES	~

Passed all tests!

