```
3
    int main()
 4
 5 ▼ {
    int arr[3][3];
 6
    for(int i=0;i<3;i++)
 7
 8 ▼ {
 9
    for(int j=0;j<3;j++)</pre>
10 √ {
    scanf("%d",&arr[i][j]);
11
12
13
   int odd=0,even=0;
14
    for(int i=0;i<3;i++)
15
```

2

```
10 1 1
   for(int j=0;j<3;j++)
17
18 → {
19
   if((i+j)%2!=0)
    odd+=arr[i][j];
20
21
    else
22
    even+=arr[i][j];
23
    }
24
25
    printf("%d\n%d",even,odd);
26
    }
```

	Input	Expected	Got	
~	1 2 3 4 5 6 7 8 9	25 20	25 20	~
~	21 422 423 443 586 645 657 846 904	2591 2356	2591 2356	~

```
2
3
    struct data
4
 5 ▼ {
    int gen;int tal;
 6
 7
    };
    int main()
 8
9 ▼ {
10
    int n;
    scanf("%d",&n);
11
12
    struct data a[n];
    for(int i=0;i<n;i++)</pre>
13
    scanf("%d %d",&a[i].gen,&a[i].tal);
14
    for(int i=0;i<n-1;i++)</pre>
15
16
```

```
16 ▼|{
   for(int j=0;j<n-i-1;++j)</pre>
17
18 ▼ {
    if(a[j].tal<a[j+1].tal)</pre>
19
20 ▼ {
21
    struct data temp=a[j];
22
    a[j]=a[j+1];
23
    a[j+1]=temp;
24
    }
25
    }
26
27
    for(int i=0;i<n;i++)</pre>
28 🕶
     if(a[i].gen==0)
29
    printf("%d ",a[i].tal);}
30
    for(int i=0.i<n.++i)
31
```

```
31 for(int i=0;i<n;++i)
32
33 * {
34
35   if(a[i].gen==1)
36   printf("%d ",a[i].tal);
37   }
38  }</pre>
```

	Input	Expected	Got
>	5	7 3 2 15 6	7 3 2 15 6
	0 3		
	1 6		
	0 2		
	0 7		
	1 15		
>	6	39 37 26 13 7 1	39 37 26 13 7 1
	0 1		
	0 26		
	0 39		
	0 37		
	0.7		

	0 37																									
	0 7																									
	0 13																									
~	12	31	29	18	14	12	10	9	8	5	3	2	1		31	29	18	14	12	10	9	8	5	3	2	1
	1 12																									
	1 14																									
	1 18																									
	1 1																									
	1 2																									
	1 3																									
	1 5																									
	1 8																									
	1 9																									
	1 10																									

	1 10																							
	0 29																							
	0 31																							
>	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	1
	0 12																							ш
	1 12																							П
	0 12																							۱
	1 12																							П
	0 12																							۱
	0 12																							
	1 12																							۱
	0 12																							
	1 12																							

	1	
1 12		
0 12		
1 12		
0 12		
0 12		
1 12		
0 12		
1 12		
1 12		
0 12		
1 12		
1		

```
2
 3
    int main()
 4
 5 ₹
 6
    int i,j,n,x1,x2,y1,y2,t=0;
7
    long long total=0;
    int arr[1001][1001]={0};
 8
    scanf("%d",&n);
 9
10
    while(n--)
11 ▼ {
    scanf("%d %d %d %d",&x1,&y1,&x2,&y2,&t);
12
13
    for(i=x1;i<=x2;i++)
14 √ {
15
    for(j=y1;j<=y2;j++)
```

```
10 + | {
17
    if(arr[i][j]==0)
18
    arr[i][j]+=t;
    else if(arr[i][j]>0)
19
20
    arr[i][j]=(-1)*(arr[i][j]+t);
21
    else if(arr[i][j]<0)</pre>
22
    arr[i][j]-=t;
23
    }
24
    }
25
    }
26
    for(i=1;i<1001;i++)
27 ▼ {
28
    for(j=1;j<1001;j++)
```

```
101(]-1,]~1001,]**/
40
29 ₹ {
30
    if(arr[i][j]<0)
31
    total+=arr[i][j];
32
    }
    }
33
    printf("%lld\n",(-1)*total);
34
35
    return 0;
36
   }
```

	Input	Expected	Got	
~	3 1 4 4 6 1 4 3 6 6 2	35	35	~
~	2 2 5 4 3 1 48 12 49 27 8	0	0	~
~	3 88 34 99 76 44 82 65 94 100 81 58 16 65 66 7	10500	10500	~