

Snort practice

Snort version

```
C:\Snort\bin>snort -U

  ,,-
 o"  )~
  ....

-*> Snort! <*-
Version 2.9.0.4-ODBC-MySQL-FlexRESP-WIN32 GRE (Build 110)
By Martin Roesch & The Snort Team: http://www.snort.org/snort/snort-team

Copyright (C) 1998-2011 Sourcefire, Inc., et al.
Using PCRE version: 8.10 2010-06-25
Using ZLIB version: 1.2.3

C:\Snort\bin>
```

Snort interface

```
C:\Snort\bin>snort -W

  ,,-
 o"  )~
  ....

-*> Snort! <*-
Version 2.9.0.4-ODBC-MySQL-FlexRESP-WIN32 GRE (Build 110)
By Martin Roesch & The Snort Team: http://www.snort.org/snort/snort-team

Copyright (C) 1998-2011 Sourcefire, Inc., et al.
Using PCRE version: 8.10 2010-06-25
Using ZLIB version: 1.2.3

Index   Physical Address      IP Address      Device Name      Description
-----
1       00:00:00:00:00:00      192.168.11.130  \Device\NPF_{5D5EB2E7-12A2-4DF0-9235-402376226E25}
UMware Accelerated AMD PCNet Adapter (Microsoft's Packet Scheduler)

C:\Snort\bin>
```

Snort flags

```
-v      Be verbose
-U      Show version number
```

```
-d      Dump the Application Layer
```

```
-i <if> Listen on interface <if>
```

Type “C:\snort\bin\snort -v -d -iN” where N is the network interface number.

Ping request from host to target

```
=====
01/27-13:27:46.941293 192.168.11.1 -> 192.168.11.130
ICMP TTL:128 TOS:0x0 ID:8227 IpLen:20 DgmLen:60
Type:8 Code:0 ID:1 Seq:56 ECHO
61 62 63 64 65 66 67 68 69 6A 6B 6C 6D 6E 6F 70  abcdefghijklmnop
71 72 73 74 75 76 77 61 62 63 64 65 66 67 68 69  qrstuvwabcdefghi
=====
```

Ping reply from target to host

```
=====
01/27-13:27:46.941338 192.168.11.130 -> 192.168.11.1
ICMP TTL:128 TOS:0x0 ID:105 IpLen:20 DgmLen:60
Type:0 Code:0 ID:1 Seq:56 ECHO REPLY
61 62 63 64 65 66 67 68 69 6A 6B 6C 6D 6E 6F 70  abcdefghijklmnop
71 72 73 74 75 76 77 61 62 63 64 65 66 67 68 69  qrstuvwabcdefghi
=====
```

Continuous ping

```
Reply from 192.168.11.130: bytes=32 time<1ms TTL=128
Reply from 192.168.11.130: bytes=32 time<1ms TTL=128

Ping statistics for 192.168.11.130:
    Packets: Sent = 153, Received = 153, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms
Control-C
PS C:\Users\adminuser> ping -t 192.168.11.130
```

Verbose, dump application layer, choose interface 1, the output is saved to a file named icmp.txt

```
C:\Snort\bin>snort -v -d -i 1 > c:\snort\output\icmp.txt
Running in packet dump mode

--== Initializing Snort ==--
Initializing Output Plugins!
pcap DAQ configured to passive.
Acquiring network traffic from "\Device\NPF_{5D5EB2E7-12A2-4DF0-9235-402376226E25}".
Decoding Ethernet

--== Initialization Complete ==--

o''~ -> Snort! <*-
''~ Version 2.9.0.4-ODBC-MySQL-FlexRESP-WIN32 GRE (Build 110)
''~ By Martin Roesch & The Snort Team: http://www.snort.org/snort/snort-team
eam Copyright (C) 1998-2011 Sourcefire, Inc., et al.
Using PCRE version: 8.10 2010-06-25
Using ZLIB version: 1.2.3

Commencing packet processing (pid=1940)
```

Indicates ping request to target machine


```

[**] [1:99999:0] TCP traffic from Kali!! [**]
[Priority: 0]
01/27-14:16:39.729402 192.168.11.133:55902 -> 192.168.11.130:8080
TCP TTL:64 TOS:0x0 ID:38864 IpLen:20 DgmLen:60 DF
*****S* Seq: 0x16566B8F Ack: 0x0 Win: 0x7210 TcpLen: 40
TCP Options (5) => MSS: 1460 SackOK TS: 2573400421 0 NOP WS: 7

[**] [1:99999:0] TCP traffic from Kali!! [**]
[Priority: 0]
01/27-14:16:39.729507 192.168.11.133:41380 -> 192.168.11.130:199
TCP TTL:64 TOS:0x0 ID:62524 IpLen:20 DgmLen:60 DF
*****S* Seq: 0x41A0863 Ack: 0x0 Win: 0x7210 TcpLen: 40
TCP Options (5) => MSS: 1460 SackOK TS: 2573400421 0 NOP WS: 7

[**] [1:99999:0] TCP traffic from Kali!! [**]
[Priority: 0]
01/27-14:16:39.729639 192.168.11.133:52800 -> 192.168.11.130:25
TCP TTL:64 TOS:0x0 ID:48853 IpLen:20 DgmLen:60 DF
*****S* Seq: 0xAB22428A Ack: 0x0 Win: 0x7210 TcpLen: 40
TCP Options (5) => MSS: 1460 SackOK TS: 2573400421 0 NOP WS: 7

```

Nmap null scan

-sN/sF/sX: TCP Null, FIN, and Xmas scans

Log any null scans

```

alert tcp $EXTERNAL_NET any -> $HOME_NET any (msg:"NULL PACKET DETECTED!!"; flags:0; sid:99998;)|

```

Null packets logged, take note of all * and no flags

```


[**] [1:99998:0] NULL PACKET DETECTED!! [**]
[Priority: 0]
01/27-14:31:12.475404 192.168.11.133:38780 -> 192.168.11.130:15000
TCP TTL:54 TOS:0x0 ID:60579 IpLen:20 DgmLen:40
***** Seq: 0x5635E15F Ack: 0x0 Win: 0x400 TcpLen: 20

[**] [1:99998:0] NULL PACKET DETECTED!! [**]
[Priority: 0]
01/27-14:31:12.475439 192.168.11.133:38780 -> 192.168.11.130:8081
TCP TTL:48 TOS:0x0 ID:33826 IpLen:20 DgmLen:40
***** Seq: 0x5635E15F Ack: 0x0 Win: 0x400 TcpLen: 20

[**] [1:99998:0] NULL PACKET DETECTED!! [**]
[Priority: 0]
01/27-14:31:12.475473 192.168.11.133:38780 -> 192.168.11.130:4444
TCP TTL:39 TOS:0x0 ID:59976 IpLen:20 DgmLen:40
***** Seq: 0x5635E15F Ack: 0x0 Win: 0x400 TcpLen: 20

```


Snort rules for tftp traffic



Include tftp rules in snort.conf

```
include $RULE_PATH\my.rules
include $RULE_PATH\tftp.rules
```

Uncomment any rules in my.rules



```
1 #alert tcp 192.168.11.133 any -> $HOME_NET any (msg:'TCP traffic from Kali!!'; si
2 #alert tcp $EXTERNAL_NET any -> $HOME_NET any (msg:'NULL PACKET DETECTED!!'; flag:
```

Tftp logs

```
[**] [1:1444:5] TFTP Get [**]
[Classification: Potentially Bad Traffic] [Priority: 2]
01/27-14:57:42.558686 192.168.11.133:40212 -> 192.168.11.130:69
UDP TTL:64 TOS:0x0 ID:46133 IpLen:20 DgmLen:46 DF
Len: 18


[**] [1:1442:6] TFTP GET shadow [**]
[Classification: Successful Administrator Privilege Gain] [Priority: 1]
01/27-14:57:47.559415 192.168.11.133:40212 -> 192.168.11.130:69
UDP TTL:64 TOS:0x0 ID:47047 IpLen:20 DgmLen:46 DF
Len: 18

[**] [1:1444:5] TFTP Get [**]
[Classification: Potentially Bad Traffic] [Priority: 2]
01/27-14:57:47.559415 192.168.11.133:40212 -> 192.168.11.130:69
UDP TTL:64 TOS:0x0 ID:47047 IpLen:20 DgmLen:46 DF
Len: 18

[**] [1:1442:6] TFTP GET shadow [**]
[Classification: Successful Administrator Privilege Gain] [Priority: 1]
01/27-14:57:52.559801 192.168.11.133:40212 -> 192.168.11.130:69
UDP TTL:64 TOS:0x0 ID:47742 IpLen:20 DgmLen:46 DF
Len: 18
```

Win2k8 event log


Will display message when new user is created



Adding new user

```
C:\Users\Administrator>net user user2 12345678 /add  
The command completed successfully.
```

When new user is created, message will pop



Linux tripwire

Searching for tripwire

```
root@kali:/var/www/html# apt-cache search tripwire  
sysraq - monitor your system and warn when system files change  
tiger - security auditing and intrusion detection tools for Linux  
tripwire - file and directory integrity checker  
root@kali:/var/www/html#
```

Install tripwire

```
root@kali:/var/www/html# apt install tripwire -y
```

Create baseline database

```
root@kali:/var/www/html# tripwire --init  
Please enter your local passphrase:  
Parsing policy file: /etc/tripwire/tw.pol  
Generating the database...  
*** Processing Unix File System ***  
### Warning: File system error.  
### Filename: /var/lib/tripwire/kali.twd  
### No such file or directory  
### Continuing...
```

Empty report on first initialization

```
root@kali:/var/www/html# ls -l /var/lib/tripwire/  
total 9.3M  
drwxr-xr-x  3 root root 4.0K Jan 27 15:18 ./  
drwxr-xr-x 83 root root 4.0K Jan 27 15:13 ../  
-rw-r--r--  1 root root 9.3M Jan 27 15:18 kali.twd  
drwxr-xr-x  2 root root 4.0K Mar 11 2019 report/  
root@kali:/var/www/html#
```

```

root@kali:/var/www/html# ls -l /var/lib/tripwire/report/
total 8.0K
drwxr-xr-x 2 root root 4.0K Mar 11 2019 ./
drwxr-xr-x 3 root root 4.0K Jan 27 15:18 ../
root@kali:/var/www/html#

```

Adduser by the name of john

```

root@kali:/tmp# adduser john
Adding user `john' ...
Adding new group `john' (1001) ...
Adding new user `john' (1001) with group `john' ...
Creating home directory `/home/john' ...
Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for john
Enter the new value, or press ENTER for the default
    Full Name []:
    Room Number []:
    Work Phone []:
    Home Phone []:
    Other []:
Is the information correct? [Y/n] Y
root@kali:/tmp#

```

Notice policy violation

```

-----
Rule Name: Security Control (/etc/passwd)
Severity Level: 66
-----

```

```

-----
Modified Objects: 1
-----

```

```

Modified object name: /etc/passwd

```

Property:	Expected	Observed
* Inode Number	1187029	1187022