Session-Level Inference Control for LLM Agents on Analytical Databases
Appendix

Sanjay Mishra
Independent researcher
Raleigh, North Carolina, USA
sanmish4@icloud.com

ABSTRACT

Online appendix to the PVLDB submission. It records the commands that regenerate the new measurements, the overlap with the author's conversational-risk manuscript, and the experiments that were not run.

PVLDB Reference Format:
Sanjay Mishra. Session-Level Inference Control for LLM Agents on Analytical Databases
Appendix. PVLDB, 20(1): XXX-XXX, 2027.
doi:XX.XX/XXX.XX

PVLDB Artifact Availability:
The source code, data, and/or other artifacts have been made available at https://github.com/sanmish4ds/least-privilege-llm-db-agents.

1 WHAT THIS REVISION RAN

All of the following are local. None calls a paid model or a warehouse.

The new scripts are the tolerance check, the attack search, the DuckDB scale run, the Laplace-plus-minimum-count baseline, and the vendor script that refuses to connect. `make_numbers.py` writes the macros.

The finance table for k=3 and k=10 uses the same loop as the existing audit evaluation, extended to k=10. The k=3 row matches the previously committed rates. The two-customer sum is a separate one-query probe.

2 OVERLAP WITH THE CONVERSATIONAL-RISK MANUSCRIPT

The arXiv paper 2607.19361, "Stateful Guardrails for Multi-Turn LLM Systems," studies dialogue. It scores semantic drift, a graph of entities mentioned in the text, and a compliance gradient. Its benchmarks are synthetic multi-turn conversations.

This paper studies SQL answers. The session state is the weight vector of entities behind an aggregate, not the text of the dialogue. The shared idea is that a score accumulated over a session can be confounded with length, which is why the finance sessions are length-matched in the earlier TKDE draft and why this paper refuses a query instead of alarming on session length.

No table, figure, or paragraph from arXiv:2607.19361 is copied here. The TKDE readme calls the journal version a TIFS manuscript. That draft is not in this repository. The review asked for a TDSC citation. The bibliography entry records the conflict and asks the author to confirm the venue.

3 NOT RUN

- A local open-weight attacker with a budget of 100 queries. No Ollama server was listening. The harness refuses to fall back to a paid API.
- Snowflake and BigQuery at k=3, 5, 10. `vendor_k_sweep.py` exits before opening a connection.
- OpenDP and Tumult Analytics. The minimum-group baseline is our own Laplace code.
- Spider 2.0. There is no agent-numbers file in the repository.
- A second BIRD audit log. Only one committed log exists.

REFERENCES

This work is licensed under the Creative Commons BY-NC-ND 4.0 International License. Visit https://creativecommons.org/licenses/by-nc-nd/4.0/ to view a copy of this license. For any use beyond those covered by this license, obtain permission by emailing info@vldb.org. Copyright is held by the owner/author(s). Publication rights licensed to the VLDB Endowment.
Proceedings of the VLDB Endowment, Vol. 20, No. 1 ISSN 2150-8097.
doi:XX.XX/XXX.XX