

Common Mistakes while passing through NHCX:

1. Improper usage of status:

Solution: Please refer to the status codes from website (Initial Request Trigger Status-> request.initiated. Response Statuses-> response.complete, response.partial, response.error)
Link: <https://nhcx.abdm.gov.in/#/technical-specifications>

2. Not Handling the error scenarios:

Solution: v1/error implementation (sender gets update regarding the request if it failed to reach recipient) provided in document : [API Response Handling to avoid Failures](#)

3. Improper implementation of the Protocol Response: Invalid response code and response body

Solution: For any request http response code should be 202 Accepted with body which provided in Acceptance scenario in document : [API Response Handling to avoid Failures](#)

4. Not following the proper Protocol Headers

Solution: Please pass the proper protocol Headers listed in the link below:

<https://nhcx.abdm.gov.in/#/technical-specifications> (Message Structure)

e.g. {"alg":"RSA-OAEP-256","enc":"A256GCM","x-hcx-api_call_id":"961b29bc-72fa-45fe-8735-xxxxxabc3e3b","x-hcx-workflow_id":"33","x-hcx-request_id":"eb1b2d8c-xxxx-438b-xxxx-8313875da3c9","x-hcx-status":"request.initiate","x-hcx-timestamp":"1723529473885","x-hcx-sender_code":"PYRxx@hcx","x-hcx-recipient_code":"INxxx@hcx","x-hcx-correlation_id":"17301a2d-fb34-4bf1-xxxx-bfxxxxxxx310","x-hcx-ben-abha-id":""}

5. In PROD when passing the registry ID

Solution: For Providers, use the HFR ID as the registry ID.

For Payers the IRDAI registry ID should be passed as the Registry ID (e.g. 125 pass 125, if 0123 then pass 123).

6. Missing the Accept parameter in the API call header

Solution: Pass the headers listed below:

Accept:application/json

Content-Type:application/json

bearer_auth:Bearer ###

7. Providers pointing to the PayerID of getPolicy API response

Solution: Providers should use the processingID from the response of the get/Policies to pass in the receiver code.

8. Use of improper Correlation ID

Solution: The Correlation ID is a UUID, and it has to be unique for each request cycle.

Note: In case of error/failure the CorrelationID is made inactive in our system and a fresh request has to be triggered.

9. 401/Unauthorized error for API call – Invalid token

Solution: The token is validated from the ABDM and must be renewed, in case of 401 error for Unauthorized, first generate a new token and try with that.

10. Policy Linking/Delinking auth restriction- Not everyone can perform the activity

Solution: Only those listed in the payerID & PolicyID during the linking are authorized.

Note: The client ID used to generate token during participant creation for these entities should be used to generate the token to perform these tasks, in case of mismatch please confirm over email.