

## Payer:

|                                    |                                                                                                             |
|------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Use case 1                         | Link ABHA with Policy                                                                                       |
| APIs to be called                  | <a href="#">/participant/link/abha/policy</a>                                                               |
| API to be Implemented              | NA                                                                                                          |
| Use case description               | Link ABHA Number to the Policy purchased by the individual at the time of policy creation at payer systems. |
| Entity to Implement the API called | NHCX                                                                                                        |

|                                    |                                                                                 |
|------------------------------------|---------------------------------------------------------------------------------|
| Use case 2                         | Get Policy                                                                      |
| APIs to be called                  | <a href="#">/participant/get/policies</a>                                       |
| API to be Implemented              | NA                                                                              |
| Use case description               | Get the list of policies for the beneficiary based on the mobile number or ABHA |
| Entity to Implement the API called | NHCX                                                                            |

|                                    |                                                 |
|------------------------------------|-------------------------------------------------|
| Use case 3                         | De-Link ABHA from Policy                        |
| APIs to be called                  | <a href="#">/participant/delink/abha/policy</a> |
| API to be Implemented              | NA                                              |
| Use case description               | De-Link Policy Number from ABHA profile         |
| Entity to Implement the API called | NHCX                                            |

|                                    |                                                                     |
|------------------------------------|---------------------------------------------------------------------|
| Use case 4                         | Get Participant List                                                |
| APIs to be called                  | <a href="#">/fetch/participants/list</a>                            |
| API to be Implemented              | NA                                                                  |
| Use case description               | Retrieve the list of participants in the registry based on the role |
| Entity to Implement the API called | NHCX                                                                |

|                                    |                                                                                                                                                                  |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 5                         | Get public Key                                                                                                                                                   |
| APIs to be called                  | <a href="#">/fetch/certs</a>                                                                                                                                     |
| API to be Implemented              | NA                                                                                                                                                               |
| Use case description               | Retrieve the public key of the receiver, that is to be used to encrypt the payload for the receiver. participant id must be mandatorily provided in the request. |
| Entity to Implement the API called | NHCX                                                                                                                                                             |

|                   |                              |
|-------------------|------------------------------|
| Use case 6        | Get the auth token           |
| APIs to be called | <a href="#">/get/session</a> |

|                                    |                                                     |
|------------------------------------|-----------------------------------------------------|
| API to be Implemented              | NA                                                  |
| Use case description               | To generate the token to authenticate the API calls |
| Entity to Implement the API called | NHCX                                                |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 7                         | Response to the coverageeligibility request                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| APIs to be called                  | <a href="#">/v1/coverageeligibility/on_check</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| API to be Implemented              | <a href="#">/v1/coverageeligibility/check</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Use case description               | Payer to respond with API payload which should contain the eligibility and plan details of the beneficiary for whom the details are requested for.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Protocol Status                    | response.complete                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| Validations                        | <ol style="list-style-type: none"> <li>1. Payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol>                                                                                                                                                                                                                                                                                                                                                                              |
| API logic                          | <p>This API should be called by payers by passing the appropriate payload. It should be prepared in two types based on the processing of the request. Prepare the response keeping the “type” param of as “JWEPayloadResponse” or “ProtocolResponse”</p> <ol style="list-style-type: none"> <li>1. Encrypt the payload (As per RFC7516) using the public key of the recipient entity.</li> </ol> <p>Encrypted payload will be prepared only when the payer validated and processed the request at their systems.</p> <ol style="list-style-type: none"> <li>2. ProtocolResponse.</li> </ol> <p>ProtocolReponse will be prepared as response only when the payer could not validate and process the request due to payload is invalid or not able to decrypt or any protocol errors.</p> |

|                       |                                              |
|-----------------------|----------------------------------------------|
| Use case 8            | Response to the insurance plan request       |
| APIs to be called     | <a href="#">/v1/insuranceplan/on_request</a> |
| API to be Implemented | <a href="#">/v1/insuranceplan/request</a>    |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                            |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case description               | Respond with the insurance plan details request via NHCX                                                                                                                                                                                                                                                                                                                                                   |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                   |
| Protocol Status                    | response.complete                                                                                                                                                                                                                                                                                                                                                                                          |
| Validations                        | <ol style="list-style-type: none"> <li>1. Payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol> |
| API logic                          | This API should be called by payers by passing the appropriate payload.                                                                                                                                                                                                                                                                                                                                    |
|                                    |                                                                                                                                                                                                                                                                                                                                                                                                            |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 9                         | Respond to the Preauthorization Submitted                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| APIs to be called                  | <a href="#">/v1/preauth/on_submit</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| API to be Implemented              | <a href="#">/v1/preauth/submit</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Use case description               | Payer to respond with API payload which should contain the adjudicated Preauthorization details.                                                                                                                                                                                                                                                                                                                                                                                                                     |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Protocol Status                    | response.complete                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Validations                        | <ol style="list-style-type: none"> <li>1. The payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol>                                                                                                       |
| API logic                          | <p>This API should be called by payers by passing the appropriate payload. It should be prepared in two types based on the processing of the request. Prepare the response keeping the “type” param of as “JWEPayloadResponse” or “ProtocolResponse”</p> <ol style="list-style-type: none"> <li>3. Encrypt the payload (As per RFC7516) using the public key of the recipient entity.</li> </ol> <p>Encrypted payload will be prepared only when the payer validated and processed the request at their systems.</p> |

|  |                                                                                                                                                                                                                          |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>4. ProtocolResponse.</p> <p>ProtocolResponse will be prepared as response only when the payer could not validate and process the request due to payload is invalid or not able to decrypt or any protocol errors.</p> |
|  |                                                                                                                                                                                                                          |

|                                    |                                                                                                                                                                                  |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 10                        | Raise communication request                                                                                                                                                      |
| APIs to be called                  | <a href="#">/v1/communication/request</a>                                                                                                                                        |
| API to be Implemented              | <a href="#">/v1/communication/on_request</a>                                                                                                                                     |
| Use case description               | Raise a communication request to Provider via HCX in a claim cycle for any additional documents required from provider.                                                          |
| Entity to Implement the API called | Provider                                                                                                                                                                         |
| Protocol Status                    | request.initiated                                                                                                                                                                |
| Validations                        | Payload should be validated against the profiles published by NRCES.                                                                                                             |
| API logic                          | API should be called by payer systems to get the additional documents from the provider. Payload will be prepared as TaskBundle having CommunicationRequest as bundle component. |
|                                    |                                                                                                                                                                                  |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 11                        | Respond to the Claim Submitted                                                                                                                                                                                                                                                                                                                                                                                 |
| APIs to be called                  | <a href="#">/v1/claim/on_submit</a>                                                                                                                                                                                                                                                                                                                                                                            |
| API to be Implemented              | <a href="#">/v1/claim/submit</a>                                                                                                                                                                                                                                                                                                                                                                               |
| Use case description               | Payer to respond with API payload which should contain the adjudicated Claim details.                                                                                                                                                                                                                                                                                                                          |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                       |
| Protocol Status                    | response.complete or response.partial                                                                                                                                                                                                                                                                                                                                                                          |
| Validations                        | <ol style="list-style-type: none"> <li>1. The payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol> |
| API logic                          | This API should be called by payers by passing the appropriate payload. It should be prepared in two types based on the processing of the request. Prepare the response keeping the "type" param of                                                                                                                                                                                                            |

|  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>as “JWEPayloadResponse” or “ProtocolResponse”</p> <ol style="list-style-type: none"> <li>5. Encrypt the payload (As per RFC7516) using the public key of the recipient entity.</li> </ol> <p>Encrypted payload will be prepared only when the payer validated and processed the request at their systems.</p> <ol style="list-style-type: none"> <li>6. ProtocolResponse.</li> </ol> <p>ProtocolResponse will be prepared as response only when the payer could not validate and process the request due to payload is invalid or not able to decrypt or any protocol errors.</p> |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 12                        | Respond to search request                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| APIs to be called                  | <a href="#">/v1/search/on_submit</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| API to be Implemented              | <a href="#">/v1/search/submit</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
| Use case description               | To respond for search requests based on the task request. It provides the ClaimResponse(s) to the given input criteria.                                                                                                                                                                                                                                                                                                                                                                                              |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Validations                        | <ol style="list-style-type: none"> <li>1. The payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol>                                                                                                       |
| API logic                          | <p>This API should be called by payers by passing the appropriate payload. It should be prepared in two types based on the processing of the request. Prepare the response keeping the “type” param of as “JWEPayloadResponse” or “ProtocolResponse”</p> <ol style="list-style-type: none"> <li>7. Encrypt the payload (As per RFC7516) using the public key of the recipient entity.</li> </ol> <p>Encrypted payload will be prepared only when the payer validated and processed the request at their systems.</p> |

|  |                                                                                                                                                                                                                          |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>8. ProtocolResponse.</p> <p>ProtocolResponse will be prepared as response only when the payer could not validate and process the request due to payload is invalid or not able to decrypt or any protocol errors.</p> |
|--|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|                                    |                                                                                            |
|------------------------------------|--------------------------------------------------------------------------------------------|
| Use case 13                        | Send Payment Notice                                                                        |
| APIs to be called                  | <a href="#">/v1/paymentnotice/request</a>                                                  |
| API to be Implemented              | <a href="#">/v1/paymentnotice/on_request</a>                                               |
| Use case description               | Send Payment notification/reconciliation objects to Providers via the HCX gateway          |
| Entity to Implement the API called | Payer                                                                                      |
| Protocol Status                    | request.initiate                                                                           |
| Validations                        | Payload should be validated against the profiles published by NRCES.                       |
| API logic                          | API should be called by payer systems. Request will be prepared as per the specifications. |

|                                    |                                                                                                                                                                                                                                                                                                                                                                                                                |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Use case 14                        | Respond to the Task request submitted                                                                                                                                                                                                                                                                                                                                                                          |
| APIs to be called                  | <a href="#">/v1/task/on_submit</a>                                                                                                                                                                                                                                                                                                                                                                             |
| API to be Implemented              | <a href="#">/v1/task/submit</a>                                                                                                                                                                                                                                                                                                                                                                                |
| Use case description               | To return the response for task requests such as reprocess/cancel.                                                                                                                                                                                                                                                                                                                                             |
| Entity to Implement the API called | Provider                                                                                                                                                                                                                                                                                                                                                                                                       |
| Protocol Status                    | response.complete                                                                                                                                                                                                                                                                                                                                                                                              |
| Validations                        | <ol style="list-style-type: none"> <li>1. The payload should be validated against the profiles published by NRCES.</li> <li>2. Api caller ID and Correlation ID should be different.</li> <li>3. Correlation ID should be the API caller ID of the request that you are responding to.</li> <li>4. Receiver code should be the same as Sender ID of the request that Payer system is responding to.</li> </ol> |
| API logic                          | <p>This API should be called by payers by passing the appropriate payload. It should be prepared in two types based on the processing of the request. Prepare the response keeping the “type” param of as “JWEPayloadResponse” or “ProtocolResponse”</p> <ol style="list-style-type: none"> <li>9. Encrypt the payload (As per RFC7516) using the public key of the recipient entity.</li> </ol>               |

|  |                                                                                                                                                                                                                                                                                                                                              |
|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  | <p>Encrypted payload will be prepared only when the payer validated and processed the request at their systems.</p> <p>10. ProtocolResponse.</p> <p>ProtocolReponse will be prepared as response only when the payer could not validate and process the request due to payload is invalid or not able to decrypt or any protocol errors.</p> |
|  |                                                                                                                                                                                                                                                                                                                                              |

|                                    |                                                                                                                                     |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Use case 15                        | Get status                                                                                                                          |
| APIs to be called                  | <a href="#">/v1/status</a>                                                                                                          |
| API to be Implemented              | <a href="#">/v1/on_status</a>                                                                                                       |
| Use case description               | Retrieve the status of any request that has been triggered to NHCX                                                                  |
| Entity to Implement the API called | NHCX                                                                                                                                |
| Protocol status                    | Request.initiated                                                                                                                   |
| Request Payload                    | Encrypted payload of request for which the status is seeking for.                                                                   |
| Validations                        | Payload should be validated against the profiles published by NRCES.                                                                |
| Callback API logic                 | Callback API should be implemented by provider systems. It should accept the payload as ProtocolHeader contains all the attributes. |