

Provider:

Use case 1	Get Participant List –
APIs to be called	/fetch/participants/list
Use case description	Retrieve the list of participants in the registry based on the role
Entity to Implement the API called	NHCX

Use case 2	Get Policy
APIs to be called	/participant/get/policies
API to be Implemented	NA
Use case description	Get the list of policies for the beneficiary based on the mobile number or ABHA
Entity to Implement the API called	NHCX

Use case 3	Get public Key
APIs to be called	/fetch/certs
API to be Implemented	NA
Use case description	Retrieve the public key of the receiver, that is to be used to encrypt the payload for the receiver. participant id must be mandatorily provided in the request.
Entity to Implement the API called	NHCX

Use case 4	Get the auth token
APIs to be called	/get/session
API to be Implemented	NA
Use case description	To generate the token to authenticate NHCX API calls
Entity to Implement the API called	NHCX

Use case 5	Check the coverage eligibility
APIs to be called	/v1/coverageeligibility/check
Callback API to be Implemented	/v1/coverageeligibility/on_check
Use case description	To check the eligibility of a beneficiary with the payers via NHCX. This API should be used to request whether the patient's coverage is in force, whether it is valid at

	this or specified date, and/or for requesting the benefits & plan details associated with the coverage.
Entity to Implement the API called	Payer
Protocol status	request.initiated
Request Payload	Encrypted payload of CoverageEligibilityRequestBundle
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms and it will be derived based on “type” param of the response. 1. Encrypted format (As per RFC7516) and decrypt using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated and verified. 2. ProtocolResponse. ProtocolResponse comes as response only when the payer couldnot able to process the request due to payload is invalid or not able to decrypt or any protocol errors.

Use case 6	Request insurance plan details
APIs to be called	/v1/insuranceplan/request
Callback API to be Implemented	/v1/insuranceplan/on_request
Use case description	Request insurance plan details from the Payer via HCX
Protocol status	request.initiated
Request Payload	Encrypted payload of TaskBundle
Validations	Payload should be validated against the profiles published by NRCES.
Entity to Implement the API called	Payer

Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms, and it will be derived based on “type” param of the response. 3. Encrypted format (As per RFC7516) of the payload InsurancePlanBundle using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated and verified. 4. ProtocolResponse. ProtocolResponse comes as response only when the payer couldnot able to process the request due to payload is invalid or not able to decrypt or any protocol errors.
--------------------	--

Use case 7	Preauthorization submission
APIs to be called	/v1/preauth/submit
API to be Implemented	/v1/preauth/on_submit
Use case description	Submit the Preauthorization request from the Provider end.
Entity to Implement the API called	Payer
Protocol status	request.initiated
Request Payload	Encrypted payload of ClaimBundle
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms, and it will be derived based on “type” param of the response. 1. Encrypted format (As per RFC7516) of the payload ClaimResponseBundle and decrypt using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated and verified. 2. ProtocolResponse.

	ProtocolResponse comes as response only when the payer could not be able to process the request due to payload is invalid or not able to decrypt or any protocol errors.

Use case 8	Respond to communication request received from Payer for additional documents
Callback APIs to be called	/v1/communication/on_request
API to be Implemented	/v1/communication/request
Use case description	Respond to the communication Request via NHCX. This API will be called by payers to seek more details of the case submitted by providers for Preauthorization or for Claims.
Entity to Implement the Callback API called	Payer
Protocol status	response.completed
Response Payload	Encrypted payload of TaskBundle should have Communication as input.
Validations	Payload should be validated against the profiles published by NRCES.

Use case 9	Claim Submission
APIs to be called	/v1/claim/submit
API to be Implemented	/v1/claim/on_submit
Use case description	Submit the Claim from the Provider end to the NHCX.
Entity to Implement the API called	Payer
Protocol status	request.initiated
Request Payload	Encrypted payload of ClaimBundle
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms, and it will be derived based on “type” param of the response. 1. Encrypted format (As per RFC7516) of the payload ClaimResponseBundle and decrypt using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated

	and verified. 2. ProtocolResponse. ProtocolReponse comes as response only when the payer couldnot able to process the request due to payload is invalid or not able to decrypt or any protocol errors.

Use case 10	Claim Search
APIs to be called	/v1/search/submit
API to be Implemented	/v1/search/on_submit
Use case description	To search the claim related information by the providers/regulatory bodies
Entity to Implement the API called	Payer
Protocol status	request.initiated
Request Payload	Encrypted payload of TaskBundle with code as "Search"
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms, and it will be derived based on "type" param of the response. 1. Encrypted format (As per RFC7516) of the payload TaskBundle and decrypt using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated and verified. 2. ProtocolResponse. ProtocolReponse comes as response only when the payer couldnot able to process the request due to payload is invalid or not able to decrypt or any protocol errors.

Use case 11	Acknowledge Payment notice
Callback APIs to be called	/v1/paymentnotice/on_request
API to be Implemented	/v1/paymentnotice/request
Use case description	Acknowledge the payment notification sent by the

	Payer.
Entity to Implement the API called	Payer
Protocol status	response.completed
Response Payload	Encrypted payload of TaskBundle with Task Resource
Validations	Payload should be validated against the profiles published by NRCES.

Use case 12	Request for Reprocess/Cancel
APIs to be called	/v1/task/submit
API to be Implemented	/v1/task/on_submit
Use case description	To reprocess/cancel the claims or preauthorisations, in case of rejection or partial approval provider can raise reprocess.
Entity to Implement the API called	Payer
Protocol status	request.initiated
Request Payload	Encrypted payload of TaskBundle with Task code as “reprocess” or “cancel” or “release” or “nullify” as per the usecase.
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload in two forms, and it will be derived based on “type” param of the response. 3. Encrypted format (As per RFC7516) of the payload TaskBundle and decrypt using the private key of the provider entity. Encrypted payload comes as response only when the payer processed the request and responded when everything is validated and verified. 4. ProtocolResponse. ProtocolResponse comes as response only when the payer couldnot able to process the request due to payload is invalid or not able to decrypt or any protocol errors.

Use case 13	Get status
APIs to be called	/v1/status
API to be Implemented	/v1/on_status
Use case description	Retrieve the status of any request that has been

	triggered to NHCX
Entity to Implement the API called	NHCX
Protocol status	request.initiated
Request Payload	Encrypted payload of request for which the status is seeking for.
Validations	Payload should be validated against the profiles published by NRCES.
Callback API logic	Callback API should be implemented by provider systems. It should accept the payload as ProtocolHeader contains all the attributes.