Name: Sanskruti Patil
Roll No: 31448

1) CREATE

```
db.students.insertMany([
  {_id:1,name: "Sanskruti",age: 20, dept: "Computer",marks: 99},
  {_id:2,name: "Mokshada",age: 19, dept: "IT",marks: 98},
  {_id:3,name: "Sayali",age: 18, dept: "ENTC",marks: 97}
  ])

db.students.insertMany([
  {_id:4,name: "Ram",age: 20, dept: "IT",marks: 80},
  {_id:5,name: "Shivraj",age: 19, dept: "AIDS",marks: 59},
  {_id:6,name: "Henna",age: 18, dept: "ENTC",marks: 97}
  ])
```

Output:

```
{ "acknowledged" : true, "insertedIds" : [ 1, 2, 3 ] }
```

2) READ/ LOGICAL OPERATION (AND,OR,NOT)

```
db.students.find()
```

Output:

```
{ "_id" : 1, "name" : "Sanskruti", "age" : 20, "dept" : "Computer", "marks" : 99 }
{ "_id" : 2, "name" : "Mokshada", "age" : 19, "dept" : "IT", "marks" : 98 }
{ "_id" : 3, "name" : "Sayali", "age" : 18, "dept" : "ENTC", "marks" : 97 }
```

```
db.students.find({age:20})
```

Output:

```
{ "_id" : 1, "name" : "Sanskruti", "age" : 20, "dept" : "Computer", "marks" : 99 }
```

// age >20 and marks>70

```
db.students.find({$and: [{age: {$gt:20}}, {marks:{$gt:70}}]})
```

Output: (no records)

// $or : sIT or marks>80

```
db.students.find({$or: [{dept: "IT"}, {marks:{$gte:80}}]})
```

Output:

```
{ "_id" : 1, "name" : "Sanskruti", "age" : 20, "dept" :
"Computer", "marks" : 99 }
{ "_id" : 2, "name" : "Mokshada", "age" : 19, "dept" : "IT",
"marks" : 98 }
{ "_id" : 3, "name" : "Sayali", "age" : 18, "dept" : "ENTC",
"marks" : 97 }
{ "_id" : 4, "name" : "Ram", "age" : 20, "dept" : "IT", "marks" :
80 }
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 97 }
```

// nor IT or marks<60

db.students.find({$nor: [{dept: "IT"}, {marks: {$lte:60}}]})

```
{ "_id" : 1, "name" : "Sanskruti", "age" : 20, "dept" :
"Computer", "marks" : 99 }
{ "_id" : 3, "name" : "Sayali", "age" : 18, "dept" : "ENTC",
"marks" : 97 }
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 97 }
```

3) UPDATE

1] Update One

before update:

```
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 97 }
```

update:

```
db.students.updateOne({_id:6},{$set:{marks:90}})
```

Output

```
{"acknowledged" : true, "matchedCount" : 1, "modifiedCount" :
1 }
```

after update:

```
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 90 }
```

2] Update Many

before update:

db.students.find({dept:"ENTC"})

{ "_id" : 3, "name" : "Sayali", "age" : 18, "dept" : "ENTC", "marks" : 97 }

```
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 90 }
```

Update:

db.students.updateMany({dept:"ENTC"},{$inc:{marks:5}})

output

{ "acknowledged" : true, "matchedCount" : 2, "modifiedCount" : 2 }

After Update

db.students.find({dept:"ENTC"})

{ "_id" : 3, "name" : "Sayali", "age" : 18, "dept" : "ENTC", "marks" : 102 }

```
{ "_id" : 6, "name" : "Henna", "age" : 18, "dept" : "ENTC",
"marks" : 95
```

4) DELETE

1] Delete One

db.students.deleteOne({_id:3})

{"acknowledged" : true, "deletedCount" : 1 }

2] Delete Many

db.students.deleteMany({dept:"IT"})

```
{ "acknowledged" : true, "deletedCount" : 2 }
```

db.students.find({dept:"IT"}) // no output

5) SAVE(INSERT+UPDATE)

db.students.save({_id:7,name:"Mayuri",dept:"Computer",marks:80})

```
WriteResult({ "nMatched" : 0, "nUpserted" : 1, "nModified" :
0, "_id" :     7 })
```

db.students.find({_id:7})

```
{ "_id" : 7, "name" : "Mayuri", "dept" : "Computer", "marks" :
80 }
```

db.students.save({_id:7,name:"Mayuri",dept:"Computer",marks:90})

```
WriteResult({ "nMatched" : 1, "nUpserted" : 0, "nModified" : 1
})
```

db.students.find({_id:7})

```
{ "_id" : 7, "name" : "Mayuri", "dept" : "Computer", "marks" :
90 }
```